### FOR CD-RW/DVD-ROM DRIVE MODEL SD-R1202 USER'S MANUAL

## TOSHIBA CD-RW/DVD-ROM DRIVE SAFETY INSTRUCTION MANUAL SD-R1202

### CAUTION

① CD-RWDVD-ROM DRIVE EMPLOY A LASER SYSTEM.

TO ENSURE PROPER USE OF THIS PRODUCT PLEASE READ THIS INSTRUCTION MANUAL CARE FULLY AND RETAIN FOR FUTURE REFERENCE. SHOULD THE UNIT EVER REQUIRE MAINTENANCE

CONTACT AN AUTHORIZED SERVICE LOCATION-SEE SERVICE PROCEDURE. USE OF CONTROLS, ADJUSTMENTS OR THE PERFORMANCE OF PROCEDURES OTHER THAN TO PREVENT DIRECT EXPOSURE TO LASER BEAM DO NOT TRY TO OPEN THE ENCLOSURE THOSE SPECIFIED MAY PESULT IN HAZARDOUS RADIATION EXPOSURE. S USE

## LOCATION OF THE REQUIRED LABEL



# 東芝 CD-RW/DVD-ROM ドライブ

女全にお使いいただくために、事業重を正しくご使用していただくために、この説明書をよくお謎みください。

TOSHIBA

半九お裾やになった後は、歩手保留してください。 無 世 ✓

本被履はアーザーシステムを使用しています。 本装履の 記春郷表には、右記シスルが表示されています。 本装面はヨーロッパは猫のレーザー概算 EN60826-1 で 光を直接被響することを助ぐために、この拡張の管体を関 分解及び改造をしないで下さい。感識の原因になります。 ザー機器・に分割されています。 けないでくがさい。 1X64.

CLASS 1 LASER PRODUCT APPAREL À LASER DE CLASSE

LASER KLASSE 1 PRODUKT TO EN 60825-1 クラス 1 レーザー製品

信頼性、安全性、性能の保証をすることができなくなりま 本装置の飛付け・取外しは、組み込み機器の艦器を辿っ てなら行ってください。 鬼器が入った主来行うと、牧器の 展展になります。

ゴアージェンツームジェジ・(発動研修) 教育の扱う団かいであられば、(手製人ジェジア)ハの製質はおひません)。 だー、八名田のディスシロ 超極や似けら 神経は致りません。 4.本装置の接続機子には、直接手で触れないでください。 静電気により故障する原因になります。 5. 万一般的などでディスクが取り出せなくなった時は、

ト方式の機種には、

TATACATAN. CELEBRATETE.

MANAGEMENT AND THE LOUISING COLUMN STATE STATE

本装置はある確保で放取り割りを起こすことがあります。従って、本装置を使用するシステムには、これらの 安全性や保全性に関する十分な影 **慮が必要です。本技器の故障、取り出されたデータの疑りによって、人体への危害や物質的損害を誘発す** ご使用中に異常が生じた場合は、鑑賞を切って、お買いあげの概点日にご程識へださい。 数りや技器に出因する二大的な指文、幕部及び学校を禁止するために、 可能性があるシステムには、本族関を使用しないでまださい。

PRINTED IN JAPAN 9876312200 🗐

This equipment has been tested and tourd to comply with the limits for a Class B digital device, pursuant to part 15 of the negative forms are designed to provide resoonable protection against fourful interference in a readdental installation. This equipment is present and are included as add or included and used in accordance with. This equipment is present in the installation and exact the installation are sometiment of the installation are protected as a facility of the experiment of and on the installation are protected as a facility of the protection and installation are protected as a facility of the protection and installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the installation are protected as a facility of the protection and the protection are protected as a facility of the protection and the protection and the protection are protected as a facility of the protection and the protection are protected as a facility of the protection and the protection are protected as a facility of the protection and the protection are protected as a protection and the pr

FOC NOTICE

Paginist or secure the receiving asterna.
Instruet in a sparation between the supprinct and received.
Connect the equipment into an outlet on a stroug offer ent from that to which the recher is connected.
Consult the decire or an experienced testion? Vientralism for help.

## Changes or modifications made to this equipment, not expressly approved by Toshba, or parties authorized by Toshba, could void the user's authority to operate the equipment. WARNING

RIZED service station". To prevent direct exposure to the laser beam, do LASER PRODUCT: To use this model property, read the instruction This appliance contains a laser system and is classified as a "CLASS

### PRODUKT 田田一井

Manual carefully and keep this menual for your future reference. In case of any trouble with this model, please contact your nearest "AUTHOnot try to open the enclosure

### VORSICHT

Direas Geria ratifiat en Laser System und stale "LASER PROCUNT DER RUÄSES I" Wisselfizer. Für den röstligen Gebeuch disses Absoldable Bestlemspranklaterig borgligt duchte kann notid af Referenz aufbreiden Rede programmer in derenn Robert aufbrein, die nichtet "supprisente Services Veri etung" benezint kirtigen. Um eien dicheten Robest mit den Laserstank zu vermeiden, sollte das Gehäuse nicht geöffnet werden. ACMARISEL.

Denne maerining er antonggi udvendigt på apparatet og ivalkerin, it opparatet indejale med lassertimker af klase i , hviket Reyder, at des anterides lasseratet af ovageste klasse, og at man ikke på apparatets yderside kan brive udset for utfladelig kantig striknin.



APPARATET BUR KUN ÄBNES AF FAGFOLK MED SERLIGT KENDSKAS TIL APPARÄTERMED LASERSTRALER!

Udvantigt på apparatet er anbragt den her gengtvin å advarskingskring, som advarskinger inted of bretsge akknine indgreb i apparatet, or man kon komme til at udsatte sig for basestiding.

ing överstigande galnsen för laserkass 1.

AAUTION. Use of controls or adjustments or performance of procedures other than those specified in the Onners manual, May result in hazardous padantom exposure. WARDITUS. Supplications at one again. Late agains trendootn, jota Whelds nelymelitate similia vaanalista beensteelydi

port som avger laserarån

Apperator innehitter laserion

VORGÂNGEN ALS IN DER BEDIENLINGSANLEITUNG BESCHRIEBEN KÖNNEN GEGÄHTLICHE STRAHLENEXPOSITIONEN ZUR CIE VERMENDUNS VON ANDEREN STEUERLINGEN ODER EINSTELLUNGEN ODER DAS DURCHFÜHREN VON ANDEREN FOLGE HABEN

This product is carrying the CE-Mark In accordance to the related European Directives Responsible for CE-marking is Toshina Europe. Harmfeddianne 8, D-41460 Neuss, Germany.

20 7月中 计解码记录 经基础数据的编辑 数 计测微表 學 法的现代表的 國際 超级晶体 法教教 中 医多红状态

## SHOULD THIS PRODUCT REQUIRE MAINTENANCE, CONTACT THE FOLLOWING TOSHIBA SERVICE STATION. TOSHIBA SERVICE PROCEDURE

TOBHIBA EUROPE GJALAH, DIBK PRODUCTS DIVISION TOBHIBA AMERICA ELECTRONIC COMPONENTS INC.

35 HAMMOND, IRVINE, CA 92618-1607

DISK PRODUCTS DIVISION

D-41460 Neuss, Germany