DIN RAIL MOUNTED ACTIVE TRACKING® FILTERS WITH SURGE PROTECTION

"MAXIMIZE PROTECTION"

0.00

SOLA Active Tracking Filter STF EBte Series SOLAHD



STFE ELITE SERIES ACTIVE TRACKING[®] FILTER WITH SURGE PROTECTION

FEATURES

- Series connected DIN Rail mounted filter
- Patented durable metal mounting clip UL Listed Surge current capacity – 45,000 Amps
- Transient protection in all modes (L-N, L-G, and N-G)
- Single Phase applications up to 20 Amp
- Operating Temperature from -40°C to +50°C
- Screw Terminal Connections
 - Reliable and convenient screw clamp connections
 - Accept 10-16 AWG wire
 - Meet IP20 specifications for ingress protection
- LED status indication

- Form C contact for remote monitoring
- UL 1449, UL 1283, cUL recognized component, CE
- 5 Year Limited Warranty

VERSATILE APPLICATIONS


- Control Panels
- Factory Automation Installations
- Point of Use Industrial Equipment
- Programmable Logic Controllers
- Dedicated Industrial and Machine Tools Equipment

ADVANTAGES

The SolaHD STFE Elite DIN Rail Mount Series combines Active Tracking[®] technology with UL Listed surge protection against the full spectrum of voltage transients and surges. It continuously tracks the input AC power line responding instantly into action upon detecting extraneous high frequency noise and high voltage transients caused by everyday events such as turning on machinery, motors, or equipment. They are designed for years of trouble free operation and require little or no operator intervention after installation.

HOW DO YOU PROTECT YOUR POWER?

Employing an entire facility protection strategy will safeguard the electrical system against most transients. Multi-stage protection involves clamping the initial high-energy surge, filtering any remaining noise or transients to the protected sensitive equipment and finally, protecting the data/signal lines entering or leaving the control panel or the factory floor. This coordination of devices provides the lowest possible let through voltage to the equipment.



A **STV200/400K:** Surge protective devices capable of handling the high-impulse, potentially damaging transients commonly found at the service entrance, distribution panels, and placement in the most severe exposure locations.

B STV100K: Surge protective devices designed to protect sensitive equipment and microprocessor-based systems from transients on distribution and sub-distribution panels, or any medium exposure locations.

C STC-POE: Surge protective devices designed to work on Power-over-Ethernet Category 5 PoE transmission lines as well as Category 6 applications.


D STC-DRS: DIN Rail mountable, single pair, low voltage data, surge protective devices. The hybrid design of these data/signal line suppressors allows them to respond quickly.

E STFE Elite: DIN Rail Mountable high-frequency noise filter/ surge suppressors that offers the original active tracking technology with UL approved transient protection to guard against commonly occurring, but very damaging transients, plus provides excellent noise reduction.



F STC-CCTV: Surge protective devices tailored to protect CCTV, data, audio and cable applications.

G STFV: High-frequency noise filter/surge suppressors that offers the original active tracking technology with transient protection to guard against commonly high voltage transients, plus provides excellent noise reduction.



Selection Table

Catalog Number			Amps	Min Wire Size* (AWG Suggested)	Fuse/Circuit Breaker Ampacity	
		Input Voltage			Suggest	Max
STFE030-10N	120 V	Single Phase 2 Wire + Ground	3.0	24	3A	3.75A
STFE050-10N	120 V	Single Phase 2 Wire + Ground	5.0	22	5A	6.25A
STFE100-10N	120 V	Single Phase 2 Wire + Ground	10.0	20	10A	12.5A
STFE200-10N	120 V	Single Phase 2 Wire + Ground	20.0	12	20A	25A
STFE030-24L	240 V	Single Phase 2 Wire + Ground	3.0	24	3A	3.75A
STFE050-24L	240 V	Single Phase 2 Wire + Ground	5.0	22	5A	6.25A
STFE100-24L	240 V	Single Phase 2 Wire + Ground	10.0	20	10A	12.5A
STFE200-24L	240 V	Single Phase 2 Wire + Ground	20.0	12	20A	25A

* 16 AWG wire or larger may be required by code dependent upon application.

For a full listing of SolaHD's Filters and Surge Suppressors, visit our website at **www.solahd.com** or consult our full line catalog.

Technical Specifications

		CATALOG NUMBER						
DESCRIPTION	STFEX	XX-10N	STFEXXX-24L					
		INPUT						
Input Voltage	120 V (0-1	50 VRMS)	240 V (0-275 VRMS)					
Line Frequency		47	-63 Hz					
Response Time		< .5 ns normal mode, <5 ns common mode						
		PHYSICAL						
Enclosure		Fully Enclosed Metal Housing						
Fusing		Reference Fuse/Circuit Breaker Chart						
Status Indication		Green LED "OK"/Form C Contact/ 10 Amps@ 250 Vac or 5 Amps@ 100 Vdc						
Connection/Mounting Type		DIN	DIN Rail Mount					
Weight (Kg)		1.7	/ lbs (0.7kg)					
Dimensions in (mm) H x W x D		4.88 x 2.56 x 4.56 (124 x 65 x 116)						
	ENVIRONMENT							
Operating Temperature		-40°C to +50°C at full load Derate Linearly to 60% at +70°C						
Operating Humidity		0% to 95% Non-condensing						
	SURGE PROTECTION							
	Per Phase	Per Phase		30,000 Amps				
Peak Surge Current	Line to Neutral	Line to Neutral		20,000 Amps				
Capability	Line to Ground		10,000 Amps					
	Neutral to Ground		10,000 Amps					
	10m Sec		5 x Nominal					
Load Surge Current Rating	1 sec		3 x Nominal					
	10 sec		2 x Nominal					
		ACTIVE TRACKING PROTECTION						
Frequency Response								
Normal Mode (Forward-Reverse)	100 kHz to 50 MHz		90 dB Max					
Common Mode (Forward-Reverse)	5 MHz to 50 MHz		60 dB Max					
Transient Reduction	Typical Category A Ringwave (6 kV, 200A, 100 kHz)		<60 V Peak					
(IEEE C62.41)	Typical Category B Ringwave (6 kV, 500A, 100 kHz)	e	<100 V Peak UL 1449					
	τ	UL 1449 (2nd EDITION) SUPPRESSOR CLASSIFICATION						
	120 V, 3-5A Models	120 V, 10-20A Models	240 V, 3-5A Models	240 V, 10-20A Models				
L-N	330 V	330 V	N/A	N/A				
L-L	N/A	N/A	600 V	600 V				
L-G	500 V	400 V	1000 V	900 V				
N-G	400 V	400 V	N/A	N/A				
		GENERAL						
Safety		UL 1449, UL1283, cUL Recognized Component, CE						
Warranty		5 Year Limited Warranty						



SolaHD is our line of premium power conversion and power quality brands. Our proven technologies power and protect throughout your facility for improved operational efficiency and productivity.

Emerson Industrial Automation brings integrated manufacturing solutions to diverse industries worldwide. Our comprehensive product line, extensive experience, world-class engineering and global presence enable us to implement solutions that give our customers the competitive edge.

For over 150 years, our electrical product brands have been providing a rich tradition of long-term, practical, high quality solutions with applications ranging from the construction and safe operation of petrochemical and process plants to providing quality power that precisely controls automotive robotic production.

Engineers, distributors, contractors, electricians and site maintenance professionals around the world trust Emerson Industrial Automation brands to make electrical installations safer, more productive and more reliable. EGS is organized into three focused businesses that provide distributors and end-users expert knowledge and excellent service.

Electrical Construction Materials

This group manufactures a broad range of electrical products including conduit and cable fittings, plugs and receptacles, enclosures and controls, conduit bodies, and industrial lighting. Whether the application is hazardous location, industrial, or commercial, the ECM group has the products to meet your needs.

Power Quality Solutions

This group offers the broadest power quality line including UPS, power conditioners, voltage regulators, shielded transformers, surge suppression devices and power supplies.

Heating Cable Systems

This group offers a broad range of electrical heating cable products for residential, commercial, and industrial applications. Electrical Construction Materials

Appleton OZ-GEDNEY A.T.X.

Power Quality Solutions

SOLAHD

Heating Cable Systems

EASYHEAT

EGS Electrical Group 9377 W. Higgins Road Rosemont, IL 60018 1.800.377.4384 www.solahd.com Canada 888.765.2226

Latin America 52.55.5366-6180 x125 Asia/Pacific 65.6745.0114

China 86.21.54260668 x305 Middle East 971.4.8838.831

Europe 33.1.4817.8502