

Data Sheet

FUJITSU Storage ETERNUS DX200F

All Flash Array

Superior performance at reasonable cost



ETERNUS® DX - Business-centric Storage

Combining leading performance architecture with automated quality of service management the Fujitsu Storage ETERNUS DX series aligns storage resources with business priorities, thus enabling higher system utilization and delivering increased system consolidation capabilities and a faster ROI.

Unified entry-level and midrange systems, a seamless family concept enabling system upgrades and ETERNUS SF, the all-encompassing management suite across the product line, reduce operational and migration costs. ETERNUS SF provides enterprise-class functionalities in the entry and midrange class and allows flexible disaster recovery concepts for the different model sizes, thus decreasing investment costs.

ETERNUS DX200F

The ETERNUS DX200F is the ideal choice for application scenarios with demanding data and performance requirements. Unlike expensive purpose-built all-flash arrays based on special architectures, it features the standard high performance architecture of the ETERNUS DX series along with the reliability you have come to expect from Fujitsu. The system delivers impressive IOPS performance with lowest latency even at full load. Thus it offers a solution that resolves all performance issues in critical applications – such as real-time business analytics or VDI environments – without requiring any complicated tuning. Flexible and scalable ready-to-run configurations, priced substantially lower than customized flash systems, makes both acquisition and installation affordable, quick and easy.



Features & Benefits

Main Features	Benefits
Based on ETERNUS DX standard architecture	<ul style="list-style-type: none">■ Performance optimized design■ Proven and mature technology■ Substantially less expensive than purpose-built flash storage systems■ Can be managed together with all other ETERNUS DX systems via central management console
Flexible SSD-based system	<ul style="list-style-type: none">■ Immediately solves the performance problems of business critical applications■ No complicated tuning measures required■ Scalable in capacity and connectivity
Quality-of-Service and Thin Provisioning	<ul style="list-style-type: none">■ Control of applications priorities according to business needs.■ Capacity optimization consisting of over-provisioning and the new space reclamation feature returning deleted capacity back to the disk pool.
Convincing performance	<ul style="list-style-type: none">■ Sufficient performance for all applications requiring high data rates and low response times■ Random access performance:<ul style="list-style-type: none">■ Max. over at 400,000 iops at 4KB Block size■ Sequential access performance: 12GB/s at 128KB Block size■ Latency: Lower than 0.5ms at 4KB Block size

Technical details

General system information

No. of controllers	2
No. of host interfaces	8 ports
Max. cache capacity	16 GB
Max. no. of drives	24
Redundancies	RAID Controller Power supply Fan
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6
Host interfaces	Fibre Channel (16 Gbit/s) iSCSI (10 Gbit/s)
Max. no. of hosts	1,024
Max. storage capacity - physical	38.4 TB
Drive Type	2.5-inch, SSD (800 GB / 1.6 TB)
Drive interface	Serial Attached SCSI (12 Gbit/s)
Back-end disk connectivity	1 pair of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide)
Max. no. of LUNs	1,536
Thin Provisioning	Yes
Quality of Service	Yes

Business Continuity Features

No. of snapshots - max.	1,536
Max. no. of copy generations	512
Remote Copy functionality	Synchronous and asynchronous
Data protection features	Cache Protection, Data Block Guard, Data Encryption, Dedicated Hot Spare, Disk Drive Patrol, Global Hot Spare
Security features	HTTPS (SSL), One Time Password, RADIUS, SSH

Options

Reporting function	Yes
Note	Options can be activated via ETERNUS SF Software

Dynamic configuration

Non-disruptive firmware upgrade	10/100/1000 Gigabit Ethernet LAN
RAID migration	Yes
LUN online expansion w/o interruption	Yes
Wide striping	Yes
Hot part replacement/ expansion	Yes

Management

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.6
Administration	Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF
Operation Management Server	Windows Server® 2012 R2 Datacenter Windows Server 2012 R2 Standard Windows Server 2012 Datacenter Windows Server 2012 Standard Windows Server2008 R2 Datacenter Windows Server 2008 R2 Enterprise Windows Server 2008 R2 Standard Windows Server 2008 Datacenter Windows Server 2008 Enterprise

Technical details

Supported OS for ETERNUS SF Express

Operation Management Client	Windows® 7 Home Premium Windows 7 Professional Windows 7 Ultimate Windows VistaHome Basic Windows Vista®Home Premium Windows Vista Business Windows Vista Enterprise Windows Vista Ultimate Windows Server® 2008 Standard Windows Server 2008 Enterprise Windows Server 2008 Datacenter Windows Server 2012 Standard Windows Server 2012 Datacenter Windows Server 2012 R2 Standard Windows Server 2012 R2 Datacenter
------------------------------------	---

Note See the ETERNUS SF datasheet for further options

Supported configurations All major host operating systems, servers and business applications

Detailed support matrix:

<http://www.fujitsu.com/global/services/computing/storage/eternus/products/diskstorage/dx200/#Tab0-4>

Installation specification

19" rackmount	Yes
Service Area	Front: 850 mm (33.5 inch) or more Rear: 850 mm (33.5 inch) or more
Power voltage	AC 100 - 120 V / AC 200 - 240 V
Power frequency	50 / 60 Hz
Power supply efficiency	92 % (80 PLUS gold)
Maximum Power Consumption	AC 100 - 120 V: 790 W (800 VA)
Maximum Power Consumption	AC 200 - 240 V: 790 W (800 VA)
Power phase	Single
Dimensions (W x D x H)	482 x 645 x 88 mm 19 x 25.4 x 3.5 inch 2 U
Weight	35 kg (77 lb)

Environmental

Maximum Heat Generation AC 100 - 120 V: 2,844: kJ/h
AC 200 - 240 V: 2,844 : kJ/h

Temperature (operating) 10 - 40 °C 50-104° F

Temperature (not operating) 0 - 50 °C 32-122° F

Humidity (operating) 20 - 80 % (relative humidity, non-condensing)

Humidity (not operating) 8 - 80 % (relative humidity, non-condensing)

Altitude 3,000 m (10,000 ft.)

Sound power (LWAd; 1B = 10dB) 6.7B

Sound pressure (LpAm) 49dB(A)

Noise notes Measured with single enclosure according to ISO 7779 and declared according to ISO 9296

Operating environment FTS 04230 – Guideline for Data Center (installation specification)

Operating environment Link <http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe>

Technical details

Compliance

Product safety	UL 60950-1, CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, GOST-R
Electromagnetic Compatibility	CNS 13438, FCC CFR 47 class A , ICES 003 Class A, EN 55022 Class A, VCCI Class A, AS/NZS CISPR 22 Class A
Electromagnetic Immunity	EN 55024
CE certification	2004/108/EC, 2006/95/EC, 2011/65/EC
Approvals	CB, CE, C-Tick, FCC, GOST, GS, VCCI
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

Warranty

Standard Warranty	3 years
Service level	Onsite Service
Warranty Terms & Conditions	www.fujitsu.com/support

Maintenance and Support Services - the perfect extension

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	5 years after end of product life
Service Weblink	www.fujitsu.com/services/product-services

About Fujitsu America

Fujitsu America, Inc., is a leading ICT solutions provider for organizations in the U.S., Canada and the Caribbean. Fujitsu enables clients to meet their business objectives through integrated offerings and solutions, including consulting, systems integration, managed services, outsourcing and cloud services for infrastructure, platforms and applications; data center and field services; and server, storage, software and mobile/tablet technologies. For more information, please visit: <http://solutions.us.fujitsu.com/> and <http://twitter.com/fujitsuamerica>

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY servers, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

As a global IT infrastructure provider, Fujitsu offers a complete range of servers designed to fill any role in today's business. Whether your business requires affordable entry-level servers, compact and scalable blade systems, or advanced multiprocessor servers capable of handling the most demanding data center applications, the PRIMERGY® line delivers Intel® Architecture servers with the rock-solid reliability and industry-leading performance you need.

PRIMERGY Servers

www.fujitsu.com/global/services/computing/

- PRIMERGY: Industrial standard server
- SPARC Enterprise: UNIX server
- PRIMEQUEST: Mission-critical IA server
- ETERNUS: Storage system

Software

www.fujitsu.com/software/

- Interstage:
Application infrastructure software
- Systemwalker:
System management software

More information

For more information, please visit:

<http://solutions.us.fujitsu.com/>

For Information on our Intel based PRIMERGY Servers:

<http://solutions.us.fujitsu.com/www/content/products/servers/primergy/index.php>

For Information on our Enterprise Storage:

<http://solutions.us.fujitsu.com/www/content/products/storage/ETERNUS/index.php>

For Information on our SPARC® Enterprise Servers:

http://solutions.us.fujitsu.com/www/products_sparc.shtml?products/servers/sparc/index

For Information on the new

PRIMEQUEST® Servers:

<http://solutions.us.fujitsu.com/www/content/products/servers/primequest/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at: www.fujitsu.com/global/about/environment/



Copyright

Fujitsu, the Fujitsu logo, and TRIOLE are trademarks or registered trademarks of Fujitsu Limited in the United States and other countries. SAP, NetWeaver and SAP HANA are trademarks or registered trademarks of SAP AG in the United States and other countries. Cisco is a trademark or registered trademark of Cisco Systems, inc. in the United States and other countries. Microsoft is a trademark or registered trademark of Microsoft Corporation in the United States and other countries. Oracle is a trademark or registered trademark of Oracle Corporation or its affiliates in the United States and other countries. Afaia is a trademark or registered trademark of iAnywhere, Inc. in the United States and other countries. All other trademarks and product names are the property of their respective owners. The statements provided herein are for informational purposes only and may be amended or altered by Fujitsu America, Inc. without notice or liability. Product description data represents Fujitsu design objectives and is provided for comparative purposes; actual results may vary based on a variety of factors. Specifications are subject to change without notice.

The statements provided herein are for informational purposes only and may be amended or altered by Fujitsu America, Inc. without notice or liability. Product description data represents Fujitsu design objectives and is provided for comparative purposes; actual results may vary based on a variety of factors. Specifications are subject to change without notice.

Copyright ©2014 Fujitsu America, Inc.

All rights reserved.

FPC65-7242-01 05/14

14.0674

Contact

FUJITSU AMERICA, INC.

Address: 1250 East Arques Avenue Sunnyvale, CA 94085-3470, U.S.A.

Telephone: 800 831 3183 or 408 746 6000

Website: <http://solutions.us.fujitsu.com>

Contact Form: <http://solutions.us.fujitsu.com/contact>

Have a question? Email us at: AskFujitsu@us.fujitsu.com