

Process Solutions

Graco's Husky™ double diaphragm pumps are built for reliable performance, long life and can handle corrosive and abrasive fluid transfer applications.



Husky™ 205

- 1/4 in (6.3 mm) connection
- Max flow: 5 gpm (19 lpm)
- Polypropylene, acetal, PVDF



Husky 307

- 3/8 in (9.4 mm) connection
- Max flow: 7 gpm (26 lpm)
- Polypropylene, acetal



Husky 515

- 1/2 in (12.7 mm) connection
- Max flow: 15 gpm (57 lpm)
- Polypropylene, acetal, PVDF



Husky 716

- 3/4 in (19.1 mm) connection
- Max flow: 16 gpm (61 lpm)
- Aluminum, stainless steel



Husky 1050

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Aluminum, polypropylene, conductive polypropylene, PVDF, stainless steel, hastelloy



Husky 1590

- 1-1/2 in (38.1 mm) connection
- Max flow: 90 gpm (340 lpm)
- Polypropylene, aluminum, stainless steel



Husky 15120

- 1-1/2 in (38.1 mm) connection
- Max flow: 120 gpm (454 lpm)
- Polypropylene, PVDF



Husky 2150

- 2 in (50.8 mm) connection
- Max flow: 150 gpm (568 lpm)
- Polypropylene, aluminum, stainless steel, iron



Husky 2200

- 2 in (50.8 mm) connection
- Max flow: 200 gpm (757 lpm)
- Polypropylene, PVDF



Husky 3300

- 3 in (76.2 mm) connection
- Max flow: 300 gpm (1135 lpm)
- Polypropylene, aluminum, stainless steel

Low and High Pressure Transfer Pumps and Pressure Washers



Priming Piston Ink Pump

- Enclosed, dual seal wet cup for longer seal life
- Runaway control with optional DataTrak™



Hydraulic Ink Pump

- Up to 3 times more efficient than pneumatic pumps
- Typical applications:
 - Letterpress inks
 - Lithographic inks



Hydra-Clean®

- High pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas
- 10:1, 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall, cart or drum mount packages



1:1 Fast-Flo®

- Max flow: 5 gpm (19 lpm)
- UL options available



Husky 515 Transfer Pump

- 1/2 in (12.7 mm) connection
- Max flow: 12 gpm (45 lpm)
- Polypropylene, acetal, PVDF



Husky 716 Transfer Pump

- 3/4 in (19.1 mm) connection
- Max flow: 14 gpm (52 lpm)
- Aluminum, stainless steel



EP2 Hose Pump

- Max flow: 2.1 gpm (7.9 lpm)
- Ideal for chemical metering applications



EP3 Hose Pump

- Max flow: 6.2 gpm (23.6 lpm)
- Typically used for chemical metering & sanitary applications



EP4 Hose Pump

- Max flow: 19.5 gpm (73.8 lpm)
- Ideal for abrasive material transfer applications

We have you covered with Graco's line of process pumps, which are designed to provide gentle pumping action or can be used in your most aggressive applications.

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com/process