

BP-2-20

Shot Blasting Machine



SPECIFICATIONS

Production Capacity:	+up to 4,500 ft ² /hr
Blast Pattern Width:	20"
Travel Speed:	0-120 ft/min
Blast Motor:	Dual 15 hp
Voltage:	460v, 3-phase, 60 hz
Amperage:	44 A
Weight:	1270 lbs
Dimensions (LxWxH):	77" x 28" x 55"
Power Cord:	55 ft.

FEATURES AND BENEFITS

- Finger tip speed and reverse control
- Easily accessible panel controls
- AC inverted ground drive motor with integrated brake
- High speed, heavy duty bearing unit
- Precision manufactured liner package

The BP-2-20 is designed for medium-to-large jobs including industrial plant and warehouse floors, parking garages, and bridge or ship decks. The BP-2-20 is an electric, self-propelled machine with a 20" blast pattern. The BP-2-20 operates on 460 V, 3-phase power. The BP-2-20 is based on a tried and true design, offering robust construction and industry leading productivity. When coupled with the BP-9-54 dust collector, the BP-2-20 is a spectacular option for your surface preparation fleet.



BP-9-54

Recommended dust collector
(see separate data sheet for specifications)



+Production rates will vary between material being removed and from job-to-job. This production rate represents production values under ideal conditions.

BLASTPRO
MFG.

877-495-6464

www.BLASTPROMFG.com