










<p>Smart Carbon Monoxide Sensor User Manual HS1CA</p>  <p>*Please read the user manual carefully before operation. The guide picture is for reference only, please in kind prevail</p>	<p>Product Introduction</p> <p>This product is a smart carbon monoxide sensor, adopts super low power consumption Zigbee wireless networking technology, used for detecting carbon monoxide. Sensor adopts high performance electrochemical sensor, support sound and flash alarm. It has high stability, super low power consumption, little sensitivity drift and many other features. Free installation design, support instant bonding.</p>  <p>Sensor LED Indicator Installation Base</p>	<p>Technical Data</p> <ol style="list-style-type: none"> Working Voltage: DC3V (CR123A Lithium Battery) Static Current: $\leq 20\mu A$ Alarm Current: $\leq 60mA$ Alarm Sound: 65dB/1m Alarm Sensitivity: 30ppm 120mins alarm 50ppm 60-90mins alarm 100ppm 10-40mins alarm 300ppm 3mins alarm Networking: ZigBee Ad-Hoc Networking Wireless Networking Distance: $\geq 70m$ (open area) Working Temperature: $-10^{\circ}C \sim +50^{\circ}C$ Environment Humidity: $\leq 95\%RH$ Dimension: 54*54*45mm 	<p>Tips</p> <ol style="list-style-type: none"> This product can not be used for detecting natural gas(methane), propane, butane and other combustible gas. Clean once a month, users may use household vacuum cleaner and soft brush when cleaning. Do not use cleanser or solvent wipe sensors, please avoid spraying air freshener, hair spray, oil paint or other aerosol near sensors. Effective working life span is 5 years, suggest replace every 5 years no matter there is fault or not. (Battery life span is 3 years). Please be attention when alarm happens. Shut-off valves immediately, opening the window, make sure indoor airiness. Besides using sensors correctly, users should strengthen the consciousness of fire protection. 	<p>Installation Instruction</p> <ol style="list-style-type: none"> Install the sensor in bedroom and living area or anywhere CO may leak, make sure each sleeping area can hear sound alarm when choose installation position. Avoid suppressing or falling down sensors, keep sensors away from humid, high voltage, strong magnetic and children. Do not suggest install sensors in garage, kitchen, boiler and places where sensor may false alarm. Do not install in dirty, dusty or greasy places, oily, dust or household chemicals may damage internal sensor, and make sensor can not work normally. Sensors can support wall mounted or placing on the table, household and travel essential. 	<p>Installation Instruction</p> <p>To increase safety factors in single-layer house, suggest to install at least a sensor in each bedroom and install a sensor at 6m from chimney and gas fixture.</p> <p>To increase safety factors in multi-layer house, suggest to install at least a sensor in each bedroom, install at least one sensor in basement. Please install a sensor at 6m from chimney and gas fixture.</p>  <p>Minimum recommended installation Avoid recommended installation</p>
--	---	---	--	---	---

<p>Installation Step1</p>  <p>• Anticlockwise rotating the bracket out from the installation base, then remove the battery insulating strip to make detector on power.</p>	<p>Installation Step2</p>  <p>• Click "Add Device" on the APP interface, and enter the networking mode.</p>	<p>Installation Step3</p>  <p>• According to APP prompt, press networking hole for 2 seconds till green LED flash quickly, APP shows slip, green LED keep on for 3 seconds, networking success. (Press the networking button for 5 seconds to disconnect the network, after the green light flashes slowly for 3 seconds, which indicates network is disconnected success).</p>	<p>Installation Step4</p>  <p>• Screw the sensor into bracket, please remove the dot side a adhesive membrane on the installation base, and stick on the wall.</p>	<p>Status and battery replacement</p> <table border="1"> <thead> <tr> <th>Status</th> <th>LED Indicator</th> <th>Alarm</th> </tr> </thead> <tbody> <tr> <td>Normal</td> <td>Not (2) flash every 10 seconds</td> <td>None</td> </tr> <tr> <td>Warning</td> <td>LED flash slowly in this case after general</td> <td>Once time every 10 seconds</td> </tr> <tr> <td>Fail</td> <td>Yellow LED flash slow</td> <td>Once time every 10 seconds</td> </tr> <tr> <td>Low Power</td> <td>Yellow LED flash red line</td> <td>Once time every 10 seconds</td> </tr> <tr> <td>Short Life Power</td> <td>Yellow LED flash red</td> <td>Once time every 10 seconds</td> </tr> <tr> <td>Stop Operation</td> <td>Yellow LED flash slow</td> <td>Once every 10 seconds</td> </tr> </tbody> </table>  <p>• Please replace battery correctly, following the battery positive and negative electrode.</p>	Status	LED Indicator	Alarm	Normal	Not (2) flash every 10 seconds	None	Warning	LED flash slowly in this case after general	Once time every 10 seconds	Fail	Yellow LED flash slow	Once time every 10 seconds	Low Power	Yellow LED flash red line	Once time every 10 seconds	Short Life Power	Yellow LED flash red	Once time every 10 seconds	Stop Operation	Yellow LED flash slow	Once every 10 seconds	<p>Troubleshooting and test</p> <p>Please take following advices for reference if sensors can not work normally</p> <ol style="list-style-type: none"> Replace battery in time, if voltage too low and reach effective life span. (Check table 1 for status reference) Please clean sensor if the fault resulted from dust or oil stain (Check table 1 for status reference). Make sure sensors screw into the base correctly.  <p>• Press test button on the product for 3 seconds, shows in above picture, till alarm happens (check table 1 for status reference). Suggest test sensor at least once a week. Please pay attention once alarm happens.</p>
Status	LED Indicator	Alarm																								
Normal	Not (2) flash every 10 seconds	None																								
Warning	LED flash slowly in this case after general	Once time every 10 seconds																								
Fail	Yellow LED flash slow	Once time every 10 seconds																								
Low Power	Yellow LED flash red line	Once time every 10 seconds																								
Short Life Power	Yellow LED flash red	Once time every 10 seconds																								
Stop Operation	Yellow LED flash slow	Once every 10 seconds																								

FCC Warning:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

To comply with FCC RF exposure compliance requirements, this grant is applicable to only mobile configurations. The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.