

Voyager™ 1200g/1202g/1202g-BF

Single-Line Laser Bar Code Scanner

User's Guide

Disclaimer

Honeywell International Inc. ("HII") reserves the right to make changes in specifications and other information contained in this document without prior notice, and the reader should in all cases consult HII to determine whether any such changes have been made. The information in this publication does not represent a commitment on the part of HII.

HII shall not be liable for technical or editorial errors or omissions contained herein; nor for incidental or consequential damages resulting from the furnishing, performance, or use of this material.

This document contains proprietary information that is protected by copyright. All rights are reserved. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of HII.

© 2010-2016 Honeywell International Inc. All rights reserved.

Other product names or marks mentioned in this document may be trademarks or registered trademarks of other companies and are the property of their respective owners.

Web Address: www.honeywellaidc.com

Microsoft® Windows® and the Windows logo are trademarks or registered trademarks of Microsoft Corporation.

The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc.

Other product names or marks mentioned in this document may be trademarks or registered trademarks of other companies and are the property of their respective owners.



Table of Contents

Customer Support

| | |
|----------------------------------|-----|
| Technical Assistance | iii |
| Product Service and Repair | iii |
| Limited Warranty | iii |
| Send Feedback | iii |

Chapter 1 - Getting Started

| | |
|---|-----|
| About This Manual | 1-1 |
| Unpacking Your Device | 1-1 |
| Connecting the Device | 1-1 |
| Connecting with USB | 1-1 |
| Connecting with Keyboard Wedge | 1-2 |
| Connecting with RS232 Serial Port | 1-4 |
| Connecting with RS485 | 1-5 |
| Reading Techniques | 1-6 |
| Menu Bar Code Security Settings | 1-6 |
| Setting Custom Defaults | 1-6 |
| Resetting the Custom Defaults | 1-7 |

Chapter 2 - Programming the Interface

| | |
|---|------|
| Introduction | 2-1 |
| Programming the Interface - Plug and Play | 2-1 |
| Keyboard Wedge | 2-1 |
| IBM PS2 Keyboard | 2-1 |
| RS232 Serial Port | 2-1 |
| RS485 | 2-2 |
| OPOS Mode | 2-2 |
| USB IBM SurePos | 2-3 |
| IBM Secondary Interface | 2-3 |
| USB PC or Macintosh Keyboard | 2-4 |
| USB HID | 2-4 |
| HID Fallback Mode | 2-4 |
| USB Serial Commands | 2-5 |
| USB Serial | 2-5 |
| CTS/RTS Emulation | 2-5 |
| ACK/NAK Mode | 2-6 |
| Communication Timeout | 2-6 |
| NAK Retries | 2-6 |
| Support BEL/CAN in ACK/NAK | 2-7 |
| Verifone® Ruby Terminal Default Settings | 2-7 |
| Gilbarco® Terminal Default Settings | 2-8 |
| Honeywell Bioptic Aux Port Configuration | 2-8 |
| Datalogic™ Magellan® Bioptic Aux Port Configuration | 2-8 |
| NCR Bioptic Aux Port Configuration | 2-9 |
| Wincor Nixdorf Terminal Default Settings | 2-9 |
| Wincor Nixdorf Beetle™ Terminal Default Settings | 2-10 |

| | |
|---|------|
| Wincor Nixdorf RS232 Mode A..... | 2-10 |
| Keyboard Country Layout..... | 2-10 |
| Keyboard Wedge Modifiers | 2-19 |
| ALT Mode | 2-19 |
| Keyboard Style | 2-19 |
| Keyboard Conversion | 2-20 |
| Keyboard Modifiers..... | 2-20 |
| Inter-Scan Code Delay | 2-21 |
| <F0> Break Character | 2-22 |
| Keyboard Wedge Defaults..... | 2-22 |
| RS232 Modifiers | 2-23 |
| RS232 Baud Rate..... | 2-23 |
| RS232 Word Length: Data Bits, Stop Bits, and Parity | 2-24 |
| RS232 Handshaking..... | 2-25 |
| RS232 Timeout..... | 2-26 |
| XON/XOFF | 2-26 |
| ACK/NAK | 2-27 |
| Communication Timeout..... | 2-27 |
| NAK Retries | 2-28 |
| Support BEL/CAN in ACK/NAK | 2-28 |
| RS232 Defaults..... | 2-28 |
| NCR Modifiers | 2-28 |
| NCR ACK/NAK | 2-28 |
| Block Check Character | 2-29 |
| NCR Prefix..... | 2-29 |
| NCR Suffix | 2-29 |
| NCR Prefix/Suffix..... | 2-29 |
| NCR NOF (Not-on-File) Error | 2-30 |
| Scanner to Bioptic Communication | 2-30 |
| Scanner-Biopic Packet Mode | 2-30 |
| ACK/NAK | 2-30 |
| Communication Timeout..... | 2-31 |

Chapter 3 - Cordless System Operation (Voyager 1202g)

| | |
|--|-----|
| How the Charge and Communications Base Works | 3-1 |
| Linking the Scanner to a Base..... | 3-1 |
| Communication Between the Cordless System and the Host..... | 3-1 |
| RF (Radio Frequency) Module Operation | 3-2 |
| System Conditions..... | 3-2 |
| Linking Process | 3-2 |
| Scanner Is Out of Range | 3-2 |
| Scanner Is Moved Back Into Range | 3-2 |
| Out of Range and Back into Range with Batch Mode On..... | 3-2 |
| Page Button..... | 3-3 |
| About the Battery | 3-3 |

| | |
|--|------|
| Voyager 1202g Battery Removal..... | 3-3 |
| Charging Information | 3-3 |
| Battery Recommendations | 3-4 |
| Proper Disposal of the Battery | 3-4 |
| Flash Updates | 3-4 |
| Beeper and LED Sequences and Meaning | 3-4 |
| Scanner LED Sequences and Meaning..... | 3-5 |
| Base LED Sequences and Meaning..... | 3-5 |
| Base Power Communication Indicator..... | 3-5 |
| Reset Scanner..... | 3-6 |
| Scanning While in Base Cradle | 3-6 |
| Base Charging Modes | 3-6 |
| Paging | 3-7 |
| Paging Mode..... | 3-7 |
| Paging Pitch..... | 3-7 |
| Scanner Address | 3-7 |
| Base Address | 3-8 |
| Scanner Modes | 3-8 |
| Charge Only Mode..... | 3-8 |
| Linked Modes | 3-8 |
| Unlinking the Scanner | 3-9 |
| Override Locked Scanner..... | 3-9 |
| Out-of-Range Alarm | 3-9 |
| Alarm Sound Type..... | 3-9 |
| Alarm Duration..... | 3-10 |
| Scanner Power Time-Out Timer..... | 3-10 |
| RangeGate | 3-10 |
| Batch Mode | 3-11 |
| Batch Mode Beep | 3-11 |
| Batch Mode Quantity | 3-12 |
| Delete Last Code | 3-13 |
| Record Counter | 3-13 |
| Total Records | 3-14 |
| Batch Mode Output Order..... | 3-14 |
| Clear All Codes After Transmission..... | 3-14 |
| Clear All Codes..... | 3-15 |
| Transmit Records Automatically | 3-15 |
| Transmit Records to Host..... | 3-15 |
| Batch Mode Transmit Delay | 3-15 |
| Scanner Name..... | 3-16 |
| Using the Scanner with Bluetooth Devices..... | 3-17 |
| Bluetooth Serial Port - PCs/Laptops | 3-17 |
| Changing the Scanner's Bluetooth PIN Code..... | 3-17 |
| Minimizing Bluetooth/ISM Band Network Activity | 3-17 |
| Auto Reconnect Mode | 3-17 |
| Maximum Link Attempts | 3-18 |
| Bluetooth/ISM Network Activity Examples..... | 3-18 |
| Reset Scanner and Base..... | 3-19 |

Chapter 4 - Cordless System Operation (Voyager 1202g-BF)

| | |
|--|------|
| How the Charge and Communications Base Works | 4-1 |
| Linking the Scanner to a Base..... | 4-1 |
| Communication Between the Cordless System and the Host..... | 4-1 |
| RF (Radio Frequency) Module Operation | 4-2 |
| System Conditions..... | 4-2 |
| Linking Process | 4-2 |
| Scanner Is Out of Range | 4-2 |
| Scanner Is Moved Back Into Range | 4-2 |
| Page Button..... | 4-3 |
| About the Instant Charge Pack..... | 4-3 |
| Charging Information | 4-3 |
| Flash Updates | 4-3 |
| Beeper and LED Sequences and Meaning | 4-3 |
| Scanner LED Sequences and Meaning..... | 4-3 |
| Base LED Sequences and Meaning..... | 4-4 |
| Base Power Communication Indicator..... | 4-4 |
| Reset Scanner..... | 4-4 |
| Scanning While in Base Cradle | 4-5 |
| Paging | 4-5 |
| Paging Mode..... | 4-5 |
| Paging Pitch..... | 4-5 |
| Scanner Address | 4-6 |
| Base Address | 4-6 |
| Scanner Modes | 4-6 |
| Charge Only Mode..... | 4-6 |
| Linked Modes | 4-6 |
| Unlinking the Scanner | 4-7 |
| Override Locked Scanner..... | 4-7 |
| Out-of-Range Alarm | 4-7 |
| Alarm Sound Type..... | 4-7 |
| Alarm Duration..... | 4-8 |
| Using the Scanner with Bluetooth Devices..... | 4-8 |
| Minimizing Bluetooth/ISM Band Network Activity | 4-8 |
| Auto Reconnect Mode | 4-8 |
| Maximum Link Attempts | 4-9 |
| Bluetooth/ISM Network Activity Examples..... | 4-9 |
| Reset Scanner and Base..... | 4-10 |

Chapter 5 - Input/Output Settings

| | |
|----------------------------|-----|
| Power Up Beeper | 5-1 |
| Beep on BEL Character..... | 5-1 |

| | |
|--|------|
| Good Read and Error Indicators..... | 5-1 |
| Beeper – Good Read..... | 5-1 |
| Beeper Volume – Good Read..... | 5-2 |
| Beeper Pitch – Good Read..... | 5-2 |
| Beeper - Transmit Order..... | 5-2 |
| Beeper Pitch – Error..... | 5-3 |
| Beeper Duration – Good Read..... | 5-3 |
| Number of Beeps – Good Read..... | 5-3 |
| Number of Beeps – Error..... | 5-3 |
| LED Indicators..... | 5-4 |
| LED Settings..... | 5-4 |
| LED Brightness..... | 5-5 |
| In-Stand and Out-Of-Stand Settings..... | 5-6 |
| In-Stand and Out-of-Stand Defaults..... | 5-6 |
| Presentation Modes..... | 5-6 |
| Manual Activation Mode..... | 5-7 |
| End Manual Activation After Good Read..... | 5-7 |
| Manual Activation Laser Timeout - Button Settings..... | 5-8 |
| CodeGate..... | 5-9 |
| Button Function..... | 5-9 |
| Object Detection Mode..... | 5-9 |
| End Object Detection After Good Read..... | 5-10 |
| Object Detection Laser Timeout..... | 5-11 |
| Object Detection Distance..... | 5-11 |
| Character Activation Mode..... | 5-11 |
| Activation Character..... | 5-12 |
| End Character Activation After Good Read..... | 5-12 |
| Character Activation Laser Timeout..... | 5-12 |
| Character Deactivation Mode..... | 5-12 |
| Deactivation Character..... | 5-13 |
| Reread Delay..... | 5-13 |
| User-Specified Reread Delay..... | 5-13 |
| Output Sequence Overview..... | 5-14 |
| Output Sequence Editor..... | 5-14 |
| To Add an Output Sequence..... | 5-14 |
| Other Programming Selections..... | 5-14 |
| Output Sequence Editor..... | 5-16 |
| Sequence Timeout..... | 5-16 |
| Sequence Match Beeper..... | 5-16 |
| Partial Sequence..... | 5-16 |
| Require Output Sequence..... | 5-17 |
| No Read..... | 5-17 |

Chapter 6 - Data Editing

| | |
|---|-----|
| Prefix/Suffix Overview..... | 6-1 |
| To Add a Prefix or Suffix:..... | 6-1 |
| To Clear One or All Prefixes or Suffixes..... | 6-2 |
| To Add a Carriage Return Suffix to All Symbologies..... | 6-2 |

| | |
|--|-----|
| Prefix Selections | 6-2 |
| Suffix Selections | 6-2 |
| Transmit Alternate Extended ASCII Characters | 6-3 |
| Function Code Transmit | 6-4 |
| Communication Check Character | 6-4 |
| Intercharacter, Interfunction, and Intermessage Delays | 6-5 |
| Intercharacter Delay | 6-5 |
| User Specified Intercharacter Delay | 6-5 |
| Interfunction Delay | 6-6 |
| Intermessage Delay | 6-6 |

Chapter 7 - Data Formatting

| | |
|--|------|
| Data Format Editor Introduction | 7-1 |
| To Add a Data Format | 7-1 |
| Other Programming Selections | 7-2 |
| Terminal ID Table | 7-3 |
| Data Format Editor Commands | 7-3 |
| Move Commands | 7-5 |
| Search Commands | 7-6 |
| Miscellaneous Commands | 7-8 |
| Data Formatter | 7-10 |
| Data Format Non-Match Error Tone | 7-11 |
| Primary/Alternate Data Formats | 7-11 |
| Single Scan Data Format Change | 7-12 |

Chapter 8 - Symbologies

| | |
|---|------|
| All Symbologies | 8-1 |
| Message Length Description | 8-1 |
| Codabar | 8-2 |
| Codabar Concatenation | 8-3 |
| Code 39 | 8-5 |
| Code 32 Pharmaceutical (PARAF) | 8-6 |
| Full ASCII | 8-7 |
| Interleaved 2 of 5 | 8-8 |
| NEC 2 of 5 | 8-9 |
| Code 93 | 8-11 |
| Straight 2 of 5 Industrial (three-bar start/stop) | 8-12 |
| Straight 2 of 5 IATA (two-bar start/stop) | 8-13 |
| Matrix 2 of 5 | 8-14 |
| Code 11 | 8-15 |
| Code 128 | 8-17 |
| ISBT 128 Concatenation | 8-18 |
| GS1-128 | 8-23 |
| Telepen | 8-24 |
| UPC-A | 8-25 |
| UPC-A/EAN-13 with Extended Coupon Code | 8-28 |
| UPC-A Number System 5 Addenda Required | 8-29 |

| | |
|------------------------------------|------|
| UPC-E0 | 8-30 |
| EAN/JAN-13 | 8-33 |
| Convert UPC-A to EAN-13 | 8-33 |
| ISBN Translate | 8-39 |
| ISSN Translate | 8-40 |
| EAN/JAN-8 | 8-41 |
| MSI | 8-43 |
| Plessey Code | 8-45 |
| GS1 DataBar Omnidirectional | 8-46 |
| GS1 DataBar Limited..... | 8-47 |
| GS1 DataBar Expanded | 8-48 |
| Trioptic Code | 8-48 |
| GS1 Emulation | 8-49 |
| Postal Codes | 8-49 |
| China Post (Hong Kong 2 of 5)..... | 8-50 |

Chapter 9 - Utilities

| | |
|---|-----|
| To Add a Test Code I.D. Prefix to All Symbolologies | 9-1 |
| Show Software Revision..... | 9-1 |
| Show Data Format..... | 9-1 |
| Test Menu..... | 9-1 |
| EZConfig-Scanning Introduction..... | 9-2 |
| Installing EZConfig-Scanning from the Web..... | 9-2 |
| Resetting the Factory Defaults | 9-3 |

Chapter 10 - Serial Programming Commands

| | |
|------------------------------|------|
| Conventions..... | 10-1 |
| Menu Command Syntax | 10-1 |
| Query Commands | 10-1 |
| Responses..... | 10-2 |
| Serial Trigger Commands..... | 10-3 |
| Read Time-Out | 10-3 |
| Menu Commands | 10-4 |

Chapter 11 - Product Specifications

| | |
|---|------|
| Voyager 1200g Product Specifications..... | 11-1 |
| Voyager 1202g and Voyager 1202g-BF Product Specifications | 11-2 |
| CCB00-010BT Product Specifications..... | 11-3 |
| CCB00-010BT-01N-BF Product Specifications | 11-4 |
| CCB00-010BT/CCB00-010BT-01N-VBF Mounting | 11-5 |
| Standard Cable Pinouts..... | 11-5 |
| Keyboard Wedge | 11-5 |
| Serial Output | 11-6 |
| RS485 Output | 11-6 |
| USB | 11-6 |

Chapter 12 - Maintenance and Troubleshooting

| | |
|--|------|
| Repairs | 12-1 |
| Maintenance | 12-1 |
| Cleaning the Device..... | 12-1 |
| Inspecting Cords and Connectors | 12-1 |
| Replacing Cables in Corded Scanners..... | 12-1 |
| Replacing an Interface Cable in a Corded Scanner | 12-2 |
| Replacing Cables in Cordless Systems..... | 12-2 |
| Replacing an Interface Cable in a Base | 12-2 |
| Troubleshooting a Voyager Scanner | 12-3 |
| Troubleshooting a Cordless System..... | 12-4 |
| Troubleshooting a Base..... | 12-4 |
| Troubleshooting a Cordless Scanner | 12-4 |

Appendix A - Reference Charts

| | |
|---|-----|
| Symbology Charts | A-1 |
| Linear Symbologies | A-1 |
| Postal Symbologies | A-2 |
| ASCII Conversion Chart (Code Page 1252)..... | A-2 |
| Lower ASCII Reference Table..... | A-3 |
| ISO 2022/ISO 646 Character Replacements | A-7 |
| Keyboard Key References..... | A-9 |

Sample Symbols

Programming Chart

Customer Support

Technical Assistance

To search our knowledge base for a solution or to log in to the Technical Support portal and report a problem, go to www.hsmcontactsupport.com.

For our latest contact information, see www.honeywellaidc.com/locations.

Product Service and Repair

Honeywell International Inc. provides service for all of its products through service centers throughout the world. To find your service center, go to www.honeywellaidc.com and select **Support**. Contact your service center to obtain a Return Material Authorization number (RMA #) before you return the product.

To obtain warranty or non-warranty service, return your product to Honeywell (postage paid) with a copy of the dated purchase record.

Limited Warranty

For warranty information, go to www.honeywellaidc.com and click **Resources>Warranty**.

Send Feedback

Your feedback is crucial to the continual improvement of our documentation. To provide feedback about this manual, contact the Honeywell Technical Communications department at ACSHSMTechnicalCommunications@honeywell.com.



Getting Started

About This Manual

This User's Guide provides installation and programming instructions for the Voyager 1200g/1202g/1202g-BF linear scanner. Product specifications, dimensions, warranty, and customer support information are also included.

Honeywell bar code scanners are factory programmed for the most common terminal and communications settings. If you need to change these settings, programming is accomplished by scanning the bar codes in this guide.

An asterisk (*) next to an option indicates the default setting.

Unpacking Your Device

After you open the shipping carton containing the product, take the following steps:

- Check for damage during shipment. Report damage immediately to the carrier who delivered the carton.
- Make sure the items in the carton match your order.
- Save the shipping container for later storage or shipping.


Connecting the Device

Connecting with USB

A scanner or a base can be connected to the USB port of a computer.

Note: Charging the scanner through a USB port takes more time than direct AC adapter charging.

1. Connect the appropriate interface cable to the scanner first, then to the computer.



2. Make sure the cables are secured in the wireways in the bottom of the base and that the base sits flat on a horizontal surface.
3. The scanner beeps.
4. Verify the scanner or base operation by scanning a bar code from the [Sample Symbols](#) in the back of this manual.

The unit defaults to a USB PC Keyboard. Refer to [page 2-4](#) for other USB terminal settings.

For additional USB programming and technical information, refer to "USB Application Note," available at Technical Support Knowledge Base (www.hsm.force.com/publickb.)


Connecting with Keyboard Wedge

A scanner or base can be connected between the keyboard and PC as a "keyboard wedge," where the scanner provides data output that is similar to keyboard entries. The following is an example of a keyboard wedge connection:


1. Turn off power and disconnect the keyboard cable from the back of the terminal/computer.

2. Connect the appropriate interface cable to the scanner and to the terminal/computer.

Note: For Voyager 1202g-BF, you must use the power supply.



**Charge and
Communications Base
Keyboard Wedge
Connection:**




3. Make sure the cables are secured in the wireways in the bottom of the base and that the base sits flat on a horizontal surface.
4. Turn the terminal/computer power back on. The scanner beeps.
5. Verify the scanner or base operation by scanning a bar code from the [Sample Symbols](#) in the back of this manual. The scanner beeps once.

The unit defaults to an IBM PC AT and compatibles keyboard wedge interface with a USA keyboard. A carriage return (CR) suffix is added to bar code data.


Connecting with RS232 Serial Port

1. Turn off power to the terminal/computer.
2. Connect the appropriate interface cable to the scanner.

Note: For the scanner or base to work properly, you must have the correct cable for your type of terminal/computer.



Charge and Communications Base RS232 Serial Port Connection:




3. Make sure the cables are secured in the wireways in the bottom of the base and that the base sits flat on a horizontal surface.
4. Plug the serial connector into the serial port on your computer. Tighten the two screws to secure the connector to the port.
5. Once the scanner or base has been fully connected, power up the computer.

The RS232 Serial Port defaults to 9600 baud, 8 data bits, no parity, and 1 stop bit.

Connecting with RS485

A scanner or base can be connected for an IBM POS terminal interface.

1. Connect the appropriate interface cable to the device, then to the computer.




2. Make sure the cables are secured in the wireways in the bottom of the base and that the base sits flat on a horizontal surface.
3. Turn the terminal/computer power back on. The scanner beeps.
4. Verify the scanner or base operation by scanning a bar code from the [Sample Symbols](#) in the back of this manual. The scanner beeps once.

For further RS485 settings, refer to [RS485](#), page 2-2.

Reading Techniques

The scanner has a view finder that projects a bright red aiming beam that corresponds to the scanner's horizontal field of view. The aiming beam should be centered horizontally over the bar code and must highlight all the vertical bars of the bar code. It will not read if the aiming beam is in any other direction.



The aiming beam is smaller when the scanner is closer to the code and larger when it is farther from the code. Symbologies with smaller bars or elements (mil size) should be read closer to the unit. Symbologies with larger bars or elements (mil size) should be read farther from the unit. To read single or multiple symbols (on a page or on an object), hold the scanner at an appropriate distance from the target, press the button, and center the aiming beam on the symbol. If the code being scanned is highly reflective (e.g., laminated), it may be necessary to tilt the code up 15° to 18° to prevent unwanted reflection.

Menu Bar Code Security Settings

Honeywell scanners are programmed by scanning menu bar codes or by sending serial commands to the scanner. If you want to restrict the ability to scan menu codes, you can use the Menu Bar Code Security settings. Please contact the nearest technical support office (see [Customer Support](#) on page -iii) for further information.

Setting Custom Defaults

You have the ability to create a set of menu commands as your own, custom defaults. To do so, scan the **Set Custom Defaults** bar code below before each menu command or sequence you want saved. If your command requires scanning numeric codes from the back cover, then a **Save** code, that entire sequence will be saved to your custom defaults. Scan the **Set Custom Defaults** code again before the next command you want saved to your custom defaults.



*Note: If using a cordless system, scanning the **Save Defaults** bar code also causes both the scanner and the base to perform a reset and become unlinked. The scanner must be placed in its base to re-establish the link before any setup codes are entered. See [Cordless System Operation \(Voyager 1202g\)](#) beginning on page 3-1 or [Cordless System Operation \(Voyager 1202g-BF\)](#) beginning on page 4-1 for additional information.*

You may have a series of custom settings and want to correct a single setting. To do so, just scan the new setting to overwrite the old one. For example, if you had previously saved the setting for Beeper Volume at Low to your custom defaults, and decide you want the beeper volume set to High, just scan the **Set Custom Defaults** bar code, then scan the Beeper Volume High menu code. The rest of the custom defaults will remain, but the beeper volume setting will be updated.

Resetting the Custom Defaults

If you want the custom default settings restored to your scanner, scan the **Activate Custom Defaults** bar code below. This resets the scanner to the custom default settings. If there are no custom defaults, it will reset the scanner to the factory default settings. Any settings that have not been specified through the custom defaults will be defaulted to the factory default settings.



DEFAULT.

Activate Custom Defaults

Note: If using a cordless system, scanning this bar code also causes both the scanner and the base to perform a reset and become unlinked. The scanner must be placed in its base to re-establish the link before any setup codes are entered. See [Cordless System Operation \(Voyager 1202g\)](#) beginning on page 3-1 or [Cordless System Operation \(Voyager 1202g-BF\)](#) beginning on page 4-1 for additional information.



Programming the Interface

Introduction

This chapter describes how to program your system for the desired interface.

Programming the Interface - Plug and Play

Plug and Play bar codes provide instant scanner set up for commonly used interfaces.

Note: After you scan one of the codes, power cycle the host terminal to have the interface in effect.

Keyboard Wedge

If you want your system programmed for an IBM PC AT and compatibles keyboard wedge interface with a USA keyboard, scan the bar code below.

Note: The following bar code also programs a carriage return (CR) suffix.



PAP_AT.

IBM PC AT and Compatibles with CR Suffix

IBM PS2 Keyboard

The following bar code programs your scanner for an IBM PS2 keyboard wedge interface with a USA keyboard.

Note: The following bar code also programs a carriage return (CR) suffix.



PAPPS2.

IBM PS2 with CR Suffix

RS232 Serial Port

The **RS232 Interface** bar code is used when connecting to the serial port of a PC or terminal. The following **RS232 Interface** bar code also programs a carriage return (CR) and a line feed (LF) suffix, baud rate, and data format as indicated below.

Note: To reset the scanner factory default baud rate of 9,600 bps, see "[Resetting the Factory Defaults](#)" on page 9-3.

| Option | Setting |
|-------------|--|
| Baud Rate | 115,200 bps |
| Data Format | 8 data bits, no parity bit, 1 stop bit |



PAP232.

RS232 Interface

RS485

Scan one of the following “Plug and Play” codes to program the scanner for an IBM POS terminal interface.

Note: After scanning one of these codes, you must power cycle the cash register.



PAPP5B.
IBM Port 5B Interface



PAP9B1.
IBM Port 9B
HHBCR-1 Interface



PAPP17.
IBM Port 17 Interface



PAP9B2.
IBM Port 9B
HHBCR-2 Interface

Each bar code above also programs the following suffixes for each symbology:

| Symbology | Suffix | Symbology | Suffix |
|-----------|--------|--------------------|----------|
| EAN 8 | 0C | Code 39 | 00 0A 0B |
| EAN 13 | 16 | Interleaved 2 of 5 | 00 0D 0B |
| UPC A | 0D | Code 128 * | 00 0A 0B |
| UPC E | 0A | Code 128 ** | 00 18 0B |

* Suffixes programmed for Code 128 with IBM 4683 Port 5B, IBM 4683 Port 9B HHBCR-1, and IBM 4683 Port 17 Interfaces

**Suffixes programmed for Code 128 with IBM 4683 Port 9 HHBCR-2 Interface

OPOS Mode

The following bar code configures your scanner for OPOS (OLE for Retail Point of Sale) by modifying the following OPOS-related settings:

| Option | Setting |
|----------------------------------|---------------------------------|
| Interface | RS232 |
| Baud Rate | 38400 |
| RS232 Handshaking | Flow Control, No Timeout |
| | XON/XOFF Off |
| | ACK/NAK Off |
| Data Bits, Stop Bits, and Parity | 8 Data, 1 Stop, Parity None |
| Prefix/Suffix | Clear All Prefixes and Suffixes |
| | Add Code ID and AIM ID Prefix |
| | Add CR Suffix |
| Intercharacter Delay | Off |

| Option | Setting |
|-------------|---|
| Symbologies | Enable UPC-A with check digit and number system |
| | Enable UPC-E0 with check digit |
| | Enable EAN/JAN-8 with check digit |
| | Enable EAN/JAN-13 with check digit |
| | Enable Code 128 |
| | Enable Code 39 |
| | Enable OPOS with automatic disable off |



USB IBM SurePos

Scan one of the following “Plug and Play” codes to program the scanner for an IBM SurePos (USB handheld scanner) or IBM SurePos (USB tabletop scanner) interface.

Note: After scanning one of these codes, you must power cycle the cash register.



Each bar code above also programs the following suffixes for each symbology:

| Symbology | Suffix | Symbology | Suffix |
|-----------|--------|--------------------|----------|
| EAN 8 | 0C | Code 39 | 00 0A 0B |
| EAN 13 | 16 | Interleaved 2 of 5 | 00 0D 0B |
| UPC A | 0D | Code 128 | 00 18 0B |
| UPC E | 0A | Code 39 | 00 0A 0B |

IBM Secondary Interface

On some older IBM cash registers, it may be necessary to disable the secondary or management interface. In particular, it has been found necessary on IBM registers using the 4690 V2R4 operating system. The following bar codes are used for this purpose. *Default = Enable Secondary Interface.*





USB PC or Macintosh Keyboard

Scan one of the following codes to program the scanner for USB PC Keyboard or USB Macintosh Keyboard. Scanning these codes also adds a CR and LF for Voyager 1200g and adds CR for Voyager 1202g and 1202g-BF.



USB HID

Scan the following code to program the scanner for USB HID bar code scanner.



HID Fallback Mode

If you attempt to set a USB interface for your scanner, but the setup fails on the host system, you can program the scanner to fall back to a USB Keyboard (PC) interface after a set length of time. For example, if the scanner is configured for Serial Emulation Mode, but the host system does not have the correct driver, the scanner would fail. If you set the **HID Fallback Mode** for a set length of time, for example, 5 minutes, the scanner would change to a USB Keyboard (PC) interface after 5 minutes of trying to configure as serial emulation.

A unique beep sequence (Voyager 1200g) or the blinking LEDs on the base (Voyager 1202g/1202g-BF) indicate that this mode has been entered. While in HID Fallback Mode, the scanner will not scan normal bar codes and sounds a unique beep sequence (Voyager 1200g) or the base LEDs will blink (Voyager 1202g/1202g-BF) to indicate the scanner is in Fallback Mode. Menu codes can still be scanned while in HID Fallback Mode, allowing you to change the scanner's programming.

Scan the bar code below, then set the length for the HID Fallback (from 0-60 minutes) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 5 minutes.*



USB Serial Commands

USB Serial

Scan one of the following codes to program the scanner to emulate a regular RS232-based COM Port. If you are using a Microsoft® Windows® PC, you will need to download the USB serial driver from the Honeywell website (www.honeywellaidc.com). The driver will use the next available COM Port number. Apple® Macintosh computers recognize the scanner as a USB CDC class device and automatically use a class driver.

Scanning either of these codes also adds a CR and LF.



PAPER130.

**USB Serial Emulation for
Windows XP, Windows Server
2003, and later**



PAPER130;REMIFC0.

USB Serial for Windows 2000

Note: No extra configuration (e.g., baud rate) is necessary.

CTS/RTS Emulation



USBCTS1.

CTS/RTS Emulation On



USBCTS0.

*** CTS/RTS Emulation Off**

ACK/NAK Mode



USBACK1.
ACK/NAK Mode On



USBACK0.
* ACK/NAK Mode Off

Communication Timeout

This allows you to set the length (in milliseconds) for a timeout for the host ACK/NAK response. Scan the bar code below, then set the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**.
Default = 2000 ms.



232DLK.
Communication Timeout

Timeout Retries

This setting limits the number of Communication Timeout retries. If the Timeout Retries is set to 0, the transmission is terminated after the initial Communication Timeout. Scan the bar code below, then set the number of retries (from 0-255) by scanning digits from the [Programming Chart](#), then scanning **Save**. (5 is the recommended setting.) *Default = 0.*



HSTRTY.
Timeout Retries

Communication Timeout Beeper

This selection programs the scanner to issue an error beep when a communication timeout has occurred. The error beep sound is programmed using [Number of Beeps – Error](#) (page 5-3). *Default = On.*



HSTTOA0.
Off



HSTTOA1.
* On

NAK Retries

This selection limits the number of NAK retries that can occur in ACK/NAK mode. Scan the bar code below, then set the number of retries (from 0-255) by scanning digits from the [Programming Chart](#), then scanning **Save**. (5 is the recommended setting.) *Default = 0, or disabled.*



HSTRTN.
NAK Retries

Support BEL/CAN in ACK/NAK

This protocol responds to <BEL> and <CAN> commands when in ACK/NAK mode. The scanner sounds an error tone when a <BEL> command is sent from the host. <CAN> terminates the transmission. *Default = BEL/CAN Off.*



BELCAN1.
BEL/CAN On



BELCAND.
* BEL/CAN Off

Verifone® Ruby Terminal Default Settings

Scan the following Plug and Play code to program the scanner for a Verifone Ruby terminal. This bar code sets the baud rate to 1200 bps and the data format to 8 data bits, Mark parity, 1 stop bit and RTS/CTS no timeout. It also adds a line feed (LF) suffix and programs the following prefixes for each symbology:

| Symbology | Prefix |
|-----------|--------|
| UPC-A | A |
| UPC-E | A |
| EAN-8 | FF |
| EAN-13 | F |



PAPERBY.
Verifone Ruby Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Gilbarco® Terminal Default Settings

Scan the following Plug and Play code to program the scanner for a Gilbarco terminal. This bar code sets the baud rate to 2400 bps and the data format to 7 data bits, even parity, 2 stop bits. It also adds a carriage return (CR) suffix and programs the following prefixes for each symbology:

| Symbology | Prefix |
|-----------|--------|
| UPC-A | A |
| UPC-E | E0 |
| EAN-8 | FF |
| EAN-13 | F |



PAPGLB.
Gilbarco Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Honeywell Bioptic Aux Port Configuration

Scan the following Plug and Play code to program the scanner for a Honeywell bioptic scanner auxiliary port configuration. This bar code sets the baud rate to 38400 bps and the data format to 8 data bits, no parity, 1 stop bit. Character RTS/CTS with timeout and 232 ACK/NAK are also enabled.



PAPBIO.
Honeywell Bioptic Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Datalogic™ Magellan® Bioptic Aux Port Configuration

Scan the following Plug and Play code to program the scanner for a Datalogic Magellan bioptic scanner auxiliary port configuration. This bar code sets the baud rate to 9600 bps and the data format to 8 data bits, no parity, 1 stop bit.



PAPMAG.
Datalogic Magellan Bioptic Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

NCR Bioptic Aux Port Configuration

Scan the following Plug and Play code to program the scanner for an NCR bioptic scanner auxiliary port configuration. This bar code sets the baud rate to 9600 bps and the data format to 7 data bits, Even parity, 1 stop bit and Message RTS/CTS with time-out. The following prefixes are programmed for each symbology:

| Symbology | Prefix | Symbology | Prefix |
|-----------|--------|--------------------------------------|--------|
| UPC-A | A | Interleaved 2 of 5 | b |
| UPC-E | E0 | Code 128 | f |
| EAN-8 | FF | GS1 DataBar Omnidirectional | r |
| EAN-13 | F | GS1 DataBar Expanded | r |
| Code 39 | a | Codabar | N |
| | | Code 32 Pharmaceutical (PARAF) | a |



PAPNCR.
NCR Bioptic Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Wincor Nixdorf Terminal Default Settings

Scan the following Plug and Play code to program the scanner for a Wincor Nixdorf terminal. This bar code sets the baud rate to 9600 bps and the data format to 8 data bits, no parity, 1 stop bit.



PAPWNX.
Wincor Nixdorf Terminal Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Wincor Nixdorf Beetle™ Terminal Default Settings

Scan the following Plug and Play code to program the scanner for a Wincor Nixdorf Beetle terminal. The following prefixes are programmed for each symbology:

| Symbology | Prefix | Symbology | Prefix |
|-------------|--------|----------------------|--------|
| Aztec Code | V | Interleaved 2 of 5 | I |
| Codabar | N | MaxiCode | T |
| Code 93 | L | MicroPDF417 | S |
| Code 128 | K | PDF417 | Q |
| Data Matrix | R | QR Code | U |
| EAN-8 | B | Straight 2 of 5 IATA | H |
| EAN-13 | A | UPC-A | A0 |
| GS1 DataBar | E | UPC-E | C |
| GS1-128 | P | All other bar codes | M |



PAPBTL

Wincor Nixdorf Beetle Settings

Note: If you are having unexpected results with this programming code, scan the [Resetting the Custom Defaults](#) bar code on page 1-7 first, then scan the programming code above.

Wincor Nixdorf RS232 Mode A

Scan the following Plug and Play code to program the scanner for a Wincor Nixdorf RS232 Mode A terminal. The following prefixes are programmed for each symbology:

| Symbology | Prefix | Symbology | Prefix |
|---------------------|--------|----------------------|--------|
| Code 128 | K | EAN-13 | A |
| Code 93 | L | GS1-128 | K |
| Codabar | N | Interleaved 2 of 5 | I |
| UPC-A | A0 | Plessey | O |
| UPC-E | C | Straight 2 of 5 IATA | H |
| EAN-8 | B | GS1 DataBar | E |
| All other bar codes | M | | |



PAPWMA

Wincor Nixdorf RS232 Mode A Settings

Keyboard Country Layout

If your interface is USB Keyboard or Keyboard Wedge, your keyboard layout default is a US keyboard. To change this layout, scan the appropriate country code below to program the keyboard for your country or language.

By default, national character replacements are used for the following characters: # \$ @ [\] ^ ' { } ~ Refer to the [ISO 2022/ISO 646 Character Replacements](#) on page A-7 chart to view the character replacements for each country.

Keyboard Countries



KBDCTY0.
*** United States**



KBDCTY35.
Albania



KBDCTY91.
Arabic



KBDCTY81.
Azeri (Cyrillic)



KBDCTY80.
Azeri (Latin)



KBDCTY82.
Belarus



KBDCTY1.
Belgium



KBDCTY33.
Bosnia



KBDCTY16.
Brazil



KBDCTY59.
Brazil (MS)



KBDCTY52.
Bulgaria (Cyrillic)

Keyboard Countries (Continued)



KBDCTY54.
Canada (French legacy)



KBDCTY55.
Canada (Multilingual)



KBDCTY32.
Croatia



KBDCTY40.
Czech (Programmers)



KBDCTY38.
Czech (QWERTZ)



KBDCTY53.
Bulgaria (Latin)



KBDCTY18.
Canada (French)



KBDCTY92.
China



KBDCTY15.
Czech



KBDCTY39.
Czech (QWERTY)



KBDCTY8.
Denmark

Keyboard Countries (Continued)



KBDCTY11.
Dutch (Netherlands)



KBDCTY83.
Faroese



KBDCTY3.
France



KBDCTY4.
Germany



KBDCTY64.
Greek (220 Latin)



KBDCTY65.
Greek (319 Latin)



KBDCTY41.
Estonia



KBDCTY2.
Finland



KBDCTY84.
Gaelic



KBDCTY17.
Greek



KBDCTY61.
Greek (220)

Keyboard Countries (Continued)



KBDCTY63.
Greek (Latin)



KBDCTY60.
Greek (Polytonic)



KBDCTY50.
Hungarian (101 key)



KBDCTY75.
Iceland



KBDCTY56.
Italian (142)



KBDCTY62.
Greek (319)



KBDCTY66.
Greek (MS)



KBDCTY12.
Hebrew



KBDCTY19.
Hungary



KBDCTY73.
Irish



KBDCTY5.
Italy

Keyboard Countries (Continued)



KBDCTY28.
Japan ASCII



KBDCTY78.
Kazakh



KBDCTY14.
Latin America



KBDCTY43.
Latvia (QWERTY)



KBDCTY45.
Lithuania (IBM)



KBDCTY74.
Malta



KBDCTY93.
Korea



KBDCTY79.
Kyrgyz (Cyrillic)



KBDCTY42.
Latvia



KBDCTY44.
Lithuania



KBDCTY34.
Macedonia

Keyboard Countries (Continued)



KBDCTY9.
Norway



KBDCTY57.
Polish (214)



KBDCTY13.
Portugal



KBDCTY26.
Russia



KBDCTY68.
Russian (Typewriter)



KBDCTY86.
Mongolian (Cyrillic)



KBDCTY20.
Poland



KBDCTY58.
Polish (Programmers)



KBDCTY25.
Romania



KBDCTY67.
Russian (MS)



KBDCTY21.
SCS

Keyboard Countries (Continued)



KBDCTY37.
Serbia (Cyrillic)



KBDCTY22.
Slovakia



KBDCTY48.
Slovakia (QWERTZ)



KBDCTY10.
Spain



KBDCTY23.
Sweden



KBDCTY6.
Switzerland (German)



KBDCTY36.
Serbia (Latin)



KBDCTY49.
Slovakia (QWERTY)



KBDCTY31.
Slovenia



KBDCTY51.
Spanish variation



KBDCTY29.
Switzerland (French)

Keyboard Countries (Continued)



KBDCTY94.
Thailand



KBDCTY24.
Turkey Q



KBDCTY7.
United Kingdom



KBDCTY88.
United States (Dvorak left)



KBDCTY30.
United States (International)



KBDCTY85.
Tatar



KBDCTY27.
Turkey F



KBDCTY76.
Ukrainian



KBDCTY87.
United States (Dvorak)



KBDCTY89.
United States (Dvorak right)



KBDCTY77.
Uzbek (Cyrillic)

Keyboard Countries (Continued)



KBDCTY95.
Vietnam

Keyboard Wedge Modifiers

ALT Mode

If your bar code contains special characters from the extended ASCII chart, for example, an e with an accent grave (è), you will use ALT Mode. (See "Extended ASCII Characters" on page A-4.)

Note: Scan the ALT mode bar code after scanning the appropriate Keyboard Country code.

If your keystrokes require the ALT key and 4 characters, scan the **4 Characters** bar code. The data is then output with the special character(s). *Default = Off.*



KBDALTO.
* Off



KBDALT7.
4 Characters

Keyboard Style

This programs keyboard styles, such as Caps Lock and Shift Lock. *Default = Regular.*

Regular is used when you normally have the Caps Lock key off.



KBDSTY0.
* Regular

Caps Lock is used when you normally have the Caps Lock key on.



KBDSTY1.
Caps Lock

Shift Lock is used when you normally have the Shift Lock key on (not common to U.S. keyboards).



KBDSTY2.
Shift Lock

Autocaps via NumLock bar code should be scanned in countries (e.g., Germany, France) where the Caps Lock key cannot be used to toggle Caps Lock. The NumLock option works similarly to the regular Autocaps, but uses the NumLock key to retrieve the current state of the Caps Lock.



Emulate External Keyboard should be scanned if you do not have an external keyboard (IBM AT or equivalent).



Note: After scanning the Emulate External Keyboard bar code, you must power cycle your computer.

Keyboard Conversion

Alphabetic keyboard characters can be forced to be all upper case or all lowercase. So if you have the following bar code: “abc569GK,” you can make the output “ABC569GK” by scanning **Convert All Characters to Upper Case**, or to “abc569gk” by scanning **Convert All Characters to Lower Case**.

Default = Keyboard Conversion Off.



Keyboard Modifiers

This modifies special keyboard features, such as CTRL+ ASCII codes and Turbo Mode.

Control + X (Control + ASCII) Mode On: The scanner sends key combinations for ASCII control characters for values 00-1F. Windows is the preferred mode. All keyboard country codes are supported. DOS mode is a legacy mode, and it does not support all keyboard country codes. New users should use the Windows mode. Refer to [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for CTRL+ X Values.

Windows Mode Prefix/Suffix Off: The scanner sends key combinations for ASCII control characters for values 00-1F, but it does not translate prefix or suffix information.

Default = Control + X Mode Off.



KBDCAS2.

**Windows Mode Control + X
Mode On**



KBDCAS1.

DOS Mode Control + X Mode On



KBDCAS0.

*** Control + X Mode Off**



KBDCAS3.

Windows Mode Prefix/Suffix Off

Numeric Keypad Mode: Sends numeric characters as if entered from a numeric keypad. *Default = Off.*



KBDNPS1.

Numeric Keypad Mode On



KBDNPS0.

*** Numeric Keypad Mode Off**

Inter-Scan Code Delay

When your keyboard detects that any key is being pressed, released, or held down, the keyboard sends a packet of information known as a “scan code” to your computer. This selection allows you to adjust the delay between scan codes. Set the length (in milliseconds) for a delay by scanning the bar code below, then setting the delay (from 1-30) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 0 (800 μs).*



KBDDLY.

Inter-Scan Code Delay

<F0> Break Character

When your keyboard detects that any key is being pressed, released, or held down, the keyboard sends a packet of information known as a “scan code” to your computer. There are two different types of scan codes: “make codes” and “break codes.” A make code is sent when a key is pressed or held down. A break code is sent when a key is released. The following selections allow you to suppress or transmit the F0 character sequence of the break code. *Default = Transmit.*



Keyboard Wedge Defaults

If you want the custom keyboard wedge default settings restored to your scanner, scan the **Keyboard Wedge Defaults** bar code below. This resets the scanner to the custom default settings (see [Setting Custom Defaults](#) on page 1-6). If there are no custom defaults, it will reset the scanner to the factory default settings. Any settings that have not been specified through the custom defaults will be defaulted to the factory default settings.



RS232 Modifiers

RS232 Baud Rate

Baud Rate sends the data from the scanner to the terminal at the specified rate. The host terminal must be set for the same baud rate as the scanner. *Default = 9600.*



232BAD0.

300



232BAD1.

600



232BAD2.

1200



232BAD3.

2400



232BAD4.

4800



232BAD5.

* 9600



232BAD6.

19200



232BAD7.

38400



232BAD8.

57,600



232BAD9.

115,200

RS232 Word Length: Data Bits, Stop Bits, and Parity

Data Bits sets the word length at 7 or 8 bits of data per character. If an application requires only ASCII Hex characters 0 through 7F decimal (text, digits, and punctuation), select 7 data bits. For applications that require use of the full ASCII set, select 8 data bits per character. *Default = 8.*

Stop Bits sets the stop bits at 1 or 2. *Default = 1.*

Parity provides a means of checking character bit patterns for validity.
Default = None.



232WRD3.

7 Data, 1 Stop, Parity Even



232WRD0.

7 Data, 1 Stop, Parity None



232WRD6.

7 Data, 1 Stop, Parity Odd



232WRD4.

7 Data, 2 Stop, Parity Even



232WRD1.

7 Data, 2 Stop Parity None



232WRD7.

7 Data, 2 Stop, Parity Odd



232WRD5.

8 Data, 1 Stop, Parity Even



232WRD2.

*** 8 Data, 1 Stop, Parity None**



232WRD8.

8 Data, 1 Stop, Parity Odd



232WRD9.

7 Data, 1 Stop, Parity Space



232WRD10.

7 Data, 2 Stop, Parity Space



232WRD11.

8 Data, 1 Stop, Parity Space



232WRD12.

7 Data, 1 Stop, Parity Mark



232WRD13.

7 Data, 2 Stop, Parity Mark



232WRD14.

8 Data, 1 Stop Parity Mark

RS232 Handshaking

RS232 Handshaking allows control of data transmission from the scanner using software commands from the host device.

RTS/CTS Off: RTS/CTS is turned off so no data flow control is used, but RTS is still active.

RTS/CTS Off, RTS Inactive: RTS/CTS is turned off so no data flow control is used and RTS is inactive.

Flow Control, No Timeout: The scanner asserts RTS when it has data to send, and will wait indefinitely for CTS to be asserted by the host.

Character-Based Flow Control, No Timeout: The scanner asserts RTS when it has a character to send, and will wait indefinitely for CTS to be asserted by the host

Two-Direction Flow Control: The scanner asserts RTS when it is OK for the host to transmit. The host asserts CTS when it is OK for the device to transmit.

Flow Control with Timeout: The scanner asserts RTS when it has data to send and waits for a delay (see [RS232 Timeout](#) on page 2-26) for CTS to be asserted by the host. If the delay time expires and CTS is not asserted, the device transmit buffer is cleared and scanning may resume.

Character-Based Flow Control with Timeout: The scanner asserts RTS when it has a character to send and waits for a delay (see [RS232 Timeout](#) on page 2-26) for CTS to be asserted by the host. If the delay time expires and CTS is not asserted, the device transmit buffer is cleared and scanning may resume.

Default = RTS/CTS Off, RTS Inactive (Voyager 1200g)

RTS/CTS Off (Voyager 1202g/1202g-BF)



232CTS0.

* RTS/CTS Off



232CTS10.

* RTS/CTS Off, RTS Inactive



232CTS1.

Flow Control, No Timeout



232CTS2.

Two-Direction Flow Control



232CTS9.

Character-Based Flow Control
with Timeout



232CTS7.

Character-Based Flow Control,
No Timeout



232CTS3.

Flow Control with Timeout

RS232 Timeout

When using Flow Control with Timeout, you must program the length of the delay you want to wait for CTS from the host. Set the length (in milliseconds) for a timeout by scanning the bar code below, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 1000 ms (1 second).*



232DEL.

RS232 Timeout

XON/XOFF

With **XON/XOFF On**, standard ASCII control characters can be used to tell the scanner to start sending data or to stop sending data. When the host sends the XOFF character (DC3, hex 13) to the scanner, data transmission stops. To resume transmission, the host sends the XON character (DC1, hex 11). Data transmission continues where it left off when XOFF was sent. *Default = XON/XOFF Off.*



232XON1.

XON/XOFF On



232XON0.

* XON/XOFF Off

ACK/NAK

After transmitting data, the scanner waits for an ACK character (hex 06) or a NAK character (hex 15) response from the host. If ACK is received, the communications cycle is completed and the scanner looks for more bar codes. If NAK is received, the last set of bar code data is retransmitted and the scanner waits for ACK/NAK again. Turn on the ACK/NAK protocol by scanning the **ACK/NAK On** bar code below. To turn off the protocol, scan **ACK/NAK Off**. *Default = ACK/NAK Off.*



Communication Timeout

This allows you to set the length (in milliseconds) for a timeout for the host ACK/NAK response. Scan the bar code below, then set the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 2000 ms.*



Timeout Retries

This setting limits the number of Communication Timeout retries. If the Timeout Retries is set to 0, the transmission is terminated after the initial Communication Timeout. Scan the bar code below, then set the number of retries (from 0-255) by scanning digits from the [Programming Chart](#), then scanning **Save**. (5 is the recommended setting.) *Default = 0.*



Communication Timeout Beeper

This selection programs the scanner to issue an error beep when a communication timeout has occurred. The error beep sound is programmed using [Number of Beeps – Error](#) (page 5-3). *Default = On.*



NAK Retries

This selection limits the number of NAK retries that can occur in ACK/NAK mode. Scan the bar code below, then set the number of retries (from 0-255) by scanning digits from the [Programming Chart](#), then scanning **Save**. (5 is the recommended setting.) *Default = 0, or disabled.*



Support BEL/CAN in ACK/NAK

This protocol responds to <BEL> and <CAN> commands when in ACK/NAK mode. The scanner sounds an error tone when a <BEL> command is sent from the host. <CAN> terminates the transmission. *Default = BEL/CAN Off.*



RS232 Defaults

If you want the custom RS232 default settings restored to your scanner, scan the **RS232 Defaults** bar code below. This resets the scanner to the custom default settings (see [Setting Custom Defaults](#) on page 1-6). If there are no custom defaults, it will reset the scanner to the factory default settings. Any settings that have not been specified through the custom defaults will be restored to the factory default settings.



NCR Modifiers

NCR ACK/NAK

This is an NCR communication protocol for ACK/NAK processing. *Default = NCR ACK/NAK Off.*



Block Check Character

When this selection is set to **Transmit**, the NCR Block Check Character (BCC) is expected with incoming messages and transmitted with outgoing messages. *Default = Transmit.*



NCR Prefix

This selection allows you to program an NCR-specific prefix. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 to find the hex equivalent for the characters you want for the NCR prefix (typically, 02 for STX). Scan the bar code below, then set the hex number (from 0-FF) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 0.*



NCR Suffix

This selection allows you to program an NCR-specific suffix. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 to find the hex equivalent for the characters you want for the NCR suffix (typically, 03 for ETX). Scan the bar code below, then set the hex number (from 0-FF) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 0D.*



NCR Prefix/Suffix

When set to **Transmit**, both the NCR prefix and suffix are transmitted with bar codes. Usually, prefixes and suffixes are programmed using the Data Editing selections (see [Data Editing](#) beginning on page 6-1), however, the following commands override any other prefix/suffix settings. *Default = Don't Transmit.*



NCR NOF (Not-on-File) Error

A scanner receives an NOF (Not on File) command from the POS whenever it cannot cross-reference the bar code to a price parameter. When set to **On**, the error tone sounds (set via [Number of Beeps – Error](#), page 5-3) for an NOF, and disables the scanner while the cashier looks up the price manually. When set to **Off**, no sound is emitted for an NOF. *Default = Off.*



Scanner to Bioptic Communication

The following settings are used to set up communication between Honeywell scanners and bioptic scanners.

Note: The scanner's baud rate must be set to 38400 and the RS232 Timeout must be set to 3000 in order to communicate with a bioptic scanner. See "RS232 Modifiers" on page 2-23, and [RS232 Timeout](#) on page 2-26 for further information.

Scanner-Bioptic Packet Mode

Packet Mode On must be scanned to set the scanner's format so it is compatible with a bioptic scanner. *Default = Packet Mode Off.*



ACK/NAK

After transmitting data, the scanner waits for an ACK character (hex 06) or a NAK character (hex 15) response from the host. If ACK is received, the communications cycle is completed and the scanner looks for more bar codes. If NAK is received, the last set of bar code data is retransmitted and the scanner waits for ACK/NAK again. Turn on the ACK/NAK protocol by scanning the **ACK/NAK On** bar code below. To turn off the protocol, scan **ACK/NAK Off**. *Default = ACK/NAK Off.*



Communication Timeout

This allows you to set the length (in milliseconds) for a timeout for the host ACK/NAK response. Scan the bar code below, then set the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**.
Default = 2000 ms.



232DLK

Communication Timeout



Cordless System Operation (Voyager 1202g)

Note: This chapter applies only to Voyager 1202g cordless scanning systems. It does not apply to corded or Voyager 1202g-BF scanners. See [Cordless System Operation \(Voyager 1202g-BF\)](#) on page 4-1 for Voyager 1202g-BF scanners (PN: 1202G-BF).

How the Charge and Communications Base Works


A charge and communications base provides the link between the cordless scanner and the host system. The base contains an interface assembly and an RF communication module. The RF communication module performs the data exchange between the cordless scanner and the interface assembly. The control assembly coordinates the central interface activities including: transmitting/receiving commands and data to/from the host system, performing software activities (parameter menuing, visual indicator support, power-on diagnostics), and data translation required for the host system.

The base is also a scanner's battery charger. Refer to [Charging Information](#), page 3-3, for additional information.

Linking the Scanner to a Base

Turn off power before connecting a base, then power up the computer once the base is fully connected. When the base is connected and powered up, put the scanner in the base to establish a link. The red LED on the base lights to indicate power, and the green LED flashes to indicate the scanner's battery is charging.

The scanner emits a two tone beep sequence when the scanner and base radios link. That indicates the scanner is linked to the base.




To determine if your cordless system is set up correctly, scan one of the sample bar codes in the back of this manual. If the scanner provides a single good read beep and the green LED lights, the scanner has successfully linked to the base. If you receive an error chirp and the bar code is not scanned, the scanner has not linked to the base.

Communication Between the Cordless System and the Host

The cordless scanner provides immediate feedback in the form of a "good read" indication (a green LED on the scanner and an audible beep) after a bar code is scanned correctly and the base has acknowledged receiving the data. This is possible since the cordless system provides two-way communication between the scanner and the base.

When data is scanned, the data is sent to the host system via the base. The cordless scanner recognizes data acknowledgment (ACK) from the base. If it cannot be determined that the data has been properly sent to the base, the scanner issues an error indication. You must then check to see if the scanned data was received by the host system.



RF (Radio Frequency) Module Operation

The cordless system uses a two-way Bluetooth® radio utilizing adaptive frequency hopping (AFH) to transmit and receive data between the scanner and the base. Designed for point-to-point applications, the radio operates using a license free ISM band. This band sends relatively small data packets at a fast data rate over a radio signal with randomly changing frequencies. This makes the cordless system highly responsive to a wide variety of data collection applications and resistant to noisy RF environments. The Bluetooth Class 2 power level provides a communication range of 33 feet (10m) between the scanner and base, depending on the environment.

System Conditions

The components of the cordless system interact in specific ways as you associate the scanner with its base, as you move a scanner out of range, or bring a scanner back in range. The following information explains the cordless system operating conditions.

Linking Process

Once a scanner is placed into a base, the scanner's battery charge status is checked, and software automatically detects the scanner and links it to the base depending on the selected link mode.

Scanner Is Out of Range

The cordless scanner is in communication with its base, even when it is not transmitting bar code data. Whenever the scanner can't communicate with the base for a few seconds, it is out of range. If the scanner is out of range and you press the scanner button, the scanner issues an error tone indicating no communication with the base. Refer to [Out-of-Range Alarm](#), page 3-9.

Scanner Is Moved Back Into Range

The scanner relinks if the scanner or the base have been reset, or the scanner comes back into range. If the scanner relinks, you will hear a two tone beep sequence from the scanner when the relinking process is complete. Refer to [Out-of-Range Alarm](#) on page 3-9 for further information.

Out of Range and Back into Range with Batch Mode On

The scanner may store a number of symbols (approximately 14,000 U.P.C. symbols; others may vary) when it is out of range and then send them to the base when back in range (see [Batch Mode](#) on page 3-11).

You will not hear a communication error tone in this mode, but you will hear a short buzz when you press the button if the radio communication is not working. Once the radio connection is made, the scanner produces a series of beeps while the data is being transferred to the base.

Page Button

When you press the Page button on the base, the scanner associated with that base will begin beeping (3 short and 1 long beep). If you press the button on a scanner that is beeping in response, or press the Page button on the base a second time, the scanner will stop beeping. See [Base Charging Modes](#) on page 3-6 for further information about Page Button settings.


About the Battery



There is a danger of explosion if the batteries are incorrectly replaced. Replace the batteries with only the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the recycle program for batteries as directed by the governing agency for the country where the batteries are to be discarded.

Power is supplied to the cordless scanner by a rechargeable battery that is integrated in the scanner handle. Batteries are not fully charged when shipped. The battery should be charged for a minimum of 4 hours before initial use to ensure optimal performance.

Voyager 1202g Battery Removal



Charging Information

The battery is designed to charge while the scanner is positioned in the base unit. Refer to [Base LED Sequences and Meaning](#), page 3-5, for an interpretation of the Charge Status indicators. Refer to [Charge Only Mode](#) (page 3-8) if you need to charge a scanner without linking it to the base.

The model Voyager 1202g is designed for use with Honeywell battery pack model 100000495 (Li-ion 3.7Vdc, 7.4 watt hour), or model BAT-SCN01 (Li-ion 3.75Vdc, 9.0 watt hour).

Place the scanner in the base that is connected to an appropriate power supply. Use only a Listed Limited Power Source (LPS) or Class 2 type power supply with output rated 5 to 5.2Vdc, 1A.

Note: If you are powering the base through the interface cable (for example, a USB cable) and not using an external power supply plugged into the aux port, the current available for charging is reduced and the charge time is increased.

Battery Recommendations

- The battery is a lithium ion cell and can be used without a full charge, and can also be charged without fully discharging, without impacting the battery life. There is no need to perform any charge/discharge conditioning on this type of battery.
- Keep the base connected to power when the host is not in use.
- Replace a defective battery immediately since it could damage the scanner.
- Although your battery can be recharged many times, it will eventually be depleted. Replace it after the battery is unable to hold an adequate charge.
- If you are not sure if the battery or charger is working properly, send it to Honeywell International Inc. or an authorized service center for inspection. Refer to [Customer Support](#) on page -iii for additional information.



Caution:

The model CCB00-010BT base is designed for use with the Honeywell model Voyager 1202g scanner. Use of any non-Honeywell battery may result in damage not covered by the warranty.

Safety Precautions for Lithium Batteries

- Do not place batteries in fire or heat the batteries.
- Do not store batteries near fire or other high temperature locations.
- Do not store or carry batteries together with metal objects.
- Do not expose batteries to water or allow the batteries to get wet.
- Do not connect (short) the positive and negative terminals, of the batteries, to each other with any metal object.
- Do not pierce, strike or step on batteries or subject batteries to strong impacts or shocks.
- Do not disassemble or modify batteries.



Caution:

Danger of explosion if batteries are incorrectly replaced. Dispose of used batteries according to the recycle program for batteries as directed by the governing agency for the country where the batteries are to be discarded.

Proper Disposal of the Battery



When the battery has reached the end of its useful life, the battery should be disposed of by a qualified recycler or hazardous materials handler. Do not incinerate the battery or dispose of the battery with general waste materials. You may send the scanner's battery to us. (postage paid). The shipper is responsible for complying with all federal, state, and local laws and regulations related to the packing, labeling, manifesting, and shipping of spent batteries. Contact the Product Service Department ([page -iii](#)) for recycling or disposal information. Since you may find that your cost of returning the batteries significant, it may be more cost effective to locate a local recycle/disposal company.

Flash Updates

The scanner can be flashed either in the base or out of the base, however, it is recommended that you flash the scanner while it is in the base. Flash updates cannot be completed when the scanner is out of the base and the battery is low, or when the scanner is out of range.

Beeper and LED Sequences and Meaning

The scanner contains LEDs on the top that indicate linking status, decoding state, and battery condition. The base has LEDs on the front that indicate its power up, communication, and battery charge condition. The unit's audible indicators have meaning as well. The following table lists the indication and cause of the LED illumination and beeps for the scanner and base.

Scanner LED Sequences and Meaning

Note: Pressing the button on the scanner causes the LED to glow red until it communicates successfully with the base.

| LED Indication | Beeper Indication | Cause |
|-------------------------|--------------------|-------------------------------------|
| Normal Operation | | |
| Red Flash | None | Battery low |
| Green Flash | 1 beep | Successful communication or linking |
| Red, blinking | Razz or error tone | Failed communication |
| Menu Operation | | |
| Green Flash | 2 beeps | Successful menu change |
| Red, blinking | Razz or error tone | Unsuccessful menu change |

Base LED Sequences and Meaning

The base contains a red LED that indicate the status of the unit and verifies its communication with the host system. The base also has a green LED that indicates the scanner battery charge condition.

| Red LED - Host Communication | |
|--|--|
| Red LED | Communication Condition |
| Off | Power off, USB suspend |
| On continuously | Power on, system idle |
| Short blinks. Occurs while transferring data to/from the RF module or the host port. | Receiving data |
| Green LED - Scanner Battery | |
| Green LED | Charge Condition |
| Off | Battery not detected or charge suspended |
| Slow flash, 1 second on, 1 second off | Pre-charge and charging |
| On continuously | Charge complete |
| Fast flash, 300 mSec on, 300 mSec off | Charge Error |

Base Power Communication Indicator

To display the power indicator on the base, scan the **Base Power Communication Indicator On** bar code. To turn off the power indicator, scan the **Off** bar code. *Default = On.*



*:BASRED1.

* Base Power Communication
Indicator On



*:BASREDO.

Base Power Communication
Indicator Off

Reset Scanner

Scanning this bar code reboots the scanner and causes it to relink with the base.



Scanning While in Base Cradle

If you want to be able to scan bar codes while the scanner is in the base, scan the following **Scanning in Cradle On** bar code. If you want to only allow scanning when the scanner is out of the base, scan **Scanning in Cradle Off**. *Default = Scanning in Cradle On.*



*Note: When **Scanning in Cradle Off** is selected, the scanner will not scan any bar codes while it is in the base. It will only scan when removed from the base.*

Base Charging Modes

When the base has both an external power supply (plugged into the auxiliary power port) and a host interface cable, it will draw its power from the external power supply. When the base does not have an external power supply, it draws its power from the interface cable. However, the scanner battery charges more slowly from a host interface cable than if auxiliary power were available. Using the following selections, you can specify whether the scanner battery is charged from power supplied via the host interface cable.

When **Base Charge Off** is selected, the scanner battery does not charge when the scanner is in the base cradle.

When **External or Interface Cable Power** is selected, the scanner battery charges from the base's external power supply, if there is one. If there is no external power supply to the base, the scanner battery charges from the interface cable.

When **External Power Only** is selected, the scanner battery only charges from the base's external power supply. If there is no external power supply, the scanner battery does not charge.

Default = External or Interface Cable Power.





BASCHG2.
External Power Only

Paging

Paging Mode

By default, the paging button on the base pages the scanner associated with that base. If you want the paging button on your base to be disabled, scan the following **Paging Mode Off** bar code. When Paging Mode is off, the base will no longer page the scanner when the button is pressed. The red LED on the base will remain lit to indicate that Paging Mode is off. (This light will go out when the button is pressed, then back on when it's released.) *Default = Paging Mode On.*



BEPPGE1.
* Paging Mode On



BEPPGE0.
Paging Mode Off

Paging Pitch

When you press the Page button on the base, the scanner associated with that base will begin beeping (see [Page Button](#) on page 3-3). You can set the pitch of the paging beep for the scanner by scanning one of the following bar codes. *Default = Low.*



BEPPFQ1000.
* Low (1000 Hz)



BEPPFQ3250.
Medium (3250 Hz)



BEPPFQ4200.
High (4200 Hz)

Scanner Address

Scan the following bar code to determine the address of the scanner you are using.



BT_LDA.
Scanner Address

Base Address

Scan the following bar code to determine the address of the base you are using.



Scanner Modes

The Voyager is capable of working with Bluetooth devices other than the CCB00-010BT base.

Charge Only Mode

There may be times when you want to charge your scanner, but not link to the base. For example, if a scanner is linked to a Bluetooth device and you need to charge the scanner, but want to retain your existing link.

In order to program the base for Charge Only Mode, you must link a scanner to it. Once the scanner is linked to the base, scan the **Charge Only Mode** bar code. Any subsequent scanners placed in that base will charge without linking to it. The scanner used to program the base remains linked to the base. To unlink this scanner, scan [Unlink Scanner](#) on page 3-9.



Note: When in Charge Only Mode, the scanner periodically wakes up and beeps. See "Power Up Beeper" on page 5-1 to change this setting.

If you want to charge a scanner and link to the base, use **Charge and Link Mode**. If the base is programmed for Charge Only Mode, you must link a scanner to it first in order to program it for Charge and Link Mode. Scan the linking bar code on the base to link the scanner, then scan **Charge and Link Mode**. *Default = Charge and Link Mode.*



Linked Modes

Locked Link Mode and Open Link Mode are the link modes that accommodate different applications. Scan the appropriate bar codes included in the Open Link and Locked Link Mode explanations that follow to switch from one mode to another. *Default = Open Link Mode.*

Locked Link Mode - Single Scanner

If you link a scanner to a base using the Locked Link Mode, other scanners are blocked from being linked if they are inadvertently placed into the base. If you do place a different scanner into a base, it will charge the scanner, but the scanner will not be linked.



To use a different scanner, you need to unlink the original scanner by scanning the **Unlink Scanner** bar code. (See [Scanner Modes](#), page 3-8.)

Open Link Mode - Single Scanner

When newly shipped or defaulted to factory settings, a scanner is not linked to a base. A link is established when the scanner is placed into a base. When in Open Link Mode, a new link is established when a new scanner is placed in the base. Each time a scanner is placed into a base, the scanner becomes the linked to the base and the old scanner is unlinked.



Unlinking the Scanner

If a base has a scanner linked to it, that scanner must be unlinked before a new scanner can be linked. Once the previous scanner is unlinked, it will no longer communicate with the base. To unlink the scanner from a base, scan the following **Unlink Scanner** bar code.



Override Locked Scanner

If you need to replace a broken or lost scanner that is linked to a base, scan the following **Override Locked Scanner** bar code with a new scanner and place that scanner in the base. The locked link will be overridden, the broken or lost scanner's link with the base will be removed, and the new scanner will be linked.



Out-of-Range Alarm

If your scanner is out of range of the base, an alarm sounds from the scanner. The alarm stops when the scanner is moved closer to the base or when the alarm duration expires.

Note: If you are out of range when you scan a bar code, you will receive an error tone even if you do not have the alarm set. You receive the error tone since the data could not be communicated to the base or the host.

Alarm Sound Type

You may change the alarm type for the scanner by scanning the appropriate bar code below and then scanning a digit (0-1) bar code and the **Save** bar code on the [Programming Chart](#) inside the back cover of this manual. *Default = 0.*

The sounds are as follows:

| Setting | Sound |
|---------|----------------------------|
| 0 | 3 long beeps, medium pitch |
| 1 | 3 long beeps, high pitch |



Alarm Duration

To set the length of time you want the Out-of-Range alarm to sound, scan the following bar code and then set the time-out duration (from 0-3000 seconds) by scanning digits on the [Programming Chart](#) inside the back cover, then scanning **Save**. *Default = 1 sec.*



Scanner Power Time-Out Timer

Note: Scanner Power Time-out Timer only applies to cordless systems. It does not apply to corded scanners.

When there is no activity within a specified time period, the scanner enters low power mode. Scan the appropriate scanner power time-out bar code to change the time-out duration (in seconds).

If the scanner is not activated during the timer interval, the scanner goes into power down mode. Whenever the scanner is activated, the timer is reset. If [Scanning While in Base Cradle](#) (page 3-6) is disabled, the scanner will still go into power down mode. *Default = 3600 seconds.*



Note: When the scanner is in power down mode, press the scanner's button to power the unit back up. There will be a set of power up beeps and a delay of up to a few seconds for the radio to join. The scanner will then be ready to use.

RangeGate

If you need RangeGate functionality, the scanner can be programmed for [Automatic Batch Mode](#) (page 3-11), which offers equivalent capabilities.

Batch Mode

Batch mode is used to store bar code data when a scanner is out of range of its base, or when performing inventory. The data is transmitted to the base once the scanner is back in range or when the records are manually transmitted.

Note: Batch Mode is only supported by the Honeywell Charge and Communication Base (CCB) and Honeywell Access Point (AP).

Automatic Batch Mode stores bar code data when the scanner is out of range of the base. The data is automatically transmitted to the base once the scanner is back in range. When the scanner's buffer space is full, any bar codes scanned generate an error tone. In order to scan bar codes again, the scanner must be moved back into range of the base so data can be transmitted.

Inventory Batch Mode stores bar code data, whether or not you are in range of the base. To transmit the stored data to the base, either place the scanner in the base, or scan [Transmit Inventory Records](#) (page 3-15). When the scanner's buffer space is full, any bar codes scanned generate an error tone. In order to scan bar codes again, the data must be transmitted to the base.

Default = Batch Mode Off.



Batch Mode Beep

When scanning in Batch Mode, the scanner beeps every time a bar code is scanned. When **Batch Mode Beep is On**, you will also hear a click when each bar code is sent to the host. If you do not want to hear these clicks, scan **Batch Mode Beep Off**. *Default = Batch Mode Beep Off.*



Batch Mode Quantity

When in [Inventory Batch Mode](#) (page 3-11), you may wish to transmit the number of multiple bar codes scanned, rather than a single bar code multiple times. For example, if you scan three bar codes called XYZ with **Batch Mode Quantity Off**, when you transmit your data it will appear as XYZ three times. Using **Batch Mode Quantity On** and the **Quantity Codes** (page 3-13), you could output your data as “00003, XYZ” instead. *Default = Batch Mode Quantity Off.*



BATQTY0.

* Batch Mode Quantity Off



BATQTY1.

Batch Mode Quantity On

Entering Quantities

Quantity Codes (page 3-13) allow you to enter a quantity for the last item scanned, up to 9999 (default = 1). Quantity digits are shifted from right to left, so if a 5th digit is scanned, the 1st digit scanned is discarded and the 2nd, 3rd and 4th digits are moved to the left to accommodate the new digit.

For example, if the Quantity 5 bar code is scanned after the quantity has been set to 1234, then the 1 is dropped, the quantity will be 2345.

Example: Add a quantity of 5 for the last item scanned.

1. Scan the item's bar code.
2. Scan the quantity 5 bar code.

Example: Add a quantity of 1,500 for the last item scanned.

1. Scan the item's bar code.
2. Scan the quantity 1 bar code.
3. Scan the quantity 5 bar code.
4. Scan the quantity 0 bar code.
5. Scan the quantity 0 bar code.

Example: Change a quantity of 103 to 10.

To correct an incorrect quantity, scan the quantity 0 bar code to replace the incorrect digits, then scan the correct quantity bar codes.

1. Scan the quantity 0 bar code to change the quantity to 1030.
2. Scan the quantity 0 bar code to change the quantity to 0300.
3. Scan the quantity 1 bar code to change the quantity to 3001.
4. Scan the quantity 0 bar code to change the quantity to 0010.

Quantity Codes



BATNUM0.

0



BATNUM1.

1



BATNUM2.

2



BATNUM4.

4



BATNUM6.

6



BATNUM8.

8



BATNUM3.

3



BATNUM5.

5



BATNUM7.

7



BATNUM9.

9

Delete Last Code

If you want to delete the last bar code scanned when in Batch Mode, scan **Delete Last Code**.



BATUND.

Delete Last Code

Record Counter

If you wish to add a record counter to each bar code scanned in Batch Mode, scan **Record Counter On**. Your batch output would add a sequential number before each bar code, for example:

00001,bar code 1

00002,bar code 2

Default = Record Counter Off.



BATENTO.

* Record Counter Off



BATENT1.

Record Counter On

Total Records

If you wish to output the total number of bar codes scanned when in Batch Mode, scan **Total Records**.



BATNRC.

Total Records

Batch Mode Output Order

When batch data is transmitted, select whether you want that data sent as **FIFO** (first-in first-out), or **LIFO** (last-in first-out).

Default = Batch Mode FIFO.



BATLIFO.

* Batch Mode FIFO



BATLIF1.

Batch Mode LIFO

Clear All Codes After Transmission

If you want to clear the scanner's buffer of all data accumulated in Batch Mode *after* the data has been transmitted to the host system, scan **Clear All Codes After Transmission**. If you do not want the buffer cleared after transmission, scan

Don't Clear All Codes After Transmission. *Default = Don't Clear All Codes After Transmission.*



BATCLXD.

* Don't Clear All Codes After
Transmission



BATCLX1.

Clear All Codes After
Transmission

Clear All Codes

If you want to clear the scanner's buffer of all data accumulated in Batch Mode, scan **Clear All Codes**.



BATCLR.
Clear All Codes

Transmit Records Automatically

If you are operating in Inventory Batch Mode (see [Inventory Batch Mode](#) on page 3-11), you can transmit all stored data to the host system when the scanner is placed in the base. If you don't want the records transmitted when the scanner is placed in the base, scan the **Don't Transmit Records Automatically** bar code. *Default = Don't Transmit Records Automatically.*



BATATX0.
* Don't Transmit Records
Automatically



BATATX1.
Transmit Records Automatically

Transmit Records to Host

If you are operating in Inventory Batch Mode (see [Inventory Batch Mode](#) on page 3-11), and your scanner is set to **Don't Transmit Records Automatically**, you must scan the following bar code to transmit all stored records to the host system.



BAT_TX.
Transmit Inventory Records

Batch Mode Transmit Delay

Sometimes when accumulated scans are sent to the host system, the transmission of those scans is too fast for the application to process. To program a transmit delay between accumulated scans, scan one of the following delays. *Default = Off.*

Note: In most cases, a short (250 ms (milliseconds)) delay is ideal, however, longer delays may be programmed. Contact Technical Support (see [Customer Support](#) on page -iii) for additional information.



BATDLY0.
* Batch Mode Transmit Delay Off
(No Delay)



BATDLY250.
Batch Mode Transmit Delay Short
(250 ms)



Scanner Name

You may assign a name to each scanner you are using for identification purposes. The default name is "Voyager."

Perform the rename operation using either the bar codes on [page 3-17](#), or by sending the serial command `:*:BT_NAMname`, where *name* is the new name for the scanner.

To rename scanners with sequential, numeric names, scan the following bar codes. Scan the **Reset** code after each name change and wait for the scanner to relink to the base.



You may also scan the following **Scanner Name** bar code and scan up to 30 numbers and/or letters for the scanner name. For example, if you wanted to name the linked scanner “312,” you would scan the following bar code, scan the **3**, **1**, and **2** bar codes on the [Programming Chart](#) inside the back cover of this manual, then scan **Save**. Scan the **Reset** bar code and wait for the scanner to relink to the base.

To output the name of the scanner, scan the following bar code. The name will be output showing the product name, model number, and the scanner’s 10-digit serial number.



Using the Scanner with Bluetooth Devices

Bluetooth Serial Port - PCs/Laptops

Scanning the **Non-Base BT Connection** bar code below unlinks your scanner and puts it into a discoverable state. Once the scanner searches for and connects with a Bluetooth host, the scanner stores the connection to the host device address and switches virtual COM ports. This allows the scanner to automatically relink to the host if the connection is lost.



Changing the Scanner’s Bluetooth PIN Code

Some devices require a PIN code as part of the Bluetooth security features. Your scanner’s default PIN is 0000, which you may need to enter the first time you connect to your non-base Bluetooth device. To change the PIN, scan the following bar code and then scan the appropriate numeric bar codes from the [Programming Chart](#) inside the back cover of this manual. (The PIN code must be between 1 and 16 characters.) Scan **Save** to save your selection. *Default = 0000.*



Minimizing Bluetooth/ISM Band Network Activity

The following settings can help you customize the relinking behavior of the cordless system to obtain the best compromise between convenience and low interference.

Note: ISM band refers to the 2.4 to 2.48 GHz frequency band used by wireless networks, cordless phones, and Bluetooth.

Auto Reconnect Mode

Auto Reconnect controls whether or not the scanner automatically begins the relink process when a loss of connection is detected. When the **Auto Reconnect On** bar code is scanned, the scanner begins the relink process immediately, without user intervention. *Default = Auto Reconnect On.*





BT_ACMO.
Auto Reconnect Off

The following table shows the results of the Auto Reconnect On and Off settings:

| Event | Auto Reconnect On | Auto Reconnect Off |
|--|--|--|
| Scanner out of range | Relink occurs automatically. If maximum number of link attempts is unsuccessful, then the scanner must be relinked by either pressing the scanner's button or placing the scanner in the base. (See "Maximum Link Attempts" on page 3-18.) | The scanner is relinked by pressing the button. |
| Base reset (firmware upgrade or power cycle) | Scanner behaves as if out of range. | No attempt to relink made while base is powered off. Button must be pressed to initiate relinking. |
| Scanner reset due to firmware upgrade | Relink occurs automatically. | |
| Scanner reset due to battery change | Relink occurs automatically. | |
| Scanner placed in different base unit | Relink to new base occurs automatically. | |

Maximum Link Attempts

The Maximum Link Attempts setting controls the number of times the scanner tries to form a connection with a base. During the connection setup process, the scanner transmits in order to search for and connect to a base. In order to prevent continuous transmissions that could interfere with other users of the ISM band, the number of attempts to connect is limited by this setting. After the maximum number of attempts is reached, the scanner will not attempt to reconnect to a base. Pressing the scanner's button or placing the scanner in the base resets the attempt count and the scanner will again try to link.

Scan the **Maximum Link Attempts** bar code, then scan the number of attempts for the setting (from 0-255) from the inside back cover. Scan Save to save the setting. *Default = 0.*



BT_MLA.
Maximum Link Attempts

Note: When Auto Reconnect Mode is On, setting Maximum Link Attempts to zero will cause the scanner to try to link until the Power Time-Out Timer setting (see [page 3-10](#)) expires. When Auto Reconnect Mode is Off, setting Maximum Link Attempts has no effect.

Bluetooth/ISM Network Activity Examples

Default values

When the scanner goes out of range, the scanner repeatedly attempts to connect to the base unit. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time. After one hour, the scanner powers off and batch mode data is lost.

Maximum Link Attempts set to 15

Other values at default settings

When the scanner goes out of range, 15 attempts are made to link to the base unit. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time. After 15 cycles (8*15 =120), or about 2 minutes, the scanner stops trying to connect to the base, but retains any bar codes that may have been saved in batch mode. After one hour, the scanner powers off and batch mode data is lost.

Auto Reconnect Mode set to 0
Maximum Link Attempts set to 15
Other values at default settings

When the scanner goes out of range, no action is taken to relink. When the scanner's button is pressed, 15 attempts are made to link to the base. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time. After 15 cycles (8*15 =120), or about 2 minutes, the scanner stops trying to connect to the base, but retains any bar codes that may have been saved in batch mode. After one hour, the scanner powers off and batch mode data is lost. Refer to [Auto Reconnect Mode](#), page 3-17, to review other events that can start the relink process.

Reset Scanner and Base

After changing settings, you may need to reset your scanner and base. Scan the **Reset Base** bar code and wait for the scanner to unlink and relink to a base. Once that is done, scan the **Reset Scanner** bar code and wait for the base to unlink and relink to the scanner.





Cordless System Operation (Voyager 1202g-BF)

Note: This chapter applies only to Voyager 1202g-BF cordless scanning systems (PN: 1202G-BF). It does not apply to corded or Voyager 1202g scanners. See [Cordless System Operation \(Voyager 1202g\)](#) on page 3-1 for Voyager 1202g scanners.

How the Charge and Communications Base Works

A charge and communications base provides the link between the cordless scanner and the host system. The base contains an interface assembly and an RF communication module. The RF communication module performs the data exchange between the cordless scanner and the interface assembly. The control assembly coordinates the central interface activities including: transmitting/receiving commands and data to/from the host system, performing software activities (parameter menuing, visual indicator support, power-on diagnostics), and data translation required for the host system.


The base is also the scanner's instant charge pack charger. Refer to [Charging Information](#), page 4-3, for additional information.

Linking the Scanner to a Base

When the base is connected and powered up, put the scanner in the base to establish a link. The red LED on the base lights to indicate power, and the green LED flashes to indicate the scanner's instant charge pack is charging.

Note: The scanner's instant charge pack must be charged to establish a link with the base.

The scanner emits a two tone beep sequence when the scanner and base radios link. That indicates the scanner is linked to the base.




To determine if your scanner has linked to the base correctly, scan one of the sample bar codes in the back of this manual. If the scanner provides a single good read beep and the green LED lights, the scanner has successfully linked to the base. If you receive an error chirp when the scanner's button is pressed and the bar code is not scanned, the scanner has not linked to the base.

Note: If the powered interface cable is unplugged from the base, the scanner will unlink. The scanner will relink once the powered interface cable is connected.

Communication Between the Cordless System and the Host

The cordless scanner provides immediate feedback in the form of a "good read" indication (a red LED will turn into a green LED on the scanner and an audible beep) after a bar code is scanned correctly and the base has acknowledged receiving the data. This is possible since the cordless system provides two-way communication between the scanner and the base.

When data is scanned, the data is sent to the host system via the base. The cordless scanner recognizes data acknowledgement (ACK) from the base. If it cannot be determined that the data has been properly sent to the base, the scanner issues an error indication. You must then check to see if the scanned data was received by the host system. If data has not been properly sent to the host, additional scanner configurations may be needed. Contact Technical Support (see page -iii) for additional information.



RF (Radio Frequency) Module Operation

The cordless system uses a two-way Bluetooth® radio utilizing adaptive frequency hopping (AFH) to transmit and receive data between the scanner and the base. Designed for point-to-point applications, the radio operates using a license free ISM band. This band sends relatively small data packets at a fast data rate over a radio signal with randomly changing frequencies. This makes the cordless system highly responsive to a wide variety of data collection applications and resistant to noisy RF environments. The Bluetooth Class 2 power level provides a communication range of 33 feet (10m) between the scanner and base, depending on the environment.

System Conditions

The components of the cordless system interact in specific ways as you associate the scanner with its base, as you move a scanner out of range, or bring a scanner back in range. The following information explains the cordless system operating conditions.

Linking Process

Once a scanner is placed into a base, the scanner's instant charge pack charge status is checked, and software automatically detects the scanner and links it to the base depending on the selected link mode.

Scanner Is Out of Range

The cordless scanner is in communication with its base, even when it is not transmitting bar code data. Whenever the scanner can't communicate with the base for a few seconds, it is out of range. If the scanner is out of range and you press the scanner button, the scanner issues an error tone indicating no communication with the base. Refer to [Out-of-Range Alarm](#), page 4-7.

Scanner Is Moved Back Into Range

The scanner relinks if the scanner or the base have been reset, or the scanner comes back into range. If the scanner relinks, you will hear a two tone beep sequence when the relinking process is complete. Refer to [Out-of-Range Alarm](#) on page 4-7 for further information.

Page Button

When you press the Page button on the base, the scanner associated with that base will begin beeping (3 short and 1 long beep). If you press the button on a scanner that is beeping in response, or press the Page button on the base a second time, the scanner will stop beeping. See [Paging](#) on page 4-5 for further information about Page Button settings.

About the Instant Charge Pack

Power is supplied to the cordless scanner by a rechargeable instant charge pack that is integrated in the scanner handle. The instant charge pack must be charged before initial use. When the scanner is not in use, return it to the base. The model CCB00-010BT-01N-BF base is designed for use with the Honeywell model Voyager 1202g-BF scanner.

Charging Information

The instant charge pack is designed to charge while the scanner is positioned in the base unit. Refer to [Base LED Sequences and Meaning](#), page 4-4, for an interpretation of the Charge Status indicators. Refer to [Charge Only Mode](#) (page 4-6) if you need to charge a scanner without linking it to the base.

Place the scanner in the base that is connected to an appropriate power supply. Use only a Listed Limited Power Source (LPS) or Class 2 type power supply with output rated 5 to 5.2Vdc, 1A.



Caution:

Voyager 1202g-BF scanner can only be charged by CCB00-010BT-01N-BF base.
Use of any non-Honeywell power supply may result in damage not covered by the warranty.

Note: If you are powering the base through the interface cable (for example, a USB cable) and not using an external power supply plugged into the auxiliary port located on the bottom of the base, the current available for charging is reduced and the charge time is significantly increased.

Flash Updates

The scanner can only be flashed while the scanner is in the base, the instant battery charge pack is fully charged, and must remain in the base until successful update notification is received.

Beeper and LED Sequences and Meaning

The scanner contains LEDs on the top that indicate linking status, decoding state, and instant charge pack condition. The base has LEDs on the front that indicate its power, communication, and instant charge pack condition. The unit's audible indicators have meaning as well. The following table lists the indication and cause of the LED illumination and beeps for the scanner and base.

Scanner LED Sequences and Meaning

Note: Pressing the button on the scanner causes the LED to glow red until it communicates successfully with the base.

| LED Indication | Beeper Indication | Cause |
|-------------------------|--------------------|-------------------------------------|
| Normal Operation | | |
| Red Flash | None | Instant charge pack low |
| Green Flash | 1 beep | Successful communication or linking |
| Red, blinking | Razz or error tone | Failed communication |
| Menu Operation | | |
| Green Flash | 2 beeps | Successful menu change |
| Red, blinking | Razz or error tone | Unsuccessful menu change |

Base LED Sequences and Meaning

The base contains a red LED that indicate the status of the unit and verifies its communication with the host system. The base also has a green LED that indicates the scanner instant charge pack charge condition. The red LED and the green LED both flash when a link is established.

| Red LED - Host Communication | |
|--|--|
| Red LED | Condition |
| Off | Power off, USB suspend |
| On continuously | Power on, system idle |
| Short blinks. Occurs while transferring data to the host port. | Receiving data |
| Green LED - Scanner Instant Charge Pack | |
| Green LED | Condition |
| Off | Instant charge pack not detected or charge suspended |
| Slow flash, 1 second on, 1 second off | Charging instant charge pack near empty |
| Slow flash, 0.5 second on, 0.5 second off | Charging instant charge pack near medium capacity |
| Slow flash, 0.25 second on, 0.25 second off | Charging instant charge pack near full capacity |
| On continuously | Charge complete |

Base Power Communication Indicator

To display the power indicator on the base, scan the **Base Power Communication Indicator On** bar code. To turn off the power indicator, scan the **Off** bar code. *Default = On.*



.*:BASRED1.
*** Base Power Communication
 Indicator On**



.*:BASREDO.
**Base Power Communication
 Indicator Off**

Reset Scanner

Scanning this bar code reboots the scanner and causes it to relink with the base.



RESET_
Reset Scanner

Scanning While in Base Cradle

If you want to be able to scan bar codes while the scanner is in the base, scan the following **Scanning in Cradle On** bar code. If you want to only allow scanning when the scanner is out of the base, scan **Scanning in Cradle Off**. *Default = Scanning in Cradle On.*



*Note: When **Scanning in Cradle Off** is selected, the scanner will not scan any bar codes while it is in the base. It will only scan when removed from the base.*

Paging

Paging Mode

By default, the paging button on the base pages the scanner associated with that base. If you want the paging button on your base to be disabled, scan the following **Paging Mode Off** bar code. When Paging Mode is off, the base will no longer page the scanner when the button is pressed. The red LED on the base will remain lit to indicate that Paging Mode is off. (This light will go out when the button is pressed, then back on when it's released.) *Default = Paging Mode On.*



Paging Pitch

When you press the Page button on the base, the scanner associated with that base will begin beeping (see [Page Button](#) on page 4-3). You can set the pitch of the paging beep for the scanner by scanning one of the following bar codes. *Default = Low.*





BEPPFQ4200.
High (4200 Hz)

Scanner Address

Scan the following bar code to determine the address of the scanner you are using.



BT_LDA.
Scanner Address

Base Address

Scan the following bar code to determine the address of the base you are using.



*:BASLDA.
Base Address

Scanner Modes

The Voyager 1202g-BF is only capable of working with the CCB00-010BT-01N-BF base.

Charge Only Mode

There may be times when you want to charge your scanner, but not link to the base. For example, if a scanner is linked to a Bluetooth device and you need to charge the scanner, but want to retain your existing link.

In order to program the base for Charge Only Mode, you must link a scanner to it. Once the scanner is linked to the base, scan the **Charge Only Mode** bar code. Any subsequent scanners placed in that base will charge without linking to it. The scanner used to program the base remains linked to the base. To unlink this scanner, scan [Unlink Scanner](#) on page 4-7.



*:BASLNKO.
Charge Only Mode

If you want to charge a scanner and link to the base, use **Charge and Link Mode**. If the base is programmed for Charge Only Mode, you must link a scanner to it first in order to program it for Charge and Link Mode. Scan the linking bar code on the base to link the scanner, then scan **Charge and Link Mode**. *Default = Charge and Link Mode.*



*:BASLNK1.
* Charge and Link Mode

Linked Modes

Locked Link Mode and Open Link Mode are the link modes that accommodate different applications. Scan the appropriate bar codes included in the Open Link and Locked Link Mode explanations that follow to switch from one mode to another. *Default = Open Link Mode.*

Locked Link Mode - Single Scanner

If you link a scanner to a base using the Locked Link Mode, other scanners are blocked from being linked if they are inadvertently placed into the base. If you do place a different scanner into a base, it will charge the scanner, but the scanner will not be linked.



To use a different scanner, you need to unlink the original scanner by scanning the **Unlink Scanner** bar code. (See [Scanner Modes](#), page 4-6.)

Open Link Mode - Single Scanner

When newly shipped or defaulted to factory settings, a scanner is not linked to a base. A link is established when the scanner is placed into a base. When in Open Link Mode, a new link is established when a new scanner is placed in the base. Each time a scanner is placed into a base, the scanner becomes the linked to the base and the old scanner is unlinked.



Unlinking the Scanner

If a base has a scanner linked to it, that scanner must be unlinked before a new scanner can be linked. Once the previous scanner is unlinked, it will no longer communicate with the base. To unlink the scanner from a base, scan the following **Unlink Scanner** bar code.



Override Locked Scanner

If you need to replace a broken or lost scanner that is linked to a base, scan the following **Override Locked Scanner** bar code with a new scanner and place that scanner in the base. The locked link will be overridden, the broken or lost scanner's link with the base will be removed, and the new scanner will be linked.



Out-of-Range Alarm

If your scanner is out of range of the base, an alarm sounds from the scanner. The alarm stops when the scanner is moved closer to the base or when the alarm duration expires.

Note: If you are out of range when you scan a bar code, you will receive an error tone even if you do not have the alarm set. You receive the error tone since the data could not be communicated to the base or the host.

Alarm Sound Type

You may change the alarm type for the scanner by scanning the appropriate bar code below and then scanning a digit (0-1) bar code and the **Save** bar code on the [Programming Chart](#) inside the back cover of this manual. *Default = 0.*

The sounds are as follows:

| Setting | Sound |
|---------|----------------------------|
| 0 | 3 long beeps, medium pitch |
| 1 | 3 long beeps, high pitch |



Alarm Duration

To set the length of time you want the Out-of-Range alarm to sound, scan the following bar code and then set the time-out duration (from 0-3000 seconds) by scanning digits on the [Programming Chart](#) inside the back cover, then scanning **Save**.
Default = 1 sec.



Using the Scanner with Bluetooth Devices

The scanner can only be used with the CCB00-010BT-01N-BF base.

Minimizing Bluetooth/ISM Band Network Activity

The following settings can help you customize the relinking behavior of the cordless system to obtain the best compromise between convenience and low interference.

Note: ISM band refers to the 2.4 to 2.48 GHz frequency band used by wireless networks, cordless phones, and Bluetooth.

Auto Reconnect Mode

Auto Reconnect controls whether or not the scanner automatically begins the relink process when a loss of connection is detected. When the **Auto Reconnect On** bar code is scanned, the scanner begins the relink process immediately, without user intervention. *Default = Auto Reconnect On.*



The following table shows the results of the Auto Reconnect On and Off settings:

| Event | Auto Reconnect On | Auto Reconnect Off |
|---|---|--|
| Scanner out of range | Relink occurs automatically. If maximum number of link attempts is unsuccessful, then the scanner must be relinked by either pressing the scanner's button or placing the scanner in the base. (See "Maximum Link Attempts" on page 4-9.) | The scanner is relinked by pressing the scanner's button. |
| Base reset (firmware upgrade or power cycle) | Scanner behaves as if out of range. | No attempt to relink made while base is powered off. The scanner's button must be pressed to initiate relinking. |
| Scanner reset due to firmware upgrade | Relink occurs automatically. | |
| Scanner reset due to instant charge pack change | Relink occurs automatically. | |
| Scanner placed in different base unit | Relink to new base occurs automatically. | |

Maximum Link Attempts

The Maximum Link Attempts setting controls the number of times the scanner tries to form a connection with a base. During the connection setup process, the scanner transmits in order to search for and connect to a base. In order to prevent continuous transmissions that could interfere with other users of the ISM band, the number of attempts to connect is limited by this setting. After the maximum number of attempts is reached, the scanner will not attempt to reconnect to a base. Pressing the scanner's button or placing the scanner in the base resets the attempt count and the scanner will again try to link.

Scan the **Maximum Link Attempts** bar code, then scan the number of attempts for the setting (from 0-255) from the inside back cover. Scan Save to save the setting. *Default = 0.*



Note: When Auto Reconnect Mode is On, setting Maximum Link Attempts to zero will cause the scanner to try to link until the Power Time-Out Timer setting (see [page 4-8](#)) expires. When Auto Reconnect Mode is Off, setting Maximum Link Attempts has no effect..

Bluetooth/ISM Network Activity Examples

Default values

When the scanner goes out of range, the scanner repeatedly attempts to connect to the base unit. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time.

Maximum Link Attempts set to 15

Other values at default settings

When the scanner goes out of range, 15 attempts are made to link to the base unit. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time. After 15 cycles ($8 \times 15 = 120$), or about 2 minutes, the scanner stops trying to connect to the base.

Auto Reconnect Mode set to 0

Maximum Link Attempts set to 15

Other values at default settings

When the scanner goes out of range, no action is taken to relink. When the scanner's button is pressed, 15 attempts are made to link to the base. Each attempt consists of approximately 5 seconds of active time followed by 3 seconds of idle time. After 15 cycles (8*15 =120), or about 2 minutes, the scanner stops trying to connect to the base. Refer to [Auto Reconnect Mode](#), page 4-8, to review other events that can start the relink process.

Reset Scanner and Base

After changing settings, you may need to reset your scanner and base. Scan the **Reset Base** bar code and wait for the scanner to unlink and relink to a base. Once that is done, scan the **Reset Scanner** bar code and wait for the base to unlink and relink to the scanner.



Input/Output Settings

Power Up Beeper

The scanner can be programmed to beep when it's powered up. Scan the **Off** bar code(s) if you don't want a power up beep. *Default = Power Up Beeper On - Scanner.*

Note: The Voyager 1202g-BF does not issue a power up beep when the scanner is in the base.



BEPPWR0.

Power Up Beeper Off -
Scanner



BEPPWR1.

* Power Up Beeper On -
Scanner

Beep on BEL Character

You may wish to force the scanner to beep upon a command sent from the host. If you scan the following **Beep on BEL On** bar code, the scanner will beep every time a BEL character is received from the host. *Default = Beep on BEL Off.*



BELBEP0.

*Beep on BEL Off



BELBEP1.

Beep on BEL On

Good Read and Error Indicators

Beeper – Good Read

The beeper may be programmed **On** or **Off** in response to a good read. Turning this option off, only turns off the beeper response to a good read indication. All error and menu beeps are still audible. *Default = Beeper - Good Read On.*



BEPBEP0.

Beeper - Good Read Off



BEPBEP1.

* Beeper - Good Read On

Beeper Volume – Good Read

The beeper volume codes modify the volume of the beep the scanner emits on a good read. *Default = High.*



BEPLVL1.
Low



BEPLVL2.
Medium



BEPLVL3.
* High



BEPLVL0.
Off

Beeper Pitch – Good Read

The beeper pitch codes modify the pitch (frequency) of the beep the scanner emits on a good read. *Default = Medium.*



BEPFQ11600.
Low (1600 Hz)



BEPFQ12350.
* Medium (2350 Hz)



BEPFQ14200.
High (4200 Hz)

Beeper - Transmit Order

The beeper transmit order determines when the good read beep occurs. The scanner can be set to emit the good read beep either before or after data transmission. *Default = For Voyager 1200g - Before Transmission. For Voyager 1202g and 1202g-BF - After Transmission*



BEPWHN1.
Before Transmission



BEPWHN2.
After Transmission

Beeper Pitch – Error

The beeper pitch codes modify the pitch (frequency) of the sound the scanner emits when there is a bad read or error. *Default = Razz.*



Beeper Duration – Good Read

The beeper duration codes modify the length of the beep the scanner emits on a good read. *Default = Normal.*



Number of Beeps – Good Read

The number of beeps of a good read can be programmed from 1 - 9. The same number of beeps will be applied to the beeper and LED in response to a good read. For example, if you program this option to have five beeps, there will be five beeps and five LED flashes in response to a good read. The beeps and LED flashes are in sync with one another.

Note: The LEDs can also be programmed separately. See [LED Settings](#) on page 5-4.

To change the number of beeps, scan the following bar code and then scan a digit (1-9) bar code and the **Save** bar code on the [Programming Chart](#) inside the back cover of this manual. *Default = 1.*



Number of Beeps – Error

The number of beeps and LED flashes emitted by the scanner for a bad read or error can be programmed from 1 - 9. For example, if you program this option to have five error beeps, there will be five error beeps and five LED flashes in response to an error.

Note: The LEDs can also be programmed separately. See [LED Settings](#) on page 5-4.

To change the number of error beeps, scan the following bar code and then scan a digit (1-9) bar code and the **Save** bar code on the [Programming Chart](#) inside the back cover of this manual. *Default = 1.*



BEPERR.

Number of Error Beeps/LED Flashes

LED Indicators

The green and red LEDs can be programmed to be On or Off and at different brightness levels to indicate various scanner states. Use the following bar codes to program the LED indicators.

LED Settings

Default = For Voyager 1200g - Red LED On with Laser . For Voyager 1202g and 1202g-BF - Red LED On with Laser/Red LED Blinks when Battery is Low.



LEDFN10.
Red LED Off



LEDFN20.
Green LED Off



LEDFN11.
Red LED On with Good Scan



LEDFN21.
Green LED On with Good Scan



LEDFN12.
Red LED On with Laser



LEDFN11026.
Red LED On with Laser/
Red LED Blinks when Battery is Low



LEDFN22.
Green LED On with Laser



LEDFN14.
Red LED On when CodeGate
Disabled



LEDFN24.
Green LED On when CodeGate
Disabled



LEDFN18.
Red LED On when In-Stand



LEDFN28.
Green LED On when In-Stand



LEDFN1128.
Red LED On with CTS



LEDFN2128.
Green LED On with CTS



LEDFN11024.
Red LED On when Battery is Low



LEDFN21024.
Green LED On when Battery is Low

LED Brightness

Default = Red High, Green High.

Note: For Voyager 1202g-BF, all LED Brightness settings result in High brightness.



LEDIN10.
Red Off



LEDIN20.
Green Off



LEDIN11.
Red Low



In-Stand and Out-Of-Stand Settings

The following settings program the scanner's behavior when it is either in the stand, or out of the stand (hand-held).

Caution: When working with In-Stand and Out-of-Stand settings, enable the settings you want before disabling those you do not want to use. If you disable settings first, you may program the scanner so it is unable to read bar codes. If this happens, power cycle the scanner and scan the defaults bar code on [page 1-7](#).

In-Stand and Out-of-Stand Defaults

If you want the In-Stand or Out-of-Stand default settings restored to your scanner, scan the appropriate **Defaults** bar code below. They reset the scanner to the custom default settings (see [Setting Custom Defaults](#) on page 1-6). If there are no custom defaults, it will reset the scanner to the factory default settings. Any settings that have not been specified through the custom defaults will be defaulted to the factory default settings.



Presentation Modes

When the scanner is in the stand, by default, bar codes are automatically read when they are detected in the scanner's field of view. When the scanner is out of the stand, by default you must push the button on top of the scanner to read a bar code. Use the following commands to adjust how the scanner behaves when it is out of the stand.

Presentation Mode Out-of-Stand: When the scanner is not in the stand, it automatically detects bar codes, then scans and transmits the data. The laser turns off afterward. (If you are accustomed to a Voyager 9520, this setting is the same as the 9520's default.)

Presentation Mode with CodeGate Out-of-Stand: When the scanner is not in the stand, it automatically detects bar codes and decodes them. However, the data is not transmitted until you press the button. The laser remains on briefly after the transmission. (If you are accustomed to a Voyager 9540, this setting is the same as the 9540's default.)



Manual Activation Mode

In Manual Activation Mode, you must press the button to scan a bar code. The scanner scans until a bar code is read, or until the button is released. *Default = Manual Activation Mode On In-Stand, Manual Activation On Out-of-Stand.*



End Manual Activation After Good Read

After a bar code is successfully read, the laser can be programmed either to remain on and scanning, or to turn off. When **End Manual Activation After Good Read** is enabled, the laser turns off and stops scanning after a good read. If you scan **Do Not End Manual Activation After Good Read**, the laser remains on after a good read. *Default = End Manual Activation After Good Read.*





AOSMGDD.

**Do Not End Manual Activation
After Good Read Out-of-Stand**



AISMGD1.

*** End Manual Activation After
Good Read In-Stand**



AOSMGD1.

*** End Manual Activation After
Good Read Out-of-Stand**

Manual Activation Laser Timeout - Button Settings

You can set a timeout for the length of time the laser remains on and attempting to decode bar codes when the button is held down, and after it is released. Set the length (in milliseconds) for a timeout by scanning one of the following bar codes, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**.

Default = Button Hold In-Stand 5000 ms, Button Hold Out-of-Stand 5000 ms, Button Release In or Out-of-Stand 0.



AISMPT.

**Laser Timeout - Button Hold
In-Stand**



AISMRT.

**Laser Timeout - Button
Release In-Stand**



AOSMPT.

**Laser Timeout - Button Hold
Out-of-Stand**



AOSMRT.

**Laser Timeout - Button
Release Out-of-Stand**

CodeGate

When CodeGate is **On**, the button is used to allow decoded data to be transmitted to the host system. The scanner remains on, scanning and decoding bar codes, but the bar code data is not transmitted until the button is pressed. When CodeGate is **Off**, bar code data is transmitted when it is decoded. *Default = CodeGate Off in-Stand, CodeGate On Out-of-Stand.*



Button Function

Note: Button Function applies only to the Voyager 1202. It is not supported in the Voyager 1200.

When Button Function is set to **On**, press and hold the button for 7 seconds to change the CodeGate setting from **CodeGate Off Out-of-Stand** to **CodeGate On Out-of-Stand**. When the scanner is power cycled, the CodeGate function reverts to the saved CodeGate setting. When Button Function is set to **Off**, holding the button down for 7 seconds shuts down the scanner. *Default = Off.*



Object Detection Mode

Object Detection Mode uses an LED to detect when an object is in the scanner's field of view. When an object is detected, the laser turns on and the scanner attempts to scan the bar code. *Default = Object Detection Mode On In-Stand.*





AISOEND.

* Object Detection Mode Off
Out-of-Stand



AISOEN1.

* Object Detection Mode On
In-Stand



AISOEN1.

Object Detection Mode On
Out-of-Stand

End Object Detection After Good Read

After a bar code is successfully detected and read from the scanner, the laser can be programmed either to remain on and scanning, or to turn off. When **End Object Detection After Good Read** is enabled, the laser turns off and stops scanning after a good read. If you scan **Do Not End Object Detection After Good Read**, the laser remains on after a good read.

Default = End Object Detection After Good Read.



AISOGD0.

Do Not End Object Detection
After Good Read In-Stand



AISOGD1.

* End Object Detection After
Good Read In-Stand



AISOGD0.

Do Not End Object Detection
After Good Read Out-of-Stand



AISOGD1.

* End Object Detection After
Good Read Out-of-Stand

Object Detection Laser Timeout

You can set a timeout for the length of time the laser remains on and attempting to decode bar codes after an object is detected. Set the length (in milliseconds) for a timeout by scanning the following bar code, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 5000 ms.*



Object Detection Distance

When you are using Object Detection Mode, you can set the distance range for detecting objects. **Short** sets the scanner to detect objects approximately 5 inches (12.7cm) away from the nose. **Long** sets it to detect objects approximately 10 inches (25.4cm) away. *Default = Short In-Stand, Long Out-of-Stand.*



Character Activation Mode

You may use a character sent from the host to trigger the scanner to begin scanning. When the activation character is received, the scanner continues scanning until either the [Character Activation Laser Timeout](#) (page 5-12), the deactivation character is received (see [Deactivation Character](#) on page 5-13), or a bar code is transmitted. Scan the following **On** bar code to use character activation, then use Activation Character (following) to select the character you will send from the host to start scanning. *Default = Off.*





Activation Character

This sets the character used to trigger scanning when using Character Activation Mode. On the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, find the hex value that represents the character you want to use to trigger scanning. Scan the following bar code, then use the [Programming Chart](#) to read the alphanumeric combination that represents that ASCII character. Scan **Save** to finish.



End Character Activation After Good Read

After a bar code is successfully detected and read from the scanner, the laser can be programmed either to remain on and scanning, or to turn off. When **End Character Activation After Good Read** is enabled, the laser turns off and stops scanning after a good read. If you scan **Do Not End Character Activation After Good Read**, the laser remains on after a good read. *Default = End Character Activation After Good Read.*



Character Activation Laser Timeout

You can set a timeout for the length of time the laser remains on and attempting to decode bar codes when using Character Activation Mode. Set the length (in milliseconds) for a timeout by scanning the following bar code, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 5000 ms.*



Character Deactivation Mode

If you have sent a character from the host to trigger the scanner to begin scanning, you can also send a deactivation character to stop scanning. Scan the following **On** bar code to use character deactivation, then use Deactivation Character (following) to select the character you will send from the host to terminate scanning. *Default = Off.*





Deactivation Character

This sets the character used to terminate scanning when using Character Deactivation Mode. On the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, find the hex value that represents the character you want to use to terminate scanning. Scan the following bar code, then use the [Programming Chart](#) to read the alphanumeric combination that represents that ASCII character. Scan **Save** to finish.



Reread Delay

This sets the time period before the scanner can read the *same* bar code a second time. Setting a reread delay protects against accidental rereads of the same bar code. Longer delays are effective in minimizing accidental rereads. Use shorter delays in applications where repetitive bar code scanning is required. *Default = Medium.*



User-Specified Reread Delay

If you want to set your own length for the reread delay, scan the following bar code, then set the delay (from 0-30,000 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**.



Output Sequence Overview

Output Sequence Editor

This programming selection allows you to program the scanner to output data (when scanning more than one symbol) in whatever order your application requires, regardless of the order in which the bar codes are scanned. Reading the **Default Sequence** symbol programs the scanner to the following Universal values. These are the defaults. Be **certain** you want to delete or clear all formats before you read the **Default Sequence** symbol.

Note: If CodeGate is enabled, you must hold the button down while reading each bar code in a sequence.

Note: To make Output Sequence Editor selections, you'll need to know the code I.D., code length, and character match(es) your application requires. Use the Alphanumeric symbols on the [Programming Chart](#) to read these options.

To Add an Output Sequence

1. Scan the **Enter Sequence** symbol (see [Require Output Sequence](#), page 5-17).
2. **Code I.D.**
On the [Symbology Charts](#) on page A-1, find the symbology to which you want to apply the output sequence format. Locate the Hex value for that symbology and scan the 2 digit hex value from the [Programming Chart](#) (inside back cover).
3. **Length**
Specify what length (up to 9999 characters) of data output will be acceptable for this symbology. Scan the four digit data length from the [Programming Chart](#). (Note: 50 characters is entered as 0050. 9999 is a universal number, indicating all lengths.) When calculating the length, you must count any programmed prefixes, suffixes, or formatted characters as part of the length (unless using 9999).
4. **Character Match Sequences**
On the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, find the Hex value that represents the character(s) you want to match. Use the [Programming Chart](#) to read the alphanumeric combination that represents the ASCII characters. (99 is the Universal number, indicating all characters.)
5. **End Output Sequence Editor**
Scan **FF** to enter an Output Sequence for an additional symbology, or **Save** to save your entries.

Other Programming Selections

- **Discard**
This exits without saving any Output Sequence changes.

Output Sequence Example

In this example, you are scanning Code 93, Code 128, and Code 39 bar codes, but you want the scanner to output Code 39 1st, Code 128 2nd, and Code 93 3rd, as shown below.

Note: Code 93 must be enabled to use this example.



A - Code 39



B - Code 128



C - Code 93

You would set up the sequence editor with the following command line:

```
SEQBLK62999941FF6A999942FF69999943FF
```

The breakdown of the command line follows:

SEQBLKsequence editor start command

62 code identifier for **Code 39**
9999 code length that must match for Code 39, 9999 = all lengths
41 start character match for Code 39, 41h = "A"
FF termination string for first code
6A code identifier for **Code 128**
9999 code length that must match for Code 128, 9999 = all lengths
42 start character match for Code 128, 42h = "B"
FF termination string for second code
69 code identifier for **Code 93**
9999 code length that must match for Code 93, 9999 = all lengths
43 start character match for Code 93, 43h = "C"
FF termination string for third code

To program the previous example using specific lengths, you would have to count any programmed prefixes, suffixes, or formatted characters as part of the length. If you use the example on [page 5-14](#), but assume a <CR> suffix and specific code lengths, you would use the following command line:

SEQBLK62001241FF6A001342FF69001243FF

The breakdown of the command line follows:

SEQBLKsequence editor start command

62 code identifier for **Code 39**
0012 A - Code 39 sample length (11) plus CR suffix (1) = 12
41 start character match for Code 39, 41h = "A"
FF termination string for first code
6A code identifier for **Code 128**
0013 B - Code 128 sample length (12) plus CR suffix (1) = 13
42 start character match for Code 128, 42h = "B"
FF termination string for second code
69 code identifier for **Code 93**
0012 C - Code 93 sample length (11) plus CR suffix (1) = 12
43 start character match for Code 93, 43h = "C"
FF termination string for third code

Output Sequence Editor



SEQBLK.

Enter Sequence



SEQDFT.

Default Sequence

Sequence Timeout

You may wish to set the maximum time between bar code scans in an output sequence. If that maximum time is not met, the output sequence operation is terminated. Set the length (in milliseconds) for a timeout by scanning the following bar code, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning [Save](#). *Default = 5000 msec.*



SEQDLY.

Sequence Timeout

Sequence Match Beeper

By default, the scanner beeps when a sequence match is found. If you want the scanner to remain silent, scan the following **Sequence Match Beeper Off** bar code. *Default = Sequence Match Beeper On.*



SEQBEP0.

Sequence Match Beeper Off



SEQBEP1.

* Sequence Match Beeper On

Partial Sequence

If an output sequence operation is terminated before all your output sequence criteria are met, the bar code data acquired to that point is a "partial sequence."

Scan **Discard Partial Sequence** to discard partial sequences when the output sequence operation is terminated before completion.

Scan **Transmit Partial Sequence** to transmit partial sequences. (Any fields in the sequence where no data match occurred will be skipped in the output.) If you have programmed a [Sequence Timeout](#) (page 5-16) and the timeout is reached, the partial sequence is transmitted. *Default = Discard Partial Sequence.*



SEQTTS1.

Transmit Partial Sequence



SEQTTSQ.

* Discard Partial Sequence

Require Output Sequence

When an output sequence is **Required**, all output data must conform to an edited sequence or the scanner will not transmit the output data to the host device. When it's **On/Not Required**, the scanner will attempt to get the output data to conform to an edited sequence but, if it cannot, the scanner transmits all output data to the host device as is.

When the output sequence is **Off**, the bar code data is output to the host as the scanner decodes it. *Default = Off.*



SEQ_EN2.

Required



SEQ_EN1.

On/Not Required



SEQ_EN0.

***Off**

No Read

With No Read turned **On**, the scanner notifies you if a code cannot be read. If using an EZConfig-Scanning Tool Scan Data Window (see page 9-2), an "NR" appears when a code cannot be read. If No Read is turned **Off**, the "NR" will not appear.

Default = Off.



SHWNRD1.

On



SHWNRD0.

*** Off**


If you want a different notation than "NR," for example, "Error," or "Bad Code," you can edit the output message (see [Data Formatting](#) beginning on page 7-1). The hex code for the No Read symbol is 9C.



Prefix/Suffix Overview

When a bar code is scanned, additional information is sent to the host computer along with the bar code data. This group of bar code data and additional, user-defined data is called a “message string.” The selections in this section are used to build the user-defined data into the message string.

Prefix and Suffix characters are data characters that can be sent before and after scanned data. You can specify if they should be sent with all symbologies, or only with specific symbologies. The following illustration shows the breakdown of a message string:



Points to Keep In Mind

- It is not necessary to build a message string. The selections in this chapter are only used if you wish to alter the default settings. *Default prefix = None. Default suffix is dependent on interface.*
- A prefix or suffix may be added or cleared from one symbology or all symbologies.
- You can add any prefix or suffix from the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, plus Code I.D. and AIM I.D.
- You can string together several entries for several symbologies at one time.
- Enter prefixes and suffixes in the order in which you want them to appear on the output.
- When setting up for specific symbologies (as opposed to all symbologies), the specific symbology ID value counts as an added prefix or suffix character.
- The maximum size of a prefix or suffix configuration is 32 characters, which includes header information.

To Add a Prefix or Suffix:

Step 1. Scan the **Add Prefix** or **Add Suffix** symbol ([page 6-2](#)).

Step 2. Determine the 2 digit Hex value from the Symbology Chart (included in the [Symbology Charts](#), beginning on page A-1) for the symbology to which you want to apply the prefix or suffix. For example, for Code 128, Code ID is “j” and Hex ID is “6A”.

Step 3. Scan the 2 hex digits from the [Programming Chart](#) inside the back cover of this manual or scan **9, 9** for all symbologies.

Step 4. Determine the hex value from the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, for the prefix or suffix you wish to enter.

*Note: To add the Code I.D., scan **5, C, 8, 0**.*

*To add AIM I.D., scan **5, C, 8, 1**.*

*To add a backslash (\), scan **5, C, 5, C**.*

To add a backslash (\) as in Step 7, you must scan 5C twice – once to create the leading backslash and then to create the backslash itself.

Step 5. Scan the 2 digit hex value from the [Programming Chart](#) inside the back cover of this manual.

Step 6. Repeat Steps 4 and 5 for every prefix or suffix character.

Step 7. Scan **Save** to exit and save, or scan **Discard** to exit without saving.

Repeat Steps 1-6 to add a prefix or suffix for another symbology.

Example: Add a Tab Suffix to All Symbologies

Step 1. Scan **Add Suffix**.

Step 2. Scan **9, 9** from the [Programming Chart](#) inside the back cover of this manual to apply this suffix to all symbologies.

Step 3. Scan **0, 9** from the [Programming Chart](#) inside the back cover of this manual. This corresponds with the hex value for a horizontal tab, shown in the [ASCII Conversion Chart \(Code Page 1252\)](#), beginning on page A-2.

Step 4. Scan **Save**, or scan **Discard** to exit without saving.

To Clear One or All Prefixes or Suffixes

You can clear a single prefix or suffix, or clear all prefixes/suffixes for a symbology. If you have been entering prefixes and suffixes for single symbologies, you can use **Clear One Prefix (Suffix)** to delete a specific character from a symbology. When you **Clear All Prefixes (Suffixes)**, all the prefixes or suffixes for a symbology are deleted.

Step 1. Scan the **Clear One Prefix** or **Clear One Suffix** symbol.

Step 2. Determine the 2 digit Hex value from the Symbology Chart (included in the [Symbology Charts](#), beginning on page A-1) for the symbology from which you want to clear the prefix or suffix.

Step 3. Scan the 2 digit hex value from the [Programming Chart](#) inside the back cover of this manual or scan **9, 9** for all symbologies.

Your change is automatically saved.

To Add a Carriage Return Suffix to All Symbologies

Scan the following bar code if you wish to add a carriage return suffix to all symbologies at once. This action first clears all current suffixes, then programs a carriage return suffix for all symbologies.



VSUF CR.
Add CR Suffix
All Symbologies

Prefix Selections



PREBK2.
Add Prefix



PRECL2.
Clear One Prefix



PRECA2.
Clear All Prefixes

Suffix Selections



SUFBK2.
Add Suffix



SUFCL2.
Clear One Suffix



SUFCA2.
Clear All Suffixes

Transmit Alternate Extended ASCII Characters

You may need to emulate special keyboard functions, such as up or down arrows, Alt/Make or Alt/Break commands, that are not supported in the Extended ASCII Character table. Refer to the [Alternate Extended ASCII Characters](#) table, below, for a range of keyboard function keys and corresponding decimal and hex characters. If you scan the **Transmit Alternate Extended ASCII** code, any hex entries in a prefix or suffix will result in the corresponding Keyboard Function output.

Example: **Transmit Alternate Extended ASCII** is enabled, and you scan **Add Suffix**, then scan **9 9 8 9**. All symbologies (99) would have a suffix of a Page Down (hex 89) added to them.

When **Transmit Normal Extended ASCII** is selected, the normal extended ASCII character is transmitted (see [ASCII Conversion Chart \(Code Page 1252\)](#) beginning on page A-2).

Example: **Transmit Normal Extended ASCII** is enabled, and you scan **Add Suffix**, then scan **9 9 8 9**. All symbologies (99) would have a suffix of a % character added to them.

Default = Transmit Alternate Extended ASCII.



KBDEXT0.
* Transmit Alternate Extended ASCII



KBDEXT1.
Transmit Normal Extended ASCII

| Alternate Extended ASCII Characters | | | | | |
|-------------------------------------|-----|-------------------|-----|-----|-------------------|
| DEC | HEX | Keyboard Function | DEC | HEX | Keyboard Function |
| 128 | 80 | up arrow ↑ | 152 | 98 | F9 |
| 129 | 81 | down arrow ↓ | 153 | 99 | F10 |
| 130 | 82 | right arrow → | 154 | 9A | F11 |
| 131 | 83 | left arrow ← | 155 | 9B | F12 |
| 132 | 84 | Insert | 156 | 9C | Numeric Keypad + |
| 133 | 85 | Delete | 157 | 9D | Numeric Keypad - |
| 134 | 86 | Home | 158 | 9E | Numeric Keypad * |
| 135 | 87 | End | 159 | 9F | Caps Lock |
| 136 | 88 | Page Up | 160 | A0 | Num Lock |
| 137 | 89 | Page Down | 161 | A1 | Left Alt |
| 138 | 8A | Right ALT | 162 | A2 | Left Ctrl |
| 139 | 8B | Right CTRL | 163 | A3 | Left Shift |
| 140 | 8C | Reserved | 164 | A4 | Right Shift |
| 141 | 8D | Reserved | 165 | A5 | Print Screen |

| Alternate Extended ASCII Characters (Continued) | | | | | |
|---|-----|----------------------|-----|-----|--------------------------------|
| DEC | HEX | Keyboard Function | DEC | HEX | Keyboard Function |
| 142 | 8E | Numeric Keypad Enter | 166 | A6 | Tab |
| 143 | 8F | Numeric Keypad / | 167 | A7 | Shift Tab |
| 144 | 90 | F1 | 168 | A8 | Enter |
| 145 | 91 | F2 | 169 | A9 | Esc |
| 146 | 92 | F3 | 170 | AA | Alt Make |
| 147 | 93 | F4 | 171 | AB | Alt Break |
| 148 | 94 | F5 | 172 | AC | Control Make |
| 149 | 95 | F6 | 173 | AD | Control Break |
| 150 | 96 | F7 | 174 | AE | Alt Sequence with 1 Character |
| 151 | 97 | F8 | 175 | AF | Ctrl Sequence with 1 Character |

Function Code Transmit

When this selection is enabled and function codes are contained within the scanned data, the scanner transmits the function code to the terminal. Charts of these function codes are provided in [Symbology Charts](#) starting on [page A-1](#). When the scanner is in keyboard wedge mode, the scan code is converted to a key code before it is transmitted. *Default = Enable*.



RMVFNC0.
* Enable



RMVFNC1.
Disable

Communication Check Character

To enhance security, you can specify the transmission type of a check character; either LRC where the calculation starts on the first transmitted character, LRC where the calculation starts on the second transmitted character, or CRC.

Note: This option adds a check character to the bar code data for all symbologies. If you need to enable or disable check characters for individual symbologies, see [Symbologies](#) beginning on page 8-1.

Scan the following bar code to set the communication check character type. *Default = None*.



HSTXRC0.
* None



HSTXRC1.
LRC Starts on 1st Character



HSTXRC2.
LRC Starts on 2nd Character




HSTXRC3.
CRC

Intercharacter, Interfunction, and Intermassage Delays

Some terminals drop information (characters) if data comes through too quickly. Intercharacter, interfunction, and intermessage delays slow the transmission of data, increasing data integrity.

Intercharacter Delay

An intercharacter delay of up to 327675 milliseconds (in 5ms increments) may be placed between the transmission of each character of scanned data. Scan the following **Intercharacter Delay** bar code, then scan the number of 5ms delays, and the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.



To remove this delay, scan the **Intercharacter Delay** bar code, then set the number of delays to 0. Scan the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.

Note: Intercharacter delays are not supported in USB serial emulation.

User Specified Intercharacter Delay

An intercharacter delay of up to 327675 milliseconds (in 5ms increments) may be placed after the transmission of a particular character of scanned data. Scan the following **Delay Length** bar code, then scan the number of 5ms delays, and the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.


Next, scan the **Character to Trigger Delay** bar code, then the 2-digit hex value for a printable character to trigger the delay (see [Lower ASCII Reference Table](#) on page A-3).



To remove this delay, scan the **Delay Length** bar code, and set the number of delays to 0. Scan the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.

Interfunction Delay

An interfunction delay of up to 327675 milliseconds (in 5ms increments) may be placed between the transmission of each segment of the message string. Scan the following **Interfunction Delay** bar code, then scan the number of 5ms delays, and the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.




DLYFNC.

Interfunction Delay

To remove this delay, scan the **Interfunction Delay** bar code, then set the number of delays to 0. Scan the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.

Intermessage Delay

An intermessage delay of up to 327675 milliseconds (in 5ms increments) may be placed between each scan transmission. Scan the following **Intermessage Delay** bar code, then scan the number of 5ms delays, and the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.



DLYMSG.

Intermessage Delay

To remove this delay, scan the **Intermessage Delay** bar code, then set the number of delays to 0. Scan the **Save** bar code using the [Programming Chart](#) inside the back cover of this manual.

Data Formatting

Data Format Editor Introduction

You may use the Data Format Editor to change the scanner's output. For example, you can use the Data Format Editor to insert characters at certain points in bar code data as it is scanned. The selections in the following pages are used only if you wish to alter the output. *Default Data Format setting = None.*

Normally, when you scan a bar code, it gets outputted automatically; however when you create a format, you must use a "send" command (see [Send Commands](#) on page 7-3) within the format program to output data.

Multiple formats may be programmed into the scanner. They are stacked in the order in which they are entered. However, the following list presents the order in which formats are applied:

1. Specific Terminal ID, Actual Code ID, Actual Length
2. Specific Terminal ID, Actual Code ID, Universal Length
3. Specific Terminal ID, Universal Code ID, Actual Length
4. Specific Terminal ID, Universal Code ID, Universal Length
5. Universal Terminal ID, Actual Code ID, Actual Length
6. Universal Terminal ID, Actual Code ID, Universal Length
7. Universal Terminal ID, Universal Code ID, Actual Length
8. Universal Terminal ID, Universal Code ID, Universal Length

The maximum size of a data format configuration is 256 bytes, which includes header information. No format can contain more than 50 bytes.

If you have changed data format settings, and wish to clear all formats and return to the factory defaults, scan the following **Default Data Format** code.



To Add a Data Format

Step 1. Scan the **Enter Data Format** symbol ([page 7-2](#)).

Step 2. Select **Primary/Alternate Format**

Determine if this will be your primary data format, or one of 3 alternate formats. This allows you to save a total of 4 different data formats. To program your primary format, scan **0** using the [Programming Chart](#) inside the back cover of this manual. If you are programming an alternate format, scan **1**, **2**, or **3**, depending on which alternate format you are programming. (See "Primary/Alternate Data Formats" on page 7-11 for further information.)

Step 3. **Terminal Type**

Refer to [Terminal ID Table](#) (page 7-3) and locate the Terminal ID number for your PC. Scan three numeric bar codes on the [Programming Chart](#) to program the scanner for your terminal ID (you must enter 3 digits). For example, scan **0 0 3** for an AT wedge.

Note: The wildcard for all terminal types is 099.

Step 4. **Code I.D.**

In the [Symbology Charts](#), beginning on page A-1, find the symbology to which you want to apply the data format. Locate the Hex value for that symbology and scan the 2 digit hex value from the [Programming Chart](#) inside the back cover of this manual.

Step 5. **Length**

Specify what length (up to 9999 characters) of data will be acceptable for this symbology. Scan the four digit data length

from the [Programming Chart](#) inside the back cover of this manual. (Note: 50 characters is entered as 0050. 9999 is a universal number, indicating all lengths.)

Step 6. Editor Commands

Refer to (page 7-3). Scan the symbols that represent the command you want to enter.

Step 7. Scan **Save** to save your data format, or **Discard** to exit without saving your changes.



DFMBK3.

Enter Data Format



MNUSAV.

Save



MNUABT.

Discard

Other Programming Selections

Clear One Data Format

This deletes one data format for one symbology. If you are clearing the primary format, scan **0** from the [Programming Chart](#) inside the back cover of this manual. If you are clearing an alternate format, scan **1**, **2**, or **3**, depending on the format you are clearing. Scan the Terminal Type and Code I.D. (see [Symbology Charts](#) on page A-1), and the bar code data length for the specific data format that you want to delete. All other formats remain unaffected.

Clear all Data Formats

This clears all data formats.

Save to exit and save your data format changes.

Discard to exit without saving any data format changes.



DFMCL3.

Clear One Data Format



DFMCA3.

Clear All Data Formats



MNUSAV.

Save



MNUABT.

Discard

Terminal ID Table

| <u>Terminal</u> | <u>Model(s)</u> | <u>Terminal ID</u> |
|-----------------|------------------------------|--------------------|
| IBM | PC/AT and compatibles | 003 |
| | PS2 Keyboard | 002 |
| | USB SurePOS Handheld Scanner | 128 |
| | USB SurePOS Tabletop Scanner | 129 |
| RS232 | True | 000 |
| | TTL | 000 |
| RS485 | | 051 |
| USB | Serial | 130 |
| | PC Keyboard | 124 |
| | Mac Keyboard | 125 |
| | Japanese Keyboard (PC) | 134 |
| | HID POS | 131 |

Data Format Editor Commands

Send Commands

Send all characters

- F1 Include in the output message all of the characters from the input message, starting from current cursor position, followed by an insert character. *Syntax = F1xx* where xx stands for the insert character's hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Send a number of characters

- F2 Include in the output message a number of characters followed by an insert character. Start from the current cursor position and continue for "nn" characters or through the last character in the input message, followed by character "xx." *Syntax = F2nnxx* where nn stands for the numeric value (00-99) for the number of characters, and xx stands for the insert character's hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

F2 Example: Send a number of characters



Send the first 10 characters from the bar code above, followed by a carriage return. Command string: **F2100D**

F2 is the "Send a number of characters" command

10 is the number of characters to send

0D is the hex value for a CR

The data is output as: **1234567890**

F2 and F1 Example: Split characters into 2 lines

Send the first 10 characters from the bar code above, followed by a carriage return, followed by the rest of the characters.

Command string: **F2100DF10D**

F2 is the "Send a number of characters" command

10 is the number of characters to send for the first line

0D is the hex value for a CR

F1 is the "Send all characters" command

0D is the hex value for a CR

The data is output as:

1234567890
ABCDEFGHIJ
<CR>

Send all characters up to a particular character

- F3 Include in the output message all characters from the input message, starting with the character at the current cursor position and continuing to, but not including, the search character “ss,” followed by an insert character. The cursor is moved forward to the “ss” character. *Syntax = F3ssxx* where ss stands for the search character’s hex value for its ASCII code, and xx stands for the insert character’s hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

F3 Example: Send all characters up to a particular character



Using the bar code above, send all characters up to but not including “D,” followed by a carriage return.

Command string: **F3440D**

F3 is the “Send all characters up to a particular character” command

44 is the hex value for a ‘D’

0D is the hex value for a CR

The data is output as:

1234567890ABC
<CR>

Send all but the last characters

- E9 Include in the output message all but the last “nn” characters, starting from the current cursor position. The cursor is moved forward to one position past the last input message character included. *Syntax = E9nn* where nn stands for the numeric value (00-99) for the number of characters that will not be sent at the end of the message.

Insert a character multiple times

- F4 Send “xx” character “nn” times in the output message, leaving the cursor in the current position. *Syntax = F4xxnn* where xx stands for the insert character’s hex value for its ASCII code, and nn is the numeric value (00-99) for the number of times it should be sent. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

E9 and F4 Example: Send all but the last characters, followed by 2 tabs



Send all characters except for the last 8 from the bar code above, followed by 2 tabs.

Command string: **E908F40902**

E9 is the “Send all but the last characters” command

08 is the number of characters at the end to ignore

F4 is the “Insert a character multiple times” command

09 is the hex value for a horizontal tab

02 is the number of times the tab character is sent

The data is output as: **1234567890AB <tab><tab>**

Insert symbology name

- B3 Insert the name of the bar code’s symbology in the output message, without moving the cursor. Only symbologies with a Honeywell ID are included (see [Symbology Charts](#) on page A-1). Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Insert bar code length

- B4 Insert the bar code's length in the output message, without moving the cursor. The length is expressed as a numeric string and does not include leading zeros.

B3 and B4 Example: Insert the symbology name and length



Send the symbology name and length before the bar code data from the bar code above. Break up these insertions with spaces. End with a carriage return.

Command string: **B3F42001B4F42001F10D**

B3 is the "Insert symbology name" command

F4 is the "Insert a character multiple times" command

20 is the hex value for a space

01 is the number of times the space character is sent

B4 is the "Insert bar code length" command

F4 is the "Insert a character multiple times" command

20 is the hex value for a space

01 is the number of times the space character is sent

F1 is the "Send all characters" command

0D is the hex value for a CR

The data is output as:

**Code128 20 1234567890ABCDEFGHIJ
<CR>**

Move Commands

Move the cursor forward a number of characters

- F5 Move the cursor ahead "nn" characters from current cursor position.
Syntax = F5nn where nn is the numeric value (00-99) for the number of characters the cursor should be moved ahead.

F5 Example: Move the cursor forward and send the data



Move the cursor forward 3 characters, then send the rest of the bar code data from the bar code above. End with a carriage return.

Command string: **F503F10D**

F5 is the "Move the cursor forward a number of characters" command

03 is the number of characters to move the cursor

F1 is the "Send all characters" command

0D is the hex value for a CR

The data is output as:

**4567890ABCDEFGHIJ
<CR>**

Move the cursor backward a number of characters

- F6 Move the cursor back "nn" characters from current cursor position.
Syntax = F6nn where nn is the numeric value (00-99) for the number of characters the cursor should be moved back.

Move the cursor to the beginning

F7 Move the cursor to the first character in the input message. *Syntax = F7.*

FE and F7 Example: Manipulate bar codes that begin with a 1



Search for bar codes that begin with a 1. If a bar code matches, move the cursor back to the beginning of the data and send 6 characters followed by a carriage return. Using the bar code above:

Command string: **FE31F7F2060D**

FE is the “Compare characters” command

31 is the hex value for 1

F7 is the “Move the cursor to the beginning” command

F2 is the “Send a number of characters” command

06 is the number of characters to send

0D is the hex value for a CR

The data is output as:

123456

<CR>

Move the cursor to the end

EA Move the cursor to the last character in the input message. *Syntax = EA.*

Search Commands

Search forward for a character

F8 Search the input message forward for “xx” character from the current cursor position, leaving the cursor pointing to the “xx” character. *Syntax = F8xx* where xx stands for the search character’s hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

F8 Example: Send bar code data that starts after a particular character



Search for the letter “D” in bar codes and send all the data that follows, including the “D.” Using the bar code above:

Command string: **F844F10D**

F8 is the “Search forward for a character” command

44 is the hex value for “D”

F1 is the “Send all characters” command

0D is the hex value for a CR

The data is output as:

DEFGHIJ

<CR>

Search backward for a character

F9 Search the input message backward for “xx” character from the current cursor position, leaving the cursor pointing to the “xx” character. *Syntax = F9xx* where xx stands for the search character’s hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Search forward for a string

- B0 Search forward for “s” string from the current cursor position, leaving cursor pointing to “s” string. Syntax = B0nnnnS where nnnn is the string length (up to 9999), and S consists of the ASCII hex value of each character in the match string. For example, B0000454657374 will search forward for the first occurrence of the 4 character string “Test.” Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

B0 Example: Send bar code data that starts after a string of characters



Search for the letters “FGH” in bar codes and send all the data that follows, including “FGH.” Using the bar code above:

Command string: **B00003464748F10D**

B0 is the “Search forward for a string” command

0003 is the string length (3 characters)

46 is the hex value for “F”

47 is the hex value for “G”

48 is the hex value for “H”

F1 is the “Send all characters” command

0D is the hex value for a CR

The data is output as:

FGHIJ

<CR>

Search backward for a string

- B1 Search backward for “s” string from the current cursor position, leaving cursor pointing to “s” string. Syntax = B1nnnnS where nnnn is the string length (up to 9999), and S consists of the ASCII hex value of each character in the match string. For example, B1000454657374 will search backward for the first occurrence of the 4 character string “Test.” Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Search forward for a non-matching character

- E6 Search the input message forward for the first non-“xx” character from the current cursor position, leaving the cursor pointing to the non-“xx” character. Syntax = E6xx where xx stands for the search character’s hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

E6 Example: Remove zeros at the beginning of bar code data



This example shows a bar code that has been zero filled. You may want to ignore the zeros and send all the data that follows. E6 searches forward for the first character that is not zero, then sends all the data after, followed by a carriage return. Using the bar code above:

Command string: **E630F10D**

E6 is the “Search forward for a non-matching character” command

30 is the hex value for 0

F1 is the “Send all characters” command

0D is the hex value for a CR

The data is output as:

37692

<CR>

Search backward for a non-matching character

- E7 Search the input message backward for the first non-“xx” character from the current cursor position, leaving the cursor pointing to the non-“xx” character. *Syntax = E7xx* where xx stands for the search character’s hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Miscellaneous Commands

Suppress characters

- FB Suppress all occurrences of up to 15 different characters, starting at the current cursor position, as the cursor is advanced by other commands. When the FC command is encountered, the suppress function is terminated. The cursor is not moved by the FB command.
Syntax = FBnnxxyy . .zz where nn is a count of the number of suppressed characters in the list, and xxyy .. zz is the list of characters to be suppressed.

FB Example: Remove spaces in bar code data



This example shows a bar code that has spaces in the data. You may want to remove the spaces before sending the data. Using the bar code above:

Command string: **FB0120F10D**

FB is the “Suppress characters” command

01 is the number of character types to be suppressed

20 is the hex value for a space

F1 is the “Send all characters” command

0D is the hex value for a CR

The data is output as:

34567890

<CR>

Stop suppressing characters

- FC Disables suppress filter and clear all suppressed characters. *Syntax = FC.*

Replace characters

- E4 Replaces up to 15 characters in the output message, without moving the cursor. Replacement continues until the E5 command is encountered. *Syntax = E4nnxx₁xx₂yy₁yy₂...zz₁zz₂* where nn is the total count of the number of characters in the list (characters to be replaced plus replacement characters); xx₁ defines characters to be replaced and xx₂ defines replacement characters, continuing through zz₁ and zz₂.

E4 Example: Replace zeroes with CRs in bar code data



If the bar code has characters that the host application does not want included, you can use the E4 command to replace those characters with something else. In this example, you will replace the zeroes in the bar code above with carriage returns.

Command string: **E402300DF10D**

E4 is the “Replace characters” command

02 is the total count of characters to be replaced, plus the replacement characters (0 is replaced by CR, so total characters = 2)

30 is the hex value for 0

0D is the hex value for a CR (the character that will replace the 0)

F1 is the “Send all characters” command

0D is the hex value for a CR

The data is output as:

1234

5678

ABC

<CR>

Stop replacing characters

E5 Terminates character replacement. *Syntax = E5.*

Compare characters

FE Compare the character in the current cursor position to the character "xx." If characters are equal, move the cursor forward one position. *Syntax = FExx* where xx stands for the comparison character's hex value for its ASCII code. Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Compare string

B2 Compare the string in the input message to the string "s." If the strings are equal, move the cursor forward past the end of the string. *Syntax = B2nnnnS* where nnnn is the string length (up to 9999), and S consists of the ASCII hex value of each character in the match string. For example, B2000454657374 will compare the string at the current cursor position with the 4 character string "Test." Refer to the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2 for decimal, hex and character codes.

Check for a number

EC Check to make sure there is an ASCII number at the current cursor position. The format is aborted if the character is not numeric.

EC Example: Only output the data if the bar code begins with a number


If you want only data from bar codes that begin with a number, you can use EC to check for the number.

Command string: **ECF10D**

EC is the "Check for a number" command

F1 is the "Send all characters" command

0D is the hex value for a CR

If this bar code is read,  the next data format, if there is one, will be used on the data. If there is no other format, the format fails and the raw data is output as **AB1234**.

is no other format, the format fails and the raw data is output as **AB1234**.

If this bar code is read:  the data is output as:
1234AB

1234AB

<CR>

Check for non-numeric character

ED Check to make sure there is a non-numeric ASCII character at the current cursor position. The format is aborted if the character is numeric.

ED Example: Only output the data if the bar code begins with a letter


If you want only data from bar codes that begin with a letter, you can use ED to check for the letter.

Command string: **EDF10D**

ED is the "Check for a non-numeric character" command

F1 is the "Send all characters" command

0D is the hex value for a CR

If this bar code is read,  the next data format, if there is one, will be used on this data. If there is no other format, the format fails and the raw data is output as **1234AB**.

If this bar code is read:  the data is output as:

AB1234
<CR>

Insert a delay

EF Inserts a delay of up to 49,995 milliseconds (in multiples of 5), starting from the current cursor position. Syntax = EFnnnn where nnnn stands for the delay in 5ms increments, up to 9999. This command can only be used with keyboard wedge interfaces.

Data Formatter

When Data Formatter is turned Off, the bar code data is output to the host as read, including prefixes and suffixes.



You may wish to require the data to conform to a data format you have created and saved. The following settings can be applied to your data format:

Data Formatter On, Not Required, Keep Prefix/Suffix

Scanned data is modified according to your data format, and prefixes and suffixes are transmitted.

Data Formatter On, Not Required, Drop Prefix/Suffix

Scanned data is modified according to your data format. If a data format is found for a particular symbol, those prefixes and suffixes are not transmitted.

Data Format Required, Keep Prefix/Suffix

Scanned data is modified according to your data format, and prefixes and suffixes are transmitted. Any data that does not match your data format requirements generates an error tone and the data in that bar code is not transmitted. If you wish to process this type of bar code without generating an error tone, see [Data Format Non-Match Error Tone](#).

Data Format Required, Drop Prefix/Suffix

Scanned data is modified according to your data format. If a data format is found for a particular symbol, those prefixes and suffixes are not transmitted. Any data that does not match your data format requirements generates an error tone. If you wish to process this type of bar code without generating an error tone, see [Data Format Non-Match Error Tone](#).

Choose one of the following options. *Default = Data Formatter On, Not Required, Keep Prefix/Suffix.*



DFM_EN1.
*** Data Formatter On,
Not Required,
Keep Prefix/Suffix**



DFM_EN3.
**Data Formatter On,
Not Required,
Drop Prefix/Suffix**



DFM_EN2.
Data Format Required,
Keep Prefix/Suffix



DFM_EN4.
Data Format Required,
Drop Prefix/Suffix

Data Format Non-Match Error Tone

When a bar code is encountered that doesn't match your required data format, the scanner normally generates an error tone. However, you may want to continue scanning bar codes without hearing the error tone. If you scan the **Data Format Non-Match Error Tone Off** bar code, data that doesn't conform to your data format is not transmitted, and no error tone will sound. If you wish to hear the error tone when a non-matching bar code is found, scan the **Data Format Non-Match Error Tone On** bar code. *Default = Data Format Non-Match Error Tone On.*



DFMDECO.
* Data Format Non-Match Error
Tone On



DFMDEC1.
Data Format Non-Match
Error Tone Off

Primary/Alternate Data Formats

You can save up to four data formats, and switch between these formats. Your primary data format is saved under **0**. Your other three formats are saved under **1**, **2**, and **3**. To set your device to use one of these formats, scan one of the following bar codes.



ALTFNMO.
Primary Data Format



ALTFNM1.
Data Format 1



ALTFNM2.
Data Format 2



ALTFNM3.
Data Format 3

Single Scan Data Format Change

You can also switch between data formats for a single scan. The next bar code is scanned using an alternate data format, then reverts to the format you have selected above (either Primary, 1, 2, or 3).

For example, you may have set your device to the data format you saved as Data Format 3. You can switch to Data Format 1 for a single button press by scanning the following **Single Scan-Data Format 1** bar code. The next bar code that is scanned uses Data Format 1, then reverts back to Data Format 3.



VSAF_0.

**Single Scan-Primary
Data Format**



VSAF_2.

Single Scan-Data Format 2



VSAF_1.

Single Scan-Data Format 1



VSAF_3.

Single Scan-Data Format 3

Symbologies

This programming section contains the following menu selections. Refer to [Chapter 10](#) for settings and defaults.

- All Symbologies
- Airline Code 5 - see Straight 2 of 5 IATA (two-bar start/stop)
- China Post (Hong Kong 2 of 5)
- Codabar
- Code 11
- Code 128
- Code 32 Pharmaceutical (PARAF)
- Code 39
- Code 93
- EAN/JAN-13
- EAN/JAN-8
- GS1 DataBar Expanded
- GS1 DataBar Limited
- GS1 DataBar Omnidirectional
- GS1 Emulation
- GS1-128
- Interleaved 2 of 5
- ISBT 128 Concatenation
- Matrix 2 of 5
- MSI
- NEC 2 of 5
- Plessey Code
- Postal Codes
- Straight 2 of 5 IATA (two-bar start/stop)
- Straight 2 of 5 Industrial (three-bar start/stop)
- Telepen
- Trioptic Code
- UPC-A
- UPC-A/EAN-13 with Extended Coupon Code
- UPC-E0

All Symbologies

If you want to decode all the symbologies allowable for your scanner, scan the **All Symbologies On** code. If on the other hand, you want to decode only a particular symbology, scan **All Symbologies Off** followed by the On symbol for that particular symbology.

Note: Scanner performance may be slower when using All Symbologies. Enable just the necessary symbologies to improve scanner performance.



ALLENA1.
All Symbologies On



ALLENA0.
All Symbologies Off

Message Length Description

You are able to set the valid reading length of some of the bar code symbologies. You may wish to set the same value for minimum and maximum length to force the scanner to read fixed length bar code data. This helps reduce the chances of a misread.

EXAMPLE: Decode only those bar codes with a count of 9-20 characters.
Min. length = 09Max. length = 20

EXAMPLE: Decode only those bar codes with a count of 15 characters.
Min. length = 15Max. length = 15

For a value other than the minimum and maximum message length defaults, scan the bar codes included in the explanation of the symbology, then scan the digit value of the message length and **Save** bar codes on the [Programming Chart](#) inside the back cover of this manual. The minimum and maximum lengths and the defaults are included with the respective symbologies.

Codabar

<Default All Codabar Settings>



Codabar On/Off



Codabar Start/Stop Characters

Start/Stop characters identify the leading and trailing ends of the bar code. You may either transmit, or not transmit Start/Stop characters. *Default = Don't Transmit.*



Codabar Check Character

Codabar check characters are created using different "modulos." You can program the scanner to read only Codabar bar codes with Modulo 16, Modulo 7 CD, or CLSI check characters. *Default = No Check Character.*

No Check Character indicates that the scanner reads and transmits bar code data with or without a check character.

When Check Character is set to **Validate and Transmit**, the scanner will only read Codabar bar codes printed with a check character, and will transmit this character at the end of the scanned data.

When Check Character is set to **Validate, but Don't Transmit**, the unit will only read Codabar bar codes printed **with** a check character, but will not transmit the check character with the scanned data.





CBRCK22.
Validate Modulo 16
and Transmit



CBRCK23.
Validate Modulo 7 CD, but Don't
Transmit



CBRCK24.
Validate Modulo 7 CD and
Transmit



CBRCK25.
Validate CLSI, but Don't
Transmit



CBRCK26.
Validate CLSI and Transmit

Codabar Concatenation

Codabar supports symbol concatenation. When you enable concatenation, the scanner looks for a “D” start character, adjacent to a symbol having a “D” stop character. In this case the two messages are concatenated into one with the “D” characters omitted.



Select Require to prevent the scanner from decoding a single “D” Codabar symbol without its companion. This selection has no effect on Codabar symbols without Stop/Start D characters.



CBRCCT1.
On



CBRCCT0.
* Off



CBRCCT2.
Require

Concatenation Timeout

When searching for bar codes during concatenation, you may wish to set a delay used to find the next bar code. Set the length (in milliseconds) for this delay by scanning the following bar code, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 750.*



Codabar Redundancy

If you are encountering errors when reading Codabar bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the following **Codabar Redundancy** bar code, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Codabar Message Length

Scan the following bar codes to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



Code 39

< Default All Code 39 Settings >



Code 39 On/Off



Code 39 Start/Stop Characters

Start/Stop characters identify the leading and trailing ends of the bar code. You may either transmit, or not transmit Start/Stop characters. *Default = Don't Transmit.*



Code 39 Check Character

No Check Character indicates that the scanner reads and transmits bar code data with or without a check character.

When Check Character is set to **Validate, but Don't Transmit**, the unit only reads Code 39 bar codes printed with a check character, but will not transmit the check character with the scanned data.

When Check Character is set to **Validate and Transmit**, the scanner only reads Code 39 bar codes printed with a check character, and will transmit this character at the end of the scanned data. *Default = No Check Character.*



Code 39 Redundancy

If you are encountering errors when reading Code 39 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Code 39 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



C39VOT.

Code 39 Redundancy

Code 39 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



C39MIN.

Minimum Message Length



C39MAX.

Maximum Message Length

Code 32 Pharmaceutical (PARAF)

Code 32 Pharmaceutical is a form of the Code 39 symbology used by Italian pharmacies. This symbology is also known as PARAF.



C39B321.

On



C39B320.

* Off

Full ASCII

If Full ASCII Code 39 decoding is enabled, certain character pairs within the bar code symbol will be interpreted as a single character. For example: \$V will be decoded as the ASCII character SYN, and /C will be decoded as the ASCII character #. *Default = Off.*

| | | | | | | | |
|---------|---------|----------|------|------|------|------|--------|
| NUL %U | DLE \$P | SP SPACE | 0 0 | @ %V | P P | ' %W | p +P |
| SOH \$A | DC1 \$Q | ! /A | 1 1 | A A | Q Q | a +A | q +Q |
| STX \$B | DC2 \$R | " /B | 2 2 | B B | R R | b +B | r +R |
| ETX \$C | DC3 \$S | # /C | 3 3 | C C | S S | c +C | s +S |
| EOT \$D | DC4 \$T | \$ /D | 4 4 | D D | T T | d +D | t +T |
| ENQ \$E | NAK \$U | % /E | 5 5 | E E | U U | e +E | u +U |
| ACK \$F | SYN \$V | & /F | 6 6 | F F | V V | f +F | v +V |
| BEL \$G | ETB \$W | ' /G | 7 7 | G G | W W | g +G | w +W |
| BS \$H | CAN \$X | (/H | 8 8 | H H | X X | h +H | x +X |
| HT \$I | EM \$Y |) /I | 9 9 | I I | Y Y | i +I | y +Y |
| LF \$J | SUB \$Z | * /J | : /Z | J J | Z Z | j +J | z +Z |
| VT \$K | ESC %A | + /K | ; %F | K K | [%K | k +K | { %P |
| FF \$L | FS %B | , /L | < %G | L L | \ %L | l +L | %Q |
| CR \$M | GS %C | - - | = %H | M M |] %M | m +M | } %R |
| SO \$N | RS %D | . . | > %I | N N | ^ %N | n +N | ~ %S |
| SI \$O | US %E | / /O | ? %J | O O | _ %O | o +O | DEL %T |

Character pairs /M and /N decode as a minus sign and period respectively.

Character pairs /P through /Y decode as 0 through 9.



C39ASC1.
Full ASCII On



C39ASC0.
* Full ASCII Off

Interleaved 2 of 5

< Default All Interleaved 2 of 5 Settings >



Interleaved 2 of 5 On/Off



NULL Characters

Interleaved 2 of 5 requires an even number of characters. When an odd number of characters is present, it is due to NULL characters embedded in the bar code. Scan the **On** bar code below to decode this type of Interleaved 2 of 5 bar code.

Default = Off.



Check Digit

No Check Digit indicates that the scanner reads and transmits bar code data with or without a check digit.

When Check Digit is set to **Validate, but Don't Transmit**, the unit only reads Interleaved 2 of 5 bar codes printed with a check digit, but will not transmit the check digit with the scanned data.

When Check Digit is set to **Validate and Transmit**, the scanner only reads Interleaved 2 of 5 bar codes printed with a check digit, and will transmit this digit at the end of the scanned data. *Default = No Check Digit.*





I25CK22.

Validate and Transmit

Interleaved 2 of 5 Redundancy

If you are encountering errors when reading Interleaved 2 of 5 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Interleaved 2 of 5 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



I25VOT.

Interleaved 2 of 5 Redundancy

Interleaved 2 of 5 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 6, Maximum Default = 80.



I25MIN.

Minimum Message Length



I25MAX.

Maximum Message Length

NEC 2 of 5

< Default All NEC 2 of 5 Settings >



N25DFT.

NEC 2 of 5 On/Off



N25ENA1.

On



N25ENA0.

* Off

Check Digit

No Check Digit indicates that the scanner reads and transmits bar code data with or without a check digit.

When Check Digit is set to **Validate, but Don't Transmit**, the unit only reads NEC 2 of 5 bar codes printed with a check digit, but will not transmit the check digit with the scanned data.

When Check Digit is set to **Validate and Transmit**, the scanner only reads NEC 2 of 5 bar codes printed with a check digit, and will transmit this digit at the end of the scanned data. *Default = No Check Digit.*



N25CK20.

* No Check Digit



N25CK21.

Validate, but Don't Transmit



N25CK22.

Validate and Transmit

NEC 2 of 5 Redundancy

If you are encountering errors when reading NEC 2 of 5 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors.

Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **NEC 2 of 5 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



N25VOT.

NEC 2 of 5 Redundancy

NEC 2 of 5 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



N25MIN.

Minimum Message Length



N25MAX.

Maximum Message Length

Code 93

< Default All Code 93 Settings >



Code 93 On/Off



Code 93 Redundancy

If you are encountering errors when reading Code 93 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Code 93 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Code 93 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



Straight 2 of 5 Industrial (three-bar start/stop)

<Default All Straight 2 of 5 Industrial Settings>



Straight 2 of 5 Industrial On/Off



Straight 2 of 5 Industrial Redundancy

If you are encountering errors when reading Straight 2 of 5 Industrial bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Straight 2 of 5 Industrial Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Straight 2 of 5 Industrial Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



Straight 2 of 5 IATA (two-bar start/stop)

<Default All Straight 2 of 5 IATA Settings>



Straight 2 of 5 IATA On/Off



Straight 2 of 5 IATA Redundancy

If you are encountering errors when reading Straight 2 of 5 IATA bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Straight 2 of 5 IATA Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Straight 2 of 5 IATA Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 13, Maximum Default = 15.



Matrix 2 of 5

<Default All Matrix 2 of 5 Settings>



Matrix 2 of 5 On/Off



Matrix 2 of 5 Check Character

No Check Character indicates that the scanner reads and transmits bar code data with or without a check character.

When Check Character is set to **Validate, but Don't Transmit**, the unit only reads Matrix 2 of 5 bar codes printed with a check character, but will not transmit the check character with the scanned data.

When Check Character is set to **Validate and Transmit**, the scanner only reads Matrix 2 of 5 bar codes printed with a check character, and will transmit this character at the end of the scanned data. *Default = No Check Character.*



Matrix 2 of 5 Redundancy

If you are encountering errors when reading Matrix 2 of 5 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Matrix 2 of 5 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Matrix 2 of 5 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



X25MIN.

Minimum Message Length



X25MAX.

Maximum Message Length

Code 11

<Default All Code 11 Settings>



C11DFT.

Code 11 On/Off



C11ENA1.

On



C11ENA0.

* Off

Check Digits Required

These options set whether 1 or 2 check digits are required with Code 11 bar codes. **Auto Select Check Digits** determines the number of check digits based on the length of the bar code. If the bar code is 10 digits or more, 2 check digits are required. If it is 9 digits or less, 1 check digit is required. The check digit data is only transmitted if you program that feature (see [Check Digit Validation](#) on page 8-16). *Default = Two Check Digits Required.*



C11CK20.

One Check Digit Required



C11CK21.

* Two Check Digits Required



C11CK22.

Auto Select Check Digits
Required

Check Digit Validation

When Check Character is set to **Validate and Transmit**, the scanner will only read Code 11 bar codes printed with the specified type check character(s), and will transmit the character(s) at the end of the scanned data.



C11CK23.

**Validate and Transmit One
Check Digit**



C11CK24.

**Validate and Transmit Two
Check Digits**



C11CK25.

**Validate and Transmit Auto
Select Check Digits**

Code 11 Redundancy

If you are encountering errors when reading Code 11 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Code 11 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



C11VOT.

Code 11 Redundancy

Code 11 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



C11MIN.

Minimum Message Length



C11MAX.

Maximum Message Length

Code 128

<Default All Code 128 Settings>



Code 128 On/Off



128 Group Separator Output

If you wish to transmit embedded FNC1 characters as group separators (1B hex) with your Code 128 bar code output, scan the **On** bar code. When **Off** is scanned, nothing is transmitted for FNC1 characters. *Default = Off.*



Code 128 Redundancy

If you are encountering errors when reading Code 128 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Code 128 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Code 128 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



128MIN.

Minimum Message Length



128MAX.

Maximum Message Length

ISBT 128 Concatenation

In 1994 the International Society of Blood Transfusion (ISBT) ratified a standard for communicating critical blood information in a uniform manner. The use of ISBT formats requires a paid license. The ISBT 128 Application Specification describes 1) the critical data elements for labeling blood products, 2) the current recommendation to use Code 128 due to its high degree of security and its space-efficient design, 3) a variation of Code 128 that supports concatenation of neighboring symbols, and 4) the standard layout for bar codes on a blood product label. Use the bar codes below to turn concatenation on or off. *Default = Off.*



ISBENA1.

On



ISBENA0.

*** Off**

Concatenation Timeout

When searching for bar codes during concatenation, you may wish to set a delay used to find the next bar code. Set the length (in milliseconds) for this delay by scanning the bar code below, then setting the timeout (from 1-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 750.*



DLYCCT.

Concatenation Timeout

ISBT 128 Predefined Concatenation Sequences

Note: You must enable Code 128 and ISBT 128 to use this feature.

The following bar codes are used to select the pre-defined ISBT 128 Concatenation Sequence you wish to use. Once you have selected the concatenation sequence, use [ISBT 128 Predefined Concatenation Sequences On/Off](#) to enable this feature. Default = Donation ID Number (001)

and ABO/RhD Blood Groups (002).



ISBPCS0.

* Donation ID Number (001)
and ABO/RhD Blood Groups (002)



ISBPCS2.

Donation ID Number (001) and
Confidential Unit Exclusion
Status



ISBPCS4.

Product Code (003) and
Expiration Date (Form 2)



ISBPCS6.

Product Code (003) and
Expiration Date (Form 4)



ISBPCS1.

Donation ID Number (001) and
Donor ID Number (019)



ISBPCS3.

Product Code (003) and
Expiration Date (Form 1)



ISBPCS5.

Product Code (003) and
Expiration Date (Form 3)

ISBT 128 Predefined Concatenation Sequences On/Off

The following selections allow you to enable or require the Predefined ISBT 128 Concatenation Sequences.

If you scan **Off**, the predefined concatenation sequences are disabled.

If you scan the **Allow Predefined Sequence** code, then the scanner will output only the data combination specified in the predefined concatenation sequence you selected.

If you scan the **Require Predefined Sequence** code, the data combination specified in the predefined concatenation sequence you selected is required to transmit the data. No data is output unless the sequence is read.

Default = Off.



ISBT 128 User-Defined Concatenation Sequences

Note: You must enable Code 128 and ISBT 128 to use this feature.

The following bar codes are used to create a custom ISBT 128 Concatenation Sequence. Select the identifiers you want to transmit in the 1st and 2nd positions, both left and right. Refer to the ISBT 128 Standard Technical Specification for the list of data identifiers.

Use the [ASCII Conversion Chart \(Code Page 1252\)](#), page A-2, to find the characters needed for the identifier. Locate the hex value for each character and scan that 2 digit/character value from the [Programming Chart](#) inside the back cover of this manual.

Example: You want to create a concatenation sequence that has the Donation Identification Number (001) as the left identifier, and Product Code (003) as the right identifier.

The ISBT Index of Data Structures shows that for the Donation Identification Number, the first character is “=” and the second character can be from A-N; P-Z; 1-9. For this example, use “G.” The Product Code first character is “=” and the second character is “<.”

- Step 1.** Scan the **1st Left Identifier** bar code, below.
- Step 2.** Use the [Programming Chart](#) to scan **3, D** (hex for “=”).
- Step 3.** Scan **Save**.
- Step 4.** Scan the **2nd Left Identifier** bar code, below.
- Step 5.** Use the [Programming Chart](#) to scan **4, 7** (hex for “G”).
- Step 6.** Scan **Save**.
- Step 7.** Scan the **1st Right Identifier** bar code, below.
- Step 8.** Use the [Programming Chart](#) to scan **3, D** (hex for “=”).
- Step 9.** Scan **Save**.
- Step 10.** Scan the **2nd Right Identifier** bar code, below.
- Step 11.** Use the [Programming Chart](#) to scan **3, C** (hex for “<”).
- Step 12.** Scan **Save**.

Once you have programmed the concatenation sequence, use [ISBT 128 User-Defined Concatenation Sequences](#) to enable this feature. *Default = 0.*





ISBUR1.
1st Right Identifier



ISBUL2.
2nd Left Identifier



ISBUR2.
2nd Right Identifier

ISBT 128 User-Defined Concatenation Sequences On/Off

The following selections allow you to enable or require the User-Defined ISBT 128 Concatenation Sequences.

If you scan **Off**, the User-Defined concatenation sequences are disabled.

If you scan the **Allow User-Defined Sequence** code, then the scanner will output only the data combination specified in the User-Defined concatenation sequence you created.

If you scan the **Require User-Defined Sequence** code, the data combination specified in the User-Defined concatenation sequence is required to transmit the data. No data is output unless the sequence is read.

Default = Off.



ISBUCE0.
* Off



ISBUCE1.
Allow User-Defined Sequence



ISBUCE2.
Require User-Defined Sequence

Content Verification

When the **On** bar code is scanned, the check character values are output along with the bar code data, thus allowing you to verify that the check character is in agreement with that calculated for the data stream. *Default = Off.*



ISBXM01.
On



ISBXM00.
* Off

Transmit Identifiers

You may disable the transmission of the ISBT Code 128 data identifiers by scanning **Off**. When this selection is **Off**, the first 2 data (ID) characters are removed from the data stream unless the ISBT code contains the Donation Identification Number identifiers. If the code contains the Donation Identification Number identifiers, only the first ID character is removed from the Donation Identification Number. The second character is transmitted as normal data. *Default = On.*



ISBXM11.

* **On**



ISBXM10.

Off

Flag Digit Conversion

Type 3 flag digits are a part of the Donation Identification Number in an ISBT 128 bar code. If you select **On**, the flag data is converted into a single MOD (37, 2) character and transmitted with the bar code data. Scan **Off** if you do not want the flag digits transmitted. *Default = Off.*



ISBXM21.

On



ISBXM20.

* **Off**

GS1-128

<Default All GS1-128 Settings>



GS1-128 On/Off



GS1-128 Application Identifier Parsing

This allows a single GS1-128 bar code to be broken into multiple transmissions based on the presence of application identifiers (AI) embedded in the bar code. To use this feature, first enable [128 Group Separator Output](#) (page 8-17). Next, scan **Transmit Without Identifiers** if you want the bar code stripped of the AI. If you want the bar code broken into packets and AI included, scan **Transmit With Identifiers**. *Default = Off.*



GS1-128 Redundancy

If you are encountering errors when reading GS1-128 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **GS1-128 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



GS1-128 Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



GS1MIN.

Minimum Message Length



GS1MAX.

Maximum Message Length

Telepen

<Default All Telepen Settings>



TELDFT.

Telepen On/Off



TELENA1.

On



TELENA0.

* Off

Telepen Output

Using AIM Telepen Output, the scanner reads symbols with start/stop pattern 1 and decodes them as standard full ASCII (start/stop pattern 1). When Original Telepen Output is selected, the scanner reads symbols with start/stop pattern 1 and decodes them as compressed numeric with optional full ASCII (start/stop pattern 2). *Default = AIM Telepen Output.*



TELOLD0.

* AIM Telepen Output



TELOLD1.

Original Telepen Output

Telepen Redundancy

If you are encountering errors when reading Telepen bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Telepen Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



TELVOT.

Telepen Redundancy

Telepen Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



TELMIN.

Minimum Message Length



TELMAX.

Maximum Message Length

UPC-A

<Default All UPC-A Settings>



UPADFT.

UPC-A On/Off



UPBENA1.

* On



UPBENA0.

Off

Note: To convert UPC-A bar codes to EAN-13, see [Convert UPC-A to EAN-13](#) on page 8-33.

UPC-A Number System and Check Digit

UPC-A sample showing the number system and check digit:



UPC-A Check Digit

This selection allows you to specify whether the check digit should be transmitted at the end of the scanned data or not. *Default = On.*



UPC-A Number System

The numeric system digit of a U.P.C. symbol is normally transmitted at the beginning of the scanned data, but the unit can be programmed so it will not transmit it. *Default = On.*



UPC-A Addenda

This selection adds 2 or 5 digits to the end of all scanned UPC-A data. *Default = Off for both 2 Digit and 5 Digit Addenda.*





UPC-A Addenda Required

When **Required** is scanned, the scanner will only read UPC-A bar codes that have addenda. You must then turn on a 2 or 5 digit addenda listed on [page 8-26](#). *Default = Not Required.*



Addenda Timeout

You can set a time during which the scanner looks for an addenda. If an addenda is not found within this time period, the data can be either transmitted or discarded, based on the setting you are using for [UPC-A Addenda Required](#) (see page 8-27). Set the length (in milliseconds) for this timeout by scanning the bar code below, then setting the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 100.*

Note: The Addenda Timeout setting is applied to all addenda and coupon code searches.



UPC-A Addenda Separator

When this feature is on, there is a space between the data from the bar code and the data from the addenda. When turned off, there is no space. *Default = Off.*



UPC-A Redundancy

If you are encountering errors when reading UPC-A bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **UPC-A Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



UPC-A/EAN-13 with Extended Coupon Code

Use the following codes to enable or disable UPC-A and EAN-13 with Extended Coupon Code. When left on the default setting (**Off**), the scanner treats Coupon Codes and Extended Coupon Codes as single bar codes.

If you scan the **Allow Concatenation** code, when the scanner sees the coupon code and the extended coupon code in a single scan, it transmits both as one symbology. Otherwise, it transmits the first coupon code it reads.

If you scan the **Require Concatenation** code, the scanner must see and read the coupon code and extended coupon code in a single read to transmit the data. No data is output unless both codes are read. *Default = Off.*



UPC-A Number System 4 Addenda Required

This setting programs the scanner to require a coupon code only on UPC-A bar codes that begin with a “4.” The following settings can be programmed:

Require Coupon Code: All UPC-A bar codes that begin with a “4” must have a coupon code. The UPC-A bar code with the coupon code is then transmitted as a single, concatenated bar code. If a coupon code is not found within the [Addenda Timeout](#) period, the UPC-A bar code is discarded.

Don't Require Coupon Code: If you have selected **Require Coupon Code**, and you want to disable this feature, scan **Don't Require Coupon Code**. UPC-A bar codes are transmitted, depending on the setting you are using for [UPC-A/EAN-13 with Extended Coupon Code](#).

Default = Don't Require Coupon Code.





ARQSY41.
Require Coupon Code

UPC-A Number System 5 Addenda Required

This setting programs the scanner to require any combination of a coupon code, a 2 digit addenda, or a 5 digit addenda on UPC-A bar codes that begin with a "5." The following settings can be programmed:

Require Coupon Code/Addenda: All UPC-A bar codes that begin with a "5" must have a coupon code, a 2 digit addenda, a 5 digit addenda, or a combination of these addenda. The UPC-A bar code with the coupon code and/or addenda is then transmitted as a single, concatenated bar code. If a coupon code and/or required addenda is not found within the [Addenda Timeout](#) period, the UPC-A bar code is discarded.

Don't Require Coupon Code/Addenda: If you have selected **Require Coupon Code/Addenda**, and you want to disable this feature, scan **Don't Require Coupon Code/Addenda**. UPC-A bar codes are transmitted, depending on the setting you are using for [UPC-A/EAN-13 with Extended Coupon Code](#).

Default = Don't Require Coupon Code/Addenda.



ARQSY50.

* Don't Require Coupon Code/
Addenda



ARQSY51.

Require 2 Digit Addenda



ARQSY52.

Require 5 Digit Addenda



ARQSY53.

Require 2 or 5 Digit Addenda



ARQSY54.

Require Coupon Code



ARQSY55.

Require Coupon Code or 2 Digit
Addenda



ARQSY56.

Require Coupon Code or 5 Digit
Addenda



ARQSY57.

Require Coupon Code, 2 Digit Addenda, or 5 Digit Addenda

Addenda Timeout

You can set a time during which the scanner looks for a coupon code. If a coupon code is not found within this time period, the data can be either transmitted or discarded, based on the setting you are using for [UPC-A/EAN-13 with Extended Coupon Code](#) or [UPC-A Number System 4 Addenda Required](#). Set the length (in milliseconds) for this timeout by scanning the bar code below, then setting the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 100.*

Note: The Addenda Timeout setting is applied to all addenda and coupon code searches.



DLYADD.

Addenda Timeout

UPC-E0

<Default All UPC-E0 Settings>



UPEDFT.

UPC-E0 On/Off

Most U.P.C. bar codes lead with the 0 number system. To read these codes, use the **UPC-E0 On** selection. If you need to read codes that lead with the 1 number system, use [EAN/JAN-13](#) (page 8-33). *Default = On.*



UPEEND01.

* UPC-E0 On



UPEEND00.

UPC-E0 Off

UPC-E0 Expand

UPC-E Expand expands the UPC-E code to the 12 digit, UPC-A format. *Default = Off.*



UPEEXP1.

On



UPEEXP0.

* Off

UPC-E0 Number System

The numeric system digit of a UPC-A symbol is normally transmitted at the beginning of scanned data. When using UPC-E Expand, the unit can be programmed so it will not transmit it. *Default = On.*



UPEEXN1.

* On



UPEEXN0.

Off

UPC-E0 Number System and Check Digit

UPC-E0 sample showing the number system and check digit:



UPC-E0 Check Digit

Check Digit specifies whether the check digit should be transmitted at the end of the scanned data or not. *Default = Off.*



UPECKX1.

On



UPECKX0.

* Off

UPC-E0 Leading Zero

This feature allows the transmission of a leading zero (0) at the beginning of scanned data. To prevent transmission, scan **Off**. *Default = Off.*



UPENSX1.

On



UPENSX0.

* Off

UPC-E0 Addenda

This selection adds 2 or 5 digits to the end of all scanned UPC-E data. *Default = Off for both 2 Digit and 5 Digit Addenda.*



UPEAD21.

2 Digit Addenda On



UPEAD20.

* 2 Digit Addenda Off



UPEAD51.

5 Digit Addenda On



UPEAD50.

* 5 Digit Addenda Off

UPC-E0 Addenda Required

When **Required** is scanned, the scanner will only read UPC-E bar codes that have addenda. *Default = Not Required.*



UPEARQ1.

Required



UPEARQ0.

* Not Required

Addenda Timeout

You can set a time during which the scanner looks for an addenda. If an addenda is not found within this time period, the data can be either transmitted or discarded, based on the setting you are using for [UPC-E0 Addenda Required](#) (page 8-32). Set the length (in milliseconds) for this timeout by scanning the bar code below, then setting the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 100.*

Note: The Addenda Timeout setting is applied to all addenda and coupon code searches.



DLYADD.

Addenda Timeout

UPC-E0 Addenda Separator

When this feature is **On**, there is a space between the data from the bar code and the data from the addenda. When turned **Off**, there is no space. *Default = Off.*



UPC-E0 Redundancy

If you are encountering errors when reading UPC-E0 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **UPC-E0 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 1.*



EAN/JAN-13

<Default All EAN/JAN Settings>



EAN/JAN-13 On/Off



Convert UPC-A to EAN-13

When **UPC-A Converted to EAN-13** is selected, UPC-A bar codes are converted to 13 digit EAN-13 codes by adding a zero to the front. When **Do not Convert UPC-A** is selected, UPC-A codes are read as UPC-A.





UPAENA1.

* Do not Convert UPC-A

EAN/JAN-13 Check Digit

This selection allows you to specify whether the check digit should be transmitted at the end of the scanned data or not. *Default = On.*



E13CKX1.

* On



E13CKX0.

Off

EAN/JAN-13 Addenda

This selection adds 2 or 5 digits to the end of all scanned EAN/JAN-13 data. *Default = Off for both 2 Digit and 5 Digit Addenda.*



E13AD21.

2 Digit Addenda On



E13AD20.

* 2 Digit Addenda Off



E13AD51.

5 Digit Addenda On



E13AD50.

* 5 Digit Addenda Off

EAN/JAN-13 Addenda Required

When **Required** is scanned, the scanner will only read EAN/JAN-13 bar codes that have addenda. *Default = Not Required.*



E13ARQ1.

Required



E13ARQ0.

* Not Required

EAN-13 Beginning with 2 Addenda Required

This setting programs the scanner to require a 2 digit addenda only on EAN-13 bar codes that begin with a “2.” The following settings can be programmed:

Require 2 Digit Addenda: All EAN-13 bar codes that begin with a “2” must have a 2 digit addendum. The EAN-13 bar code with the 2 digit addendum is then transmitted as a single, concatenated bar code. If a 2 digit addendum is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Note: if you are using [EAN-13 Beginning with 290 Addenda Required](#) (page 8-35), that setting will take precedence over this one.

Don't Require 2 Digit Addenda: If you have selected **Require 2 Digit Addenda**, and you want to disable this feature, scan **Don't Require 2 Digit Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require 2 Digit Addenda.



ARQSY20.

* Don't Require 2 Digit Addenda



ARQSY21.

Require 2 Digit Addenda

EAN-13 Beginning with 290 Addenda Required

This setting programs the scanner to require a 5 digit addenda only on EAN-13 bar codes that begin with “290.” The following settings can be programmed:

Require 5 Digit Addenda: All EAN-13 bar codes that begin with “290” must have a 5 digit addendum. The EAN-13 bar code with the 5 digit addendum is then transmitted as a single, concatenated bar code. If a 5 digit addendum is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Note: if you are using [EAN-13 Beginning with 2 Addenda Required](#) (page 8-35), this setting will take precedence.

Don't Require 5 Digit Addenda: If you have selected **Require 5 Digit Addenda**, and you want to disable this feature, scan **Don't Require 5 Digit Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require 5 Digit Addenda.



ARQ2900.

* Don't Require 5 Digit Addenda



ARQ2901.

Require 5 Digit Addenda

EAN-13 Beginning with 378/379 Addenda Required

This setting programs the scanner to require any combination of a 2 digit addenda or a 5 digit addenda on EAN-13 bar codes that begin with a “378” or “379.” The following settings can be programmed:

Require Addenda: All EAN-13 bar codes that begin with a “378” or “379” must have a 2 digit addenda, a 5 digit addenda, or a combination of these addenda. The EAN-13 bar code with the addenda is then transmitted as a single, concatenated bar code. If the required addenda is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require Addenda: If you have selected **Require Addenda**, and you want to disable this feature, scan **Don't Require Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require Addenda.



ARQ3780.

* Don't Require Addenda



ARQ3781.

Require 2 Digit Addenda



ARQ3782.

Require 5 Digit Addenda



ARQ3783.

Require 2 or 5 Digit Addenda

EAN-13 Beginning with 414/419 Addenda Required

This setting programs the scanner to require any combination of a 2 digit addenda or a 5 digit addenda on EAN-13 bar codes that begin with a “414” or “419.” The following settings can be programmed:

Require Addenda: All EAN-13 bar codes that begin with a “414” or “419” must have a 2 digit addenda, a 5 digit addenda, or a combination of these addenda. The EAN-13 bar code with the addenda is then transmitted as a single, concatenated bar code. If the required addenda is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require Addenda: If you have selected **Require Addenda**, and you want to disable this feature, scan **Don't Require Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require Addenda.



ARQ4140.

* Don't Require Addenda



ARQ4141.

Require 2 Digit Addenda



ARQ4142.

Require 5 Digit Addenda



ARQ4143.

Require 2 or 5 Digit Addenda

EAN-13 Beginning with 434/439 Addenda Required

This setting programs the scanner to require any combination of a 2 digit addenda or a 5 digit addenda on EAN-13 bar codes that begin with a “434” or “439.” The following settings can be programmed:

Require Addenda: All EAN-13 bar codes that begin with a “434” or “439” must have a 2 digit addenda, a 5 digit addenda, or a combination of these addenda. The EAN-13 bar code with the addenda is then transmitted as a single, concatenated bar code. If the required addenda is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require Addenda: If you have selected **Require Addenda**, and you want to disable this feature, scan **Don't Require Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require Addenda.



ARQ4340.

* Don't Require Addenda



ARQ4341.

Require 2 Digit Addenda



ARQ4342.

Require 5 Digit Addenda



ARQ4343.

Require 2 or 5 Digit Addenda

EAN-13 Beginning with 977 Addenda Required

This setting programs the scanner to require a 2 digit addenda only on EAN-13 bar codes that begin with “977.” The following settings can be programmed:

Require 2 Digit Addenda: All EAN-13 bar codes that begin with “977” must have a 2 digit addendum. The EAN-13 bar code with the 2 digit addendum is then transmitted as a single, concatenated bar code. If a 2 digit addendum is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require 2 Digit Addenda: If you have selected **Require 2 Digit Addenda**, and you want to disable this feature, scan **Don't Require 2 Digit Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require 2 Digit Addenda.



ARQ9770.

* Don't Require 2 Digit Addenda



ARQ9771.

Require 2 Digit Addenda

EAN-13 Beginning with 978 Addenda Required

These settings program the scanner to require a 5 digit addenda only on EAN-13 bar codes that begin with "978." The following settings can be programmed:

Require 5 Digit Addenda: All EAN-13 bar codes that begin with "978" must have a 5 digit addendum. The EAN-13 bar code with the 5 digit addendum is then transmitted as a single, concatenated bar code. If a 5 digit addendum is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require 5 Digit Addenda: If you have selected **Require 5 Digit Addenda**, and you want to disable this feature, scan **Don't Require 5 Digit Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require 5 Digit Addenda.



ARQ9780.

* Don't Require 5 Digit Addenda



ARQ9781.

Require 5 Digit Addenda

EAN-13 Beginning with 979 Addenda Required

These settings program the scanner to require a 5 digit addenda only on EAN-13 bar codes that begin with "979." The following settings can be programmed:

Require 5 Digit Addenda: All EAN-13 bar codes that begin with "979" must have a 5 digit addendum. The EAN-13 bar code with the 5 digit addendum is then transmitted as a single, concatenated bar code. If a 5 digit addendum is not found within the [Addenda Timeout](#) period, the EAN-13 bar code is discarded.

Don't Require 5 Digit Addenda: If you have selected **Require 5 Digit Addenda**, and you want to disable this feature, scan **Don't Require 5 Digit Addenda**. EAN-13 bar codes are transmitted, depending on the setting you are using for [EAN/JAN-13 Addenda Required](#).

Default = Don't Require 5 Digit Addenda.



ARQ9790.

* Don't Require 5 Digit Addenda



ARQ9791.

Require 5 Digit Addenda

Addenda Timeout

You can set a time during which the scanner looks for an addenda. If an addenda is not found within this time period, the data can be either transmitted or discarded, based on the setting you are using for [EAN/JAN-13 Addenda Required](#). Set the length (in milliseconds) for this timeout by scanning the bar code below, then setting the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning [Save](#). *Default = 100.*

Note: The Addenda Timeout setting is applied to all addenda and coupon code searches.



DLYADD.

Addenda Timeout

EAN/JAN-13 Addenda Separator

When this feature is **On**, there is a space between the data from the bar code and the data from the addenda. When turned **Off**, there is no space. *Default = Off.*



E13ADS1.

On



E13ADS0.

* Off

Note: If you want to enable or disable EAN13 with Extended Coupon Code, refer to [UPC-A/EAN-13 with Extended Coupon Code](#) (page 8-28).

EAN/JAN-13 Redundancy

If you are encountering errors when reading EAN/JAN-13 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **EAN/JAN-13 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the [Save](#) bar code. *Default = 0.*



E13VOT.

EAN/JAN-13 Redundancy

ISBN Translate

When **On** is scanned, EAN-13 Bookland symbols are translated into their equivalent ISBN number format. *Default = Off.*



E13ISB1.

On



Convert ISBN to 13-Digit

When translating EAN-13 codes to the ISBN format, you can convert the bar code to a 13 digit format by scanning the **Convert to 13-Digit On** bar code below. *Default = Convert to 13-Digit Off.*



ISBN Reformat

In normal use, the first two or three digits of an EAN-13 bar code identify the country of origin. The country prefixes are 978 and 979. To reformat ISBN codes so the country prefix is dropped out, scan the **Reformat On** bar code below. *Default = Reformat Off.*



ISSN Translate

When **On** is scanned, EAN-13 977 Bookland symbols are translated into their equivalent 8-digit ISSN number format. For example, 9770123456787 will be transmitted as 01234560. *Default = Off.*



ISSN Reformat

When **Reformat On** is scanned, EAN-13 977 Bookland symbols are translated into their equivalent 8-digit ISSN number format, with hyphens added to the output. For example, 9770123456787 will be transmitted as 0123-456-0. (You must first scan ISSN [On](#) (page 8-40) before scanning **Reformat On**.) *Default = Reformat Off.*



E13ISR1.
Reformat On



E13ISRO.
*** Reformat Off**

EAN/JAN-8

<Default All EAN/JAN-8 Settings>



EABDFT.

EAN/JAN-8 On/Off



EABENA1.
*** On**



EABENA0.
Off

EAN/JAN-8 Check Digit

This selection allows you to specify whether the check digit should be transmitted at the end of the scanned data or not.
Default = On.



EABCKX1.
*** On**



EABCKX0.
Off

EAN/JAN-8 Addenda

This selection adds 2 or 5 digits to the end of all scanned EAN/JAN-8 data. *Default = Off for both 2 Digit and 5 Digit Addenda.*



EAN/JAN-8 Addenda Required

When **Required** is scanned, the scanner will only read EAN/JAN-8 bar codes that have addenda. *Default = Not Required.*



Addenda Timeout

You can set a time during which the scanner looks for an addenda. If an addenda is not found within this time period, the data can be either transmitted or discarded, based on the setting you are using for [EAN/JAN-8 Addenda Required](#). Set the length (in milliseconds) for this timeout by scanning the bar code below, then setting the timeout (from 0-65535 milliseconds) by scanning digits from the [Programming Chart](#), then scanning **Save**. *Default = 100.*

Note: The Addenda Timeout setting is applied to all addenda and coupon code searches.



EAN/JAN-8 Addenda Separator

When this feature is **On**, there is a space between the data from the bar code and the data from the addenda. When turned **Off**, there is no space. *Default = Off.*



EAN/JAN-8 Redundancy

If you are encountering errors when reading EAN/JAN-8 bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **EAN/JAN-8 Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



MSI

<Default All MSI Settings>



MSI On/Off



MSI Check Character

Different types of check characters are used with MSI bar codes. You can program the scanner to read MSI bar codes with Type 10 check characters. *Default = Validate Type 10, but Don't Transmit.*

When Check Character is set to **Validate Type 10/11 and Transmit**, the scanner will only read MSI bar codes printed with the specified type check character(s), and will transmit the character(s) at the end of the scanned data.

When Check Character is set to **Validate Type 10/11, but Don't Transmit**, the unit will only read MSI bar codes printed with the specified type check character(s), but will not transmit the check character(s) with the scanned data.



MSICK0.

* **Validate Type 10, but Don't Transmit**



MSICK1.

Validate Type 10 and Transmit



MSICK2.

Validate 2 Type 10 Characters, but Don't Transmit



MSICK3.

Validate 2 Type 10 Characters and Transmit



MSICK4.

Validate Type 11 then Type 10 Character, but Don't Transmit



MSICK5.

Validate Type 11 then Type 10 Character and Transmit



MSICK6.

Disable MSI Check Characters

MSI Redundancy

If you are encountering errors when reading MSI bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **MSI Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



MSIVOT.

MSI Redundancy

MSI Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



Plessey Code

< Default All Plessey Code Settings >



Plessey Code On/Off



Plessey Check Character

No Check Character indicates that the scanner reads and transmits bar code data with or without a check character.

When Check Character is set to **Validate, but Don't Transmit**, the unit only reads Plessey bar codes printed with a check character, but will not transmit the check character with the scanned data.

When Check Character is set to **Validate and Transmit**, the scanner only reads Plessey bar codes printed with a check character, and will transmit this character at the end of the scanned data. *Default = No Check Character.*



Plessey Redundancy

If you are encountering errors when reading Plessey bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **Plessey Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



Plessey Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



GS1 DataBar Omnidirectional

< Default All GS1 DataBar Omnidirectional Settings >



GS1 DataBar Omnidirectional On/Off



GS1 DataBar Omnidirectional Redundancy

If you are encountering errors when reading GS1 DataBar Omnidirectional bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the

redundancy, scan the **GS1 DataBar Omnidirectional Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



RSSVOT.
**GS1 DataBar Omnidirectional
Redundancy**

GS1 DataBar Limited

< *Default All GS1 DataBar Limited Settings* >



RSLDFT.

GS1 DataBar Limited On/Off



RSENA1.
* On



RSENA0.
Off

GS1 DataBar Limited Redundancy

If you are encountering errors when reading GS1 DataBar Limited bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **GS1 DataBar Limited Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



RSLVOT.
**GS1 DataBar Limited
Redundancy**

GS1 DataBar Expanded

< Default All GS1 DataBar Expanded Settings >



GS1 DataBar Expanded On/Off



GS1 DataBar Expanded Redundancy

If you are encountering errors when reading GS1 DataBar Expanded bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **GS1 DataBar Expanded Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the **Save** bar code. *Default = 0.*



GS1 DataBar Expanded Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



Trioptic Code

Trioptic Code is used for labeling magnetic storage media.





GS1 Emulation

The scanner can automatically format the output from any GS1 data carrier to emulate what would be encoded in an equivalent GS1-128 or GS1 DataBar symbol. GS1 data carriers include UPC-A and UPC-E, EAN-13 and EAN-8, ITF-14, GS1-128, and GS1-128 DataBar and GS1 Composites. (Any application that accepts GS1 data can be simplified since it only needs to recognize one data carrier type.)

If **GS1-128 Emulation** is scanned, all retail codes (U.P.C., UPC-E, EAN8, EAN13) are expanded out to 16 digits. If the AIM ID is enabled, the value will be the GS1-128 AIM ID,]C1 (see [Symbology Charts](#) on page A-1).

If **GS1 DataBar Emulation** is scanned, all retail codes (U.P.C., UPC-E, EAN8, EAN13) are expanded out to 16 digits. If the AIM ID is enabled, the value will be the GS1-DataBar AIM ID,]em (see [Symbology Charts](#) on page A-1).

If **GS1 Code Expansion Off** is scanned, retail code expansion is disabled, and UPC-E expansion is controlled by the [UPC-E0 Expand](#) (page 8-30) setting. If the AIM ID is enabled, the value will be the GS1-128 AIM ID,]C1 (see [Symbology Charts](#) on page A-1).

If **EAN8 to EAN13 Conversion** is scanned, all EAN8 bar codes are converted to EAN13 format.

Default = GS1 Emulation Off.



Postal Codes

The following lists linear postal codes. Any combination of linear postal code selections can be active at a time.

China Post (Hong Kong 2 of 5)

<Default All China Post (Hong Kong 2 of 5) Settings>



CPCDFT.

China Post (Hong Kong 2 of 5) On/Off



CPCENA1.

On



CPCENAD.

* Off

China Post (Hong Kong 2 of 5) Redundancy

If you are encountering errors when reading China Post (Hong Kong 2 of 5) bar codes, you may want to adjust the redundancy count. Redundancy adjusts the number of times a bar code is decoded before transmission, which may reduce the number of errors. Note that the higher the redundancy count, the longer it will take to decode the bar code. To adjust the redundancy, scan the **China Post (Hong Kong 2 of 5) Redundancy** bar code below, then scan a redundancy count between 0 and 10 on the [Programming Chart](#) inside the back cover of this manual. Then scan the [Save](#) bar code. *Default = 0.*



CPCVOT.

China Post (Hong Kong 2 of 5)
Redundancy

China Post (Hong Kong 2 of 5) Message Length

Scan the bar codes below to change the message length. Refer to [Message Length Description](#) (page 8-1) for additional information. Minimum and Maximum lengths = 1-80. Minimum Default = 3, Maximum Default = 80.



CPCMIN.

Minimum Message Length



CPCMAX.

Maximum Message Length

To Add a Test Code I.D. Prefix to All Symbologies

This selection allows you to turn on transmission of a Code I.D. before the decoded symbology. (See the [Symbology Charts](#), beginning on page A-1) for the single character code that identifies each symbology.) This action first clears all current prefixes, then programs a Code I.D. prefix for all symbologies. This is a temporary setting that will be removed when the unit is power cycled.



PRECA2,BK2995C80!

Add Code I.D. Prefix to
All Symbologies (Temporary)

Show Software Revision

Scan the bar codes below to output the current software revision, unit serial number, and other product information for the scanner or base.



REVINF.

Show Revision of Scanner



!*:REVINF.

Show Revision of Base

Show Data Format

Scan the bar code below to show current data format settings.



DFMBK3?.

Data Format Settings

Test Menu

When you scan the Test Menu **On** code, then scan a programming code in this manual, the scanner displays the content of a programming code. The programming function will still occur, but in addition, the content of that programming code is output to the terminal.

Note: This feature should not be used during normal scanner operation.



TSTMNU1.

On



TSTMNU0.

* Off

EZConfig-Scanning Introduction

EZConfig-Scanning provides a wide range of PC-based programming functions that can be performed on a scanner connected to your PC. EZConfig-Scanning allows you to download upgrades to the scanner's firmware, change programmed parameters, and create and print programming bar codes. Using EZConfig-Scanning, you can even save/open the programming parameters for a scanner. This saved file can be e-mailed or, if required, you can create a single bar code that contains all the customized programming parameters and mail or fax that bar code to any location. Users in other locations can scan the bar code to load in the customized programming.

EZConfig-Scanning Operations

The EZConfig-Scanning software performs the following operations:

Scan Data

Scan Data allows you to scan bar codes and display the bar code data in a window. Scan Data lets you send serial commands to the scanner and receive scanner response that can be seen in the Scan Data window. The data displayed in the Scan Data window can either be saved in a file or printed.

Configure

Configure displays the programming and configuration data of the scanner. The scanner's programming and configuration data is grouped into different categories. Each category is displayed as a tree item under the "Configure" tree node in the application explorer. When one of these tree nodes is clicked, the right-hand side is loaded with the parameters' form belonging to that particular category. The Configure tree option has all the programming and configuration parameters specified for a scanner. You can set or modify these parameters as required. You can later write the modified settings to the scanner, or save them to a dcf file.

Installing EZConfig-Scanning from the Web

Note: EZConfig-Scanning requires .NET software. If .NET is not installed on your PC, you will be prompted to install it during the EZConfig-Scanning installation.

1. Access the Honeywell web site at www.honeywellaidc.com
2. Click on the **Products** tab. Under **Software**, select **Device Management**.
3. Click on **EZConfig-Device Configuration Software**.
4. Click on the **Software** tab. Select **EZConfig Cloud For Scanning** (online version, must register for access) or **EZConfig for Scanning** (to install on your PC, follow the next steps).
5. To install on your PC, when prompted, select **Save File**, and save the files to the **c:\windows\temp** directory.
6. Once you have finished downloading the file, exit the web site.
7. Using Explorer, go to the **c:\windows\temp** file.
8. Double click on the **Setup.exe** file. Follow the screen prompts to install the EZConfig-Scanning program.
9. If you've selected the defaults during installation, you can click on **Start Menu-All Programs-Honeywell-EZConfig-Scanning** and select EZConfig for your browser.

Resetting the Factory Defaults



This selection erases all your settings and resets the scanner to the original factory defaults.

If you aren't sure what programming options are in your scanner, or you've changed some options and want to restore the scanner to factory default settings, first scan the **Remove Custom Defaults** bar code, then scan **Activate Defaults**. Power cycle the scanner to reset it to the factory default settings.



DEFOVR.

Remove Custom Defaults



DEFAULT.

Activate Defaults

*Note: If using a cordless system, scanning the **Activate Defaults** bar code also causes both the scanner and the base or Access Point to perform a reset and become unlinked. The scanner must be placed in its base to re-establish the link before any setup codes are entered. If using an Access Point, the linking bar code must be scanned. See [Cordless System Operation \(Voyager 1202g\)](#) beginning on page 3-1 or [Cordless System Operation \(Voyager 1202g-BF\)](#) beginning on page 4-1 for additional information.*

The [Serial Programming Commands](#), beginning on page 10-1 list the factory default settings for each of the commands (indicated by an asterisk (*) on the programming pages).



Serial Programming Commands

The serial programming commands can be used in place of the programming bar codes. Both the serial commands and the programming bar codes will program the scanner. For complete descriptions and examples of each serial programming command, refer to the corresponding programming bar code in this manual.

The device must be set to an RS232 interface (see [page 2-1](#)). The following commands can be sent via a PC COM port using terminal emulation software.

Conventions

The following conventions are used for menu and query command descriptions:

*parameter*A label representing the actual value you should send as part of a command.

[*option*]An optional part of a command.

{*Data*}Alternatives in a command.

boldNames of menus, menu commands, buttons, dialog boxes, and windows that appear on the screen.

Menu Command Syntax

Menu commands have the following syntax (spaces have been used for clarity only):

Prefix [*:Name:*] *Tag* *SubTag* {*Data*} [, *SubTag* {*Data*}] [*:* *Tag* *SubTag* {*Data*}] [...] *Storage*

*Prefix*Three ASCII characters: **SYN M CR** (ASCII 22,77,13).

*:Name:*To send information to the scanner (with the base connected to host), use **:Voyager:**. The default factory setting for a Voyager scanner is Voyager scanner. If the name is not known, a wildcard (*) can be used **:***.

Note: *Since the base stores all work group settings and transfers to them to scanner once they are linked, changes are typically done to the base and not to the scanner.*

*Tag*A 3 character case-insensitive field that identifies the desired menu command group. For example, all RS232 configuration settings are identified with a Tag of **232**.

*SubTag*A 3 character case-insensitive field that identifies the desired menu command within the tag group. For example, the SubTag for the RS232 baud rate is **BAD**.

*Data*The new value for a menu setting, identified by the Tag and SubTag.

*Storage*A single character that specifies the storage table to which the command is applied. An exclamation point (!) performs the command's operation on the device's volatile menu configuration table. A period (.) performs the command's operation on the device's non-volatile menu configuration table. Use the non-volatile table only for semi-permanent changes you want saved through a power cycle.

Query Commands

Several special characters can be used to query the device about its settings.

- ^ What is the default value for the setting(s).
- ? What is the device's current value for the setting(s).
- * What is the range of possible values for the setting(s). (The device's response uses a dash (-) to indicate a continuous range of values. A pipe (|) separates items in a list of non-continuous values.)

:Name: Field Usage (Optional)

This command returns the query information from the scanner.

Tag Field Usage

When a query is used in place of a Tag field, the query applies to the *entire* set of commands available for the particular storage table indicated by the Storage field of the command. In this case, the SubTag and Data fields should not be used because they are ignored by the device.

SubTag Field Usage

When a query is used in place of a SubTag field, the query applies only to the subset of commands available that match the Tag field. In this case, the Data field should not be used because it is ignored by the device.

Data Field Usage

When a query is used in place of the Data field, the query applies only to the specific command identified by the Tag and SubTag fields.

Concatenation of Multiple Commands

Multiple commands can be issued within one Prefix/Storage sequence. Only the Tag, SubTag, and Data fields must be repeated for each command in the sequence. If additional commands are to be applied to the same Tag, then the new command sequence is separated with a comma (,) and only the SubTag and Data fields of the additional command are issued. If the additional command requires a different Tag field, the command is separated from previous commands by a semicolon (;).

Responses

The device responds to serial commands with one of three responses:

ACKIndicates a good command which has been processed.

ENQIndicates an invalid Tag or SubTag command.

NAKIndicates the command was good, but the Data field entry was out of the allowable range for this Tag and SubTag combination, e.g., an entry for a minimum message length of 100 when the field will only accept 2 characters.

When responding, the device echoes back the command sequence with the status character inserted directly before each of the punctuation marks (the period, exclamation point, comma, or semicolon) in the command.

Examples of Query Commands

In the following examples, a bracketed notation [] depicts a non-displayable response.

Example: What is the range of possible values for Codabar Coding Enable?

Enter: **cbrena*.**

Response: **CBRENA0-1[ACK]**

This response indicates that Codabar Coding Enable (CBRENA) has a range of values from 0 to 1 (off and on).

Example: What is the default value for Codabar Coding Enable?

Enter: **cbrena^.**

Response: **CBRENA1[ACK]**

This response indicates that the default setting for Codabar Coding Enable (CBRENA) is 1, or on.

Example: What is the device's current setting for Codabar Coding Enable?

Enter: **cbrena?.**

Response: **CBRENA1[ACK]**

This response indicates that the device's Codabar Coding Enable (CBRENA) is set to 1, or on.

Example: What are the device's settings for all Codabar selections?

Enter: **cbr?.**

Response: **CBRENA1[ACK],**
SSX0[ACK],
CK20[ACK],
CCT1[ACK],
MIN2[ACK],
MAX60[ACK],
DFT[ACK].

This response indicates that the device's Codabar Coding Enable (CBRENA) is set to 1, or on;
the Start/Stop Character (SSX) is set to 0, or Don't Transmit;
the Check Character (CK2) is set to 0, or Not Required;
concatenation (CCT) is set to 1, or Enabled;
the Minimum Message Length (MIN) is set to 2 characters;
the Maximum Message Length (MAX) is set to 60 characters;
and the Default setting (DFT) has no value.

Serial Trigger Commands

You can activate and deactivate the scanner with serial trigger commands. The button is activated and deactivated by sending the following commands:

Activate: **SYN T CR**

Deactivate: **SYN U CR**

The scanner scans until a bar code has been read or until the deactivate command is sent. The scanner can also be set to turn itself off after a specified time has elapsed (see [Read Time-Out](#), which follows).

Read Time-Out

Use this selection to set a time-out (in milliseconds) of the scanner's button when using serial commands to trigger the scanner. Once the scanner has timed out, you can activate the scanner either by pressing the button or using a serial trigger command. After scanning the **Read Time-Out** bar code, set the time-out duration (from 0-300,000 milliseconds) by scanning digits on the [Programming Chart](#) inside the back cover, then scanning **Save**. *Default = 30,000 ms.*



TRGSTO.
Read Time-Out

Menu Commands

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|----------------------------------|---|--|------|
| Product Default Settings | | | |
| Setting Custom Defaults | Set Custom Defaults | MNUCDF | 1-6 |
| Resetting the Custom Defaults | Activate Custom Defaults | DEFAULT | 1-7 |
| Programming the Interface | | | |
| Plug and Play Codes | Keyboard Wedge: IBM PC AT and Compatibles with CR suffix | PAP_AT | 2-1 |
| | IBM PS2 Keyboard | PAPPS2 | 2-1 |
| | RS232 Serial Port | PAP232 | 2-1 |
| Plug and Play Codes: RS485 | IBM Port 5B Interface | PAPP5B | 2-2 |
| | IBM Port 9B HHBCR-1 Interface | PAP9B1 | 2-2 |
| | IBM Port 17 Interface | PAPP17 | 2-2 |
| | IBM Port 9B HHBCR-2 Interface | PAP9B2 | 2-2 |
| OPOS Mode | OPOS Mode | PAPOPS | 2-3 |
| Plug and Play Codes: IBM SurePos | USB IBM SurePos Handheld | PAPSPH | 2-3 |
| | USB IBM SurePos Tabletop | PAPSPT | 2-3 |
| IBM Secondary Interface | * Enable Secondary Interface | REMIFC1 | 2-3 |
| | Disable Secondary Interface | REMIFC0 | 2-4 |
| Plug and Play Codes: USB | USB Keyboard (PC) | PAP124 | 2-4 |
| | USB Keyboard (Mac) | PAP125 | 2-4 |
| | USB Japanese Keyboard (PC) | PAP134 | 2-4 |
| | USB HID | PAP131 | 2-4 |
| HID Fallback Mode | HID Fallback Mode (Range 0-60 *5 minutes) | USBFTO | 2-4 |
| USB Serial Commands | USB Serial Emulation for Windows XP, Windows Server 2003, and later | PAP130 | 2-5 |
| | USB Serial Emulation for Windows 2000 | PAP130;REMIFCO | 2-5 |
| | CTS/RTS Emulation On | USBCTS1 | 2-5 |
| | CTS/RTS Emulation Off* | USBCTS0 | 2-5 |
| | ACK/NAK Mode On | USBACK1 | 2-6 |
| | ACK/NAK Mode Off* | USBACK0 | 2-6 |
| | Communication Timeout (Range 0-65535) *2000 ms | 232DLK##### | 2-6 |
| | Timeout Retries | HSTRTY | 2-6 |
| | Communication Timeout Beeper - Off | HSTTOA0 | 2-6 |
| | *Communication Timeout Beeper - On | HSTTOA1 | 2-6 |
| | NAK Retries (Range 0-255) *0 | HSTRTN### | 2-6 |
| | BEL/CAN Mode On | BELCAN1 | 2-7 |
| | BEL/CAN Mode Off* | BELCAN0 | 2-7 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|-----------------------------|--|---|----------------------|
| Plug and Play Codes | Verifone Ruby Terminal | PAPRBY | 2-7 |
| | Gilbarco Terminal | PAPGLB | 2-8 |
| | Honeywell Bioptic Aux Port | PAPBIO | 2-8 |
| | Datalogic Magellan Bioptic Aux Port | PAPMAG | 2-8 |
| | NCR Bioptic Aux Port | PAPNCR | 2-9 |
| | Wincor Nixdorf Terminal | PAPWNX | 2-9 |
| | Wincor Nixdorf Beetle | PAPBTL | 2-10 |
| | Wincor Nixdorf RS232 Mode A | PAPWMA | 2-10 |
| Program Keyboard Country | *U.S.A. | KBDCTY0 | 2-11 |
| | Albania | KBDCTY35 | 2-11 |
| | Arabic | KBDCTY91 | 2-11 |
| | Azeri (Cyrillic) | KBDCTY81 | 2-11 |
| | Azeri (Latin) | KBDCTY80 | 2-11 |
| | Belarus | KBDCTY82 | 2-11 |
| | Belgium | KBDCTY1 | 2-11 |
| | Bosnia | KBDCTY33 | 2-11 |
| | Brazil | KBDCTY16 | 2-11 |
| | Brazil (MS) | KBDCTY59 | 2-11 |
| | Bulgaria (Cyrillic) | KBDCTY52 | 2-11 |
| | Bulgaria (Latin) | KBDCTY53 | 2-12 |
| | Canada (French legacy) | KBDCTY54 | 2-12 |
| | Canada (French) | KBDCTY18 | 2-12 |
| | Canada (Multilingual) | KBDCTY55 | 2-12 |
| | China | KBDCTY92 | 2-12 |
| | Croatia | KBDCTY32 | 2-12 |
| | Czech | KBDCTY15 | 2-12 |
| | Czech (Programmers) | KBDCTY40 | 2-12 |
| | Czech (QWERTY) | KBDCTY39 | 2-12 |
| | Czech (QWERTZ) | KBDCTY38 | 2-12 |
| | Denmark | KBDCTY8 | 2-12 |
| | Dutch (Netherlands) | KBDCTY11 | 2-13 |
| | Estonia | KBDCTY41 | 2-13 |
| | Faeroese | KBDCTY83 | 2-13 |
| | Finland | KBDCTY2 | 2-13 |
| | France | KBDCTY3 | 2-13 |
| | Gaelic | KBDCTY84 | 2-13 |
| | Germany | KBDCTY4 | 2-13 |
| | Greek | KBDCTY17 | 2-13 |
| | Greek (220 Latin) | KBDCTY64 | 2-13 |
| | Greek (220) | KBDCTY61 | 2-13 |
| Greek (319 Latin) | KBDCTY65 | 2-13 | |
| Greek (319) | KBDCTY62 | 2-14 | |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|-----------|--|---|----------------------|
| | Greek (Latin) | KBDCTY63 | 2-14 |
| | Greek (MS) | KBDCTY66 | 2-14 |
| | Greek (Polytonic) | KBDCTY60 | 2-14 |
| | Hebrew | KBDCTY12 | 2-14 |
| | Hungarian (101 key) | KBDCTY50 | 2-14 |
| | Hungary | KBDCTY19 | 2-14 |
| | Iceland | KBDCTY75 | 2-14 |
| | Ireland | KBDCTY73 | 2-14 |
| | Italian (142) | KBDCTY56 | 2-14 |
| | Italy | KBDCTY5 | 2-14 |
| | Japan ASCII | KBDCTY28 | 2-15 |
| | Kazakh | KBDCTY78 | 2-15 |
| | Korea | KBDCTY93 | 2-15 |
| | Kyrgyz (Cyrillic) | KBDCTY79 | 2-15 |
| | Latin America | KBDCTY14 | 2-15 |
| | Latvia | KBDCTY42 | 2-15 |
| | Latvia (QWERTY) | KBDCTY43 | 2-15 |
| | Lithuania | KBDCTY44 | 2-15 |
| | Lithuania (IBM) | KBDCTY45 | 2-15 |
| | Macedonia | KBDCTY34 | 2-15 |
| | Malta | KBDCTY74 | 2-15 |
| | Mongolian (Cyrillic) | KBDCTY86 | 2-16 |
| | Norway | KBDCTY9 | 2-16 |
| | Poland | KBDCTY20 | 2-16 |
| | Polish (214) | KBDCTY57 | 2-16 |
| | Polish (Programmers) | KBDCTY58 | 2-16 |
| | Portugal | KBDCTY13 | 2-16 |
| | Romania | KBDCTY25 | 2-16 |
| | Russia | KBDCTY26 | 2-16 |
| | Russian (MS) | KBDCTY67 | 2-16 |
| | Russian (Typewriter) | KBDCTY68 | 2-16 |
| | SCS | KBDCTY21 | 2-16 |
| | Serbia (Cyrillic) | KBDCTY37 | 2-17 |
| | Serbia (Latin) | KBDCTY36 | 2-17 |
| | Slovakia | KBDCTY22 | 2-17 |
| | Slovakia (QWERTY) | KBDCTY49 | 2-17 |
| | Slovakia (QWERTZ) | KBDCTY48 | 2-17 |
| | Slovenia | KBDCTY31 | 2-17 |
| | Spain | KBDCTY10 | 2-17 |
| | Spanish variation | KBDCTY51 | 2-17 |
| | Sweden | KBDCTY23 | 2-17 |
| | Switzerland (French) | KBDCTY29 | 2-17 |
| | Switzerland (German) | KBDCTY6 | 2-17 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---------------------------------|---|---|----------------------|
| | Tatar | KBDCTY85 | 2-18 |
| | Thailand | KBDCTY94 | 2-18 |
| | Turkey F | KBDCTY27 | 2-18 |
| | Turkey Q | KBDCTY24 | 2-18 |
| | Ukrainian | KBDCTY76 | 2-18 |
| | United Kingdom | KBDCTY7 | 2-18 |
| | United States (Dvorak right) | KBDCTY89 | 2-18 |
| | United States (Dvorak left) | KBDCTY88 | 2-18 |
| | United States (Dvorak) | KBDCTY87 | 2-18 |
| | United States (International) | KBDCTY30 | 2-18 |
| | Uzbek (Cyrillic) | KBDCTY77 | 2-18 |
| | Vietnam | KBDCTY95 | 2-19 |
| Keyboard Wedge Modifiers | | | |
| ALT Mode | *Off | KBDALT0 | 2-19 |
| | 4 Characters | KBDALT7 | 2-19 |
| Keyboard Style | *Regular | KBDSTY0 | 2-19 |
| | Caps Lock | KBDSTY1 | 2-19 |
| | Shift Lock | KBDSTY2 | 2-19 |
| | Autocaps via NumLock | KBDSTY7 | 2-20 |
| | Emulate External Keyboard | KBDSTY5 | 2-20 |
| Keyboard Conversion | *Keyboard Conversion Off | KBDCNV0 | 2-20 |
| | Convert all Characters to Upper Case | KBDCNV1 | 2-20 |
| | Convert all Characters to Lower Case | KBDCNV1 | 2-20 |
| Keyboard Modifiers | *Control + ASCII Off | KBDCAS0 | 2-21 |
| | DOS Mode Control + ASCII | KBDCAS1 | 2-21 |
| | Windows Mode Control + ASCII | KBDCAS2 | 2-21 |
| | Windows Mode Prefix/Suffix Off | KBDCAS3 | 2-21 |
| | *Numeric Keypad Off | KBDNPS0 | 2-21 |
| | Numeric Keypad On | KBDNPS1 | 2-21 |
| Inter-Scan Code Delay | Inter-Scan Code Delay *0 (Range 1-30 msec) | KBDDLY## | 2-21 |
| <F0> Break Character | Suppress <F0> Break Character | KBDF0B0 | 2-22 |
| | *Transmit <F0> Break Character | KBDF0B1 | 2-22 |
| Keyboard Wedge Defaults | Reset Keyboard Wedge Defaults | KBDDFT | 2-22 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|--|---|----------------------|
| RS-232 Modifiers | | | |
| RS232 Baud Rate | 300 BPS | 232BAD0 | 2-23 |
| | 600 BPS | 232BAD1 | 2-23 |
| | 1200 BPS | 232BAD2 | 2-23 |
| | 2400 BPS | 232BAD3 | 2-23 |
| | 4800 BPS | 232BAD4 | 2-23 |
| | *9600 BPS | 232BAD5 | 2-23 |
| | 19200 BPS | 232BAD6 | 2-23 |
| | 38400 BPS | 232BAD7 | 2-23 |
| | 57600 BPS | 232BAD8 | 2-23 |
| | 115200 BPS | 232BAD9 | 2-23 |
| Word Length: Data Bits, Stop Bits, and Parity | 7 Data, 1 Stop, Parity Even | 232WRD3 | 2-24 |
| | 7 Data, 1 Stop, Parity None | 232WRD0 | 2-24 |
| | 7 Data, 1 Stop, Parity Odd | 232WRD6 | 2-24 |
| | 7 Data, 2 Stop, Parity Even | 232WRD4 | 2-24 |
| | 7 Data, 2 Stop, Parity None | 232WRD1 | 2-24 |
| | 7 Data, 2 Stop, Parity Odd | 232WRD7 | 2-24 |
| | 8 Data, 1 Stop, Parity Even | 232WRD5 | 2-24 |
| | *8 Data, 1 Stop, Parity None | 232WRD2 | 2-24 |
| | 8 Data, 1 Stop, Parity Odd | 232WRD8 | 2-24 |
| | 7 Data, 1 Stop, Parity Space | 232WRD9 | 2-24 |
| | 7 Data, 2 Stop, Parity Space | 232WRD10 | 2-25 |
| | 8 Data, 1 Stop, Parity Space | 232WRD11 | 2-25 |
| | 7 Data, 1 Stop, Parity Mark | 232WRD12 | 2-25 |
| | 7 Data, 2 Stop, Parity Mark | 232WRD13 | 2-25 |
| 8 Data, 1 Stop, Parity Mark | 232WRD14 | 2-25 | |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|--|---|----------------------|
| RS232 Handshaking | *RTS/CTS Off | 232CTS0 | 2-25 |
| | Flow Control, No Timeout | 232CTS1 | 2-26 |
| | Character-Based Flow Control, No Timeout | 232CTS7 | 2-26 |
| | Two-Direction Flow Control | 232CTS2 | 2-26 |
| | Flow Control with Timeout | 232CTS3 | 2-26 |
| | Character-Based Flow Control with Timeout | 232CTS9 | 2-26 |
| | *RTS/CTS Off, RTS Inactive | 232CTS10 | 2-25 |
| | RS232 Timeout (Range 1-65535) *1000 ms | 232DEL#### | 2-26 |
| | *XON/XOFF Off | 232XON0 | 2-26 |
| | XON/XOFF On | 232XON1 | 2-26 |
| | *ACK/NAK Off | 232ACK0 | 2-27 |
| | ACK/NAK On | 232ACK1 | 2-27 |
| | Communication Timeout (Range 1-65535) *2000 ms | 232DLK##### | 2-27 |
| | Communication Timeout Beeper - Off | HSTTOA0 | 2-27 |
| | *Communication Timeout Beeper - On | HSTTOA1 | 2-27 |
| BEL/CAN Mode On | BELCAN1 | 2-28 | |
| *BEL/CAN Mode Off | BELCAN0 | 2-28 | |
| RS232 Defaults | Reset RS232 Defaults | 232DFT | 2-28 |
| NCR Modifiers | | | |
| NCR ACK/NAK | *NCR ACK/NAK Off | NCRACK0 | 2-28 |
| | NCR ACK/NAK On | NCRACK1 | 2-28 |
| Block Check Character | *Transmit | NCRBCC1 | 2-29 |
| | Don't Transmit | NCRBCC0 | 2-29 |
| NCR Prefix/Suffix | NCR Prefix | NCRPR2## | 2-29 |
| | NCR Suffix *0D | NCRSF2## | 2-29 |
| | Transmit Prefix/Suffix | NCRBCP1 | 2-29 |
| | *Don't Transmit Prefix/Suffix | NCRBCP0 | 2-29 |
| NCR NOF (Not-on-File) Error | On | NCRRAZ1 | 2-30 |
| | *Off | NCRRAZ0 | 2-30 |
| Scanner to Biopptic Communication | *Packet Mode Off | 232PKT0 | 2-30 |
| | Packet Mode On | 232PKT2 | 2-30 |
| | *ACK/NAK Off | 232ACK0 | 2-30 |
| | ACK/NAK On | 232ACK1 | 2-30 |
| | Communication Timeout (Range 1-65535) *2000 ms | 232DLK##### | 2-31 |
| <i>Cordless System Operation (Voyager 1202g)</i> | | | |
| <i>Note: This section applies only to Voyager 1202g cordless systems. It does not apply to corded scanners.</i> | | | |
| Base Power Communication Indicator | *On | :::BASRED1 | 3-5 |
| | Off | :::BASRED0 | 3-5 |
| Reset Scanner | Reset Scanner | RESET_ | 3-6 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|-------------------------------|--|---|-------------|
| Scanning While in Base Cradle | Scanning in Cradle Off | BT_SIC0 | 3-6 |
| | *Scanning in Cradle On | BT_SIC1 | 3-6 |
| Paging Mode | *On | BEPPGE1 | 3-7 |
| | Off | BEPPGE0 | 3-7 |
| Paging Pitch | Low (*1000) (min 100Hz) | BEPPFQ1000 | 3-7 |
| | Medium (3250) | BEPPFQ3250 | 3-7 |
| | High (4200) (min 5000Hz) | BEPPFQ4200 | 3-7 |
| Scanner Address | Scanner Address | BT_LDA | 3-7 |
| Base Address | Base Address | :::BASLDA | 3-8 |
| Scanner Modes | Charge Only Mode | :::BASLNK0 | 3-8 |
| | *Charge and Link Mode | :::BASLNK1 | 3-8 |
| | Locked Link Mode | :::BASCON0 | 3-8 |
| | *Open Link Mode | :::BASCON1 | 3-9 |
| | Unlink Scanner | BT_RMV | 3-9 |
| | Override Locked Scanner | BT_RPL1 | 3-9 |
| Out-of-Range Alarm | Alarm Sound Type | BT_ORW | 3-9 |
| | Scanner Alarm Duration (Range 1 - 3000 sec (*1)) | BT_ORD | 3-10 |
| Scanner Power Time-Out Timer | Timer Off | BT_LPT0 | 3-10 |
| | 200 Seconds | BT_LPT200 | 3-10 |
| | 400 Seconds | BT_LPT400 | 3-10 |
| | 900 Seconds | BT_LPT900 | 3-10 |
| | 3600 Seconds | BT_LPT3600 | 3-10 |
| | 7200 Seconds | BT_LPT7200 | 3-10 |
| Batch Mode | Automatic Batch Mode | BATENA1 | 3-11 |
| | *Batch Mode Off | BATENA0 | 3-11 |
| | Inventory Batch Mode | BATENA2 | 3-11 |
| Batch Mode Beep | *Off | BATBEP0 | 3-11 |
| | On | BATBEP1 | 3-11 |
| Batch Mode Quantity | *Off | BATQTY0 | 3-12 |
| | On | BATQTY1 | 3-12 |
| Quantity Codes | 0 | BATNUM0 | 3-12 |
| | 1 | BATNUM1 | 3-12 |
| | 2 | BATNUM2 | 3-13 |
| | 3 | BATNUM3 | 3-13 |
| | 4 | BATNUM4 | 3-13 |
| | 5 | BATNUM5 | 3-13 |
| | 6 | BATNUM6 | 3-13 |
| | 7 | BATNUM7 | 3-13 |
| | 8 | BATNUM8 | 3-13 |
| 9 | BATNUM9 | 3-13 | |
| Delete Last Code | Delete Last Code | BATUND | 3-13 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|--|---|-------------|
| Record Counter | *Record Counter Off | BATENT0 | 3-14 |
| | Record Counter On | BATENT1 | 3-14 |
| Total Records | Total Records | BATNRC | 3-14 |
| Batch Mode Output Order | *FIFO | BATLIF0 | 3-14 |
| | LIFO | BATLIF1 | 3-14 |
| Clear All Codes After Transmission | *Don't Clear All Codes After Transmission | BATCLX0 | 3-14 |
| | Clear All Codes After Transmission | BATCLX1 | 3-14 |
| Clear All Codes | Clear All Codes | BATCLR | 3-15 |
| Transmit Records Automatically | *Don't Transmit Records Automatically | BATATX0 | 3-15 |
| | Transmit Records Automatically | BATATX1 | 3-15 |
| Transmit Records to Host | Transmit Inventory Records | BAT_TX | 3-15 |
| Batch Mode Transmit Delay | *Off | BATDLY0 | 3-15 |
| | Short (ms) | BATDLY250 | 3-15 |
| | Medium (ms) | BATDLY500 | 3-16 |
| | Long (ms) | BATDLY1000 | 3-16 |
| Scanner Name | Scanner Name | BT_NAM | 3-17 |
| Using the Scanner with Bluetooth Devices | Bluetooth Serial Port - PCs/Laptops | BT_TRM0;BT_DNG5 | 3-17 |
| Bluetooth PIN Code | Bluetooth PIN *0000 | BT_PIN | 3-17 |
| Auto Reconnect Mode | *Auto Reconnect On | BT_ACM1 | 3-17 |
| | Auto Reconnect Off | BT_ACM0 | 3-18 |
| Maximum Link Attempts | Maximum Link Attempts Range 0-255 (*0) | BT_MLA### | 3-18 |
| Reset | Reset Base | RESET_ | 3-19 |
| | Reset Scanner | :::RESET_ | 3-19 |
| <i>Cordless System Operation (Voyager 1202g-BF)</i> | | | |
| <i>Note: This section applies only to Voyager 1202gt-BF cordless systems. It does not apply to corded scanners.</i> | | | |
| Base Power Communication Indicator | *On | :::BASRED1 | 4-4 |
| | Off | :::BASRED0 | 4-4 |
| Reset Scanner | Reset Scanner | RESET_ | 4-4 |
| Scanning While in Base Cradle | Scanning in Cradle Off | BT_SIC0 | 4-5 |
| | *Scanning in Cradle On | BT_SIC1 | 4-5 |
| Paging Mode | *On | BEPPGE1 | 4-5 |
| | Off | BEPPGE0 | 4-5 |
| Paging Pitch | Low (*1000) (min 100Hz) | BEPPFQ1000 | 4-5 |
| | Medium (3250) | BEPPFQ3250 | 4-5 |
| | High (4200) (min 5000Hz) | BEPPFQ4200 | 4-6 |
| Scanner Address | Scanner Address | BT_LDA | 4-6 |
| Base Address | Base Address | :::BASLDA | 4-6 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---------------------------------------|--|---|-------------|
| Scanner Modes | Charge Only Mode | :::BASLNK0 | 4-6 |
| | *Charge and Link Mode | :::BASLNK1 | 4-6 |
| | Locked Link Mode | :::BASCON0 | 4-7 |
| | *Open Link Mode | :::BASCON1 | 4-7 |
| | Unlink Scanner | BT_RMV | 4-7 |
| | Override Locked Scanner | BT_RPL1 | 4-7 |
| Out-of-Range Alarm | Scanner Alarm Type | BT_ORW | 4-8 |
| | Scanner Alarm Duration (Range 1 - 3000 sec (*1)) | BT_ORD | 4-8 |
| Auto Reconnect Mode | *Auto Reconnect On | BT_ACM1 | 4-8 |
| | Auto Reconnect Off | BT_ACM0 | 4-8 |
| Maximum Link Attempts | Maximum Link Attempts Range 0-255 (*0) | BT_MLA### | 4-9 |
| Reset | Reset Base | RESET_ | 4-10 |
| | Reset Scanner | :::RESET_ | 4-10 |
| <i>Input/Output Selections</i> | | | |
| Power Up Beeper | Power Up Beeper Off - Scanner | BEPPWR0 | 5-1 |
| | *Power Up Beeper On - Scanner | BEPPWR1 | 5-1 |
| Beep on BEL Character | Beep on BEL On | BELBEP1 | 5-1 |
| | *Beep on BEL Off | BELBEP0 | 5-1 |
| Beeper - Good Read | Off | BEPBEP0 | 5-1 |
| | *On | BEPBEP1 | 5-1 |
| Beeper Volume - Good Read | Off | BEPLVL0 | 5-1 |
| | Low | BEPLVL1 | 5-2 |
| | Medium | BEPLVL2 | 5-2 |
| | *High | BEPLVL3 | 5-2 |
| Beeper Pitch - Good Read (Frequency) | Low (1600 Hz) | BEPFQ11600 | 5-2 |
| | *Medium (2350 Hz) | BEPFQ12350 | 5-2 |
| | High (4200 Hz) | BEPFQ14200 | 5-2 |
| Beeper - Transmit Order | Before Transmission | BEPWHN1 | 5-2 |
| | After Transmission | BEPWHN2 | 5-2 |
| Beeper Pitch - Error (Frequency) | *Razz (100 Hz) | BEPFQ2100 | 5-3 |
| | Medium (2000 Hz) | BEPFQ22000 | 5-3 |
| | High (4200 Hz) | BEPFQ24200 | 5-3 |
| Beeper Duration - Good Read | *Normal Beep | BEPBIP0 | 5-3 |
| | Short Beep | BEPBIP1 | 5-3 |
| Number of Beeps - Good Read | Range 1 - 9 (*1) | BEPRPT# | 5-3 |
| Number of Beeps - Error | Range 1 - 9 (*1) | BEPERR# | 5-4 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|---|---|-------------|
| LED Settings | Red LED Off | LEDFN10 | 5-4 |
| | Green LED Off | LEDFN20 | 5-4 |
| | Red LED On with Good Scan | LEDFN11 | 5-4 |
| | Green LED On with Good Scan | LEDFN21 | 5-4 |
| | *Red LED On with Laser | LEDFN12 | 5-4 |
| | *Red LED On with Laser/Red LED Blinks when Battery is Low | LEDFN11026 | 5-4 |
| | Green LED On with Laser | LEDFN22 | 5-4 |
| | Red LED On when CodeGate Disabled | LEDFN14 | 5-4 |
| | Green LED On when CodeGate Disabled | LEDFN24 | 5-5 |
| | Red LED On when In-Stand | LEDFN18 | 5-5 |
| | Green LED On when In-Stand | LEDFN28 | 5-5 |
| | Red LED On with CTS | LEDFN1128 | 5-5 |
| | Green LED On with CTS | LEDFN2128 | 5-5 |
| | Red LED when Battery is Low | LEDFN11024 | 5-5 |
| Green LED when Battery is Low | LEDFN21024 | 5-5 | |
| LED Brightness | Red Off | LEDIN10 | 5-5 |
| | Green Off | LEDIN20 | 5-5 |
| | Red Low | LEDIN11 | 5-5 |
| | Green Low | LEDIN21 | 5-6 |
| | Red Medium | LEDIN12 | 5-6 |
| | Green Medium | LEDIN22 | 5-6 |
| | *Red High | LEDIN13 | 5-6 |
| | *Green High | LEDIN23 | 5-6 |
| In-Stand and Out-of-Stand Settings | In-Stand Defaults | AISDFT | 5-6 |
| | Out-of-Stand Defaults | AOSDFT | 5-6 |
| | Presentation Mode Out-of-Stand | PAPPM1 | 5-7 |
| | Presentation Mode with CodeGate Out-of-Stand | PAPPM2 | 5-7 |
| | Manual Activation Mode Off In-Stand | AISMEN0 | 5-7 |
| | *Manual Activation Mode On In-Stand | AISMEN1 | 5-7 |
| | Manual Activation Mode Off Out-of-Stand | AOSMEN0 | 5-7 |
| | *Manual Activation Mode On Out-of-Stand | AOSMEN1 | 5-7 |
| | Do Not End Manual Activation After Good Read In-Stand | AISMGD0 | 5-7 |
| | *End Manual Activation After Good Read In-Stand | AISMGD1 | 5-8 |
| | Do Not End Manual Activation After Good Read Out-of-Stand | AOSMGD0 | 5-8 |
| | *End Manual Activation After Good Read Out-of-Stand | AOSMGD1 | 5-8 |
| | Laser Timeout - Button Hold In-Stand (Range 1 - 65525) *5000 ms | AISMPT##### | 5-8 |
| Laser Timeout - Button Release In-Stand (Range 1 - 65525) *0 ms | AISMRT##### | 5-8 | |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---------------------------|---|---|-------------|
| | Laser Timeout - Button Hold Out-of-Stand (Range 1 - 65525) *5000 ms | AOSMPT##### | 5-8 |
| | Laser Timeout - Button Release Out-of-Stand (Range 1 - 65525) *0 ms | AOSMRT##### | 5-8 |
| | *CodeGate Off In-Stand | AISCGD0 | 5-9 |
| | CodeGate On In-Stand | AISCGD1 | 5-9 |
| | CodeGate Off Out-of-Stand | AOSCGD0 | 5-9 |
| | *CodeGate On Out-of-Stand | AOSCGD1 | 5-9 |
| | *Button Function Off | BTNFNC0 | 5-9 |
| | Button Function On | BTNFNC1 | 5-9 |
| | Object Detection Mode Off In-Stand | AISOEN0 | 5-9 |
| | Object Detection Mode On Out-of-Stand | AOSOEN1 | 5-10 |
| | *Object Detection Mode Off Out-of-Stand | AOSOEN0 | 5-9 |
| | *Object Detection Mode On In-Stand | AISOEN1 | 5-10 |
| | Do Not End Object Detection After Good Read In-Stand | AISOGD0 | 5-10 |
| | *End Object Detection After Good Read In-Stand | AISOGD1 | 5-10 |
| | Do Not End Object Detection After Good Read Out-of-Stand | AOSOGD0 | 5-10 |
| | *End Object Detection After Good Read Out-of-Stand | AOSOGD1 | 5-10 |
| | Object Detection Laser Timeout In-Stand (Range 1 - 65525) *5000 ms | AISODT##### | 5-11 |
| | Object Detection Laser Timeout Out-of-Stand (Range 1 - 65525) *5000 ms | AOSODT##### | 5-11 |
| | *Object Detection Distance - Short In-Stand | AISRNG2 | 5-11 |
| | Object Detection Distance - Long In-Stand | AISRNG1 | 5-11 |
| | Object Detection Distance - Short Out-of-Stand | AOSRNG2 | 5-11 |
| | *Object Detection Distance - Long Out-of-Stand | AOSRNG1 | 5-11 |
| Character Activation Mode | *Off | HSTCEN0 | 5-11 |
| | On | HSTCEN1 | 5-12 |
| | Activation Character | HSTACH## | 5-12 |
| | Do Not End Character Activation After Good Read | HSTCGD0 | 5-12 |
| | *End Character Activation After Good Read | HSTCGD1 | 5-12 |
| | Character Activation Laser Timeout (Range 1 - 65525) *5000 ms | HSTCDT##### | 5-12 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|--|--|--|----------------------|
| Character Deactivation Mode | *Off | HSTDEN0 | 5-12 |
| | On | HSTDEN1 | 5-13 |
| | Deactivation Character | HSTDCH## | 5-13 |
| Reread Delay | Short (500 ms) | DLYRRD500 | 5-13 |
| | *Medium (750 ms) | DLYRRD750 | 5-13 |
| | Long (1000 ms) | DLYRRD1000 | 5-13 |
| | Extra Long (2000 ms) | DLYRRD2000 | 5-13 |
| User-Specified Reread Delay | Range 0 - 30,000 ms | DLYRRD##### | 5-13 |
| Output Sequence Editor | Enter Sequence | SEQBLK | 5-16 |
| | Default Sequence | SEQDFT | 5-16 |
| Sequence Timeout | (Range 1 - 65535) *5000 ms | SEQDLY##### | 5-16 |
| Sequence Match Beeper | *On | SEQBEP1 | 5-16 |
| | Off | SEQBEP0 | 5-16 |
| Partial Sequence | Transmit Partial Sequence | SEQTTS1 | 5-16 |
| | *Discard Partial Sequence | SEQTTS0 | 5-17 |
| Require Output Sequence | Required | SEQ_EN2 | 5-17 |
| | On/Not Required | SEQ_EN1 | 5-17 |
| | *Off | SEQ_EN0 | 5-17 |
| No Read | On | SHWNRD1 | 5-17 |
| | *Off | SHWNRD0 | 5-17 |
| Prefix/Suffix Selections | | | |
| Add CR Suffix to All Symbologies | | VSUFCR | 6-2 |
| Prefix | Add Prefix | PREBK2## | 6-2 |
| | Clear One Prefix | PRECL2 | 6-2 |
| | Clear All Prefixes | PRECA2 | 6-2 |
| Suffix | Add Suffix | SUFBK2## | 6-2 |
| | Clear One Suffix | SUFCL2 | 6-2 |
| | Clear All Suffixes | SUFCA2 | 6-2 |
| Transmit Alternate Extended ASCII Characters | *Transmit Alternate Extended ASCII | KBDEXT0 | 6-3 |
| | Transmit Normal Extended ASCII | KBDEXT1 | 6-3 |
| Function Code Transmit | *Enable | RMVFNC0 | 6-4 |
| | Disable | RMVFNC1 | 6-4 |
| Communication Check Character | *None | HSTXRC0 | 6-4 |
| | LRC Starts on 1st Character | HSTXRC1 | 6-4 |
| | LRC Starts on 2nd Character | HSTXRC2 | 6-4 |
| | CRC | HSTXRC3 | 6-4 |
| Intercharacter Delay | Range 0 - 65535 (5ms increments) | DLYCHR## | 6-5 |
| User Specified Intercharacter Delay | Delay Length 0 - 65535 (5ms increments) | DLYCRX## | 6-5 |
| | Character to Trigger Delay | DLY_XX## | 6-5 |
| Interfunction Delay | Range 0 - 65535 (5ms increments) | DLYFNC## | 6-6 |
| Intermessage Delay | Range 0 - 65535 (5ms increments) | DLYMSG## | 6-6 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|----------------------------------|--|--|------|
| Data Formatter Selections | | | |
| Data Format Editor | *Default Data Format (None) | DFMDF3 | 7-1 |
| | Enter Data Format | DFMBK3## | 7-2 |
| | Clear One Data Format | DFMCL3 | 7-2 |
| | Clear All Data Formats | DFMCA3 | 7-2 |
| Data Formatter | Data Formatter Off | DFM_EN0 | 7-10 |
| | *Data Formatter On, Not Required, Keep Prefix/Suffix | DFM_EN1 | 7-10 |
| | Data Format Required, Keep Prefix/Suffix | DFM_EN2 | 7-11 |
| | Data Formatter On, Not Required, Drop Prefix/Suffix | DFM_EN3 | 7-10 |
| | Data Format Required, Drop Prefix/Suffix | DFM_EN4 | 7-11 |
| Data Format Non-Match Error Tone | *Data Format Non-Match Error Tone On | DFMDEC0 | 7-11 |
| | Data Format Non-Match Error Tone Off | DFMDEC1 | 7-11 |
| Primary/Alternate Data Formats | Primary Data Format | ALTFNM0 | 7-11 |
| | Data Format 1 | ALTFNM1 | 7-11 |
| | Data Format 2 | ALTFNM2 | 7-11 |
| | Data Format 3 | ALTFNM3 | 7-11 |
| Single Scan Data Format Change | Single Scan-Primary Data Format | VSAF_0 | 7-12 |
| | Single Scan-Data Format 1 | VSAF_1 | 7-12 |
| | Single Scan-Data Format 2 | VSAF_2 | 7-12 |
| | Single Scan-Data Format 3 | VSAF_3 | 7-12 |
| Symbologies | | | |
| All Symbologies | All Symbologies Off | ALLENA0 | 8-1 |
| | All Symbologies On | ALLENA1 | 8-1 |
| Codabar | Default All Codabar Settings | CBRDFT | 8-2 |
| | Off | CBRENA0 | 8-2 |
| | *On | CBRENA1 | 8-2 |
| Codabar Start/Stop Char. | *Don't Transmit | CBRSSX0 | 8-2 |
| | Transmit | CBRSSX1 | 8-2 |
| Codabar Check Char. | *No Check Char. | CBRCK20 | 8-2 |
| | Validate Modulo 16, But Don't Transmit | CBRCK21 | 8-2 |
| | Validate Modulo 16, and Transmit | CBRCK22 | 8-3 |
| | Validate Modulo 7 CD, But Don't Transmit | CBRCK23 | 8-3 |
| | Validate Modulo 7 CD, and Transmit | CBRCK24 | 8-3 |
| | Validate CLSI, But Don't Transmit | CBRCK25 | 8-3 |
| Validate CLSI, and Transmit | CBRCK26 | 8-3 | |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|-----------------------------------|--|---|---------------------|
| Codabar Concatenation | *Off | CBRCCT0 | 8-3 |
| | On | CBRCCT1 | 8-3 |
| | Require | CBRCCT2 | 8-3 |
| | Concatenation Timeout | DLYCCT | 8-4 |
| Codabar Redundancy | Range (0 - 10) *0 | CBRVOT## | 8-4 |
| Codabar Message Length | Minimum (1 - 80) *3 | CBRMIN## | 8-4 |
| | Maximum (1 - 80) *80 | CBRMAX## | 8-4 |
| Code 39 | Default All Code 39 Settings | C39DFT | 8-5 |
| | Off | C39ENA0 | 8-5 |
| | *On | C39ENA1 | 8-5 |
| Code 39 Start/Stop Char. | *Don't Transmit | C39SSX0 | 8-5 |
| | Transmit | C39SSX1 | 8-5 |
| Code 39 Check Char. | *No Check Char. | C39CK20 | 8-5 |
| | Validate, But Don't Transmit | C39CK21 | 8-5 |
| | Validate, and Transmit | C39CK22 | 8-5 |
| Code 39 Redundancy | Range (0 - 10) *0 | C39VOT## | 8-6 |
| Code 39 Message Length | Minimum (1 - 80) *3 | C39MIN## | 8-6 |
| | Maximum (1 - 80) *80 | C39MAX## | 8-6 |
| Code 32 Pharmaceutical (PARAF) | *Off | C39B320 | 8-6 |
| | On | C39B321 | 8-6 |
| Code 39 Full ASCII | *Off | C39ASC0 | 8-7 |
| | On | C39ASC1 | 8-7 |
| Interleaved 2 of 5 | Default All Interleaved 2 of 5 Settings | I25DFT | 8-8 |
| | Off | I25ENA0 | 8-8 |
| | *On | I25ENA1 | 8-8 |
| NULL Characters | *Off | I25NUL0 | 8-8 |
| | On | I25NUL1 | 8-8 |
| Interleaved 2 of 5 Check Digit | *No Check Char. | I25CK20 | 8-8 |
| | Validate, But Don't Transmit | I25CK21 | 8-8 |
| | Validate, and Transmit | I25CK22 | 8-9 |
| Interleaved 2 of 5 Redundancy | Range (0 - 10) *0 | I25VOT## | 8-9 |
| Interleaved 2 of 5 Message Length | Minimum (1 - 80) *6 | I25MIN## | 8-9 |
| | Maximum (1 - 80) *80 | I25MAX## | 8-9 |
| NEC 2 of 5 | Default All NEC 2 of 5 Settings | N25DFT | 8-9 |
| | *Off | N25ENA0 | 8-9 |
| | On | N25ENA1 | 8-9 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|---|---|----------------------|
| NEC 2 of 5 Check Digit | *No Check Char. | N25CK20 | 8-10 |
| | Validate, But Don't Transmit | N25CK21 | 8-10 |
| | Validate, and Transmit | N25CK22 | 8-10 |
| NEC 2 of 5 Redundancy | Range (0 - 10) *0 | N25VOT## | 8-10 |
| NEC 2 of 5 Message Length | Minimum (1 - 80) *3 | N25MIN## | 8-10 |
| | Maximum (1 - 80) *80 | N25MAX## | 8-10 |
| Code 93 | Default All Code 93 Settings | C93DFT | 8-11 |
| | Off | C93ENA0 | 8-11 |
| | *On | C93ENA1 | 8-12 |
| Code 93 Redundancy | Range (0 - 10) *0 | C93VOT## | 8-11 |
| Code 93 Message Length | Minimum (1 - 80) *3 | C93MIN## | 8-11 |
| | Maximum (1 - 80) *80 | C93MAX## | 8-11 |
| Straight 2 of 5 Industrial | Default All Straight 2 of 5 Industrial Settings | R25DFT | 8-12 |
| | *Off | R25ENA0 | 8-12 |
| | On | R25ENA1 | 8-12 |
| Straight 2 of 5 Industrial Redundancy | Range (0 - 10) *0 | R25VOT## | 8-12 |
| Straight 2 of 5 Industrial Message Length | Minimum (1 - 80) *3 | R25MIN## | 8-12 |
| | Maximum (1 - 80) *80 | R25MAX## | 8-12 |
| Straight 2 of 5 IATA | Default All Straight 2 of 5 IATA Settings | A25DFT | 8-13 |
| Straight 2 of 5 IATA | *Off | A25ENA0 | 8-13 |
| | On | A25ENA1 | 8-13 |
| Straight 2 of 5 IATA Redundancy | Range (0 - 10) *0 | A25VOT## | 8-13 |
| Straight 2 of 5 IATA Message Length | Minimum (1 - 80) *13 | A25MIN## | 8-13 |
| | Maximum (1 - 80) *15 | A25MAX## | 8-13 |
| Matrix 2 of 5 | Default All Matrix 2 of 5 Settings | X25DFT | 8-14 |
| | *Off | X25ENA0 | 8-14 |
| | On | X25ENA1 | 8-14 |
| Matrix 2 of 5 Redundancy | Range (0 - 10) *0 | X25VOT## | 8-14 |
| Matrix 2 of 5 Message Length | Minimum (1 - 80) *3 | X25MIN## | 8-15 |
| | Maximum (1 - 80) *80 | X25MAX## | 8-15 |
| Matrix 2 of 5 Check Char. | *No Check Char. | X25CK20 | 8-14 |
| | Validate, But Don't Transmit | X25CK21 | 8-14 |
| | Validate and Transmit | X25CK22 | 8-14 |
| Code 11 | Default All Code 11 Settings | C11DFT | 8-15 |
| | *Off | C11ENA0 | 8-15 |
| | On | C11ENA1 | 8-15 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|--|---|---|----------------------|
| Code 11 Check Digits Required | 1 Check Digit Required | C11CK20 | 8-15 |
| | *2 Check Digits Required | C11CK21 | 8-15 |
| | Auto Select Check Digits Required | C11CK22 | 8-15 |
| Check Digit Validation | Validate and Transmit One Check Digit | C11CK23 | 8-16 |
| | Validate and Transmit Two Check Digits | C11CK24 | 8-16 |
| | Validate and Transmit Auto Select Check Digits | C11CK25 | 8-16 |
| Code 11 Redundancy | Range (0 - 10) *0 | C11VOT## | 8-16 |
| Code 11 Message Length | Minimum (1 - 80) *3 | C11MIN## | 8-16 |
| | Maximum (1 - 80) *80 | C11MAX## | 8-16 |
| Code 128 | Default All Code 128 Settings | 128DFT | 8-17 |
| | Off | 128ENA0 | 8-17 |
| | *On | 128ENA1 | 8-17 |
| 128 Group Separator Output | *Off | 128GSE0 | 8-17 |
| | On | 128GSE1 | 8-17 |
| Code 128 Redundancy | Range (0 - 10) *0 | 128VOT## | 8-17 |
| Code 128 Message Length | Minimum (1 - 80) *3 | 128MIN## | 8-18 |
| | Maximum (1 - 80) *80 | 128MAX## | 8-18 |
| ISBT 128 | *Off | ISBENA0 | 8-18 |
| | On | ISBENA1 | 8-18 |
| | Concatenation Timeout | DLYCCT | 8-18 |
| ISBT128 Predefined Concatenation Sequences | * Donation ID Number (001) and ABO/RhD Blood Groups (002) | ISBPCS0 | 8-19 |
| | Donation ID Number (001) and Donor ID Number (019) | ISBPCS1 | 8-19 |
| | Donation ID Number (001) and Confidential Unit Exclusion Status | ISBPCS2 | 8-19 |
| | Product Code (003) and Expiration Date (Form 1) | ISBPCS3 | 8-19 |
| | Product Code (003) and Expiration Date (Form 2) | ISBPCS4 | 8-19 |
| | Product Code (003) and Expiration Date (Form 3) | ISBPCS5 | 8-19 |
| | Product Code (003) and Expiration Date (Form 4) | ISBPCS6 | 8-19 |
| ISBT 128 Predefined Concatenation Sequences On/Off | *Off | ISBPCE0 | 8-20 |
| | Allow Predefined Sequence | ISBPCE1 | 8-20 |
| | Require Predefined Sequence | ISBPCE2 | 8-20 |
| ISBT 128 User-Defined Concatenation Sequences | 1st Left Identifier (0-255) *0 | ISBUL1## | 8-20 |
| | 2nd Left Identifier (0-255) *0 | ISBUL2## | 8-21 |
| | 1st Right Identifier (0-255) *0 | ISBUR1## | 8-21 |
| | 2nd Right Identifier (0-255) *0 | ISBUR2## | 8-21 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|--|--|---|----------------------|
| ISBT 128 User-Defined Concatenation Sequences On/Off | *Off | ISBUCE0 | 8-21 |
| | Allow User-Defined Sequence | ISBUCE1 | 8-21 |
| | Require User-Defined Sequence | ISBUCE2 | 8-21 |
| Content Verification | *Off | ISBXM00 | 8-21 |
| | On | ISBXM01 | 8-21 |
| Transmit Identifiers | Off | ISBXM10 | 8-22 |
| | *On | ISBXM11 | 8-22 |
| Flag Conversion | *Off | ISBXM20 | 8-22 |
| | On | ISBXM21 | 8-22 |
| GS1-128 | Default All GS1-128 Settings | GS1DFT | 8-23 |
| | *On | GS1ENA1 | 8-23 |
| | Off | GS1ENA0 | 8-23 |
| GS1-128 Application Identifier Parsing | *Off | GS1EMU0 | 8-23 |
| | Transmit Without Identifiers | GS1EMU1 | 8-23 |
| | Transmit With Identifiers | GS1EMU2 | 8-23 |
| GS1-128 Redundancy | Range (0 - 10) *0 | GS1VOT## | 8-23 |
| GS1-128 Message Length | Minimum (1 - 80) *3 | GS1MIN | 8-24 |
| | Maximum (0 - 80) *80 | GS1MAX | 8-24 |
| Telepen | Default All Telepen Settings | TELDFT | 8-24 |
| | *Off | TELENA0 | 8-24 |
| | On | TELENA1 | 8-24 |
| Telepen Output | *AIM Telepen Output | TELOLD0 | 8-24 |
| | Original Telepen Output | TELOLD1 | 8-24 |
| Telepen Redundancy | Range (0 - 10) *0 | TELVOT## | 8-25 |
| Telepen Message Length | Minimum (1 - 80) *3 | TELMIN## | 8-25 |
| | Maximum (1 - 80) *80 | TELMAX## | 8-25 |
| UPC-A | Default All UPC-A Settings | UPADFT | 8-25 |
| | Off | UPBENA0 | 8-25 |
| | *On | UPBENA1 | 8-25 |
| UPC-A Number System | Off | UPANSX0 | 8-26 |
| | *On | UPANSX1 | 8-26 |
| UPC-A Check Digit | Off | UPACKX0 | 8-26 |
| | *On | UPACKX1 | 8-26 |
| UPC-A 2 Digit Addenda | *Off | UPAAD20 | 8-26 |
| | On | UPAAD21 | 8-26 |
| UPC-A 5 Digit Addenda | *Off | UPAAD50 | 8-27 |
| | On | UPAAD51 | 8-26 |
| UPC-A Addenda Required | *Not Required | UPAARQ0 | 8-27 |
| | Required | UPAARQ1 | 8-27 |
| Addenda Timeout | Range (0 - 65535) *100 | DLYADD##### | 8-27 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|--|--|---|----------------------|
| UPC-A Addenda Separator | *Off | UPAADS0 | 8-27 |
| | On | UPAADS1 | 8-27 |
| UPC-A Redundancy | Range (0 - 10) *0 | UPAVOT## | 8-28 |
| UPC-A/EAN-13 with Extended Coupon Code | *Off | CPNENA0 | 8-28 |
| | Allow Concatenation | CPNENA1 | 8-28 |
| | Require Concatenation | CPNENA2 | 8-28 |
| UPC-A Number System 4 Addenda Required | * Don't Require Coupon Code | ARQSY40 | 8-28 |
| | Require Coupon Code | ARQSY41 | 8-28 |
| UPC-A Number System 5 Addenda Required | * Don't Require Coupon Code/Addenda | ARQSY50 | 8-29 |
| | Require 2 Digit Addenda | ARQSY51 | 8-29 |
| | Require 5 Digit Addenda | ARQSY52 | 8-29 |
| | Require 2 or 5 Digit Addenda | ARQSY53 | 8-29 |
| | Require Coupon Code | ARQSY54 | 8-29 |
| | Require Coupon Code or 2 Digit Addenda | ARQSY55 | 8-29 |
| | Require Coupon Code or 5 Digit Addenda | ARQSY56 | 8-29 |
| | Require Coupon Code, 2 Digit Addenda, or 5 Digit Addenda | ARQSY57 | 8-30 |
| Addenda Timeout | Range (0 - 65535) *100 | DLYADD##### | 8-30 |
| UPC-E0 | Default All UPC-E Settings | UPEDFT | 8-30 |
| | Off | UPEEN00 | 8-30 |
| | *On | UPEEN01 | 8-30 |
| UPC-E0 Expand | *Off | UPEEXP0 | 8-30 |
| | On | UPEEXP1 | 8-30 |
| UPC-E0 Number System | *On | UPEEXN1 | 8-31 |
| | Off | UPEEXN0 | 8-31 |
| UPC-E0 Check Digit | *Off | UPECKX0 | 8-31 |
| | On | UPECKX1 | 8-31 |
| UPC-E0 Leading Zero | *Off | UPENSX0 | 8-31 |
| | On | UPENSX1 | 8-31 |
| UPC-E0 Addenda | 2 Digit Addenda On | UPEAD21 | 8-32 |
| | *2 Digit Addenda Off | UPEAD20 | 8-32 |
| | 5 Digit Addenda On | UPEAD51 | 8-32 |
| | *5 Digit Addenda Off | UPEAD50 | 8-32 |
| UPC-E0 Addenda Required | Required | UPEARQ1 | 8-32 |
| | *Not Required | UPEARQ0 | 8-32 |
| Addenda Timeout | Range (0 - 65535) *100 | DLYADD##### | 8-32 |
| UPC-E0 Addenda Separator | On | UPEADS1 | 8-33 |
| | *Off | UPEADS0 | 8-33 |
| UPC-E0 Redundancy | Range (0 - 10) *1 | UPEVOT## | 8-33 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|--|---|----------------------|
| EAN/JAN-13 | Default All EAN/ JAN Settings | E13DFT | 8-33 |
| | Off | E13ENA0 | 8-30 |
| | *On | E13ENA1 | 8-30 |
| Convert UPC-A to EAN-13 | UPC-A Converted to EAN-13 | UPAENA0 | 8-33 |
| | *Do not Convert UPC-A | UPAENA1 | 8-33 |
| EAN/JAN-13 Check Digit | Off | E13CKX0 | 8-34 |
| | *On | E13CKX1 | 8-33 |
| EAN/JAN-13 2 Digit Addenda | 2 Digit Addenda On | E13AD21 | 8-34 |
| | *2 Digit Addenda Off | E13AD20 | 8-34 |
| | 5 Digit Addenda On | E13AD51 | 8-34 |
| | *5 Digit Addenda Off | E13AD50 | 8-34 |
| EAN/JAN-13 Addenda Required | *Not Required | E13ARQ0 | 8-35 |
| | Required | E13ARQ1 | 8-34 |
| EAN-13 Beginning with 2 Addenda Required | * Don't Require 2 Digit Addenda | ARQSY20 | 8-35 |
| | Require 2 Digit Addenda | ARQSY21 | 8-35 |
| EAN-13 Beginning with 290 Addenda Required | * Don't Require 5 Digit Addenda | ARQ2900 | 8-35 |
| | Require 5 Digit Addenda | ARQ2901 | 8-35 |
| EAN-13 Beginning with 378/379 Addenda Required | * Don't Require Addenda | ARQ3780 | 8-36 |
| | Require 2 Digit Addenda | ARQ3781 | 8-36 |
| | Require 5 Digit Addenda | ARQ3782 | 8-36 |
| | Require 2 or 5 Digit Addenda | ARQ3783 | 8-36 |
| EAN-13 Beginning with 414/419 Addenda Required | * Don't Require Addenda | ARQ4140 | 8-36 |
| | Require 2 Digit Addenda | ARQ4141 | 8-36 |
| | Require 5 Digit Addenda | ARQ4142 | 8-37 |
| | Require 2 or 5 Digit Addenda | ARQ4143 | 8-37 |
| EAN-13 Beginning with 434/439 Addenda Required | * Don't Require Addenda | ARQ4340 | 8-37 |
| | Require 2 Digit Addenda | ARQ4341 | 8-37 |
| | Require 5 Digit Addenda | ARQ4342 | 8-37 |
| | Require 2 or 5 Digit Addenda | ARQ4343 | 8-37 |
| EAN-13 Beginning with 977 Addenda Required | * Don't Require 2 Digit Addenda | ARQ9770 | 8-38 |
| | Require 2 Digit Addenda | ARQ9771 | 8-38 |
| EAN-13 Beginning with 978 Addenda Required | * Don't Require 5 Digit Addenda | ARQ9780 | 8-38 |
| | Require 5 Digit Addenda | ARQ9781 | 8-38 |
| EAN-13 Beginning with 979 Addenda Required | * Don't Require 5 Digit Addenda | ARQ9790 | 8-38 |
| | Require 5 Digit Addenda | ARQ9791 | 8-38 |
| Addenda Timeout | Range (0 - 65535) *100 | DLYADD##### | 8-39 |
| EAN/JAN-13 Addenda Separator | *Off | E13ADS0 | 8-39 |
| | On | E13ADS1 | 8-39 |
| EAN/JAN-13 Redundancy | Range (0 - 10) *0 | E13VOT## | 8-39 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|-----------------------------|---|---|----------------------|
| ISBN Translate | *Off | E13ISB0 | 8-40 |
| | On | E13ISB1 | 8-39 |
| | Convert to 13-Digit On | E13I131 | 8-40 |
| | *Convert to 13-Digit Off | E13I130 | 8-40 |
| | Reformat On | E13IBR1 | 8-40 |
| | *Reformat Off | E13IBR0 | 8-40 |
| ISSN Translate | *Off | E13ISS0 | 8-40 |
| | On | E13ISS1 | 8-40 |
| | Reformat On | E13ISR1 | 8-41 |
| | *Reformat Off | E13ISR0 | 8-41 |
| EAN/JAN-8 | Default All EAN/ JAN 8 Settings | EA8DFT | 8-41 |
| | Off | EA8ENA0 | 8-41 |
| | *On | EA8ENA1 | 8-41 |
| EAN/JAN-8 Check Digit | Off | EA8CKX0 | 8-41 |
| | *On | EA8CKX1 | 8-41 |
| EAN/JAN-8 Addenda | *2 Digit Addenda Off | EA8AD20 | 8-42 |
| | 2 Digit Addenda On | EA8AD21 | 8-42 |
| | *5 Digit Addenda Off | EA8AD50 | 8-42 |
| | 5 Digit Addenda On | EA8AD51 | 8-42 |
| EAN/JAN-8 Addenda Required | *Not Required | EA8ARQ0 | 8-42 |
| | Required | EA8ARQ1 | 8-42 |
| Addenda Timeout | Range (0 - 65535) *100 | DLYADD##### | 8-42 |
| EAN/JAN-8 Addenda Separator | *Off | EA8ADS0 | 8-43 |
| | On | EA8ADS1 | 8-43 |
| EAN/JAN-8 Redundancy | Range (0 - 10) *0 | EA8VOT## | 8-43 |
| MSI | Default All MSI Settings | MSIDFT | 8-43 |
| | *Off | MSIENA0 | 8-43 |
| | On | MSIENA1 | 8-43 |
| MSI Check Character | *Validate Type 10, but Don't Transmit | MSICHK0 | 8-44 |
| | Validate Type 10 and Transmit | MSICHK1 | 8-44 |
| | Validate 2 Type 10 Chars, but Don't Transmit | MSICHK2 | 8-44 |
| | Validate 2 Type 10 Chars and Transmit | MSICHK3 | 8-44 |
| | Validate 11 Type 10 Chars, but Don't Transmit | MSICHK4 | 8-44 |
| | Validate 11 Type 10 Chars and Transmit | MSICHK5 | 8-44 |
| | Disable MSI Check Characters | MSICHK6 | 8-44 |
| MSI Redundancy | Range (0 - 10) *0 | MSIVOT## | 8-44 |
| MSI Message Length | Minimum (1 - 80) *3 | MSIMIN## | 8-45 |
| | Maximum (1 - 80) *80 | MSIMAX## | 8-45 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|--|--|---|-------------|
| Plessey Code | Default All Plessey Code Settings | PLSDFT | 8-45 |
| | Off | PLSENA0 | 8-45 |
| | *On | PLSENA1 | 8-45 |
| Plessey Check Char. | *No Check Char. | PLSCHK0 | 8-45 |
| | Validate, But Don't Transmit | PLSCHK1 | 8-45 |
| | Validate, and Transmit | PLSCHK2 | 8-45 |
| Plessey Redundancy | Range (0 - 10) *0 | PLSVOT## | 8-46 |
| Plessey Message Length | Minimum (1 - 80) *3 | PLSMIN## | 8-46 |
| | Maximum (1 - 80) *80 | PLSMAX## | 8-46 |
| GS1 DataBar Omnidirectional | Default All GS1 DataBar Omnidirectional Settings | RSSDFT | 8-46 |
| | Off | RSSENA0 | 8-46 |
| | *On | RSSENA1 | 8-46 |
| GS1 DataBar Omnidirectional Redundancy | Range (0 - 10) *0 | RSSVOT## | 8-47 |
| GS1 DataBar Limited | Default All GS1 DataBar Limited Settings | RSLDFT | 8-47 |
| | Off | RSENA0 | 8-47 |
| | *On | RSENA1 | 8-47 |
| GS1 DataBar Limited Redundancy | Range (0 - 10) *0 | RSLVOT## | 8-47 |
| GS1 DataBar Expanded | Default All GS1 DataBar Expanded Settings | RSEDFT | 8-48 |
| | Off | RSEENA0 | 8-48 |
| | *On | RSEENA1 | 8-48 |
| GS1 DataBar Expanded Redundancy | Range (0 - 10) *0 | RSEVOT## | 8-48 |
| GS1 DataBar Expanded Msg. Length | Minimum (1 - 80) *3 | RSEMIN## | 8-48 |
| | Maximum (1 - 80) *80 | RSEMAX## | 8-48 |
| Trioptic Code | *Off | TRIENA0 | 8-49 |
| | On | TRIENA1 | 8-48 |
| GS1 Emulation | GS1-128 Emulation | EANEMU1 | 8-49 |
| | GS1 DataBar Emulation | EANEMU2 | 8-49 |
| | GS1 Code Expansion Off | EANEMU3 | 8-49 |
| | EAN8 to EAN13 Conversion | EANEMU4 | 8-49 |
| | *GS1 Emulation Off | EANEMU0 | 8-49 |
| Postal Codes | | | |
| China Post (Hong Kong 2 of 5) | Default All China Post (Hong Kong 2 of 5) Settings | CPCDFT | 8-50 |
| | *Off | CPCENA0 | 8-50 |
| | On | CPCENA1 | 8-50 |
| China Post (Hong Kong 2 of 5) Redundancy | Range (0 - 10) *0 | CPCVOT## | 8-50 |

| Selection | Setting <i>* Indicates default</i> | Serial Command <i># Indicates a numeric entry</i> | Page |
|---|--|---|-------------|
| China Post (Hong Kong 2 of 5) Msg. Length | Minimum (1 - 80) *3 | CPCMIN## | 8-50 |
| | Maximum (1 - 80) *80 | CPCMAX## | 8-50 |
| Utilities | | | |
| Add Code I.D. Prefix to All Symbolologies (Temporary) | | PRECA2,BK2995C80! | 9-1 |
| Show Software Revision | Revision of Scanner | REVINF | 9-1 |
| | Revision of Base | .*:REVINF | 9-1 |
| Show Data Format | | DFMBK3? | 9-1 |
| Test Menu | On | TSTMNU1 | 9-1 |
| | *Off | TSTMNU0 | 9-1 |
| Resetting the Factory Defaults | Remove Custom Defaults | DEFOVR | 9-3 |
| | Activate Defaults | DEFALT | 9-3 |
| Serial Trigger Commands | | | |
| Read Time-Out | 0 - 300,000 *30,000 ms | TRGSTO#### | 10-3 |



Product Specifications

Voyager 1200g Product Specifications

| Parameter | Specification |
|--|--|
| Mechanical | |
| Height | 3.8 in. (97mm) |
| Length | 7.1 in. (180mm) |
| Width | 2.6 in. (66mm) |
| Weight | 4.41 oz. (125g) |
| Electrical | |
| Input Voltage | 5V + 5% |
| Operating Power | 700mW; 140 mA (typical) @ 5V |
| Standby Power | 350mW; 70 mA (typical) @ 5V |
| Environmental | |
| Operating Temperature | 32°F to 122°F (0°C to 50°C) |
| Storage Temperature | -4°F to 140°F (-20°C to 60°C) |
| Humidity | 0 to 95% non-condensing |
| Drop | Operational after 30 drops to concrete from 5 ft. (1.5m) |
| Environmental Sealing | IP42 |
| Light Levels | 0 - 70,000 lux (direct sunlight) |
| ESD | 16kV, 9kV contact |
| Scan Performance | |
| Scan Pattern | Single scan line |
| Scan Angle | Horizontal: 30° |
| Scan Speed | 100 scan lines per second |
| Print Contrast | 10% minimum reflectance difference |
| Pitch, Skew | 60°, 60° |
| Decode Capabilities | Reads standard 1D and GS1 DataBar symbologies |
| DOF with 3.5 mil resolution at standard range | |
| Typical Performance | |
| 5 mil Code 39 | 27 - 151mm (1.1 - 5.9 in.) |
| 7.5 mil Code 39 | 16 - 216mm (.6 - 8.5 in.) |
| 10.4 mil Code 39 | 0 - 277mm (0 - 10.9 in.) |
| 13 mil UPC-A | 0 - 311mm (0 - 12.2 in.) |
| 20 mil Code 39 | 0 - 367mm (0 - 14.4 in.) |
| Guaranteed Performance | |
| 5 mil Code 39 | 38 - 132mm (1.5 - 5.2 in.) |
| 7.5 mil Code 39 | 26 - 189mm (1 - 7.4 in.) |
| 10.4 mil Code 39 | 0 - 229mm (0 - 9 in.) |
| 13 mil UPC-A | 0 - 253mm (0 - 10 in.) |
| 20 mil Code 39 | 0 - 293mm (0 - 11.5 in.) |
| Laser Beam | |
| Wavelength | 645 - 660 nm |
| Divergence | < 1.5 mrad. per IEC 60825-1 worst case |

| Parameter | Specification |
|-----------------------|--|
| Maximum Power Output | < 1 mw |
| Embedded Laser | |
| Wavelength | 645 - 660 nm |
| Divergence | < 1.5 mrad. per IEC 60825-1 worst case |
| Maximum Power Output | 10 mw |

Voyager 1202g and Voyager 1202g-BF Product Specifications

| Parameter | Specification |
|--|---|
| Mechanical | |
| Height | 3.6 in. (92mm) |
| Length | 7.1 in. (180mm) |
| Width | 2.6 in. (66mm) |
| Weight (1202g includes battery) | 6.3 oz. (180g) |
| Weight (1202g-BF) | 5.6 oz. (160g) |
| Battery (Voyager 1202g Only) | |
| Lithium Ion | 1800 mAHr minimum |
| Number of Scans | Up to 45,000 per charge |
| Expected Hours of Operation | 12 |
| Expected Charge Time | 4 hours (external supply) 8 hours (USB power) |
| Instant Charge Pack (Voyager 1202g-BF Only) | |
| Number of Scans | At least 35 scans with one scan every six seconds At least 100 scans with one scan every second |
| Use Time per Full Charge | 2-6 minutes depending on use |
| Expected Full Charge Time | Less than 35 seconds via wall adapter Less than 90 seconds via USB power |
| Radio | |
| Frequency | 2.4 to 2.5 GHz (ISM Band) Frequency Hopping Bluetooth v.2.1 |
| Range | 33 ft. (10 m) typical line of sight |
| Data Rate | Up to 3 MBps |
| Environmental | |
| Temperature Ranges for Voyager 1202g: | |
| Operating - Charging | 41° F to +104° F (5° C to 40° C) |
| Operating - Non-Charging | 32° F to +122° F (0° C to 50° C) |
| Storage | 23°F to +95°F (-5°C to 35°C) |
| Humidity | 0 to 95% relative humidity, non-condensing |
| Temperature Ranges for Voyager 1202g-BF: | |
| Operating - Charging | 32° F to +122° F (0° C to 50° C) |
| Operating - Non-Charging | 32° F to +122° F (0° C to 50° C) |
| Storage | -4°F to 140°F (-20°C to 60°C)* <i>*High storage temperature will degrade the performance of the instant charge pack.</i> |
| Humidity | 0 to 95% relative humidity, non-condensing |
| Mechanical Drop | Designed to withstand 30 drops from 5 feet (1.5m) to concrete |
| Environmental Sealing | IP42 |

| Parameter | Specification |
|--|---|
| ESD Sensitivity | 16kV air 9kV contact |
| Scan Performance | |
| Pitch, Skew | 60°, 60° |
| Scan Pattern | Single scan line |
| Scan Angle | Horizontal: 30° |
| Scan Speed | 100 scan lines per second |
| Print Contrast | 10% minimum reflectance difference |
| Decode Capabilities | Reads standard 1D and GS1 DataBar symbologies |
| DOF with 3.5 mil resolution at standard range | |
| Typical Performance | |
| 5 mil Code 39 | 27 - 151mm (1.1 - 5.9 in.) |
| 7.5 mil Code 39 | 16 - 216mm (.6 - 8.5 in.) |
| 1.40 mil Code 39 | 0 - 277mm (0 - 10.9 in.) |
| 13 mil UPC-A | 0 - 311mm (0 - 12.2 in.) |
| 20 mil Code 39 | 0 - 367mm (0 - 14.4 in.) |
| Guaranteed Performance | |
| 5 mil Code 39 | 38 - 132mm (1.5 - 5.2 in.) |
| 7.5 mil Code 39 | 26 - 189mm (1 - 7.4 in.) |
| 10.4 mil Code 39 | 0 - 229mm (0 - 9 in.) |
| 13 mil UPC-A | 0 - 253mm (0 - 10 in.) |
| 20 mil Code 39 | 0 - 293mm (0 - 11.5 in.) |
| Laser Beam | |
| Wavelength | 645 - 660 nm |
| Divergence | < 1.5 mrad. per IEC 60825-1 worst case |
| Maximum Power Output | < 1 mw |
| Embedded Laser | |
| Wavelength | 645 - 660 nm |
| Divergence | < 1.5 mrad. per IEC 60825-1 worst case |
| Maximum Power Output | 10 mw |

CCB00-010BT Product Specifications

| Parameter | Specification |
|----------------------------|--|
| Mechanical | |
| Dimensions (Typical): | |
| Height | 3.8 inches (97mm) |
| Length | 7.9 inches (200mm) |
| Width | 2.6 inches (67mm) |
| Weight | 7.6 oz (216g) |
| Electrical | |
| Input Voltage | 5 volts \pm 5% |
| Operating Power - Charging | 5W (1A@5V) (external supply) 2.5W (0.5A@5V) (USB power) |
| Non-Charging Power | 0.625W (0.125A@5V) |
| Expected Charge Time | 4 hours (external supply) 8 hours (USB power) |
| Radio | |


| | |
|--------------------------|---|
| Frequency | 2.4 to 2.5 GHz (ISM Band) Frequency Hopping Bluetooth v.2.1 |
| Range | 33 ft. (10 m) typical (line of sight) |
| Data Rate | Up to 3 MBps |
| Temperature Ranges: | |
| Operating - Charging | 41° F to +104° F (5° C to 40° C) |
| Operating - Non-Charging | 32° F to +122° F (0° C to 50° C) |
| Storage* | 23°F to +95°F (-5°C to 35°C) |
| Humidity | 0 to 95% relative humidity, non-condensing |
| Environmental | |
| Mechanical Drop | Operational after 30 drops from 3.28 feet (1m) to concrete |
| ESD Sensitivity | 16kV air 9kV contact |

CCB00-010BT-01N-BF Product Specifications

| Parameter | Specification |
|----------------------------|--|
| Mechanical | |
| Dimensions (Typical): | |
| Height | 3.8 inches (97mm) |
| Length | 7.9 inches (200mm) |
| Width | 2.6 inches (67mm) |
| Weight | 7.6 oz (216g) |
| Electrical | |
| Input Voltage | 5 volts \pm 5% |
| Operating Power - Charging | 5W (1A@5V) (external supply) 2.5W (0.5A@5V) (USB power) |
| Typical Non-Charging Power | |
| Base with scanner | 1W (0.2A@5V) |
| Base, no scanner | 0.5W (0.1A@5V) |
| Suspend Mode | 0.0125W (0.0025A@5V) |
| Expected Full Charge Time | <35s (external supply) <90s (USB power) |
| Radio | |
| Frequency | 2.4 to 2.5 GHz (ISM Band) Frequency Hopping Bluetooth v.2.1 |
| Range | 33 ft. (10 m) typical (line of sight) |
| Data Rate | Up to 3 MBps |
| Temperature Ranges: | |
| Operating - Charging | 32° F to +122° F (0° C to 50° C) |
| Operating - Non-Charging | 32° F to +122° F (0° C to 50° C) |
| Storage* | -4°F to 140°F (-20°C to 60°C) <i>*High storage temperature will degrade the performance of the instant charge pack.</i> |
| Humidity | 5 to 95% relative humidity, non-condensing |
| Environmental | |
| Mechanical Drop | Operational after 30 drops from 3.28 feet (1m) to concrete |
| ESD Sensitivity | 16kV air 9kV contact |

CCB00-010BT/CCB00-010BT-01N-VBF Mounting

Use 2 M3x15mm PHP, self-tapping wood screws




Standard Cable Pinouts

Keyboard Wedge

10 Pin RJ41 Modular Plug

connects to the scanner or the base




Note: Pin assignments are not compatible with Honeywell legacy products. Use of a cable with improper pin assignments may lead to damage to the unit. Use of any cables not provided by the manufacturer may result in damage not covered by your warranty.

Serial Output

10 Pin RJ41 Modular Plug

connects to the scanner or the base




Note: Pin assignments are not compatible with Honeywell legacy products.
Use of a cable with improper pin assignments may lead to damage to the unit. Use of any cables not provided by the manufacturer may result in damage not covered by your warranty.

Standard Cable Pinouts

RS485 Output

10 Pin RJ41 Modular Plug

connects to the scanner or the base




Note: RS485 signal conversion is performed in the cable.
Pin assignments are not compatible with Honeywell legacy products.
Use of a cable with improper pin assignments may lead to damage to the unit. Use of any cables not provided by the manufacturer may result in damage not covered by your warranty.

USB


10 Pin Modular Plug

connects to the scanner or the base




Note: Pin assignments are not compatible with Honeywell legacy products.
Use of a cable with improper pin assignments may lead to damage to the unit. Use of any cables not provided by the manufacturer may result in damage not covered by your warranty.


Voyager 1200g Safety Label Locations



Voyager 1202g/Voyager 1202g-BF Safety Label Locations



CCB00-010BT/CCB00-010BT-01N-BF Safety Label Locations





Maintenance and Troubleshooting

Repairs

Repairs and/or upgrades are not to be performed on this product. These services are to be performed only by an authorized service center (see [Customer Support](#) on page -iii).

Maintenance

Your device provides reliable and efficient operation with a minimum of care. Although specific maintenance is not required, the following periodic checks ensure dependable operation:

Cleaning the Device

Reading performance may degrade if the scanner's window is not clean. If the window is visibly dirty, or if the scanner isn't operating well, clean the window with a soft cloth or lens tissue dampened with water (or a mild detergent- water solution). If a detergent solution is used, rinse with a clean lens tissue dampened with water only.

The scanner and base's housing may also be cleaned the same way.



Caution:

Do not submerge the scanner in water. The scanner's housing is not watertight.

Do not use abrasive wipes or tissues on the scanner's window – abrasive wipes may scratch the window. Never use solvents (e.g., alcohol or acetone) on the housing or window – solvents may damage the finish or the window.

Inspecting Cords and Connectors

Inspect the interface cable and connector for wear or other signs of damage. A badly worn cable or damaged connector may interfere with scanner operation. Contact your distributor for information about cable replacement. Cable replacement instructions are on [page 12-1](#).


Replacing Cables in Corded Scanners

The standard interface cable is attached to the scanner with an 10-pin modular connector. When properly seated, the connector is held in the scanner's handle by a flexible retention tab. The interface cable is designed to be field replaceable.

- Order replacement cables from Honeywell or from an authorized distributor.
- When ordering a replacement cable, specify the cable part number of the original interface cable.

Replacing an Interface Cable in a Corded Scanner


1. Turn the power to the host system OFF.
2. Disconnect the scanner's cable from the terminal or computer.
3. Locate the small hole on the underside of the scanner's handle. This is the cable release.
4. Straighten one end of a paper clip.
5. Insert the end of the paper clip into the small hole and press in. This depresses the retention tab, releasing the connector. Pull the connector out while maintaining pressure on the paper clip, then remove the paper clip.
6. Replace with the new cable.
Insert the connector into the opening and press firmly. The connector is keyed to go in only one way, and will click into place.



Replacing Cables in Cordless Systems


Replacing an Interface Cable in a Base

1. Turn the power to the host system OFF.
2. Disconnect the base's cable from the terminal or computer.
3. Turn the base upside down.
4. Locate the pinhole for the cable release and insert a straightened paper clip.



5. Pull the connector out while maintaining pressure on the connector release clip.

6. Replace with the new cable.



Insert the connector into the opening and press firmly. The connector is keyed to go in only one way, and will click into place.

Troubleshooting a Voyager Scanner

The scanner automatically performs self-tests whenever you turn it on. If your scanner is not functioning properly, review the following Troubleshooting Guide to try to isolate the problem.

Note: Visit our website (www.honeywellaidc.com) to check for the latest software for the scanner or the base.

Is the power on? Is the laser aimer on?

If the laser aimer isn't illuminated, check that:

- The cable is connected properly.
- The host system power is on (if external power isn't used).
- The button works.

Is the scanner having trouble reading your symbols?

If the scanner isn't reading symbols well, check that the scanner window is clean and that the symbols:

- Aren't smeared, rough, scratched, or exhibiting voids.
- Aren't coated with frost or water droplets on the surface.
- Are enabled in the scanner or in the decoder to which the scanner connects.

Is the bar code displayed but not entered?

The bar code is displayed on the host device correctly, but you still have to press a key to enter it (the Enter/Return key or the Tab key, for example).

- You need to program a suffix. Programming a suffix enables the scanner to output the bar code data plus the key you need (such as "CR") to enter the data into your application. Refer to [Prefix/Suffix Overview](#) on page 6-1 for further information.

The scanner won't read your bar code at all.

1. Scan the sample bar codes in the back of this manual. If the scanner reads the sample bar codes, check that your bar code is readable. Verify that your bar code symbology is enabled (see [Chapter 8](#)).
2. If the scanner still can't read the sample bar codes, scan [All Symbologies On](#), page 8-1.

The cordless scanner won't scan bar codes while it is in the base.

1. Scanning While in Cradle Off may be programmed.
2. Scan the * [Scanning in Cradle On](#) (page 3-6) bar code so the scanner will also scan bar codes while in the base.

If you aren't sure what programming options have been set in the scanner, or if you want the factory default settings restored, refer to [Setting Custom Defaults](#) on page 1-6.

Troubleshooting a Cordless System

Troubleshooting a Base

Note: Visit our website (www.honeywellaidc.com) to check for the latest software for the scanner or the base.

If your base is not functioning properly, review the following troubleshooting guidelines to try to isolate the problem.

Is the red LED on?

If the red LED isn't illuminated, check that:

- The power cable is connected properly and there is power at the power source.
- The host system power is on (if external power isn't used).

Is the green LED on?

If the *green* LED isn't illuminated, check that:

- The scanner is correctly placed in the base.
- There is external power or host power.
- The contacts are clean.
- Voyager 1202g only: Charge mode is turned on. (See "[Base Charging Modes](#)" on page 3-6)
- Voyager 1202g only: The battery is not bad or deeply discharged. In some cases, the scanner's battery may trickle charge to bring it into an acceptable level and then transition to a normal charge cycle.

Troubleshooting a Cordless Scanner

Note: Make sure that your scanner's battery or instant charge pack is charged.

Visit our website (www.honeywellaidc.com) to check for the latest software for the scanner, the base, or Access Point.

Is the scanner having trouble reading your symbols?

If the scanner isn't reading symbols well, check that the symbols:

- Aren't smeared, rough, scratched, or exhibiting voids.
- Aren't coated with frost or water droplets on the surface.
- Are enabled in the base or Access Point to which the scanner connects.

Is the bar code displayed but not entered into the application?

The bar code is displayed on the host device correctly, but you still have to press a key to enter it (the Enter/Return key or the Tab key, for example).

- You need to program a suffix. Programming a suffix enables the scanner to output the bar code data plus the key you need (such as "CR") to enter the data into your application. Refer to [Prefix/Suffix Overview](#) on page 6-1 for further information.

The scanner won't read your bar code at all.

- Scan the sample bar codes in the back of this manual. If the scanner reads the sample bar codes, check that your bar code is readable.

Verify that your bar code symbology is enabled (see [Chapter 8](#)).

If the scanner still can't read the sample bar codes, scan [All Symbologies](#) on page 8-1.

Reference Charts

Symbology Charts

Note: “m” represents the AIM modifier character. Refer to International Technical Specification, Symbology Identifiers, for AIM modifier character details.

Prefix/Suffix entries for specific symbologies override the universal (All Symbologies, 99) entry.

Refer to [Data Editing](#) beginning on page 6-1 and [Data Formatting](#) beginning on page 7-1 for information about using Code ID and AIM ID.

Linear Symbologies

| Symbology | AIM | | Honeywell | |
|------------------------------------|-----|---------------------------|-----------|-----|
| | ID | Possible modifiers (m) | ID | Hex |
| All Symbologies | | | | 99 |
| Codabar |]Fm | 0-1 | a | 61 |
| Code 11 |]H3 | | h | 68 |
| Code 128 |]Cm | 0, 1, 2, 4 | j | 6A |
| Code 32 Pharmaceutical (PARAF) |]X0 | | < | 3C |
| Code 39 (supports Full ASCII mode) |]Am | 0, 1, 3, 4, 5, 7 | b | 62 |
| TCIF Linked Code 39 (TLC39) |]L2 | | T | 54 |
| Code 93 and 93i |]Gm | 0-9, A-Z, a-m | i | 69 |
| EAN |]Em | 0, 1, 3, 4 | d | 64 |
| EAN-13 (including Bookland EAN) |]E0 | | d | 64 |
| EAN-13 with Add-On |]E3 | | d | 64 |
| EAN-13 with Extended Coupon Code |]E3 | | d | 64 |
| EAN-8 |]E4 | | D | 44 |
| EAN-8 with Add-On |]E3 | | D | 44 |
| GS1 | | | | |
| GS1 DataBar |]em | 0 | y | 79 |
| GS1 DataBar Limited |]em | | { | 7B |
| GS1 DataBar Expanded |]em | | } | 7D |
| GS1-128 |]C1 | | l | 49 |
| 2 of 5 | | | | |
| China Post (Hong Kong 2 of 5) |]X0 | | Q | 51 |
| Interleaved 2 of 5 |]Im | 0, 1, 3 | e | 65 |
| Matrix 2 of 5 |]X0 | | m | 6D |
| NEC 2 of 5 |]X0 | | Y | 59 |
| Straight 2 of 5 IATA |]Rm | 0, 1, 3 | f | 66 |
| Straight 2 of 5 Industrial |]S0 | | f | 66 |
| MSI |]Mm | 0, 1 | g | 67 |
| Telepen |]Bm | | t | 74 |
| UPC | | 0, 1, 2, 3, 8, 9, A, B, C | | |

| Symbology | AIM | | Honeywell | |
|---------------------------------|-----|------------------------|-----------|-----|
| | ID | Possible modifiers (m) | ID | Hex |
| UPC-A |]E0 | | c | 63 |
| UPC-A with Add-On |]E3 | | c | 63 |
| UPC-A with Extended Coupon Code |]E3 | | c | 63 |
| UPC-E |]E0 | | E | 45 |
| UPC-E with Add-On |]E3 | | E | 45 |
| UPC-E1 |]X0 | | E | 45 |

| | | | | |
|-----------------------|--|--|---|------|
| Add Honeywell Code ID | | | | 5C80 |
| Add AIM Code ID | | | | 5C81 |
| Add Backslash | | | | 5C5C |
| Batch mode quantity | | | 5 | 35 |

Postal Symbologies

| Symbology | AIM | | Honeywell | |
|---------------------------|-----|------------------------|-----------|-----|
| | ID | Possible modifiers (m) | ID | Hex |
| <i>All Symbologies</i> | | | | 99 |
| Australian Post |]X0 | | A | 41 |
| British Post |]X0 | | B | 42 |
| Canadian Post |]X0 | | C | 43 |
| China Post |]X0 | | Q | 51 |
| InfoMail |]X0 | | , | 2c |
| Intelligent Mail Bar Code |]X0 | | M | 4D |
| Japanese Post |]X0 | | J | 4A |
| KIX (Netherlands) Post |]X0 | | K | 4B |
| Korea Post |]X0 | | ? | 3F |
| Planet Code |]X0 | | L | 4C |
| Postal-4i |]X0 | | N | 4E |
| Postnet |]X0 | | P | 50 |

ASCII Conversion Chart (Code Page 1252)

In keyboard applications, ASCII Control Characters can be represented in 3 different ways, as shown below. The CTRL+X function is OS and application dependent. The following table lists some commonly used Microsoft functionality. This table applies to U.S. style keyboards. Certain characters may differ depending on your Country Code/PC regional settings.

| Non-printable ASCII control characters | | | Keyboard Control + ASCII (CTRL+X) Mode | | |
|--|-----|------|--|--|-------------------|
| DEC | HEX | Char | Control + X Mode Off (KBDCAS0) | Windows Mode Control + X Mode On (KBDCAS2) | |
| | | | | CTRL + X | CTRL + X function |
| 0 | 00 | NUL | Reserved | CTRL+ @ | |

| Non-printable characters | | ASCII control | Keyboard Control + ASCII (CTRL+X) Mode | | |
|--------------------------|-----|---------------|--|--|---------------------|
| DEC | HEX | Char | Control + X Mode Off (KBDCAS0) | Windows Mode Control + X Mode On (KBDCAS2) | |
| | | | | CTRL + X | CTRL + X function |
| 1 | 01 | SOH | NP Enter | CTRL+ A | Select all |
| 2 | 02 | STX | Caps Lock | CTRL+ B | Bold |
| 3 | 03 | ETX | ALT Make | CTRL+ C | Copy |
| 4 | 04 | EOT | ALT Break | CTRL+ D | Bookmark |
| 5 | 05 | ENQ | CTRL Make | CTRL+ E | Center |
| 6 | 06 | ACK | CTRL Break | CTRL+ F | Find |
| 7 | 07 | BEL | Enter / Ret | CTRL+ G | |
| 8 | 08 | BS | (Apple Make) | CTRL+ H | History |
| 9 | 09 | HT | Tab | CTRL+ I | Italic |
| 10 | 0A | LF | (Apple Break) | CTRL+ J | Justify |
| 11 | 0B | VT | Tab | CTRL+ K | hyperlink |
| 12 | 0C | FF | Delete | CTRL+ L | list, left align |
| 13 | 0D | CR | Enter / Ret | CTRL+ M | |
| 14 | 0E | SO | Insert | CTRL+ N | New |
| 15 | 0F | SI | ESC | CTRL+ O | Open |
| 16 | 10 | DLE | F11 | CTRL+ P | Print |
| 17 | 11 | DC1 | Home | CTRL+ Q | Quit |
| 18 | 12 | DC2 | PrtScn | CTRL+ R | |
| 19 | 13 | DC3 | Backspace | CTRL+ S | Save |
| 20 | 14 | DC4 | Back Tab | CTRL+ T | |
| 21 | 15 | NAK | F12 | CTRL+ U | |
| 22 | 16 | SYN | F1 | CTRL+ V | Paste |
| 23 | 17 | ETB | F2 | CTRL+ W | |
| 24 | 18 | CAN | F3 | CTRL+ X | |
| 25 | 19 | EM | F4 | CTRL+ Y | |
| 26 | 1A | SUB | F5 | CTRL+ Z | |
| 27 | 1B | ESC | F6 | CTRL+ [| |
| 28 | 1C | FS | F7 | CTRL+ \ | |
| 29 | 1D | GS | F8 | CTRL+] | |
| 30 | 1E | RS | F9 | CTRL+ ^ | |
| 31 | 1F | US | F10 | CTRL+ - | |
| 127 | 7F | ␣ | NP Enter | | |

Lower ASCII Reference Table

Note: Windows Code page 1252 and lower ASCII use the same characters.

| Printable Characters | | | | | | | | |
|----------------------|-----|-----------|-----|-----|-----------|-----|-----|-----------|
| DEC | HEX | Character | DEC | HEX | Character | DEC | HEX | Character |
| 32 | 20 | <SPACE> | 64 | 40 | @ | 96 | 60 | ` |
| 33 | 21 | ! | 65 | 41 | A | 97 | 61 | a |
| 34 | 22 | " | 66 | 42 | B | 98 | 62 | b |
| 35 | 23 | # | 67 | 43 | C | 99 | 63 | c |
| 36 | 24 | \$ | 68 | 44 | D | 100 | 64 | d |
| 37 | 25 | % | 69 | 45 | E | 101 | 65 | e |
| 38 | 26 | & | 70 | 46 | F | 102 | 66 | f |

| Printable Characters (Continued) | | | | | | | | |
|----------------------------------|-----|-----------|-----|-----|-----------|-----|-----|-----------|
| DEC | HEX | Character | DEC | HEX | Character | DEC | HEX | Character |
| 39 | 27 | ' | 71 | 47 | G | 103 | 67 | g |
| 40 | 28 | (| 72 | 48 | H | 104 | 68 | h |
| 41 | 29 |) | 73 | 49 | I | 105 | 69 | i |
| 42 | 2A | * | 74 | 4A | J | 106 | 6A | j |
| 43 | 2B | + | 75 | 4B | K | 107 | 6B | k |
| 44 | 2C | , | 76 | 4C | L | 108 | 6C | l |
| 45 | 2D | - | 77 | 4D | M | 109 | 6D | m |
| 46 | 2E | . | 78 | 4E | N | 110 | 6E | n |
| 47 | 2F | / | 79 | 4F | O | 111 | 6F | o |
| 48 | 30 | 0 | 80 | 50 | P | 112 | 70 | p |
| 49 | 31 | 1 | 81 | 51 | Q | 113 | 71 | q |
| 50 | 32 | 2 | 82 | 52 | R | 114 | 72 | r |
| 51 | 33 | 3 | 83 | 53 | S | 115 | 73 | s |
| 52 | 34 | 4 | 84 | 54 | T | 116 | 74 | t |
| 53 | 35 | 5 | 85 | 55 | U | 117 | 75 | u |
| 54 | 36 | 6 | 86 | 56 | V | 118 | 76 | v |
| 55 | 37 | 7 | 87 | 57 | W | 119 | 77 | w |
| 56 | 38 | 8 | 88 | 58 | X | 120 | 78 | x |
| 57 | 39 | 9 | 89 | 59 | Y | 121 | 79 | y |
| 58 | 3A | : | 90 | 5A | Z | 122 | 7A | z |
| 59 | 3B | ; | 91 | 5B | [| 123 | 7B | { |
| 60 | 3C | < | 92 | 5C | \ | 124 | 7C | |
| 61 | 3D | = | 93 | 5D |] | 125 | 7D | } |
| 62 | 3E | > | 94 | 5E | ^ | 126 | 7E | ~ |
| 63 | 3F | ? | 95 | 5F | _ | 127 | 7F | Δ |

| Extended ASCII Characters | | | | | |
|---------------------------|-----|---------|-------|----------------------|---------------|
| DEC | HEX | CP 1252 | ASCII | Alternate Extended | PS2 Scan Code |
| 128 | 80 | € | Ç | up arrow ↑ | 0x48 |
| 129 | 81 | | ü | down arrow ↓ | 0x50 |
| 130 | 82 | , | é | right arrow → | 0x4B |
| 131 | 83 | f | â | left arrow ← | 0x4D |
| 132 | 84 | „ | ä | Insert | 0x52 |
| 133 | 85 | … | à | Delete | 0x53 |
| 134 | 86 | † | á | Home | 0x47 |
| 135 | 87 | ‡ | ç | End | 0x4F |
| 136 | 88 | ^ | ê | Page Up | 0x49 |
| 137 | 89 | %o | ë | Page Down | 0x51 |
| 138 | 8A | Š | è | Right ALT | 0x38 |
| 139 | 8B | ‹ | ï | Right CTRL | 0x1D |
| 140 | 8C | Œ | î | Reserved | n/a |
| 141 | 8D | | ì | Reserved | n/a |
| 142 | 8E | Ž | Ä | Numeric Keypad Enter | 0x1C |
| 143 | 8F | | Å | Numeric Keypad / | 0x35 |
| 144 | 90 | | É | F1 | 0x3B |
| 145 | 91 | ‘ | æ | F2 | 0x3C |
| 146 | 92 | ’ | Æ | F3 | 0x3D |
| 147 | 93 | “ | ô | F4 | 0x3E |
| 148 | 94 | ” | ö | F5 | 0x3F |
| 149 | 95 | • | ò | F6 | 0x40 |

Extended ASCII Characters (Continued)

| DEC | HEX | CP 1252 | ASCII | Alternate Extended | PS2 Scan Code |
|-----|-----|---------|-------|--------------------------------|---------------|
| 150 | 96 | – | ú | F7 | 0x41 |
| 151 | 97 | — | ù | F8 | 0x42 |
| 152 | 98 | ˘ | ÿ | F9 | 0x43 |
| 153 | 99 | ™ | Ö | F10 | 0x44 |
| 154 | 9A | š | Ü | F11 | 0x57 |
| 155 | 9B | › | ç | F12 | 0x58 |
| 156 | 9C | œ | £ | Numeric Keypad + | 0x4E |
| 157 | 9D | | ¥ | Numeric Keypad - | 0x4A |
| 158 | 9E | ž | Pts | Numeric Keypad * | 0x37 |
| 159 | 9F | ÿ | f | Caps Lock | 0x3A |
| 160 | A0 | | á | Num Lock | 0x45 |
| 161 | A1 | ı | í | Left Alt | 0x38 |
| 162 | A2 | ç | ó | Left Ctrl | 0x1D |
| 163 | A3 | £ | ú | Left Shift | 0x2A |
| 164 | A4 | ¤ | ñ | Right Shift | 0x36 |
| 165 | A5 | ¥ | Ñ | Print Screen | n/a |
| 166 | A6 | ı | ª | Tab | 0x0F |
| 167 | A7 | § | º | Shift Tab | 0x8F |
| 168 | A8 | ˆ | ¿ | Enter | 0x1C |
| 169 | A9 | © | ƒ | Esc | 0x01 |
| 170 | AA | ª | ¬ | Alt Make | 0x36 |
| 171 | AB | « | ½ | Alt Break | 0xB6 |
| 172 | AC | ¬ | ¼ | Control Make | 0x1D |
| 173 | AD | | ı | Control Break | 0x9D |
| 174 | AE | ® | « | Alt Sequence with 1 Character | 0x36 |
| 175 | AF | ¯ | » | Ctrl Sequence with 1 Character | 0x1D |
| 176 | B0 | ° | █ | | |
| 177 | B1 | ± | █ | | |
| 178 | B2 | ² | █ | | |
| 179 | B3 | ³ | | | |
| 180 | B4 | ´ | | | |
| 181 | B5 | µ | | | |
| 182 | B6 | ¶ | | | |
| 183 | B7 | · | | | |
| 184 | B8 | ¸ | | | |
| 185 | B9 | ¹ | | | |
| 186 | BA | º | | | |
| 187 | BB | » | | | |
| 188 | BC | ¼ | | | |
| 189 | BD | ½ | | | |
| 190 | BE | ¾ | | | |
| 191 | BF | ¿ | | | |
| 192 | C0 | À | | | |
| 193 | C1 | Á | | | |
| 194 | C2 | Â | | | |
| 195 | C3 | Ã | | | |
| 196 | C4 | Ä | | | |
| 197 | C5 | Å | | | |
| 198 | C6 | Æ | | | |
| 199 | C7 | Ç | | | |
| 200 | C8 | È | | | |
| 201 | C9 | É | | | |

| Extended ASCII Characters (Continued) | | | | | |
|---------------------------------------|-----|---------|-------|--------------------|---------------|
| DEC | HEX | CP 1252 | ASCII | Alternate Extended | PS2 Scan Code |
| 202 | CA | Ê | ⌚ | | |
| 203 | CB | Ë | ⌛ | | |
| 204 | CC | Ì | ⌜ | | |
| 205 | CD | Í | ⌝ | | |
| 206 | CE | Î | ⌞ | | |
| 207 | CF | Ï | ⌟ | | |
| 208 | D0 | Ð | ⌠ | | |
| 209 | D1 | Ñ | ⌡ | | |
| 210 | D2 | Ò | ⌢ | | |
| 211 | D3 | Ó | ⌣ | | |
| 212 | D4 | Ô | ⌤ | | |
| 213 | D5 | Õ | ⌥ | | |
| 214 | D6 | Ö | ⌦ | | |
| 215 | D7 | × | ⌧ | | |
| 216 | D8 | Ø | ⌨ | | |
| 217 | D9 | Ù | 〈 | | |
| 218 | DA | Ú | 〉 | | |
| 219 | DB | Û | ■ | | |
| 220 | DC | Ü | ■ | | |
| 221 | DD | Ý | ■ | | |
| 222 | DE | Þ | ■ | | |
| 223 | DF | ß | ■ | | |
| 224 | E0 | à | α | | |
| 225 | E1 | á | β | | |
| 226 | E2 | â | Γ | | |
| 227 | E3 | ã | π | | |
| 228 | E4 | ä | Σ | | |
| 229 | E5 | å | σ | | |
| 230 | E6 | æ | μ | | |
| 231 | E7 | ç | τ | | |
| 232 | E8 | è | Φ | | |
| 233 | E9 | é | Θ | | |
| 234 | EA | ê | Ω | | |
| 235 | EB | ë | δ | | |
| 236 | EC | ì | ∞ | | |
| 237 | ED | í | φ | | |
| 238 | EE | î | ε | | |
| 239 | EF | ï | ∩ | | |
| 240 | F0 | ð | ≡ | | |
| 241 | F1 | ñ | ± | | |
| 242 | F2 | ò | ≥ | | |
| 243 | F3 | ó | ≤ | | |
| 244 | F4 | ô | ∫ | | |
| 245 | F5 | õ | ∫ | | |
| 246 | F6 | ö | ÷ | | |
| 247 | F7 | ÷ | ≈ | | |
| 248 | F8 | ø | ° | | |
| 249 | F9 | ù | · | | |
| 250 | FA | ú | · | | |
| 251 | FB | û | √ | | |
| 252 | FC | ü | ⁿ | | |
| 253 | FD | ý | ² | | |

| Extended ASCII Characters (Continued) | | | | | |
|---------------------------------------|-----|---------|-------|--------------------|---------------|
| DEC | HEX | CP 1252 | ASCII | Alternate Extended | PS2 Scan Code |
| 254 | FE | þ | ■ | | |
| 255 | FF | ÿ | | | |

ISO 2022/ISO 646 Character Replacements

Code pages define the mapping of character codes to characters. If the data received does not display with the proper characters, it may be because the bar code being scanned was created using a code page that is different from the one the host program is expecting. If this is the case, select the code page with which the bar codes were created. The data characters should then appear properly.

| Code Page Selection Method/Country | Standard | Keyboard Country | Honeywell Code Page Option |
|--|------------------|------------------|----------------------------|
| United States (standard ASCII) | ISO/IEC 646-IRV | n/a | 1 |
| Automatic National Character Replacement | ISO/IEC 2022 | n/a | 2 (default) |
| Binary Code page | n/a | n/a | 3 |
| <i>Default "Automatic National Character replacement" will select the below Honeywell Code Page options for Code 128, Code 39 and Code 93.</i> | | | |
| United States | ISO/IEC 646-06 | 0 | 1 |
| Canada | ISO /IEC 646-121 | 54 | 95 |
| Canada | ISO /IEC 646-122 | 18 | 96 |
| Japan | ISO/IEC 646-14 | 28 | 98 |
| China | ISO/IEC 646-57 | 92 | 99 |
| Great Britain (UK) | ISO /IEC 646-04 | 7 | 87 |
| France | ISO /IEC 646-69 | 3 | 83 |
| Germany | ISO/IEC646-21 | 4 | 84 |
| Switzerland | ISO /IEC 646-CH | 6 | 86 |
| Sweden / Finland (extended Annex C) | ISO/IEC 646-11 | 2 | 82 |
| Ireland | ISO /IEC 646-207 | 73 | 97 |
| Denmark | ISO/IEC 646-08 | 8 | 88 |
| Norway | ISO/IEC 646-60 | 9 | 94 |
| Italy | ISO/IEC 646-15 | 5 | 85 |
| Portugal | ISO/IEC 646-16 | 13 | 92 |
| Spain | ISO/IEC 646-17 | 10 | 90 |
| Spain | ISO/IEC 646-85 | 51 | 91 |

| Dec | | | 35 | 36 | 64 | 91 | 92 | 93 | 94 | 96 | 123 | 124 | 125 | 126 |
|----------------|-------------------------|---------------------------|--|----|----|----|----|----|----|----|-----|-----|-----|-----|
| Hex | | | 23 | 24 | 40 | 5B | 5C | 5D | 5E | 60 | 7B | 7C | 7D | 7E |
| US | 0 | 1 | # | \$ | @ | [| \ |] | ^ | ` | { | | } | ~ |
| CA | 54 | 95 | # | \$ | à | â | ç | ê | î | ô | é | ù | è | û |
| CA | 18 | 96 | # | \$ | à | â | ç | ê | É | ô | é | ù | è | û |
| JP | 28 | 98 | # | \$ | @ | [| ¥ |] | ^ | ` | { | | } | - |
| CN | 92 | 99 | # | ¥ | @ | [| \ |] | ^ | ` | { | | } | - |
| GB | 7 | 87 | £ | \$ | @ | [| \ |] | ^ | ` | { | | } | ~ |
| FR | 3 | 83 | £ | \$ | à | ° | ç | § | ^ | μ | é | ù | è | .. |
| DE | 4 | 84 | # | \$ | § | Ä | Ö | Ü | ^ | ` | ä | ö | ü | ß |
| CH | 6 | 86 | ù | \$ | à | é | ç | ê | î | ô | ä | ö | ü | û |
| SE/FI | 2 | 82 | # | ¤ | É | Ä | Ö | Å | Ü | é | ä | ö | å | ü |
| DK | 8 | 88 | # | \$ | @ | Æ | Ø | Å | ^ | ` | æ | ø | å | ~ |
| NO | 9 | 94 | # | \$ | @ | Æ | Ø | Å | ^ | ` | æ | ø | å | - |
| IE | 73 | 97 | £ | \$ | Ó | É | Í | Ú | Á | ó | é | í | ú | á |
| IT | 5 | 85 | £ | \$ | § | ° | ç | é | ^ | ù | à | ò | è | ì |
| PT | 13 | 92 | # | \$ | § | Ã | Ç | Õ | ^ | ` | ã | ç | õ | ° |
| ES | 10 | 90 | # | \$ | § | i | Ñ | ¿ | ^ | ` | ° | ñ | ç | ~ |
| ES | 51 | 91 | # | \$ | · | i | Ñ | Ç | ¿ | ` | ´ | ñ | ç | .. |
| COUNTRY | Country Keyboard | Honeywell CodePage | ISO / IEC 646 National Character Replacements | | | | | | | | | | | |

Keyboard Key References

| | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 6E | 70 | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 7A | 7B | 7C | 7D | 7E | | | | | |
| 01 | 02 | 03 | 04 | 05 | 06 | 07 | 08 | 09 | 0A | 0B | 0C | 0D | 0F | 4B | 50 | 55 | 5A | 5F | 64 | 69 |
| 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 1A | 1B | 1C | 1D | 4C | 51 | 56 | 5B | 60 | 65 | 6A |
| 1E | 1F | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 2B | | | | 5C | 61 | 66 | | |
| 2C | 2E | 2F | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 39 | 53 | 5D | 62 | 67 | | | | 6C | |
| 3A | 3B | 3C | | | 3D | | | | 3E | 3F | 38 | 40 | 4F | 54 | 59 | 63 | 68 | | | |

104 Key U.S. Style Keyboard

| | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 6E | 70 | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 7A | 7B | 7C | 7D | 7E | | | | | |
| 01 | 02 | 03 | 04 | 05 | 06 | 07 | 08 | 09 | 0A | 0B | 0C | 0D | 0F | 4B | 50 | 55 | 5A | 5F | 64 | 69 |
| 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 1A | 1B | 1C | 2B | 4C | 51 | 56 | 5B | 60 | 65 | 6A |
| 1E | 1F | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 2A | | | | 5C | 61 | 66 | | |
| 2C | 2D | 2E | 2F | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 39 | 53 | 5D | 62 | 67 | | | | 6C |
| 3A | 3B | 3C | | | 3D | | | | 3E | 3F | 38 | 40 | 4F | 54 | 59 | 63 | 68 | | | |

105 Key European Style Keyboard




Sample Symbols

UPC-A



0 123456 7890

Interleaved 2 of 5



1234567890

Code 128




Code 128

EAN-13



9 780330 290951

Code 39



BC321

Codabar




A13579B

Code 93



123456-9\$

Straight 2 of 5 Industrial



123456

Matrix 2 of 5



6543210

GS1 DataBar



(01)00123456789012

Programming Chart



Programming Chart



*Note: If you make an error while scanning the letters or digits (before scanning Save), scan Discard, scan the correct letters or digits, and **Save** again.*

Honeywell Scanning & Mobility

9680 Old Bailes Road
Fort Mill, SC 29707

Agency Models: CCB00-010BT

Table with 8 columns: Product documentation is available at www.honeywellaidc.com., La documentation sur le produit est disponible à www.honeywellaidc.com., La documentation du produit est disponible sur le site www.honeywellaidc.com., La documentazione sul prodotto è disponibile sul sito www.honeywellaidc.com., Die Produktdokumentation ist unter www.honeywellaidc.com verfügbar., La documentación del producto está disponible en www.honeywellaidc.com., La documentación del producto está disponible en www.honeywellaidc.com., A documentação do produto está disponível em www.honeywellaidc.com.

FCC Part 15 Subpart B Class B
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

RF Exposure
The equipment complies with FCC RF exposure limits set forth for an uncontrolled environment. The equipment must not be co-located or operating in conjunction with any other antenna or transmitter.

Table with 2 columns: UL US UL and C-UL Statement, UL and C-UL listed: UL 60950-1, Second Edition and CSA C22.2 No.60950-1-07, Second Edition. Norme UL et C-UL, Homologué UL et C-UL : UL 60950-1, seconde édition et CSA C22.2 No. 60950-1-07, seconde édition.

Table with 8 columns: Cautions in multiple languages (English, French, German, Italian, Spanish, Chinese, Hebrew, Turkish) regarding modifications and safety.

Table with 8 columns: Safety warnings in multiple languages (Chinese, English, French, German, Italian, Spanish, Hebrew, Turkish) regarding fire and explosion risks.

Para su uso en México, la operación de este equipo está sujeta a las siguientes dos condiciones:
1. Es posible que este equipo o dispositivo no cause interferencia perjudicial.
2. Este equipo o dispositivo debe aceptar cualquier interferencia, incluyendo la que pueda causar su operación no deseada.

Canadian Compliance
This ISM device complies with Canadian RSS-210. Operation is subject to the following conditions:
1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

Table with 8 columns: Use only shielded data cables with this system. Utiliser uniquement des câbles de données blindés avec ce système. Utilizzare solo cavi dati schermati con questo sistema. Für dieses System nur abgeschirmte Datenkabel verwenden. Utilice sólo cables de datos blindados con este sistema. Use únicamente cables protegidos para datos con este sistema. Use somente cabos de dados blindados com este sistema.

Table with 8 columns: Safety warnings in multiple languages (Chinese, English, French, German, Italian, Spanish, Hebrew, Turkish) regarding fire and explosion risks.

Table with 8 columns: Bluetooth Class II, Frequency 2400-2483.5 MHz, Maximum power 4dBm. Bluetooth Classe II, Fréquences 2400 à 2483,5 MHz, Puissance maximale 4dBm. Bluetooth Catégorie II, Fréquences 2400 à 2483,5 MHz, Puissance maximale 4dBm. Bluetooth Classe II, Frequenza 2400-2483,5 MHz, Potenza massima 4dBm. Bluetooth Klasse II, Frequenz 2400-2483,5 MHz, Max. Leistung 4dBm. Bluetooth Classe II, Frecuencia 2400 MHz a 2483,5 MHz, Potencia máxima 4dBm. Bluetooth Ⅱ类, 频率 2400-2483.5 MHz, 最大功率 4dBm.

Table with 8 columns: Bluetooth Class II, Frequency 2400-2483.5 MHz, Maximum power 4dBm. Bluetooth Classe II, Fréquences 2400 à 2483,5 MHz, Puissance maximale 4dBm. Bluetooth Catégorie II, Fréquences 2400 à 2483,5 MHz, Puissance maximale 4dBm. Bluetooth Classe II, Frequenza 2400-2483,5 MHz, Potenza massima 4dBm. Bluetooth Klasse II, Frequenz 2400-2483,5 MHz, Max. Leistung 4dBm. Bluetooth Classe II, Frecuencia 2400 MHz a 2483,5 MHz, Potencia máxima 4dBm. Bluetooth Ⅱ类, 频率 2400-2483.5 MHz, 最大功率 4dBm.

Table with 8 columns: CAUTION: Improper battery replacement or incompatible device usage may result in risk of burns, fire, explosion, or other hazard. ATTENTION: Un remplacement inadéquat de la batterie ou une utilisation incompatible de l'appareil peut présenter des risques de brûlures, d'incendie, d'explosion ou d'autres dangers. MISE EN GARDE: Le remplacement incorrect de la pile ou l'usage d'un appareil non compatible peut représenter des risques de brûlures, d'incendie, d'explosion ou d'autres dangers. Attention: La sostituzione inadeguata delle batterie o un uso incompatibile del dispositivo possono causare rischi di ustioni, incendi, esplosioni o altri pericoli. VORSICHT: Ungeeignete Ersatz-Akkus oder nicht kompatible Gerätenutzung kann zu Verbrennungen, Feuer, Explosion oder anderen Gefahren führen. PRECAUCIÓN: El reemplazo inadecuado de la batería o el uso de un dispositivo incompatible pueden dar como resultado quemaduras, un incendio, explosión u otros riesgos. PRECAUCIÓN: El reemplazo inadecuado de la batería o el uso de un dispositivo incompatible puede presentar riesgo de quemaduras, incendio, explosión u otros tipos de riesgos. CUIDADO: a substituição incorreta da bateria ou o uso de um dispositivo incompatível pode resultar em riscos de queimaduras, incêndio, explosão ou outros perigos.

Table with 8 columns: Safety warnings in multiple languages (Chinese, English, French, German, Italian, Spanish, Hebrew, Turkish) regarding fire and explosion risks.

Table with 8 columns: Patents, Brevets, Brevets, Brevetti, Patente, Patentes, Patentes, Patentes. Refer to www.hsmpats.com for patent information.

Table with 8 columns: Patents, Brevets, Brevets, Brevetti, Patente, Patentes, Patentes, Patentes. Refer to www.hsmpats.com for patent information.

Table with 8 columns: Patents, Brevets, Brevets, Brevetti, Patente, Patentes, Patentes, Patentes. Refer to www.hsmpats.com for patent information.

Table with 8 columns: Product Environmental Information, Renseignements relatifs à l'environnement à propos des produits, Informations environnementales sur les produits, Informazioni ambientali relative al prodotto, Informationen zur Umweltverträglichkeit von Produkten, Información ambiental del producto, Información ambiental de producto, Informações ambientais sobre produtos. Refer to www.honeywellaidc.com for environmental information.




















Table with 8 columns: Product Environmental Information, Renseignements relatifs à l'environnement à propos des produits, Informations environnementales sur les produits, Informazioni ambientali relative al prodotto, Informationen zur Umweltverträglichkeit von Produkten, Información ambiental del producto, Información ambiental de producto, Informações ambientais sobre produtos. Refer to www.honeywellaidc.com for environmental information.

Table with 8 columns: Product Environmental Information, Renseignements relatifs à l'environnement à propos des produits, Informations environnementales sur les produits, Informazioni ambientali relative al prodotto, Informationen zur Umweltverträglichkeit von Produkten, Información ambiental del producto, Información ambiental de producto, Informações ambientais sobre produtos. Refer to www.honeywellaidc.com for environmental information.

Table with 8 columns: This document was prepared and executed in the English language. Ce document a été préparé et exécuté dans la langue anglaise. Ce document est préparé et finalisé en anglais. Questo documento è stato preparato e redatto in lingua inglese. Dieses Dokument wurde in englischer Sprache erstellt und ausgefertigt.

Table with 8 columns: Originalmente, este documento se creó y redactó en inglés. Este documento se preparó y redactó en inglés. Este documento foi preparado e feito em língua inglesa. 本文件以英文撰寫。 本文件的原稿是以英文撰寫。 如果本文件翻譯為其他語言，而英文版和非英文版之間產生衝突，應以英文版為準。

| | | | | |
|---|--|--|--|---|
| 本書は英語で作成され発行されています。本書を他の言語に翻訳し、英語版と英語以外の版に矛盾が生じた場合は、関係者の意向を最も明確に表すものが英語版であることを認識および承認し、英語版が優先するものとします。さらに、本書に関連して与えられる告知や通知は、すべて英語版を含むものとします。 | 본 문서는 영어로 준비되어 작성된 것입니다. 본 문서를 다른 언어로 번역했는데 영문본과 번역본 사이에 상충하는 부분이 발생하는 경우에는 영문본이 우선이며, 영문본이 정확 당사자의 의도를 가장 명확하게 보여주고 있음을 인식하고 확인합니다. 본 문서와 관련한 모든 고지 또는 전달 사항에는 영문본이 동봉되어야 합니다. | Данный документ был подготовлен и выполнен на английском языке. При переводе данного документа на другой язык, в случае возникновения противоречий между английской версией и версией на другом языке, английская версия имеет преимущественную силу. Данным признается, что версия документа на английском языке наиболее четко выражает намерения сторон. Любые уведомления или письма, направляемые в связи с данным документом, должны включать в себя версию на английском языке. | تحررت هذه الوثيقة وكتبته باللغة الإنجليزية. تسري النسخة الإنجليزية للوثيقة ويعترف بها وتقر بأنها النسخة التي تعبر صراحة عن مقصد أطراف العقد في حال ترجمتها لأي لغة أخرى ونشب ذلك نازعاً بين النسخة المترجمة والنسخة الإنجليزية. ترفق نسخة باللغة الإنجليزية لأي إخطارات أو اتصالات مرسله تتعلق بهذه الوثيقة. | סמך זה נכתב ויצא לאור בשפה האנגלית. במקרה שמסמך זה תורגם לשפה אחרת קיימת סתירה בין הגרסה האנגלית לבין הגרסה שאינה באנגלית, הגרסה האנגלית תישאר תקפה, מאחר וידוע וברור כי הגרסה האנגלית מבטאת את כוונת הצדדים בצורה ברורה ביותר. כל הודעה או תקשורת הניתנת בנוגע למסמך זה כוללת גרסה בשפה האנגלית. |
| Bu belge, İngilizce olarak hazırlanmış ve yayınlanmıştır. Bu belge başka bir dile çevrilirse ve İngilizce metin ile İngilizce olmayan metin arasında ihtilaf olursa İngilizce metin geçerli olacak ve İngilizce metnin tarafların niyetini açıkça ifade ettiği kabul edilip onaylanacaktır. Bu belgeyle bağlantılı olarak yapılan beyanlar veya yazışmalara İngilizce çevirileri de eklenecektir. | | | | |
| For warranty information, go to www.honeywellaidc.com and click Get Resources > Product Warranty . | Pour obtenir des renseignements sur la garantie, rendez-vous sur www.honeywellaidc.com et cliquez sur Ressources > Garantie du produit . | Pour obtenir des informations sur la garantie, rendez-vous sur www.honeywellaidc.com et cliquez sur Get Resources (Obtenir des ressources) > Product Warranty (Garantie du produit) . | Per informazioni sulla garanzia, visitare www.honeywellaidc.com e fare clic su Ottieni risorse > Garanzia prodotto . | Informationen zur Garantie finden Sie auf unserer Website www.honeywellaidc.com unter Get Resources > Product Warranty . |
| Obtenga información sobre la garantía en www.honeywellaidc.com y seleccione Get Resources (Obtener recursos) > Product Warranty (Garantía del producto) . | Para obtener información sobre la garantía, visite el sitio www.honeywellaidc.com y haga clic en Obtener Recursos > Garantía del producto . | Para ver informações sobre a garantia, acesse www.honeywellaidc.com e clique em Recursos > Informações de garantia . | 有关保修信息，请访问 www.honeywellaidc.com ，然后单击 Get Resources (获取资源) > Product Warranty (产品保修) 。 | 請前往 www.honeywellaidc.com ，然後按一下 Get Resources (取得資源) > Product Warranty (產品保固) 以瞭解保固資訊。 |
| 保証情報については、 www.honeywellaidc.com に移動し、 Get Resources (リソース) > Product Warranty (製品保証) をクリックしてください。 | 보증 정보는 www.honeywellaidc.com 을 방문해서 Get Resources(자료 가져오기) > Product Warranty(제품 보증) 을 선택하십시오. | Чтобы ознакомиться с информацией о гарантии, перейдите на веб-сайт www.honeywellaidc.com и выберите пункт GetResources > Product Warranty (Получить ресурсы > Гарантия на устройстве) . | Garanti bilgileri için www.honeywellaidc.com adresinden Get Resources (Kaynakları Edin) > Product Warranty (Ürün Garantisi) ögesine tıklayın. | Informace o záruce naleznete na stránce www.honeywellaidc.com v části Ziskat zdroje > Záruka na produkt . |
| Informácie o záruke nájdete na www.honeywellaidc.com v časti Get Resources (Získat zdroje) > Product Warranty (Záruka výrobku) . | Aby uzyskać informacje dotyczące gwarancji, należy odwiedzić stronę www.honeywellaidc.com i kliknąć opcję Get Resources > Product Warranty (Pobierz zasoby > Gwarancja produktu) . | www.honeywellaidc.com للاطلاع على معلومات الضمان، اذهب إلى www.honeywellaidc.com وانقر على Get Resources (ضمان المنتج > Product Warranty) | לקבלת מידע בנושא אחריות, עבור אל www.honeywellaidc.com ולחץ על Get Resources (מצא משאבים > אחריות מוצר) . | |

| | | | | | | | |
|---|--|---|---|---|--|---|---|
| The following statements may not apply to products assembled in Mexico: | Les énoncés suivants pourraient ne pas concerner les produits assemblés au Mexique : | Les énoncés suivants peuvent ne pas s'appliquer aux produits assemblés au Mexique : | Le seguenti affermazioni potrebbero non essere applicabili ai prodotti assemblati in Messico: | Die folgenden Aussagen gelten möglicherweise nicht für Produkte, die in Mexiko gefertigt wurden. | Los siguientes puntos puede que no se apliquen a los productos ensamblados en México: | Es posible que las siguientes afirmaciones no apliquen para productos ensamblados en México: | A seguinte declaração pode não se aplicar a produtos montados no México: |
| 以下声明可能不適用於在墨西哥組裝的產品： | 以下聲明可能不適用於在墨西哥組裝的產品： | 次の記述はメキシコで組み立てられた製品には当てはまらない場合があります。 | 다음 선언문은 멕시코에서 조립된 제품에 적용되지 않을 수 있습니다. | Следующие утверждения, возможно, не относятся к устройствам, собранным в Мексике: | Aşağıdaki açıklamalar montajı Meksika'da yapılan ürünler için geçerli olmayabilir: | البيانات التالية قد لا تنطبق على المنتجات التي تم جمعها في المكسيك: | יתכן שהאמרות להלן לא יחול על מוצרים שורכבו במקסיקו: |
| CB Scheme Certified to CB Scheme IEC 60950-1, Second Edition. | Plan OC (organismes de certification) Certifié CB CEI 60950-1, deuxième édition. | Schéma OC Certifié selon la norme CEI 60950-1 seconde édition (schéma OC). | Schema CB Certificato in base allo Schema CB IEC 60950-1, seconda edizione. | CB-Zertifizierung CB-zertifiziert gemäß IEC 60950, Second Edition. | Esquema CB Se ha certificado que cumple el esquema CB IEC 60950-1, segunda edición. | Esquema CB Se ha certificado que cumple con el esquema CB IEC 60950-1, segunda edición. | Esquema CB Certificação CB Scheme IEC 60950-1, Segunda edição. |
| CB 方案 已通过 CB 方案 IEC 60950-1 第二版的认证。 | CB Scheme 經過認證符合 CB Scheme IEC 60950-1 標準第二版。 | CB Scheme CB Scheme IEC 60950-1, Second Edition に認定されています。 | CB Scheme CB Scheme IEC 60950-1, Second Edition 인증을 받았습니다. | Схема CB Сертификация согласно схеме CB МЭК 60950-1, издание второе. | CB Scheme اتفاقية CB Scheme رقم IEC 60950-1، الإصدار الثاني. | CB Scheme מורשה ל- CB Scheme IEC 60950-1، הגרסה השנייה. | CB Planı CB Planı IEC 60950-1, ikinci Sürüm sertifikasına sahiptir. |
|  Honeywell International Inc., hereby declares that the radio equipment type, non-specific SRD, is in compliance with the following directives: • 2014/53/EU Radio Equipment • 2011/65/EU RoHS (Recast) The full text of the EU declaration of conformity is available at the following internet address: www.honeywellaidc.com/compliance . European contact: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Honeywell International Inc. déclare par la présente que le type d'équipement radio, SRD non spécifique est conforme aux directives suivantes: • Equipement radio 2014/53/EU • 2011/65/UE – RoHS (Refonte) Le texte intégral de la déclaration de conformité de l'UE est disponible à l'adresse Internet suivante: www.honeywellaidc.com/compliance . Personne-ressource en Europe: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Les Pays-Bas |  Honeywell International Inc. déclare par la présente que le type d'équipement radioélectrique de faible portée non spécifique est conforme aux directives suivantes: • 2014/53/EU Equipement radio • 2011/65/UE RoHS (refonte) Le texte intégral de la déclaration de conformité de l'UE est disponible à l'adresse internet suivante: www.honeywellaidc.com/compliance . Contact en Europe: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Pays-Bas |  Honeywell International Inc. dichiara che il tipo di apparecchiature radio, SRD (dispositivi a corto raggio) non specific è conforme alle seguenti direttive: • 2014/53/UE - Apparecchiature radio • Direttiva RoHS 2011/65/UE (rifusione) Il testo completo della Dichiarazione di conformità UE è disponibile al seguente indirizzo Internet: www.honeywellaidc.com/compliance . Contatto in Europa: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Paesi Bassi |  Honeywell International Inc. erklärt hiermit, dass das nicht näher spezifizierte SRD folgende Richtlinien erfüllt: • Richtlinie 2014/53/EU (Funkanlagen) • 2011/65/EU RoHS (Recast) Die vollständige EU-Konformitätserklärung finden Sie im Internet unter: www.honeywellaidc.com/compliance . Ansprechpartner Europa: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Niederlande |  Honeywell International Inc. declara que el tipo de equipo de radio, SRD no específico, es conforme a las directivas siguientes: • 2014/53/EU sobre equipos de radio • 2011/65/UE RoHS (Refundida) El texto completo de la declaración de conformidad de la UE está disponible en la siguiente dirección de internet: www.honeywellaidc.com/compliance . Contacto europeo: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Países Bajos |  Honeywell International Inc. declara que o tipo de equipamento de rádio, sem SRD específico, está em conformidade com as seguintes diretivas: • Normativa 2014/53/UE sobre equipamentos radioelétricos • 2011/65/UE RoHS (Reformulada) O texto completo da declaração de conformidade da UE está disponível em www.honeywellaidc.com/compliance . Contato na Europa: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Holanda |  Por meio deste documento, a Honeywell International Inc. declara que o tipo de equipamento de rádio, sem SRD específico, está em conformidade com as seguintes diretivas: • Equipamento de rádio 2014/53/UE • 2011/65/UE RoHS (Reformulação) O texto completo da declaração de conformidade da União Europeia está disponível em www.honeywellaidc.com/compliance . Contato na Europa: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Holanda |
|  Honeywell International Inc. 特此声明，无线电设备类型“非特定 SRD”符合以下指令的规范： • 2014/53/EU 无线电设备 • 2011/65/EU RoHS (新版) 关于欧盟符合性声明的全文，请访问以下网址： www.honeywellaidc.com/compliance 。 欧洲联系信息： Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Honeywell International Inc. 特此聲明，無線電設備類型「非特定 SRD」符合下列指令的規範： • 2014/53/EU 無線電設備 • 2011/65/UE RoHS (重訂) 如需歐盟符合性聲明的全文，請造訪下列網址： www.honeywellaidc.com/compliance 。 歐洲聯絡資訊： Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Honeywell International Inc. は、無線装置タイプ、非特定 SRD が、以下の指令に準拠することをここに宣言します。 • 2014/53/EU 無線機器 • 2011/65/UE RoHS (改正) EU 適合宣言書の全文は、 www.honeywellaidc.com/compliance で利用可能です。 欧州でのお問い合わせ： Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Honeywell International Inc. 는 무선 장비 유형, 일반 SRD 가 다음 지침을 준수함을 선언합니다. • 2014/53/EU 무선 장비 • 2011/65/UE RoHS (Recast) EU 준수 선언문의 전문은 인터넷 주소 www.honeywellaidc.com/compliance 에서 참조할 수 있습니다. 유럽 연락처: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Настоящим компания Honeywell International Inc. заявляет, что радиосистемы ближнего действия соответствуют следующим директивам: • Директива 2014/53/ЕС по радиооборудованию • 2011/65/ЕU Директива RoHS (исправленная) Полный текст декларации соответствия стандартам ЕС доступен на странице www.honeywellaidc.com/compliance . Контактное лицо в Европе: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |  Honeywell International Inc. isbu belge ile radyo ekipman türlerini, belirsiz SRD nin ve hücrelerin, aşağıdaki direktiflerle uyumlu olduğunu beyan eder. • 2014/53/EU Telsiz Ekipmanı • 2011/65/EU RoHS (Yeni düzenleme) AB uygunluk beyanının tam metnine şu internet adresinden ulaşabilirsiniz: www.honeywellaidc.com/compliance . Avrupa için iletişim: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen Hollanda |  تقرر شركة Honeywell International Inc. إعلان نوعية جهاز الإرسال اللاسلكي المصنف كونه جهاز SRD غير محدد يتفق مع التوجيهات التالية. • جهاز الإرسال اللاسلكي وفقاً للوائح الاتحاد الأوروبي 2014/53 • توجيهات الاتحاد الأوروبي (المعاد صاغتها). الاتحاد الأوروبي 2011/65 يمكن الاطلاع على النص الكامل لإعلان المطابقة وفقاً للوائح الاتحاد الأوروبي بزيارة الموقع التالي: www.honeywellaidc.com/compliance . جهات الاتصال الأوروبية: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen هولندا |  תחמייהררה בואת כי סוג ציוד הרדיו, SRD לא ספציפי, עומד בהנחיות הבאות: • ציוד רדיו 2014/53/UE • RoHS(2011/65 (מערך מחדש) הטקסט המלא של הוצהרת ההתאמה של היחידור האירופי יזמין בכותרת האינטרנט הבאה: www.honeywellaidc.com/compliance . ליצירת קשר באירופה: Honeywell Productivity Solutions BV Lagelandseweg 70 6545CG Nijmegen The Netherlands |
| Este produto está homologado pela ANATEL, de acordo com os procedimentos regulamentados pela Resolução No. 242/2000 e atende aos requisitos técnicos aplicados. Este equipamento opera em caráter secundário, isto é, não tem direito a proteção contra interferência prejudicial, mesmo de estações do mesmo tipo, e não pode causar interferência a sistemas operando em caráter primário. Para maiores informações, consulte o site da ANATEL – www.anatel.gov.br . |  Modelo: CCB00-010BT |  依據標準：低功率射頻電機技術規範：LP0002 NCC standard: Low power frequency electric machinerie technical standard: LP0002 根據交通部低功率管理辦法規定： 第十二條 型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。 第十四條 低功率射頻電機之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾後方得繼續使用。 前項合法通信，指依電波法規定之無線電、低功率射頻電機須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。 台灣 RoHS 網頁限用物質含有情況資訊，請依下列步驟操作： 1. 網頁連結： https://www.honeywellaidc.com/Taiwan-RoHS 2. 限用物質含有情況資訊表格是以產品型號命名的，找到對應產品型號為首的超連結，單擊即可以打開。 |  If the following label is attached to your product, the product meets Korean agency approval for Class B equipment: 이 기기는 가정용 (B 급) 전자파적합기기로서 주로 가정에서 사용하는 것을 목적으로 하며, 모든 지역에서 사용할 수 있습니다. | | | | |

| 型号 (Model) : CCB00-010BT 产品中有害物质的名称及含量 (Names and Content of Hazardous Substances in the Product) | | | | | | | |
|--|-----------------------------|--------|--------|------------|------------|--------------|--|
| 部件名称 (Parts Name) | 有害物质 (Hazardous Substances) | | | | | | |
| | 铅 (Pb) | 汞 (Hg) | 镉 (Cd) | 六价铬 (Cr6+) | 多溴联苯 (PBB) | 多溴二苯醚 (PBDE) | |
| 印刷电路板 (PCB) | x | o | o | o | o | o | |
| 外壳 (Housing) | o | o | o | o | o | o | |
| 连线 (Cables) | o | o | o | o | o | o | |
| 本表格依据 SJ/T11364 的规定编制。(The table is created by SJ/T11364 requirement.) o: 表示该有害物质在该部件所有均质材料中的含量均在 GB/T26572 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in China's GB/T26572.) x: 表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T26572 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials for this part is above the limit requirement in China's GB/T26572.) | | | | | | | |