

**HARDWARE / SPECIFICATIONS / FEATURES**



**QC51**



**QC52**



HARDWARE	
Power Requirements	115/230V, 15 amp*, 50/60 Hz, 1 ph †
Processor	3.06 Ghz Intel® Core™ i3
Memory	4 GB of DDR3 SDRAM
Hard Drive	120 GB Solid State Hard Drive (or greater)
DVD-RW/CD-RW Drive	Standard
Monitor Class	24" Widescreen LCD
Wireless Network Module	Yes - Standard
Operating System	Windows® 7 - 64 Bit
Custom Drawer with Open Printer	Standard
Printer	HP Color Printer
Wireless Remote	Standard
Power Line Filter	Standard
Drive-on Camera Compatible	Yes

PRODUCTIVITY TOOLS	
Hunter QuickCheck® Software	Standard
Vehicle Specifications (30 plus years)	Standard - 2 Years Free Updates
Real-Time Specs Delivered by Web	WebSpecs®
VIN Barcode Reader	Standard
HunterNet®	3 Years Free Access for 1 User
QC Alignment Printout	3 Available Options

\*Amperage shown is minimal circuit rating † Isolated Ground Recommended

SPECIFICATIONS	
Metal on Metal Contact	Non-Contact
Weight of Target	6 lbs (2.72 kg)
Profile of Target	9 in. (228.6 mm)
Installation Time	5 seconds
Wheel Assembly Range	40 in. (1016 mm)
Rolling Compensation Style	Forward
Mobile Storage Carts	2
Camera Resolution	2,608 x 1,952 20,000,000 px
Recommended Bay Length	25 ft. (7620 mm)

**OPTIONS / ACCESSORIES**

Tread Depth Tool  
20-2782-1\*



CodeLink® 2 w/o Pod  
20-2813-1



XF-2 Pod  
20-2072-1



Battery Tester  
20-2781-3\*



Accessory Bundle  
20-2992-1



\*20-2072-1 XF-2 Pod Required if kit 20-2785-1 or 20-2796-1 not purchased

**Continued on Reverse**



**For aligner information visit:**  
[www.hunter.com/inspection](http://www.hunter.com/inspection)

**For local contact visit:**  
[www.hunter.com/company/findrep.cfm](http://www.hunter.com/company/findrep.cfm)

**For general inquiries visit:**  
[www.hunter.com](http://www.hunter.com) or call **800-448-6848**

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

Copyright © 2013-2015, Hunter Engineering Company  
Form 6681-T, 03-14b  
Supersedes Form 6681-T, 07-13

### CONSOLE CONFIGURATIONS

	QC51	QC51A	QC51B	QC52	QC52A	QC52B			
Battery Tester 20-2781-3		✓	✓		✓	✓			
Tread Depth Tool 20-2782-1		✓	✓		✓	✓			
CodeLink 2 w/ Pod 20-2785-1		✓	✓		✓	✓			
Brake Plates B424-01-PNT		✓			✓				
Drive Thru Sensors	✓	✓	✓						
Drive Under Sensors				✓	✓	✓			

### QC51 - DRIVE THRU DIMENSIONS

	QC Drawer	QC51
Width (W)	22.50 in. 571.5 mm	132 in. 3353 mm
Height (H)	20.25 in. 514.35 mm	50 in. 1270 mm
Depth (D)	23.25 in. 590.55 mm	11 in. 279 mm
	37.25 in. (fully extended) 946.15 mm	
Sensor Range	-	78 to 106 in. 1981 to 2692 mm
Shipping Weight	44 lbs 20 kg	578 lbs 262 kg

QC51 systems offer a custom mounting option for customers unable to incorporate a standard Quick Check console. Mounting components include monitor / keyboard panel, drawer tray and drawer slides. QC51 systems **Do Not** include a cabinet. Components allow for mounting in service writer's desk, Shure® #791595 wall mounted cabinet and built in wall mounted cabinets.

### QC52 - DRIVE UNDER DIMENSIONS

	QC Drawer	QC52
Width (W)	22.50 in. 571.5 mm	135 in. 3429 mm
Width (W) (With Monitor Kit)	-	135 in. 3429 mm
Height (H)	20.25 in. 514.35 mm	15 in. 381 mm
Height (H) (With Monitor Kit)	-	18 in. 457 mm
Depth (D)	23.25 in. 590.55 mm	15 in. 406 mm
	37.25 in. (fully extended) 946.15 mm	
Depth (D) (With Monitor Kit)	-	22 in. 559 mm
Sensor Range	-	119 in. 3023 mm
Shipping Weight	44 lbs 20kg	657 lbs 298 kg

QC51 systems offer a custom mounting option for customers unable to incorporate a standard Quick Check console. Mounting components include monitor / keyboard panel, drawer tray and drawer slides. QC51 systems **Do Not** include a cabinet. Components allow for mounting in service writer's desk, Shure® #791595 wall mounted cabinet and built in wall mounted cabinets.

It is recommended that a low clearance warning be suspended at the entrance of Drive Under Quick Check® bays.

