



ProLite E1980SD

Reliable office solution

The 19" ProLite E1980SD is a LED-backlit monitor with 5ms response time, high contrast and sRGB and gamma correction functions that permit even the finest nuances of colour to be set accurately. The ProLite E1980SD includes DVI and VGA connectivity and is available in black.

DISPLAY CHARACTERISTICS

Diagonal	19"
Panel	TN
Display area h x w	301.05 x 376.32 mm; 11.9" x 14.8"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	250 cd/m² typical
Brightness	300 cd/m² max.
Viewing zone	horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 75°/ 85°
Display colour	16.7 million
Pixel pitch h x v	0.294 x 0.294 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate Sync

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	16 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

INTERFACES CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D
HDCP	yes
	D-Sub, DVI-D

SF

PECIAL FEATURES	
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, RU, JP, Chinese) and 5 front controls (Power, Menu, +/ Volume Button, -/ ECO Button, AUTO)
User controls	is luminance (contrast, brightness, ECO, i-Style colour, ACR), image setup (clock, phase, H. position, V. position), colour adjust (gamma, colour temperature, sRGB), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, information), volume, auto adjust
Speakers	2 x 1 W (Stereo)
Anti-theft-device	 Kensington-lock™ prepared
Safety	CE, TÜV-GS, VCCI-B, TCO 6, CU
Tilt angle	e 21° up; 4° down
VESA mounting	100 x 100 mm

ACCESSORIES

DIMENSIONS & WEIGHT

Dimensions w x h x d	411 x 402 x 189.5 mm
Weight	3.2 kg

	8
Included accessories	power cable, VGA (D-Sub) cable, DVI-D
	cable, audio cable, stand, stand-base, quick
	start guide, safety guide

Driver Windows 95 / 98 / 2000 / ME / XP / Vista / 7/