



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: QHC-060203A**

**IC: 4393B-060203A**

**FCC Rule Part: 15.247**

**IC Radio Standards Specification: RSS-210**

**ACS Project Number: 13-0256**

Manufacturer: Itron

Model: OW31SASL5BE-1

## **Manual**



OpenWay 3.1  
User Information Manual  
Itron Model OW31SASL5BE-1



## Labeling

The following requirements will be applied to any products that use this module:

The end product label will include the following text:

Contains:  
FCC ID: QHC-060203A  
IC: 4393B-060203A  
Model: OW31SASL5BE-1

The user's manual for any product that contains this module will contain the following text. If the device is large enough, this information will also be placed on the label:

"THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS. (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION."

## Regulatory Compliance

The user's manual for any product that contains this module will contain the following text:

### FCC Part 15, Class B

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, the user is encouraged to try to correct the interference by one or more of the following measures:

- *Reorient or relocate the receiving antenna.*
- *Increase the separation between the equipment and receiver.*
- *Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.*
- *Consult the dealer or an experienced radio/TV technician for help.*

## Industry Canada

*This device complies with Part 15 of the FCC Rules [and with RSS-210 of Industry Canada].*

*Operation is subject to the following two conditions:*

- (1) this device may not cause harmful interference, and*
- (2) this device must accept any interference received, including interference that may cause undesired operation.*

*Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:*

- (1) l'appareil ne doit pas produire de brouillage, et*
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.*

Under Industry Canada regulations, this radio transmitter may only operate using antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication.

En vertu de la réglementation d'Industrie Canada, cet émetteur radio peut fonctionner uniquement à l'aide de l'antenne d'un type et maximale (ou moins) obtenir une approbation pour l'émetteur par Industrie Canada. Pour réduire les interférences radio potentielles à d'autres utilisateurs, le type d'antenne et son gain doivent être choisie que la puissance isotrope rayonnée équivalente (p.i.r.e.) n'est pas plus que celui nécessaire à une communication efficace.



## RF Exposure

The antennas used for this transmitter must be installed to provide a minimum separation distance of 20 cm from all persons, and must not be co-located or operate in conjunction with any other antenna or transmitter. End users and installers must be provided with antenna installation procedures and transmitter operating conditions for satisfying RF exposure compliance.

## Miscellaneous

The user's manual for any product that contains this module will contain the following text:

## Professional Installation

This module is intended for professional installation by the integrator. The OEM integrator is still responsible for the FCC compliance requirement of the end product which uses this module.

## Modification and Repairs

To ensure FCC compliance and system performance, this device, antenna and/or coaxial assembly shall not be changed or modified without the express written approval of Itron. Any unauthorized modification will void the user's authority to operate the equipment.

**WARNING!** This device contains no user serviceable parts. Attempts to repair this device by unauthorized personnel may subject the person to shock hazard if removal of protective covers is attempted. Unauthorized repair will void the warranty and/or any maintenance contract with your company.

## General Description

The Itron OW31SASL5BE-1 (OpenWay 3.1) is an electricity metering module which includes a Cellular EVDO WAN module operating in the GSM 800 MHz and PCS 1900 MHz bands and a LAN transmitter operating in the 902 MHz to 928 MHz band. The module operates on alternating current which is supplied by the host meter device.



## ANTENNAS

*This radio transmitter (identify the device by certification number, or model number if Category II) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.*

*Le présent émetteur radio (identifier le dispositif par son numéro de certification ou son numéro de modèle s'il fait partie du matériel de catégorie I) a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur.*

Both antennas used with the OPENWAY 3.1 are slot antennas terminated at 50ohms into a U.FL RF connector. Typical VSWR is 2.5:1 in keeping with recommended practices.

WAN Antenna:

GAIN: -3.5dBi Cellular & +2.5 PCS  
PASSBAND: 824-894 Cellular Band & 1850-1990 PCS Band

LAN Antenna:

GAIN: 0dBi  
PASSBAND: 900MHz to 990MHz