

SPECIFICATION & FEATURES

Transmitter

- ◆ Omnidirectional
- ◆ Effective transmitting range: Up to 400'
- ◆ Frequency: 2.412 GHz
- ◆ Left / Right audio line level inputs
- ◆ UL-Listed AC adapters (rated 12V DC 600mA)

Speaker

- ◆ 10W Integrated Amplifier with two way speaker design
- ◆ Bass Reflex Type
- ◆ Tweeter: 1" dome tweeter
Woofer: 5" waterproof woofer
- ◆ RF Frequency: 2.412GHz
- ◆ Acoustic Frequency: 70 Hz ~ 20k Hz
- ◆ 50dB Signal-To-Noise Ratio
- ◆ Distortion: 5 %

Name of each Control

- A. Indicator Light
- B. Power & Volume Control Knob
- C. Speaker Power Input Jack
- D. Audio Level Indicator Light
- E. Audio Input Jack
- F. Transmitter Power Input Jack
- G. Transmitter AC Adapter 12V DC 600mA
- H. Speaker AC Adapter 12V DC 1000mA
- I. RCA Audio Cable

Notice: The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.