Page 18

FCC ID: FPW 2151B-68W

EXHIBIT 5

User's Manual

User's Manual

FCCID: FPW2151B-68W TOK98-FOGO / ALDIX SNENZHEN

JING MOLD ENTERPRISE CO.,LTD USER'S MANUAL MODEL: FPW 2151B-68W 104 KEYS KEYBOARD

FCC NOTICE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of teh FCC Rules. These limits are designed to provide reasonable protection against harrmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is concouraged to try to correct the interference by one of the following measures;

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and the receiver

 Connect the equipment into an outlet on a circuit different form that to which the receiver is connected.

- Consult the deler or an experienced radio/TV technic-ian for help.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

2151B KEYBOARD SPECIFICATIONS

Structure

Size: 474mmX200mmX52mm (LXWXH)

Keystroke Travel: 3.5mm±0.5mm (0.15"±0.02")

Actuation Force: 55g 2.0 oz

Reliability: ≥ 10X10⁶ MCBF

Electron

Out. Voltage: +5Vdc 0.25v @300mA Max.

Key Rollver: Multi-Key rollver

Out Code: Synchronous 8bit

Environmerntal

Operational Temperature : 0 to 50 $^{\circ}$ C

Operational Humidity: 10%-90%RH At 40

Storage Temperature : -20 To 60

Storage Humidity: 5%-95%RH At 40℃

Address: Xin Qiao 3rd Industrial Estate Sha Jing. Pao An. Shen Zhen, China