Page 16

FCC ID: FPW JME-5651A

EXHIBIT 5

User's Manual

User's Manual

FCCID: FPWJME-7551A

JING MOLD ENTERPRISE CO., LTD USER'S MANUAL

MODEL: JME-7551A 107 KEYS KEYBOARD

FCC NOTICE

This equipment has been tested and found to comply with the limits for a class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and , if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

FCC ID: FPWSHE -7551A

JME-7551A KEYBOARD SPECIFICATIONS

Structure

Size: 474mm $\times 172$ mm $\times 39.9$ mm (L \times W \times H)

Keystroke Travel: 3.5mm ± 0.5 mm $(0.15" \pm 0.02")$

Actuation Force: 55g 2.0 oz

Reliability: $\geq 10 \times 10^6 MCBF$

Electron

Inpet Voltage: +5Vdc 0.25v @300mA Max.

Key Rollver: Multi-Key rollver

Out Code: Synchronous 8bit

Environmental

Operational Temperature: 0 to 50 °C

Operational Humidity: 10% - 90%RH At $40~^{\circ}$ C

Storage Temperature: -20 to $60 \,^{\circ}\text{C}$

Storage Humidity: 5% - 95%RH At 40 $^{\circ}$ C

Address: Xin Qiao 3rd Industrial Estate Sha Jing. Bao An, Shen Zhen, China.