

EUT:MOUSE

EXHIBIT C

FCC ID:FSUGMZG2

KYE Systems Corp.

USER'S MANUAL

U805/U806 Mouse Installation Guide

Introduction

This mouse device with its innovative shape will give you better comfort, quality, and control over a long period of time. It has plug and play features and is very easy to install.

Installing U805/U806 mouse driver for Windows 98

1. Turn on power of computer
2. Plug the USB connector into the USB port on the computer firmly.
3. Computer will detect your USB mouse.
4. Installation completely.

Cleaning Your Mouse

You can protect your mouse by keeping your work area clean and free from dust.

Note: Make sure the system is off before you attempt to clean it

1. Remove the ball by turning the ball retainer counter-clockwise until it becomes loose.
2. Use a soft or non-abrasive cleaner to clean the ball and rollers. You can also use a cotton swab to clean the ball container.
3. Reinstall the ball and the ball retainer.

FEDERAL COMMUNICATIONS COMMISSION

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection. This equipment generates, uses and can radiated radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient o relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Shielded interface cables must be used in order to comply with emission limits.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.