

BT40SC User Guide

Appearance



Specification

- 1.Part Number: JLDP.15.302.001;
- 2.Working Voltage: 18-30V;
- 3.Working Current: 5mA @29V;
- 4.Operation Temperature:-20~55℃;
- 5.Storage temperature: -45~85℃;
- 6.RF Frequency Range: 2402MHz to 2480MHz;
- 7.RF Modulation: GFSK;
- 8.RF Transmitted Power: 0 dBm;
- 9.Housing Material: ABS 765A, 94V-0;

NOTE:

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement:

To satisfy FCC RF Exposure requirements for this transmission devices, This equipment can contact with the body, according to KDB447498 D01 General RF Exposure Guidance, This equipment doesn't need to evaluate the stand-alone SAR . The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.