

SELECTION



Page 1 of 2

KENMORE








Kenmore 21.9 cu. ft. French Door Bottom Freezer Refrigerator

O White 46-72002

- O Stainless 46-72003
- Black 46-72009
- Internal water filtration system
- Full-width, temperature-controlled gourmet pantry drawer with slide controls
- 2 humidity-controlled crispers
- 5 glass shelves (4 adjustable, 4 spill-proof, 4 slide-out)
- 5 door storage bins (3 adjustable)
- 2 full-width slide-out freezer baskets
- Electronic up-front temperature controls with digital display
- · Factory-installed icemaker
- Smooth, contoured doors with hidden hinges and aluminum handles
- 32 5/8" W x 70 1/8" H x 34 1/2" D



- $A-\text{Height without Hinge} \qquad D-\text{Depth with Handle}$
- B Height with Hinge
- $\mbox{\bf E}-\mbox{\bf Max}.$  Depth with Doors / Drawer Open
- C Depth without Handle F Width


Clearance - Additional Width Required to Open the Doors 90°

Left Hinge – Facing the refrigerator, handle is on your right and hinges are on your left. Right Hinge – Facing the refrigerator, handle is on your left and hinges are on your right.

Dimensions.	Hei	ight		Depth		Width	Clear	ances
Inches	Α	В	С	D	Е	F	Door Edge	Handle
46-7200X	68 7/8	70 1/8	33	34 1/2	47	32 5/8	1 3/8	3 7/8

MINIMUM OPENING REQUIRED: When installing next to cabinets, add Width (F) and Door Edge Clearance. When installing next to a wall, add Width (F) and Handle Clearance.

OLLLOTION	KLINIVIOTIL			
FACTORY ICE				
White	46-72002			
Stainless	46-72003			
Black	46-72009			
INTERIOR CAPACITIES				
Total Volume (cu. ft.)	21.9			
Refrigerator / Freezer Volume (cu. ft.)	15.6 / 6.3			
REFRIGERATION FEATURES				
Total Interior Glass Shelves	5 (4 Adjustable)			
Spill-Proof Shelves	4			
Slide-Out Shelves	4			
Full-Width Gourmet Pantry Drawer	1 TempControlled w/Slide Controls			
Humidity-Controlled Crisper	2 Clear			
Total Door Shelves / Bins	5 (5 Adjustable)			
Gallon Door Storage	2			
Covered Dairy Bin	1 Clear			
Refrigerator Light(s)	•			
WATER FILTRATION AND DISPENSER				
Water Filtration System	Internal, NSF® Certified <sup>↑†</sup>			
Water Filter Location	Fresh Food Compartment			
Water Filter Replacement <sup>†</sup>	46-9006			
Type of Ice	Crescent			
FREEZER FEATURES				
Drawer / Door Type	Pull-Out			
Factory-Installed Icemaker	•			
Removable Ice Caddie	•			
Fast Ice Production*	Acceler-Ice™			
Freezer Light(s)	•			
Freezer Organization	2 Full-Width Slide-Out Baskets			
GENERAL FEATURES				
Temperature Controls	Electronic Up-Front with Digital Display			
Door Style / Finish	Contoured, Smooth Doors			
Color-Matched Cabinet / Hinge	•			
Hidden Hinges	•			
Door Handle Finish	Aluminum			
ENERGY STAR® Qualified	•			
Est. Energy Consumption (kWh / yr.)	459			
Est. Yearly Operating Cost**	\$49			
Volts / Amps	115 / 7.1			
1: 14/ 1 1 : / 4				



<sup>&</sup>quot;All energy \$ / Yr. figures a variance at local bears stores".

\$0.1065 / kWh. Energy rebates are offered and paid by the energy supplier in states where such programs exist. Criterion is based on percentage of energy efficiency attained beyond the 2007 standard. Dollar amounts may differ.



††NSF® Certified; the NSF (National Sanitation Foundation) is an independent national agency that establishes standards by which water filtration products are manufactured and tested.









Item Weight (Approx. Lbs.)

1 Year Limited Warranty -Entire Appliance\*\*

WARRANTY

Shipping Weight (Approx. Lbs.)

240

265



Page 2 of 2

## MEASURE TWICE...ORDER ONCE

Step-by-Step Instructions to Assure You Order the Proper Size Refrigerator

It's Just Good Measure To Double Check Before You Order!

- Measure the opening for the refrigerator. Don't forget baseboards, molding, tile, countertop overhang, etc. If there is an island in your kitchen, be sure there is enough room to open the door.
- 2. Refer to the chart for the exact dimensions of the refrigerator.
- 3. IMPORTANT! Calculate the minimum opening required. When installing next to cabinets, you must allow for Door Edge Clearance. (Multiply Door Edge Clearance by 2 for counter-depth models.) When installing next to a wall, you must allow for the Handle Clearance.

Adjacent Cabinet: \_\_\_\_ "F" + \_\_\_ Door Edge = \_\_\_ Min. Opening

Adjacent Wall: \_\_\_ "F" + \_\_\_ Handle = \_\_\_ Min. Opening

4. Calculate how much the refrigerator will protrude from cabinetry. If the result is undesired, consider a counter-depth model.

"C" - 24" Cabinet Depth + approx. 2" Electric and Water Connection Clearances = \_\_\_\_ which will Protrude Past Cabinets

Measure each door and entry way in the home leading to the kitchen to ensure the refrigerator can be moved through.

