Page 1 of 2





Kenmore Elite 27-Inch Electric Double Oven

O White 22-48172

- Stainless 22-48173
- Black 22-48179
- Flush-to-cabinet design
- 4.2 cu. ft. capacity (both ovens)
- True convection with third element (both ovens)
- Auto convection conversion
- Variable speed convection cooking
- True hidden bake element
- Flex Clean self-cleaning oven (both ovens)

- Three porcelain-coated, self-clean oven racks with integrated handles (both ovens)
- Advanced variable broiling
- Easy Set™ 615W5 controls
- Oven control and door lockout
- Cook and hold warm oven
- Slow cook
- Recipe Recall
- Delay cook and clean
- Two halogen interior oven lights in each oven
- Blue LED lights

Model	22-48172	22-48173	22-48179
Overall	White	Stainless	Black
Console	White	Black w/Stainless	Black
Controls	White	Black / Grey	Black
Door	White	Stainless	Black
Handle	White	Stainless	Black
Bottom Trim	White	Stainless	Black

SELECTION	ELITE		
White	22-48172		
Stainless	22-48173		
Black	22-48179		
OVEN FEATURES			
Overall Width, Inches	27		
Oven Capacity (cu. ft.)	3.5U / 3.5L		
Cleaning System Upper Oven	Self-Clean		
Cleaning System Lower Oven	Self-Clean		
Variable Time Self-Cleaning	Flex Clean (2-4 Hrs.)		
Electronic Oven Controls	Easy Set™ 615W5		
Control Lockout	•		
Recipe Recall	•		
Slow Cook	•		
Add-1-Minute Timer	•		
Temperature Recall	•		
Cook & Hold Warm Oven	•		
Delay Start	•		
Automatic Oven Shutoff	•		
Sabbath Mode*	Certified		
True Convection with Third Element	•		
Variable Speed Convection	•		
Auto Convection Conversion	•		
Hidden Bake Element	•		
Variable Broiling System	Advanced, 400°-550°		
Integrated Handle Oven Racks	3 Upper / 3 Lower		
Self-Clean Porcelain-Coated Racks	•		
Oven Rack Positions	3 in Each Oven		
Food Temperature Probe	Upper		
Oven Lights (Both ovens)	2 Halogen, Auto / Manual		
Removable Glass Door	• (48173: Stainless Door)		
Frameless Oven Door	•		
Window	X-Large		
Reach-Through Handle(s)	Metal		
Upper Oven Interior W x H x D (In.)	20 1/2 x 16 1/2 x 18 1/32		
Lower Oven Interior W x H x D (In.)	20 ¹ / ₂ x 16 ¹ / ₂ x 18 ¹ / ₃₂		
GENERAL FEATURES			
Flush Fit Design	•		
Power Rating (kW) @ 240V / 208V	6.8 / 5.1		
Bake @ 240V (Watts) Both Ovens 8-Pass	2,700		
Broil @ 240V (Watts) Both Ovens 8-Pass	3,400		
Convection @ 240V (Watts)	2,500		
Breaker / Copper Wire Size (240V)	30 / 10		
Shipping Weight (Approx. Lbs.)	255		
WARRANTY			
1-Year Limited Warranty –	D . 0.1.1		
Entire Appliance	Parts & Labor		

If used for other than private family purposes, warranty applies for only 90 days. U = Upper Oven $\;\;L=$ Lower Oven "Sabbath Mode overrides auto oven shutoff







Page 2 of 2

NOTES:

- 1. Base must be capable of supporting: 30" 375 pounds, 27" 300 pounds
- Cutout depth is critical to the proper installation of the built-in oven.If the oven decorative trim does not butt against the cabinet, or if noise is heard on convection models, verify the dimension to assure it is the required depth.
- 3. For a cutout height greater than 49 1/4* for 27* and 30* models, add one 2* wide wood shim of appropriate height to each side of the opening under the appliance rails.

 For cutout height between 51 $^{13}/16^$ and 51 $^{15}/16^*$ for 30 * models, use the larger interior trim supplied with the wall oven.

Dimensions, Inches					Cut	out					
	Α	В	С	D	Е	F	G	Н	ı	J	K
22-4817X	27	50 1/2	24 5/8	24 1/2	21	48 5/8	24 7/8 - 25 1/4	49 7/8 - 49 7/8	27 1/8	1	1 1/4

