Page 1 of 2





Kenmore Elite 30-Inch Electric Double Oven

O White 22-48182

- O Stainless 22-48183
- Black 22-48189
- Flush-to-cabinet design
- 4.2 cu. ft. capacity (both ovens)
- True convection with third element (both ovens)
- Auto convection conversion
- Variable speed convection cooking
- True hidden bake element
- Flex Clean self-cleaning oven (both ovens)

- Three porcelain-coated, self-clean oven racks with integrated handles (both ovens)
- Advanced variable broiling
- Easy Set™ 615W5 controls
- Oven control and door lockout
- · Cook and hold warm oven
- Slow cook
- Recipe Recall
- Delay cook and clean
- Two halogen interior oven lights in each oven
- Blue LED lights

Model	22-48182	22-48183	22-48189	
Overall	White	Stainless	Black	
Console	White	Black w/Stainless	Black	
Controls	White	Black / Grey	Black	
Door	White	Stainless	Black	
Handle	White	Stainless	Black	
Bottom Trim	White	Stainless	Black	

SELECTION	ELITE
White	22-48182
Stainless	22-48183
Black	22-48189
OVEN FEATURES	
Overall Width, Inches	30
Oven Capacity (cu. ft.)	4.2U / 4.2L
Cleaning System Upper Oven	Self-Clean
Cleaning System Lower Oven	Self-Clean
Variable Time Self-Cleaning	Flex Clean (2-4 Hrs.)
Electronic Oven Controls	Easy Set™ 615W5
Control Lockout	•
Recipe Recall	•
Slow Cook	•
Add-1-Minute Timer	•
Temperature Recall	•
Cook & Hold Warm Oven	•
Delay Start	Cook / Clean
Automatic Oven Shutoff	•
Sabbath Mode*	Certified
True Convection with Third Element	•
Variable Speed Convection	•
Auto Convection Conversion	•
Hidden Bake Element	True
Variable Broiling System	Advanced, 400°-550°
Integrated Handle Oven Racks	3 Upper / 3 Lower
Self-Clean Porcelain-Coated Racks	•
Oven Rack Positions	4
Food Temperature Probe	Upper
Oven Lights (Both ovens)	2 Halogen, Auto / Manua
Removable Stainless Door	•
Frameless Oven Door	•
Window	X-Large
Reach-Through Handle(s)	Metal
Upper Oven Interior W x H x D (In.)	24 1/8 x 16 1/2 x 18 1/32
Lower Oven Interior W x H x D (In.)	24 ¹ /8 x 16 ¹ /2 x 18 ¹ /32
GENERAL FEATURES	
Flush Fit Design	•
Power Rating (kW) @ 240V / 208V	8.0 / 6.0
Bake @ 240V (Watts) Both Ovens 8-Pass	2,200
Broil @ 240V (Watts) Both Ovens 8-Pass	4,000
Convection @ 240V (Watts)	2,500
Breaker / Copper Wire Size (240V)	40 / 8
Shipping Weight (Approx. Lbs.)	302
WARRANTY	
1-Year Limited Warranty – Entire Appliance	Parts & Labor

If used for other than private family purposes, warranty applies for only 90 days. U = Upper Oven L = Lower Oven "Sabbath Mode overrides auto oven shutoff

Effective 10/04/10





Page 2 of 2

NOTES:

- 1. Base must be capable of supporting: 30" 375 pounds, 27" 300 pounds
- 2. Cutout depth is critical to the proper installation of the built-in oven. If the oven decorative trim does not butt against the cabinet, or if noise is heard on convection models, verify the dimension to assure it is the required depth.
- 3. For a cutout height greater than 49 1/4* for 27* and 30* models, add one 2* wide wood shim of appropriate height to each side of the opening under the appliance rails.

*For cutout height between 51 $^{13/16"}$ and 51 $^{15/16"}$ for 30" models, use the larger interior

Dimensions, Inches					Cutout						
	Α	В	С	D	Е	F	G	Н	ı	J	K
22-4818X	30	50 1/2	28 1/4	24 1/2	21	48 5/8	28 1/2 - 29	49 1/8 - 49 7/8	30 1/8	1	1 1/4

