

Fire Control Fire Extinguisher (FC340M-VB)

Part number 466425

Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



For use on the following types of fire:



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FC340M-VB unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Supplied with metal retention bracket.

At a Glance

- Model FC340M-VB
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty



Pt # 466425 - 4 pack

Pt # 46642527 - 4 pack Navistar

Pt # 46642525 - 4 pack Balkamp

UPC: 0-47871-66425-2

I2F: 20047871664256

Pt # 46642521 - 4 pack Carquest

UPC: 0-47871-42521-1

I2F: 10047871425218

Pt # 21006446 - 4 pack Grainger

UPC: 0-47871-66425-2

I2F: 10047871664259

Product Specification

Net agent weight (Average)	5.5 lb.
Unit weight (Average)	8.4 lb.
Diameter	4.5 inches
Height	16.88 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Master Pack	13.0	17.25	9.87



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com