

KONAMI

e-AMUSEMENT IC CARD READER (Slot Type)

Manual

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

You are cautioned that changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

This device complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The antenna used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

Specifications

Item	Specification / Function
Power supply	+12V DC \pm 5% 120mA(Typ.) / 700mA(Max)
RF communication part(Radio)	In conformity to ISO15693(Non-contact vicinity type) Carrier frequency:13.56MHz This device satisfies a demand about an antenna of FCC Part.15.204.
Host I/F	RS232C level(Full duplex transmission) serial I/F
Connector specification	S3B-XH(JST ^{*1}): Power supply connection S3B-PH(JST ^{*1}): RS232C communication S10B-PH(JST ^{*1}): Input device I/F
Board mount method	Screw cramp with M3 screws at 4 points
Outer dimensions	58mm \times 118mm \times 18mm(\pm 0.5mm)
Operation temperature and humidity	0 to +55 $^{\circ}$ C,25 to 85%RH, Non condensing
Storage temperature and humidity	-20 to +65 $^{\circ}$ C,25 to 85%RH, Non condensing

JST^{*1} : J.S.T. Mfg. Co., Ltd.