

YMF744/754 PCI SOUND CARD

Device Driver and Application Installation
under
WINDOWS® 98

July 1999

TABLE OF CONTENTS

| | |
|--|---|
| 1. INSTALLING DEVICE DRIVER..... | 2 |
| 1.1 Installing Device Driver under Windows® 98..... | 2 |
| 1.1.1 <i>Installing the Device Driver by Setup.exe</i> | 2 |
| 1.1.2 <i>Installing the Device Driver</i> | 3 |
| 2. Verifying the Device Driver Installation | 6 |
| 3. APPLICATION SOFTWARE..... | 7 |
| 3.1 “Ystation32” Installation Guide Under Windows® 98..... | 7 |

1. INSTALLING DEVICE DRIVER

1.1 Installing Device Driver under Windows® 98


This section contains the procedures for installing the YMF744/754 PCI sound card device driver software on your computer. The YMF744/754 PCI sound card is a Windows® 98 Plug-and-Play device. Once the YMF744/754 PCI sound card is installed and your computer starts up, Windows® 98 will automatically detect the device and start the Install Wizard. You can install the device driver by following the procedure either in Section 1.1.1 or in Section 1.1.2.

1.1.1 Installing the Device Driver by Setup.exe

- 1.) Please bypass the Microsoft® Windows® installation wizard by clicking on the **CANCEL** button as shown in the figure below.



- 2.) In Microsoft® Windows® 98, click on the “**Start**”->”**Run**” item. Assuming your CD-ROM drive is D, type **D:\YMF744\Win95&98\AUTOINST\SETUP.exe** in the command line of the RUN dialog box. Click **OK**.



- 3.) Follow the on-screen instructions. The SETUP program will ask you to restart the computer as a necessary procedure to install the device driver successfully.

1.1.2 Installing the Device Driver

If you want to install the device driver please follow the steps as described below:

- 1.) After you have installed your YMF744/754 PCI sound card start up your Microsoft® Windows® 98 operating system.
- 2.) The “**Add New Hardware Wizard**” dialog box will appear as shown below. Click “**Next>**” to continue.



- 3.) As recommended choose “**Search for the best driver for your device**”. Click “**Next>**”.



- 4.) In the next “**Add New Hardware Wizard**” dialog box, select “**Specify a location**”. Assuming your CD-ROM drive is D, please type the path **D:\YMF744\Win95&98** in the command line. Click “**Next>**”.



- 5.) The next “**Add New Hardware Wizard**” dialog box will inform you that the wizard has found the “**YAMAHA DS-XG Audio CODEC**” in the specified location. Just click “**Next>**” to accept the location of the new device driver.




- 6.) The next dialog box will display the message “**YAMAHA DS-XG PCI Audio CODEC**”. Just click “**Finish**” to complete the installation of the new device driver.



2. Verifying the Device Driver Installation

If you want to view the correct installation of the device driver for your YMF744/754 PCI sound card, please follow the steps as described below.

- 1.) Go to >"**Start**"->"**Settings**"->"**Control Panel**" and double-click on the "**System**" icon.
- 2.) From the "**System Properties**" dialog box select the "**Device Manager**" tab and you will see the following figure.



- 3.) Double-click on "**Sound, video and game controllers**" and you will see the following three devices have been added to your system:

Make sure that there is no yellow Question mark or Exclamation mark on each of the devices to ensure the driver is successfully installed.

- *YAMAHA DS-XG GamePort*
- *YAMAHA DS-XG Legacy Sound System*
- *YAMAHA DS-XG PCI Audio CODEC*

3. APPLICATION SOFTWARE


3.1 “Ystation32” Installation Guide Under Windows® 98

If you want to install the application software “Ystation32” for your YMF744/754 PCI sound card, please follow the steps as described below.


- 1.) Start up your Microsoft® Windows® 98 operating system.
- 2.) Click on the **START** and choose the **RUN** from the START menu.
- 3.) Please insert your driver CD into your CD-ROM drive. Assuming your CD-ROM drive is D, type **D:\YMF744\Ystation\Setup.exe** in the command line of the RUN dialog box.




- 4.) The first “**Setup**” dialog box will flash by, preparing the **InstallShield® Wizard** which will guide you through the rest of the SETUP program.




- 5.) The “**Welcome**” dialog box will recommend that you exit all Windows programs before you run the installation program. Please click “**Next>**” to continue.




- 6.) The “**Choose Destination Location**” dialog box will display the default destination directory, to where the SETUP program will install the program files. To continue the installation, you may accept the default directory **C:\Program Files\YAMAHA\DS-XG**, click “**Next>**”. If you want a different location, click on the “Browse..” to browse to another directory as the destination directory and click “**Next>**”.



- 7.) The SETUP program will retrieve files from your driver CD. The figure below shows you the status of the copying process.



- 8.) The SETUP program is now complete. Click e **OK** and you may run YStation32 by double clicking the program icon in the new "Yamaha" Program group. You may also select the program icon in the Programs menu.



- 9.) The "**Yamaha DS-XG**" program group will appear at the end of the SETUP procedure. The application "Ystation32" has been successfully installed on your computer.

