



ThinkCentre M83 Tiny with optional floor stand, wireless keyboard/mouse, and monitor



ThinkCentre M83 Tiny with optional floor stand



ThinkCentre M83 Tiny with optional VESA mount kit



ThinkCentre M83 Tiny with optional optical box



ThinkCentre M83 Tiny with optional I/O box



ThinkCentre M83 Tiny

# ThinkCentre M83 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Intel Pentium®, or 4th Generation Intel Core™ i3 / i5 / i7 Processor						Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Some:</i> Lenovo USB Fingerprint Keyboard (USB connector) <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black	
	Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics	Mouse		
	Core i3-4130T	2 / 4	2.90 GHz	3MB	DDR3-1600	Intel HD 4400	Mechanical	Tiny (1L), business black color; metal case	
	Core i3-4150T	2 / 4	3.00 GHz	3MB	DDR3-1600	Intel HD 4400	M83 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration	
	Core i5-4590T	4 / 4	2.00 / 3.00 GHz	6MB	DDR3-1600	Intel HD 4600	M83 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration	
Core i7-4785T	4 / 8	2.20 / 3.20 GHz	8MB	DDR3-1600	Intel HD 4600	VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation		
Memory	16GB max / DDR3 Low Voltage, DDR3L-1600*, non-parity, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)	
Disk	<i>Some:</i> hard disk, 2.5" Wide, 5400 or 7200 rpm, Active Protection System™ <i>Some:</i> 500GB (5400 rpm) Solid State Hybrid Drive (SSHD) / with 8GB MLC NAND flash memory, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / 2.5" Wide						Limited warranty <sup>3</sup>	<i>Some:</i> <b>3-years, limited onsite service</b> / service upgrades available <i>Some:</i> <b>3-years, limited onsite service, IWS</b> (International Warranty Service <sup>9</sup> ) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i>	
Optical	<i>Some:</i> external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB <i>Some:</i> external optical box with slim DVD±RW, 12.7mm high, tray-in, via USB						Preload	<i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 32/64 <b>Ready to install applications</b> (only some listed) <ul style="list-style-type: none"> <li>● Rescue and Recovery™</li> <li>● Password Manager</li> </ul> <b>Preloaded applications</b> (only some listed) <ul style="list-style-type: none"> <li>● ThinkVantage® Product Recovery</li> <li>● ThinkVantage System Update</li> <li>● ThinkVantage Communication Utility</li> <li>● PC Device Stage</li> <li>● Desktop Power Manager</li> <li>● View Management Utility</li> <li>● Lenovo Solution Center</li> <li>● Lenovo Message Center Plus</li> <li>● Lenovo SHAREit</li> <li>● Norton™ Internet Security (30 days of virus definitions)</li> <li>● Adobe® Reader®</li> <li>● Skype™</li> <li>● Microsoft Office preloaded; purchase a product key to activate</li> <li>● Cyberlink Power2Go (DVD±RW)</li> <li>● Cyberlink PowerProducer (DVD±RW)</li> <li>● Evernote®</li> <li>● Nitro Pro</li> </ul>	
Onboard SATA Media reader	SATA 6.0Gb/s controller, one connector on planar None						Chipset	<b>Intel Q85 Chipset</b>	
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600, in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on some models, supports up to 3 independent displays; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI) @60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)						Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)	
DP cable	Optional DisplayPort to DVI-D monitor cable						Rear ports	Two USB 3.0, one USB 2.0 (optional external optical box or external I/O box occupies specific USB 2.0 on some models), ethernet (RJ-45), VGA, DisplayPort, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on some models)	
Chipset	<b>Intel Q85 Chipset</b>						I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port	
Audio support	High Definition (HD) Audio, Realtek ALC233 / optional internal speaker (1.5 watt)						WLAN <sup>13</sup>	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11ac/b/g/n wireless, PCIe Half Mini Card, Broadcom BCM4352, dual band (2.4/5GHz), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 7260, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo 4.0 adapter, 2x2	
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter						Bluetooth™ Ethernet Modem	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN® None	
Manageability Security chip	Intel Standard Manageability Trusted Platform Module, TCG 1.2-compliant						Environment	ENERGY STAR® 6.0; EPEAT™ Gold rating (U.S.); GREENGUARD®; RoHS-compliant; ErP Lot 3; UL Environment Gold; TUV; Cisco EnergyWise compatible	
Security features	<ul style="list-style-type: none"> <li>● Security slot (in rear for optional Kensington® MicroSaver® cable)</li> <li>● Smart USB protection, allows keyboard/mouse only, blocks all storage devices</li> <li>● Power-on password</li> <li>● Administrator password</li> </ul>		<ul style="list-style-type: none"> <li>● Hard disk password</li> <li>● Boot sequence control</li> <li>● Boot without keyboard and mouse</li> <li>● Individual USB port disablement</li> <li>● Optional Chassis intrusion switch</li> </ul>				Accessories	For compatible accessories, please go to TC-AQP sheet	

See footnotes for more detailed information

# ThinkCentre M83 Tiny (10E9) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Graphics	Memory	Storage	External optical / I/O box	WLAN	DP Cable	Optional port	Chassis intrusion switch	Floor Stand	VESA mount	Keyboard/ Mouse	Internal Speaker	Kensington cable lock	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10E9000NUS	i3-4130T	Intel HD 4400	4GBx1	500GB 7200	None	7260 b/g/n	None	USB	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000PUS	i3-4130T	Intel HD 4400	4GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000QUS	i3-4130T	Intel HD 4400	4GBx1	256GB SSD	None	7260 b/g/n	None	2nd DP	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000RUS	i3-4130T	Intel HD 4400	8GBx1	500GB 7200	None	7260 b/g/n	None	None	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000SUS	i5-4590T	Intel HD 4600	4GBx1	500GB 7200	None	7260 b/g/n	None	None	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000TUS	i5-4590T	Intel HD 4600	8GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000UUS	i5-4590T	Intel HD 4600	4GBx1	256GB SSD	None	7260 b/g/n	None	2nd DP	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000VUS	i7-4785T	Intel HD 4600	4GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	Stand	Mount	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000WUS	i7-4785T	Intel HD 4600	8GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	Stand	Mount	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000XUS	i7-4785T	Intel HD 4600	8GBx1	256GB SSD	None	7260 b/g/n	None	USB	None	Stand	Mount	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E9000YUS	i7-4785T	Intel HD 4600	4GBx1	256GB SSD	None	7260 b/g/n	None	USB	None	Stand	Mount	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E90010US	i7-4785T	Intel HD 4600	4GBx1	180GB SSD	None	7260 b/g/n	None	2nd DP	None	Stand	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14

• For detailed platform specifications, please see [ThinkCentre M83 Tiny Platform Specifications sheet](#)

Processor	Intel® Celeron®, Intel Pentium®, or 4th Generation Intel Core™ i3 / i5 / i7 Processor	Manageability Security chip	Intel Standard Manageability Trusted Platform Module, TCG 1.2-compliant																														
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency (Max/Base)</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Core i3-4130T</td> <td>2 / 4</td> <td>2.90 GHz</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i3-4150T</td> <td>2 / 4</td> <td>3.00 GHz</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i5-4590T</td> <td>4 / 4</td> <td>2.00 / 3.00 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i7-4785T</td> <td>4 / 8</td> <td>2.20 / 3.20 GHz</td> <td>8MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics	Core i3-4130T	2 / 4	2.90 GHz	3MB	DDR3-1600	Intel HD 4400	Core i3-4150T	2 / 4	3.00 GHz	3MB	DDR3-1600	Intel HD 4400	Core i5-4590T	4 / 4	2.00 / 3.00 GHz	6MB	DDR3-1600	Intel HD 4600	Core i7-4785T	4 / 8	2.20 / 3.20 GHz	8MB	DDR3-1600	Intel HD 4600	Security features	<ul style="list-style-type: none"> <li>• Security slot (in rear for optional Kensington® MicroSaver® cable)</li> <li>• Smart USB protection, allows keyboard/ mouse only, blocks all storage devices</li> <li>• Power-on password</li> <li>• Administrator password</li> <li>• Hard disk password</li> <li>• Boot sequence control</li> <li>• Boot without keyboard and mouse</li> <li>• Individual USB port disablement</li> <li>• Optional <i>Chassis intrusion switch</i></li> </ul>
Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics																												
Core i3-4130T	2 / 4	2.90 GHz	3MB	DDR3-1600	Intel HD 4400																												
Core i3-4150T	2 / 4	3.00 GHz	3MB	DDR3-1600	Intel HD 4400																												
Core i5-4590T	4 / 4	2.00 / 3.00 GHz	6MB	DDR3-1600	Intel HD 4600																												
Core i7-4785T	4 / 8	2.20 / 3.20 GHz	8MB	DDR3-1600	Intel HD 4600																												
Memory	16GB max / DDR3 Low Voltage, DDR3L-1600*, non-parity, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller	Keyboard	<b>USB:</b> Preferred Pro USB Keyboard (USB connector), Lenovo logo <b>Finger:</b> Lenovo USB Fingerprint Keyboard (USB connector) <b>2.4G:</b> Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black																														
Disk	<i>Some:</i> hard disk, 2.5" Wide, 5400 or 7200 rpm, Active Protection System™ <i>Some:</i> 500GB (5400 rpm) SSHD / with 8GB flash memory, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / 2.5" Wide	Mouse	<b>USB:</b> Enhanced Optical USB Mouse, black, Lenovo logo <b>2.4G:</b> Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black																														
Optical	<i>Some:</i> external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB <i>Some:</i> external optical box with slim DVD±RW, 12.7mm high, tray-in, via USB	Mechanical	Tiny (1L), business black color; metal case																														
Onboard SATA Media reader	SATA 6.0Gb/s controller, one connector on planar None		<table border="1"> <tbody> <tr> <td>M83 Tiny only</td> <td>7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration</td> </tr> <tr> <td>M83 Tiny with VESA mount &amp; optical box</td> <td>7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration</td> </tr> </tbody> </table>	M83 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration	M83 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration																										
M83 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration																																
M83 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration																																
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600, in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on some models, supports up to 3 independent displays; Maximum resolution: 2560x1600 (DisplayPort) @60Hz; 1920x1080 (HDMI) @60Hz; 1920x1200 (VGA) @60Hz (Reduced Blanking)	VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation																														
DP cable	Optional DisplayPort to DVI-D monitor cable	Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)																														
Chipset	Intel Q85 Chipset	Limited warranty <sup>3</sup>	<i>Some:</i> <b>3-years, limited onsite service</b> / service upgrades available <i>Some:</i> <b>3-years, limited onsite service, IWS</b> (International Warranty Service <sup>9</sup> ) / service upgrades available For Lenovo service upgrade options, please go to S-TC sheet																														
Front ports Rear ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm) Two USB 3.0, one USB 2.0 (optional external optical box or external I/O box occupies specific USB 2.0 on some models), ethernet (RJ-45), VGA, DisplayPort, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on some models)	Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit																														
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port	Environment	ENERGY STAR® 6.0; EPEAT™ Gold rating (U.S.) GREENGUARD®; RoHS-compliant; ErP Lot 3; UL Environment Gold; TUV; Cisco EnergyWise compatible																														
Audio support	High Definition (HD) Audio, Realtek ALC233 / optional internal speaker (1.5 watt)	Accessories	For compatible accessories, please go to TC-AQP sheet																														
WLAN <sup>13</sup>	<i>Some:</i> 11b/g/n, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 <i>Some:</i> 11b/g/n, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/b/g/n, Broadcom BCM4352, dual band, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11b/g/n, Intel Centrino® Wireless-N 7260, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/a/b/g/n, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo, 2x2																																
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®																																
Modem	None																																

See footnotes for more detailed information

# ThinkCentre M83 Tiny (10E8)

Product Specifications Reference (PSREF)

Type-model	Processor	Graphics	Memory	Storage	External optical / I/O box	WLAN	DP Cable	Optional port	Chassis intrusion switch	Floor Stand	VESA mount	Keyboard/ Mouse	Internal Speaker	Kensington cable lock	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10E80017US	i3-4150T	Intel HD 4400	4GBx1	500GB 7200	None	7260 b/g/n	None	None	None	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E80018US	i5-4590T	Intel HD 4600	4GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E80019US	i5-4590T	Intel HD 4600	8GBx1	256GB SSD	None	7260 b/g/n	None	2nd DP	None	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E8001AUS	i5-4590T	Intel HD 4600	4GBx1	500GB 7200	None	7260 b/g/n	None	Serial	None	None	Mount	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E8001BUS	i7-4785T	Intel HD 4600	8GBx1	500GB 7200	None	7260 b/g/n	None	2nd DP	None	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E8001CUS	i7-4785T	Intel HD 4600	8GBx1	256GB SSD	None	7260 b/g/n	None	USB	None	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite	No	10/14
10E8000HUS	i5-4590T	Intel HD 4600	4GBx1	500GB 7200	None	7260 b/g/n	None	None	Switch	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite IWS	Yes	10/14
10E8000JUS	i5-4590T	Intel HD 4600	4GBx1	500GB 5400	None	7260 b/g/n	None	None	Switch	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite IWS	Yes	10/14
10E8000KUS	i5-4590T	Intel HD 4600	4GBx1	500GB 7200	None	8723BE	None	None	Switch	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite IWS	Yes	10/14
10E8000LUS	i5-4590T	Intel HD 4600	4GBx1	500GB 5400	None	8723BE	None	None	Switch	None	None	USB	Speaker	None	Win7 P64 DG Win8.1	3-onsite IWS	Yes	10/14
10E8000MUS	i3-4130T	Intel HD 4400	2GBx1	500GB 7200	None	8723BE	None	None	Switch	None	None	USB	Speaker	None	Win7 Pro64	3-onsite IWS	Yes	10/14
10E8000NUS	i3-4130T	Intel HD 4400	2GBx1	500GB 5400	None	8723BE	None	None	Switch	None	None	USB	Speaker	None	Win7 Pro64	3-onsite IWS	Yes	10/14

• For detailed platform specifications, please see [ThinkCentre M83 Tiny Platform Specifications sheet](#)

Processor	Intel® Celeron®, Intel Pentium®, or 4th Generation Intel Core™ i3 / i5 / i7 Processor	Manageability Security chip	Intel Standard Manageability Trusted Platform Module, TCG 1.2-compliant																														
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency (Max/Base)</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Core i3-4130T</td> <td>2 / 4</td> <td>2.90 GHz</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i3-4150T</td> <td>2 / 4</td> <td>3.00 GHz</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i5-4590T</td> <td>4 / 4</td> <td>2.00 / 3.00 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i7-4785T</td> <td>4 / 8</td> <td>2.20 / 3.20 GHz</td> <td>8MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics	Core i3-4130T	2 / 4	2.90 GHz	3MB	DDR3-1600	Intel HD 4400	Core i3-4150T	2 / 4	3.00 GHz	3MB	DDR3-1600	Intel HD 4400	Core i5-4590T	4 / 4	2.00 / 3.00 GHz	6MB	DDR3-1600	Intel HD 4600	Core i7-4785T	4 / 8	2.20 / 3.20 GHz	8MB	DDR3-1600	Intel HD 4600	Security features	<ul style="list-style-type: none"> <li>• Security slot (in rear for optional Kensington® MicroSaver® cable)</li> <li>• Smart USB protection, allows keyboard/ mouse only, blocks all storage devices</li> <li>• Power-on password</li> <li>• Administrator password</li> <li>• Hard disk password</li> <li>• Boot sequence control</li> <li>• Boot without keyboard and mouse</li> <li>• Individual USB port disablement</li> <li>• Optional <i>Chassis intrusion switch</i></li> </ul>
Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics																												
Core i3-4130T	2 / 4	2.90 GHz	3MB	DDR3-1600	Intel HD 4400																												
Core i3-4150T	2 / 4	3.00 GHz	3MB	DDR3-1600	Intel HD 4400																												
Core i5-4590T	4 / 4	2.00 / 3.00 GHz	6MB	DDR3-1600	Intel HD 4600																												
Core i7-4785T	4 / 8	2.20 / 3.20 GHz	8MB	DDR3-1600	Intel HD 4600																												
Memory	16GB max / DDR3 Low Voltage, DDR3L-1600*, non-parity, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller	Keyboard	<b>USB:</b> Preferred Pro USB Keyboard (USB connector), Lenovo logo <b>Finger:</b> Lenovo USB Fingerprint Keyboard (USB connector) <b>2.4G:</b> Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black																														
Disk	<i>Some:</i> hard disk, 2.5" Wide, 5400 or 7200 rpm, Active Protection System™ <i>Some:</i> 500GB (5400 rpm) SSHD / with 8GB flash memory, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / 2.5" Wide	Mouse	<b>USB:</b> Enhanced Optical USB Mouse, black, Lenovo logo <b>2.4G:</b> Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black																														
Optical	<i>Some:</i> external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB <i>Some:</i> external optical box with slim DVD±RW, 12.7mm high, tray-in, via USB	Mechanical	Tiny (1L), business black color; metal case																														
Onboard SATA Media reader	SATA 6.0Gb/s controller, one connector on planar None		<table border="1"> <tbody> <tr> <td>M83 Tiny only</td> <td>7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration</td> </tr> <tr> <td>M83 Tiny with VESA mount &amp; optical box</td> <td>7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration</td> </tr> </tbody> </table>	M83 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration	M83 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration																										
M83 Tiny only	7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration																																
M83 Tiny with VESA mount & optical box	7.2" W X 7.2" D X 2.6" H 184mm W X 182mm D X 65mm H 5.1 lb (2.3 kg), weight may vary by configuration																																
Graphics	<b>Intel HD Graphics or Intel HD Graphics 4400/4600</b> , in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on some models, supports up to 3 independent displays; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)	VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation																														
DP cable	Optional DisplayPort to DVI-D monitor cable	Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)																														
Chipset	<b>Intel Q85 Chipset</b>	Limited warranty <sup>3</sup>	<i>Some:</i> <b>3-years, limited onsite service</b> / service upgrades available <i>Some:</i> <b>3-years, limited onsite service, IWS</b> (International Warranty Service <sup>9</sup> ) / service upgrades available For Lenovo service upgrade options, please go to <i>S-TC sheet</i>																														
Front ports Rear ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm) Two USB 3.0, one USB 2.0 (optional external optical box or external I/O box occupies specific USB 2.0 on some models), ethernet (RJ-45), VGA, DisplayPort, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on some models)	Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit																														
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port	Environment	ENERGY STAR® 6.0; EPEAT™ Gold rating (U.S.) GREENGUARD®; RoHS-compliant; ErP Lot 3; UL Environment Gold; TUV; Cisco EnergyWise compatible																														
Audio support	High Definition (HD) Audio, Realtek ALC233 / optional internal speaker (1.5 watt)	Accessories	For compatible accessories, please go to TC-AQP sheet																														
WLAN <sup>13</sup>	<i>Some:</i> 11b/g/n, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 <i>Some:</i> 11b/g/n, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/b/g/n, Broadcom BCM4352, dual band, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11b/g/n, Intel Centrino® Wireless-N 7260, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/a/b/g/n, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo, 2x2																																
Bluetooth™ Ethernet Modem	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN® None																																

See footnotes for more detailed information