

Name Bezel color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty Available date	T24v Wide Flat Panel Monitor Black 61BCMAR6US / 61BCMAT6EU TFT-LCD, In-Plane Switching (IPS), White LED backlight 23.8" (604.5mm) diagonal 20.75" x 11.67" (527.04mm x 296.46mm) 1920x1080 16:9 0.2745 x 0.2745 mm 92 dpi 250 nits or cd/m ² (typical) 1000:1 (typical) 6ms (typical); 4ms (extreme mode) 72% 178° (+/- 89°) horizontal, 178° (+/- 89°) vertical Tilt, swivel, pivot, and height adjustable stand <i>Sides:</i> 0.08" (2.0mm) 19.72" H x 21.28" W x 10.32" D; 500.5mm H x 540.2mm W x 261.9mm D 20 watts typical, 45 watts maximum (with USB 3.0 hub), <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 11.18 lb; 5.07 kg 3 year (includes backlight) October 2017	Features • Widescreen 23.8-inch monitor • Supports 1920x1080 resolution • Supports ThinkCentre Tiny Clamp Bracket • Supports optional soundbar • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified				
VESA-compliant Power management Ergonomics Emission standards Environmental Preset resolutions Presets display modes	VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Gold rating VGA: 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 Presets: 24; user modes: 20	 ThinkVision T24v Wide Monitor				
Viewing adjustments Rotating screen On screen display Control features USB hub Multimedia Camera Multiple input Monitor connectors Signal cables Mounting features Security Ship group	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access for power, menu, input source select, volume up / down, speaker mute and microphone mute USB 3.0 Hub: 1 port into PC (USB 3.0); 2 ports for accessories (2 USB 3.0) Integrated speakers, dual-array microphone, audio-in and Audio-out, optional sound bar supported Integrated FHD camera with IR Support HDMI, DisplayPort, VGA (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, HDMI at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible) Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter USB signal cable, 1.8 meter black power cord, 1.8 meter HDMI signal cable (Row)					
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582					
Kensington Twin Head Cable Lock	45K1620					