

Overview for Lenovo USB-C Travel Hub (4X90M60789)

Lenovo USB-C Travel Hub is an essential extension adapter that enables you to easily connect to an external monitor, wired network, and USB device via single robust USB Type-C™ port.

Portable design of Lenovo hub is great for traveler. Fewer transition cables and more space in your bag.

Features:

- Simply get UHD external display (4k@30Hz) via HDMI port or FHD display (1080p) via VGA port
- Plug and play
- Support PXE boot & MAC address pass through on selected systems that have enabled these two features.

To find more information about docks, please visit:

http://support.lenovo.com/docs/usb_c_travel_hub

For the latest compatible systems, please visit the Accessories Compatibility Guide:

<http://www.lenovo.com/accessoriesguide>

ELECTRICAL SPECIFICATIONS

■ Type-C™ port:

- For connecting with Type-C™ Female port of Notebook;
- Bus powered;
- Compatible with Notebooks which Type-C™ port Vbus power is 5V&3A*;
- Compatible with Notebooks which Type-C™ port with USB3.1 Gen 1(5G);
- Support DP alternate mode, fixed at 2lane DP mode;
- No PD support;

■ USB port:

- USB Standard-A type receptacle connector, support USB3.0;
- USB3.0 port with 900mA continue current support;

■ HDMI port:

- Support resolution up to 4k@30hz on HDMI;

■ VGA port:

- Support up to 1920x1080@60hz on VGA port;

■ Gigabit Ethernet Port:

- Meet IEEE802.3ab network specification for Gigabit data rate transmit
- Meet IEEE802.3 network specification 10Mbps/100Mbps data rate transmit
- Support PXE boot and load image from remote server are required both on legacy BIOS and UEFI BIOS system if host systems support
- Support Wake-On-LAN under S3 mode if host system support
- Support Mac pass through if host system support
- LEDs on connector to indicate activity and link status

Note:

*Bus power only: the Hub will work when Vbus power is 5V@3A, the Hub no work when Vbus power is [5V@1.5A](#) and [5V@0.9A](#);

**The travel hub with two video connectors but supports only one external monitor at a time. When both video connectors are plugged, only HDMI connector with functions.

PHYSICAL SPECIFICATIONS

- Approximate height: 18 mm (0.71 in)
- Approximate width: 63 mm (2.48 in)
- Approximate depth: 68 mm (2.68 in)
- Approximate weight: 80g (0.176 lb)

- Full Packaging Size(Brown box):
 - Approximate height: 31 mm (1.22 in)
 - Approximate width: 167 mm (6.57 in)
 - Approximate depth: 133 mm (5.24 in)
 - Approximate weight: 163 g (0.359 lb)

- Full Packaging Size(Retail box-ThinkPad):
 - Approximate height: 31 mm (1.22 in)
 - Approximate width: 112 mm (4.41 in)
 - Approximate depth: 223 mm (8.78 in)
 - Approximate weight: 168 g (0.374 lb)

- Full Packaging Size(Retail box-Lenovo):
 - Approximate height: 25 mm (0.98 in)
 - Approximate width: 93 mm (3.66 in)
 - Approximate depth: 166 mm (6.54 in)
 - Approximate weight: 124 g (0.374 lb)

OPERATING ENVIRONMENT

Temperature: -5 °C - +40 °C

Humidity: 20%-95%

AGENCY APPROVALS

- KCC
- FCC/ICES
- EAC
- RCM
- VCCI
- CE
- BSMI
- CB

PACKAGING:

Brown box/Retail Box

SHIPMENT GROUP

- Lenovo USB-C Travel Hub
- Warranty Poster

WARRANTY TERMS

- 1 Year

CHARGES - FRU PARTS

Field Replaceable Units (FRU)

<i>DESC</i>	<i>FRU Part #</i>	<i>Option Part #</i>	<i>HS</i>
<i>Lenovo USB-C Travel Hub</i>	<i>03X7417</i>	<i>4X90M60789</i>	<i>R1</i>
<i>Lenovo USB-C Travel Hub-PRC</i>	<i>03X7417</i>	<i>4X90M60793</i>	<i>R1</i>
<i>Lenovo USB-C Travel Hub-ROW</i>	<i>03X7417</i>	<i>GX90M61237</i>	<i>R1</i>
<i>Lenovo USB-C Travel Hub-NA</i>	<i>03X7417</i>	<i>GX90M61235</i>	<i>R1</i>