Output

Weld-Pak® 140HD



120 Volt AC Input Compact Wire Welder

Whether you have a home project, farm repairs or basic autobody welding to complete, the Weld-Pak[®] 140HD should be at the top of your shopping list!

Requiring common 120 volt input power, the Weld-Pak® 140HD can be used almost anywhere. With simple two knob tapped control, the machine is easy to set up for gas-less flux-cored welding for deep penetration on thicker steel or gas-shielded MIG welding on thin gauge steel, stainless or aluminum. Compare the precise drive, rugged construction and full list of standard accessories. . . Lincoln Weld-Pak® is an excellent choice!



MIG. Flux-Cored



Advantage Lincoln

Superior Arc Performance:

- Forgiving arc makes dialing in your application easy.
- Smooth arc starts with minimal spatter.
- Wide 30-140 amp welding output range.
- MIG weld 24 gauge up to 10 gauge (.135") sheet metal in a single pass. Weld up to 5/16" steel using self-shielded Lincoln Innershield[®] wire (FCAW-S).

Professional Features:

- Precise Wire Drive features:
 - Precision full adjustment drive system reduces chance of wire tangling and crushing.
 - Brass-to-Brass gun connections for enhanced connectivity.
 - Large industrial closed-design drive motor for improved torque and trouble-free performance.

- Spool Gun Ready add the optional Magnum[®] 100SG spool gun for reliable operation at the high wire feed speeds aluminum welding demands. No expensive outboard modules required.
- No Hassle Tool-less Design for wire spool mounting, wire drive service and polarity changes.
- Innovative contact tip, drive roll and nozzle storage keeps all your consumables close at hand.

Superb Quality:

- Power Chassis™ channels airflow to cool power systems, structurally secures key components and traps wires and cables to avoid unnecessary abrasion.
- Toughest PC Board Protection in the industry 'Potted' to seal sensitive components from the environment, 'trayed' in a tough plastic tray to add rigidity and shock resistance.
- Three Year Lincoln Warranty/90 Days on gun and cable assembly.

TECHNICAL SPECIFICATIONS									
Product Name	Product Number	Input Power	Rated Output Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	Dimensions H x W x D inches (mm)	Net Weight Ibs.(kg)		
Weld-Pak® 140HD	K2514-1	120/1/60	90A/19.5V/20%	20A	30-140 Amps DC 50-500 ipm WFS (1.3-12.7 m/min) Max. OCV: 33	14 x 10.15 x 18.6 (357 x 258 x 472)	58 (26.3)		





A CLOSER LOOK

SUPERIOR ARC PERFORMANCE

- Forgiving arc characteristics make dialing in your application easy.
- Smooth arc starts with minimal spatter.



Farm Welding

Repair Work


PRECISE WIRE DRIVE

Enhanced Quality

- 1. Brass Gun Connection Enhances Connectivity
- 2. Rigid Drive Aids Wire Alignment

Easy to Use

- 3. Easy Turn Tension Adjustment
- **4.** Tool-less Quick Lock Drive Roll Changeovers



PRECISION ALUMINUM WELDING

Magnum® 100SG Spool Gun

Our low-priced spool gun is your most reliable aluminum feeding solution.





Complete Kit. No Bulky Module Required. Order K2532-1



Weld-Pak® 140HD

WHAT'S INCLUDED

Weld-Pak® 140HD (K2514-1) Includes:

Gun

- Magnum® 100L gun and 10 ft. (3.0 m) cable assembly with brass gun connection and 4-pin MS-Type connection for trigger control (K530-6)
- .025" (0.6 mm) Contact Tips (Qty. 3) (KH710)
- .035" (0.9 mm) Contact Tips (Qty. 3) (KH712)
- Gasless Nozzle for Innershield® welding (KH726)
- Gas Nozzle for MIG welding (KH725)

Drive

- Spindle Adapter for 8" (203 mm) Diameter Spools (KH720)
- .025" (0.6 mm) Wire Diameter Drive Roll for MIG welding (KP2529-1)
- .035" (0.9 mm) Wire Diameter Drive Roll for MIG welding (KP2529-2)
- .030"-.045" (0.7-1.1 mm) Wire Diameter Knurled Drive Roll for Flux-Cored welding (KP2529-3)

Shielding Gas Apparatus

Harris® 3000290 Gas Regulator (S25805) and 52 in. (1.3 m)
Hose (S19303) for use with CO₂ or argon blend gases. (For use with CO₂ shielding gas, order a Lincoln® S19298 CO₂ shielding gas bottle adapter.)

Welding Wire


- 2 lb. (0.90 kg) Spool of .025" (0.6 mm) diameter SuperArc® L-56® premium MIG wire (ED030583)
- 1 lb. (0.45 kg) Spool of .035" (0.9 mm) diameter Innershield® NR®-211-MP flux-cored wire (ED027641)

Other

- Work Clamp and 10 ft. (3.0 m) Cable
- Handshield (G3364)
- Instruction Manual (IM-891)
- How to Use DVD (S26375)
- Learn to Weld Manual (LTW1)

PERFORMANCE PLUS

Weld-Pak® 140HD Welding Capabilities



SP- Single Pass. MP- Multiple Pass.

RECOMMENDED OPTIONS



GENERAL OPTIONS

Welding Cart

Full-featured cart is designed to store and transport a welder, 80 cubic foot gas cylinder, welding cables and accessories. Includes an angled top shelf for easy access to welder controls, a lower tray for added storage space, a sturdy handle and a convenient cable wrap hanger.

Order K2275-1



Utility Cart

Heavy duty cart stores and transports welder, 150 cubic foot shielding gas cylinder, welding cables and accessories. Includes stable platforms for welder and gas bottle platform, lower tray for added storage capacity and adjustable height handle.

Order K520



¹ Aluminum welding requires optional K2532-1 Magnum[®] spool gun.

RECOMMENDED OPTIONS



GENERAL OPTIONS CONT.

Small Canvas Cover

Protect your welder when not in use. Made from attractive red canvas that is flame retardant, mildew resistant and water repellent. Includes a convenient side pocket to hold your welding torch or gun.

Order KH495



WIRE FEEDER OPTIONS

Magnum® 100SG Spool Gun Designed to easily feed 4" (102 mm) diameter 1 lb. (0.45 kg) spools of .030" (0.8 mm) or .035" (0.9 mm) diameter SuperGlaze® aluminum MIG wire. Includes gun, adapter kit, .035" (0.9 mm) contact tips (qty. 3), gas nozzle, and a 1 lb. (0.45 kg) spool of SuperGlaze® 4043 .035" (0.9 mm) MIG wire. Packaged in a convenient carrying case.

Order K2532-1



Spot Timer Kit

This timer allows you to set a fixed weld time of up to 10 seconds that is initiated when you pull the gun trigger. Ideal for making consistent spot welds on thin sheet metal.

Order K2525-1

WELD-PAK® 140HD ORDER FORM							
PRODUCT DESCRIPTION	ORDER NUMBER	QUANTITY	PRICE				
Weld-Pak® 140HD - 120/1/60	K2514-1						
Recommended General Options							
Welding Cart	K2275-1						
Utility Cart	K520						
Small Canvas Cover	K2377-1						
Recommended Wire Feeder Options							
Magnum® 100SG Spool Gun	K2532-1						
Spot Timer Kit	K2525-1						
	TOTAL:						

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company® is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or after any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any expectifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change - This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

