

Internet Fast

Just connect your DSL or Cable Modem to the EtherFast® Cable/DSL Router with 4-Port Switch and all the computers in your household can share a wired connection to the Internet, at the same time.

When Four is Plenty

The built-in 4-port switch lets you attach four local devices directly, or daisy-chain out to more hubs and switches as your network grows. Once your computers are connected to the Internet through the Router, they can communicate with each other, sharing resources and files.

Easy Installation

The step-by-step Setup Wizard shows you how to configure your router. Universal Plug-and-Play (UPnP) lets specialized Internet applications configure the Router so you don't have to.

Secure Operation

Built-in NAT technology helps keep intruders out of your computers.

DATASHEET

Share your high-speed cable or DSL Internet connection with multiple computers

Built-in switch connects four local PCs directly, and daisy-chain out to more hubs and switches as your network grows

Supports DHCP, Universal Plug-and-Play (UPnP), and includes a user-friendly Setup Wizard for easy configuration



EtherFast Cable/DSL Router with 4-Port Switch

Model: BEFSR41 (EU)

Features

- Supports Universal Plug-and-Play for Easy Configuration
- QoS prioritization based on port or service type
- Supports IPSec and PPTP Pass-through
- Administer and Upgrade the Router Remotely over the Internet
- Configurable as a DHCP Server on Your Network
- Advanced Security Management Function for Port Filtering, MAC Address Filtering, and DMZ Hosting
- Automatically Detects Straight or Cross-over Cable

Specifications

Model Number	BEFSR41
Standards	IEEE 802.3 (10BaseT), IEEE 802.3u (100BaseTX)
Ports	One 10/100 RJ-45 Port for Broadband Modem
LED Indicators	Four 10/100 RJ-45 Switched Ports
OS Support	Power, Ethernet, Internet
Network Protocols	Windows 98SE/Me/2000/XP
	TCP/IP

Environmental

Dimensions	7.32" x 6.06" x 1.89" (186 x 154 x 48 mm)
Weight	11.04 oz (320 g)
Power	External, 9V AC, 1000 mA
Certification	FCC, CE
Operating Temp.	32 to 104°F (0 to 40°C)
Storage Temp.	-4 to 158°F (-20 to 70°C)
Operating Humidity	10 to 85% Noncondensing
Storage Humidity	5 to 90% Noncondensing

Package Contents

- EtherFast Cable/DSL Router
- Power Adapter
- Network Cable
- Setup CD-ROM with User Guide
- Fast Start Guide
- Registration Card

Minimum Requirements

- Broadband connection and Cable/DSL modem
- CD-ROM Drive
- Internet Explorer 5.0 or Netscape 6 for web-based configuration



Cisco Consumer Business Group

www.linksys.com/international

Linksys, Cisco and the Cisco Logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2008 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.

The maximum performance for wireless is derived from IEEE Standard 802.11 specifications. Actual performance can vary, including lower wireless network capacity, data throughput rate, range and coverage. Performance depends on many factors, conditions and variables, including distance from the access point, volume of network traffic, building materials and construction, operating system used, mix of wireless products used, interference and other adverse conditions.

Specifications are subject to change without notice.

8122210A-ST

Model: BEFSR41 (EU)