

www.acclock.com

TRILOGY - STANDALONE ACCESS CONTROL SYSTEMS

TRILOGY™ DL2700 SERIES DIGITAL LOCKS

The self-contained, battery powered trilogy provides valuable digital security features for virtually the same cost as most mechanical digital locks. Trilogy allows up to (100) different group or individual codes with easy keypad programming. Clutch mechanism permits turning lever without retracting latch and reduces stress on Flex Drive® motor. Outside lever free turning in locked position. Entering access code, key bypass, or remote bypass will allow lever to retract latch. Inside lever always free. Built in remote release eliminates the need for electric strike.

UL Fire Rated, meets or exceeds ANSI/BHMA Certification Requirements A156.2, Series 4000 Grade 1, FCC Certified, conforms to ADA requirements.

Regal Curved Handle available, extra charge.

Standard IC models accept 6 & 7 pin cylinders from Best, Falcon, Arrow, KSP, Medeco Keymark & Kaba Peaks.

IC core models prepped for 6 & 7 pin Yale, Medeco, Sargent,

Regal Curved Handle

Corbin Russwin & Schlage* also available. Extra Charge.

AKS6061 Battery Pack for Most Trilogies 47.00

NEW! LocDown™ Model!

DL2700 w/LocDown™ capability via wireless key fob. Inside housing has a light bar that indicates that the door is locked down.

*Schlage IC requires Regal handle.



· Clutch mechanism insures long life and durability

- Self-contained, fully programmable 12 digit metal keypad
- Battery operated, uses 5 AA batteries
- · Low power audible alert
- Visual and audible entry indicators
- · UL Listed fire rated
- Rekeyable and accepts cylinders keyable to most key systems
- Key bypass
- Remote override

Backset: 2 3/4" standard. Comes with 5 AA alkaline batteries.

> Use Pro-Lok IN15-PRO/INCL-PRO Templates Use Pro-Lok EWP-IN15-FP-S Flat Plate

WITH LEVER HANDLE (Regal handle available)

Part No.	Description	Finish	Retail
AKDL2700-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	853.00
AKDL2700-US3	Digital Lever Handed Lockset w/KO	Polished Brass	980.00
AKDL2700WP-26D	Digital Lockset - Weatherproof	Satin Chrome	959.00
AKDL2700IC-US26D	Digital Lever Lockset for Int.Core	Satin Chrome	889.00
AKDL2700IC-US3	Digital Lever Lockset for Int.Core	Polished Brass	998.00
	Digital Lockset - Weatherproof IC	Satin Chrome	975.00
AKDL2700LD-US26D	Digital Lockset w/LocDown	Satin Chrome	900.00
AKDL2700LDIC-26D	Digital Lockset w/LocDown IC	Satin Chrome	930.00

DL2800 TRILOGY ACCESS CONTROL SYSTEMS WITH AUDIT TRAIL - WEATHER RESISTANT

- Rugged clutch mechanism insures long life & durability
- 150 scheduled events, including 4 "quick schedules" for programming the 4 most common time schedules in one step
- 200 user codes including: Master, Manager, Supervisor and Basic User. Also one-time entry Service Code
- Weather resistant performance with operational temperature range of + 151°F to -20°F (+66°C to -29°C)
- Times entry allowance from 5-15 seconds
- Greater security with "Temporary Keypad Lockout" after 3 unsuccessful code-entry attempts. "Keep would-be intruders arbitrarily guessing codes out!"
- Audit Trail with Time/Date Stamp for a printable record of all electronic activity
- Real Time Clock allows logging of events to within 1 second of accuracy
- · Relay may be programmed to energize when one or more selected events occur
- 4 Time-Out functions allow a user to enable other users or unlock the lock for some time period without needing to return to the lock
- 1000 Event Log
- Easy to install. Retrofits most cylindrical locksets and digital locks
- Battery operated; uses 5 AA batteries
- · Available in standard key override and interchangeable core models accepting 6 or 7 pin cores from Arrow, Best, Falcon or KSP. Other IC core preps available.
- · Available in standard Trilogy leverset (straight) or with Regal (curved) lever.

Part No.	Description	Finish	Retail
AKDL2800-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	1046.00
AKDL2800IC-US26D	Digital Lever Lockset for Int.Core	Satin Chrome	1069.00



Regal Curved Handle available, extra charge.

Standard IC models accept 6 & 7 pin cylinders from Best, Falcon, Arrow, KSP, Medeco Keymark & Kaba Peaks.


IC core models prepped for 6 & 7 pin Yale, Medeco, Sargent, Corbin Russwin & Schlage* also available. Extra Charge.

*Schlage IC requires Regal handle.



Use Pro-Lok IN15-PRO/INCL-PRO Templates Use Pro-Lok EWP-IN15-FP-S Flat Plate

Handle



Accredited Lock Supply

www.acclock.com




T3 Stand Alone Access Systems push all the right buttons to get your Use Pro-Lok IN15-PRO/INCL-PRO Templates foot in the door with the best in reliable single-door access, now with Use Pro-Lok EWP-IN15-FP-S Flat Plate something extra - comprehensive logging of user entry by time and date, plus access scheduling.

These rugged, self-contained, battery powered systems provide remarkably sophisticated keyless access with the features and multiple security levels that meet or surpass even the most discriminating consumers' needs.

Regal Curved Handle available, extra charge.

Standard IC models accept 6 & 7 pin cylinders from Best, Falcon, Arrow, KSP, Medeco Keymark & Kaba

IC core models prepped for 6 & 7 pin Yale, Medeco,



Sargent, Corbin Russwin & Schlage* also available. Extra Charge.

*Schlage IC requires Regal handle.

75
TRILOGY
AUDIT TRAII

DIGITAL ACCESS SYSTEM FEATURING:

- 300 User Codes: Master, Manager, Supervisor & Basic Users
- 4 Programming Levels
- 4 User Groups
- 3,4,5 or 6 Digit Codes
- 1 -Time Service Code
- · Real Time Clock
- Time Zones
- 150 Scheduled Events (Lock/Unlock, Code Disable/Enable)
- 4 "Quick Schedules" of the most common routines built in.
- 100% Fingertip Programmable or PC Programmable with Intuitive-Use Alarm Lock DL-WINDOWS Windows Software with built-in error check.
- · Non-volatile Memory
- 1600 Event Log
- Passage Mode Enabled by Master's and Manager's Codes
- . Optional Hand-Held AL-IR1 Infrared Printer may be used to Print the Event Log and User Code List
- · ADA-Compliant Leverset Clutch Design.
- · UL-Listed Electrically-controlled single-point lock.

Part No.	Description	Finish	Retail
AKDL3000-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	1270.00
AKDL3000	Digital Lever Handed Lockset w/KO	3,10B	1359.00
AKDL3000IC-US26D	Digital Lever Lockset for Int.Core Satin Chrome		1265.00
AKDL3000IC	Digital Lever Lockset for Int. Core 3,10B		1337.00
AKAL-DTMIII	Data Transfer Module		448.00
AKAL-IR1	1 Hand Held Infrared Printer		520.00
AKAL-PC12-U	Personal Computer Interface Cable-Serial/USB		237.00
AKMX1130	Serial to USB Adapter		118.00

TRILOGY PROX LOCK WITH AUDIT TRAIL

- Accepts most HID Proximity cards and keyfobs including 26 48 bit formats
- 2000 User codes; Master; manager; supervisor; basic users
- Users are individually programmed to use a card only, code only, or for the highest security - both card and code
- Card data can be added to software via the lock, card reader module or PC
- Batch enroll feature allows many cards to be quicldy added to the software via the lock without the use of a PC
- Weatherproof and operates from -20° F to 151° F (-29° C to 66° C)
- Fingertip (keypad) or Windows PC-programmable
- Program data transferred to lock via AL-PCI (PC interface) or AL-DTM (data transfer module)
- Real time clock enables up to 500 scheduled events and holiday schedules
- Up to 40.000 event Audit Trail with printed time/date-stamped log of all electronic activity can be extracted from the lock by using the AL-IRI (infrared printer), the AL-DTM (data transfer module) or AL-PCI (PC interface)
- 5 AA batteries furnished; 60,000 cycles typical. Audible low battery alert
- 'Quick Passage' Mode enabled with an authorized user code and function code (does not require lock to be in program mode)
- Available in four finishes (US 26D, 26, 5 & 3), plus special order finishes (including Duronodic US10B)
- Comes with either a standard or Regal curved handle trim

Part No.	Description	Finish	Retail
AKPDL3000-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	1782.00
AKPDL3000IC-US26D	Digital Lever Lockset for Int.Core	Satin Chrome	1811.00
AKPDL3000	Digital Lever Lockset w/KO	3, 10B	1860.00
AKPDL3000IC	Digital Lever Lockset for Int.Core	3, 10B	1882.00
AKALHID1326	Proximity Access Card	100/box	505.00
AKAL-IR1	Hand Held Infrared Printer		520.00
AKAL-PCI2	PC Interface Cable (w/DL-Windows)		129.00





C LOCK

Accredited Lock Supply


www.acclock.com

TRILOGY ELECTRONIC DOUBLE SIDED DIGITAL LOCKS

- 2000 user access using PIN-code and/or HID Prox card/fob with multilevel access hierarchy
- Kevpad and/or computer programmable
- Direction-specific access assignable per user programmable access for each user for one or both sides of door
- Up to 40,000 event directional audit trail with time/date
- 500 scheduled events including 4 "quick schedules"
- Real time clock allow logging of events to withing 1 second of accuracy
- Programmable relays energize when one or more selected events occur
- "Temporary Keypad Lockout" after 3 unsuccessful attempts to enter code/ID
- Weatherproof performance for indoor and outdoor applications, wide operating temperature range of -31° F for $+151^{\circ}$ F (-35° C to $+66^{\circ}$ C)
- Grade 1 BHMA Certified durability and rugged clutch mechanism
- Quick Passage Mode
- 5 AA battery operation; 60,000 cycles, typical

Part No.	Description	Finish	Retail
AKDL5300-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	1814.00
AKDL5300IC-US26D	BOOIC-US26D Digital Lever Lockset for Int.Core Satin Chrom		1819.00
AKPDL5300-US26D	PDL5300-US26D Digital Lever Lockset w/KO & PROX Satin Chrom		2163.00
AKPDL5300IC-US26D	OOIC-US26D Digital Lever Lockset Int.Core/PROX Satin Chron		2179.00
AKALHID1326	326 Proximity Access Card 100/box		505.00
AKAL-IR1	Hand Held Infrared Printer		520.00
AKAL-PC12	PC Interface Cable (w/DL-Windows)		129.00





Double Sided Version of the 2700

Part No.	Description	Finish	Retail
AKDL5200-US26D	Digital Lever Handed Lockset w/KO	Satin Chrome	1442.00
AKDL5200IC-US26D	Digital Lever Lockset for Int.Core	Satin Chrome	1464.00

TRILOGY MORTISE LOCKS DL3500 SERIES

Similar in functionality to T3 DL3000 Series, but with:

- 300 User codes: Master, manager, supervisor & basic users
- Weatherproof operates from -20°F to 151°F (-29°C to 66°C)
- Fingerfip or Windows PC-programmable
- Real fime clock enables up to 500 scheduled events and holiday schedules
 40,000 Event Audit Trafl provides a printed fime/date-stamped log of all electronic activity
- Long-life batteries and low-battery alert
- US versions: Choose either Classroom or Deadbolt versions and left or right handing (if reverse hand is required, lock is field reversible.)
- Available in standard Trilogy US leverset (straight) or with new Regal (curved) handle trim.
- Five finishes (US 26D, 26, 5, 3 & IOB, plus special order finishes)

Specify Handing - RH or LH

Part No.	Description	Finish	Retail
AKDL3500CRR-US26D	Straight Lever,Classroom Function	Satin Chrome	1471.00
AKDL3500CRR	Straight Lever, Classroom Function	3,10B	1543.00
AKDL3500DBR-US26D	Straight Lever, Deadbolt Function	Satin Chrome	1471.00
AKDL3500DBR	Straight Lever, Deadbolt Function	3,10B	1543.00

USB to RS-232 CABLE ADAPTER

This mini USB to RS-232 cable adds a high speed RS-232 serial port conveniently via USB 2.0 or USB 1.1 port connection.

AKMX1130 11800



Cable length of 10" and 2 LED's for port monitoring.



Accredited Lock Supply

www.acclock.com

TRILOGY NARROW STILE ACCESS LOCKS

DL 1200 Series supports 100 users, fingertip/keypad programmable. (Includes 2 Lithium 3V batteries). DL 1300 Series supports 2000 users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3Vbatteries).

PDL 1300 Series supports 2000 PIN or Prox users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3V batteries)

ALL MODELS FEATURE:

- Aluminum door retrofit outside trim for Adams Rite® 1850, 1950,4710,4070,4730,4900 Series and MS1850S and MS1950S Series latch locks.
- PIN code and PIN/Prox Models support 100 to 2000 users (see model info.)
- 40,000 event audit trail in 1300 Series models, provides door usage activity reports at wireless handheld printer,
- All-metal, vandal-resistant 12-button keypad supports 3-6 digit PIN codes, and multilevel user hierarchy (master, manager, supervisor, basic users)
- Keypad or PC programmable (see model info). Quickly and easily add or delete users and enter "passage mode", service codes, group lock-out & group-enable
- HID Prox 10 cards, keyfobs and prox tags supported in PDL-1300 Series models featuring built in Prox reader. (High security applications can require use of both PIN code plus Prox 10 for access.)
- Real time clock and PC programmable automatic lock/unlock scheduling for 500 events (1300 Series models).
- Wide weatherproof operating range from -31 to 151°F (-35 to 66C)
 Wireless standalone locks: Long-life, battery- operated; Includes audible and visual low battery alert. Uses standard off-the-shelf batteries, or AKS6170 battery pack (preferred).
- Non-handed; fully field-reversible .
- Key override: interchangeable cores supported (Corbin/Russwin, Yale, Schlage, Medeco).
- Mortise Cylinder, 1-1/4" supplied. (Supports 1-1/8, 1-1/4 and 1-3/8")
 Compact styling 14-3/8"H x 1-5/8"D x 1-3/4"W
- Backsets 31/32",1-1/8" and 1-1/2"; Stile thickness 1-3/4"
- Two attractive standard finishes US26D Satin Chrome, US10B Duronodic

Part No.	Description	Finish	Retail
AKDL1200-26D1	Digital Lever Lockset w/KO	Satin Chrome	652.00
AKDL1225-26D2	Digital Thumb Turn Lockset w/KO	Satin Chrome	652.00
AKDL1250-26D2	Digital Knob Lockset w/KO	Satin Chrome	652.00
AKDL1300-26D1	Digital Lever Lockset w/KO	Satin Chrome	818.00
AKDL1350-26D2	Digital Knob Lockset w/KO	Satin Chrome	818.00
AKPDL1300-26D1	Digital Lever Lockset w/KO & PROX	Satin Chrome	1186.00
AKPDL1350-26D2	Digital Knob Lockset w/KO & PROX	Satin Chrome	1186.00
AKALHID1326	Proximity Access Card	100/box	520.00
AKAL-IR1	Hand Held Infrared Printer		520.00
AKAL-PCI2	Serial PC Interface Cable (w/DL-Windows)		129.00
AKAL-PCI2-U	Serial/USB Interface Cable (w/DL-Windows)		237.00

DK3000


- 100% fingertip or PC programmable
- 2,000 user codes, master, manager, supervisor and basic
- Weatherproof, rugged all-metal 12-button keypad
- 2 high-current rated 10A relays for entry, alarm zone shunning or lock release by real-time schedule
- Timed egress input allows door open for 5, 10 or 15 seconds
- Ideal for use with 12V or 24V (AC or DC) electric door strikes, mag lock or Alarm Lock Remote Release Mag Lock Kit
- Easiest installation in minutes: Wall mount or single gang box
- 40,000 event audit trail: query by PC or handheld printer or DTM module
- Real time clock with time-zone adjustments, enables 500 scheduled or holiday events
- Remote-release feature/request-to-exit input
- Independent tamper -reports attempts to vandalize or remove DK3000 via an alarm system
- Available in 5 finishes: US26D Satin Chrome, US10B Duronodic, US3 Brass, MS Metallic Silver, and MB Metallic Bronze

PDK3000

All the features of the DK3000 plus:

Accepts most HID proximity cards and keyfobs
 Users are individually programmed to use a card only, code only, or for the highest security
 both card and code







Part No.	Finish	Retail
AKDK3000-26D	Satin Chrome	813.00
AKDK3000-3	Polished Brass	813.00
AKDK3000MS	Metallic Silver	662.00
AKDK3000MB	Metallic Bronze	662.00
AKPDK3000-26D	Satin Chrome	1175.00
AKPDK3000-3	Polished Brass	1175.00
AKPDK3000MS	Metallic Silver	1035.00
AKPDK3000MB	Metallic Bronze	1035.00

ALARM LOCK

www.acclock.com

C

Accredited Lock Supply

TRILOGY EXIT/ TRILOGY EXIT WITH PROX

AK9ETBATCASE

Replacement Battery

TRILOGY EXIT

• Field-proven clutch Mechanism ensures long life and durability

- Fingertip and/or Windows Programmable
- 2000 User Codes: Master, manager, supervisor and users
- Real Time Clock for up to 40,000 Event Time/Date-Stamped Audit Trail
- Up to 500 Lock/Unlock Schedules (with Time Zone Support)
- Rugged 12-Button Weather-Resistant Metal Keypad
- Non-Handed; Fully Field Reversible
- Adaptable to most major manufacturers of standard RIM and IC RIM Cylinders
- · Battery operated; uses 5 AA batteries
- Battery pack mounts to interior door. Located over or under panic bar (position dependent upon exit device manufacturer).

TRILOGY EXIT WITH PROX

- · Accepts most HID Proximity cards and keyfobs
- Users are individually programmed to use a card only, code only, or for the highest security -both card and code
- 2000 User Codes: Master, manager, supervisor & users
- Real Time Clock for up to 40,000 Event Time/Date-Stamped Audit Trail
- Up to 500 Lock/Unlock Schedules (with Time Zone Support)
- Prox Card data can be added to software by uploading from lock, by using AL-PRE or entering directly from computer using DL-Windows software.
- Field-proven clutch Mechanism ensures long life and durability
- Fingertip and/or Windows Programmable
- Rugged 12-Button Weather-Resistant Metal Keypad; Non-Handed; Fully Field Reversible
- Adaptable to most major manufacturers of standard RIM and IC RIM Cylinders
- Battery pack mounts to interior door. Located over or under panic bar (position dependent upon exit device manufacturer). Battery operated; uses 5 AA batteries.





TRII	OGY	FXIT

Part No.	Description	Finish	Retail
AKETDLS1G/26DV99	Trilogy Exit Trim, Von Duprin 99	Satin Chrome	1281.00
AKETDLS1G/26DY71	Trilogy Exit Trim, Yale 7100	Satin Chrome	1281.00
AKETDLS1G/26DS88	Trilogy Exit Trim, Sargent 8800	Satin Chrome	1281.00
AKETDLS1G/26DM99	Trilogy Exit Trim, Marks M9900	Satin Chrome	1281.00

TRILOGY EXIT WITH PROX

Part No.		Description	Finish	Retail
AKETPD	LS1G/26DV99	Trilogy Exit w/Prox, Von Duprin 99	Satin Chrome	1671.00

Models available for: Von Duprin 99 Yale 7100

Corbin ED5000 Precision 1100 & 1200
Dorma 9300 Cal Royal 9800
Arrow 3800 Marks M9900

Sargent 8800 Sargent 8888

Cylinder adapter kit required when ordering.

Trilogy Remote Release Kit - Retrofit Wireless Convenience to any Cylindrical Trilogy

- Add Remote Release convenience to any cylindrical Trilogy installation with keyfob(s) or desk-mounted button
- Easy & Cost Effective
- Retrofits Cylindrical Trilogy Locks dating all the way back to 2000 with a serviceable battery pack
- Buy components separately -or -the Keyfob & Receiver in the

For Networx Locks, too! Solely purchase either the keyfob or desk-mount release button

AKRR-TRILOGYKIT: Remote release kit for all Trilogy Cylindrical models includes the RR-1BUTTON for desk mount applications and RR-RECEIVER which is designed to be installed inside the battery compartment next to the battery pack of any cylindrical Trilogy lock. The RR-RECEIVER connects to the 2 white remote release wires inside the battery compartment and to the black and red battery pack wires to power the receiver. These kits will retro fit to any existing cylindrical Trilogy manufactured since 1994. **221.00**

AKRR-RECEIVER: You will need to purchase separately either an RR-1BUTTON OR 4BKEYFOB to activate the receiver. **128.00**

AKRR-1BUTTON: Remote release desk mounted button designed to be used with any existing Networx lock enrolled with a simple keypad program. **92.00**

AKRR-4BKEYFOB: Remote release 4 button keyfob designed to be used with any existing Networx lock enrolled with a simple keypad program. **103.00**

Discount Code 'E'



AKRR-MORTISEKIT: Remote release kit for all Trilogy Mortise Locks, includes the RR-1BUTTON for desk mount applications and a RECEIVER mounted on a Lexan battery cover. **242.00**

AKRR-EXITTRIMKIT: Remote release kit for all Trilogy Exit Trim Locks, includes the RR-1BUTTON for desk mount applications and a RECEIVER mounted on a Lexan battery cover. **242.00**



Ε

Accredited Lock Supply

www.acclock.com

Trilogy Networx Lock Specifications:

Weatherproof locks for indoor/outdoor use with wide operating temperature range (-31 to 151 degrees F). Industrial strength BHMA Grade 1 durability and vandal-resistant all-metal keypad for PIN codes. PDL6100 version, also has built in HID prox reader. ADA-compliant leversets. Easy-to-install modified ANSI A115 Series door prep; easily/neatly retrofit standard cylindrical knobsets and mechanical standalone locks, in under an hour. Non-handed. 3 hour UL fire-rated deadlatch.

Supports 1-5/8 to 1-7/8" door thickness; 2-3/4" backset (2-3/8" available.) Manual key override standard; most IC cores also supported on interchangeable core models. Wide choice of seven architectural finishes and IC core preps (6-7 pin).

Ordering Information:

PDL6100 Cylindrical Trilogy Networx[™] PIN/Prox. Wireless Access Control Lock with built in HID proximity ID card reader, full-metal digital keypad, integral bi-directional radio, 4-C cell battery-operated (batteries supplied), serial number ID card, standard format SC1 keyway for manual key override, 4-7/8" ASA Strike (included).

DL6100 Cylindrical Trilogy® Networx PIN-Code Wireless Access Control Lock, as above, with full-metal digital keypad only.

PDL6500 Mortise version Networx PIN/Prox. lock, similar to 6100 Series above

DL6500 Morise version Networx PIN-code only lock, similar to 6100 Series above.

DL-WINDOWS Free Alarm Lock Trilogy Microsoft Windows-based software application, v4.0.1 or higher, supports Trilogy Networx and Trilogy standalone locks, with single database. No-charge, downloadable online at www.alarmlock.com

AL-IM80211 Hardwire/Wireless Gateway Interface Module, with integral bi-directional radio, interfaces Networx locks with PC network with hardwired Ethernet and wireless 802.11. Powered with Class 2, 6VAC transformer (supplied). Supports up to 63 Networx Locks. Two antennas. Ceiling or wall mountable.

AL-IME Hardwire Gateway Interface Module, supports up to 63 Networx Locks, similar to above, but using hardwired connection to the network via RJ45 Ethernet cable. One antenna. Powered with Class 2, 6VAC transformer (supplied). Ceiling or wall mountable.

AL-IMEPOEP Hardwire Gateway Interface Module + POE, supports up to 63 Networx Locks, as above, but using hardwired Ethernet and Power Over Ethernet (P.O.E.), plus hardwire gateway interface capability. Connects directly to a network via Ethernet cable. One antenna. Ceiling or wall mountable.

Cylinder Adapter Kits for Exit Trim

AKET-AL	Alarm Lock standard (SC1)	57.00
AKET-AR	Arrow Standard Rim Cylinder	57.00
AKET-AS	ASSA Standard Rim Cylinder	57.00
AKET-C	Corbin Standard Rim Cylinder	57.00
AKET-M	Medeco Standard Rim Cylinder	57.00
AKET-R	Sargent Standard Rim Cylinder	57.00
AKET-S	Schlage Standard Rim Cylinder	57.00
AKET-Y	Yale Standard Rim Cylinder	57.00
AKET-ARIC	Arrow IC 6/7 Pin Rim Cylinder	79.00
AKET-BIC	Best IC 6/7 Pin Rim Cylinder	79.00
AKET-CIC	Corbin IC Rim Cylinder	79.00
AKET-MIC	Medeco IC 6/7 Pin Rim Cylinder	79.00
AKET-RIC	Sargent IC Rim Cylinder	79.00
AKET-SIC	Schlage IC Rim Cylinder	79.00
AKET-YIC	Yale IC 6 Pin Rim Cylinder	79.00

These Are Adapter Kits, They Do Not Include Cylinders

Cylindrical

and

Mortise Locks

AKS6196

Replacement Battery Pack **47.00**



Part No.	Description Finish		Retail
AKDL6100-US26D	Digital Lever Lockset	Satin Chrome	1452.00
AKDL6100IC-US26D	Digital Lever Lockset for Int.Core	Satin Chrome	1472.00
AKPDL6100-US26D	Prox Digital Lever Lockset	Satin Chrome	1864.00
AKPDL6100IC-US26D	Prox Digital Lever Lockset for Int.Core Satin Chrome		1879.00
AKDL6500-US26D*	Mortise Digital Lever Lockset Satin Chrome		1586.00
AKPDL6500-US26D*	Prox Mortise Digital Lever Lockset Satin Chrome		1951.00
AKAL-IME	Ethernet Connected Gateway w/AC Adapter		510.00
AKAL-IM80211	Wi-Fi Gateway to Connect to 802.11 network		710.00
AKAL-IMEPOEP	Power Over Ethernet,plus hardware gateway		610.00
AKAL-IME-USB	USB Gateway		300.00
AKAL-NSG	Networx Signal Generator		240.00
AKAL-NSM	Networx Signal Meter		296.00

^{*}Specify RH or LH

Exit Trim

Locks



Part No.	Description	Finish	Retail
AKETDLN-US26D	Digital Lever Exit Trim	Satin Chrome	1426.00
AKETPDN-US26D	Prox Digital Lever Exit Trim	Satin Chrome	1766.00

Compatible Panic Devices:

V99	Von Duprin 99	S88	Old Style Sargent 8800
C50	Corbin ED5000	NS8	New Style Sargent 8888
Y71	Yale 7100	P11	Precision 1100
D93	Dorma 9300	CR8	Cal Royal 9800
A38	Arrow 3800		•

LOCK

www.acclock.com

Accredited Lock Supply

- EXIT ALARMS
- PULL HANDLE
- BATTERY ELIMINATOR
- DOOR HOLDER

MULTIGUARD EXIT ALARM **MODEL 250 X 28 (WITHOUT CYLINDER)**



AK250 x 28 46000 **AK250WP x 28 522**00

Maximum protection from unauthorized use with easy. instant emergency exit. Specify single or double doors.

Depressing paddle retracts deadbolt and deadlatch while sounding 95dB alarm. Bypass and alarm reset by key. Low battery warning beep. Optional alarm shutdown after two minutes if desired. Includes (9) volt battery. Requires rim cylinder (not included). Accepts outside rim cylinder and model 707 pull. Finish: metallic silver (Duranodic available)

AK260 x 28

Rearming

477.00

UL PANIC DEVICE WITH DEADLOCK SAFEGARD MODEL 700 x 28

AK700 x 28

556ºº



AK700WP x 28 634⁰⁰

design for long lasting protection. Full door coverage for 36" door (48" length available). Can be shortened for narrow doors. Depressing bar retracts deadbolt and deadlatch while sounding 95 dB alarm. Bypass and alarm reset by key.

Specify single or double doors. Optional alarm shutdown after two minutes if desired. Low battery warning beep. Includes (9) volt battery. Bar dogging. Requires rim cylinder (not included). Accepts outside rim cylinder and model 707 pull. Finish: metallic silver. (Duranodic available).

AK710-US28 595.00 Rearming AK715-US28 15 Second Exit Delay 1046.00

Meets NFPA 101 Life Safety Requirement Includes: armored door cable, transformer and egress interface.

OUTSIDE ACCESS DOOR PULL

Allows outside access for alarm lock panic devices. After deadbolt is retracted by outside key, a slight pull releases deadlatch and opens door.

Dimensions:8" x 1 1/2" Note: Not for use with Model 11 A. Finish: Metallic Silver (Duranodic available) Requires rim cylinder (not included).

AK707MS

AK707MB



EMERGENCY EXIT ALARM DEADBOLT LOCK SENTRYGARD MODEL 11A

AK11A **580**00

Dimensions: 4 1/2" x 10" x 3" Overall width to end of clapper: 18" Weight: 8 lbs.



The best features of a panic device; plus a deadbolt, plus a warning alarm. Provides full time locking of emergency exit doors while complying with standard safety, fire and building department codes. For maximum day and night security and a powerful deterrent against pilferage-from within or without. Always panic proof, with instant automatic exit in case of emergency.

Supplied without cylinders. Locks will accommodate all standard rim cylinders. May be operated from outside the door by mounting an extra cylinder.

AC POWER SUPPLY

Provides constant power supply with battery backup for Models 11A, PG10, PG20, 80, 250, 260, 700, 710.

Built-in circuit breaker with push-button reset eliminates fuse replacement. Includes a camlock cylinder and six ft. of armored cable. Plug-in installation. 117 volt AC to 6 or 9 volt DC.

AKPP100 **265⁰⁰**

DOUBLE DOOR HOLDER

Secures the inactive door to the door frame while the active door is closed. Releasing the active door automatically allows both doors to swing freely. Reversible; right or left hand doors. Cast aluminum. Dimensions: 8 1/2"(L) x 3" (W) x 2 1/2" (H)

AK44 125⁰⁰

CABLE ENERGY SWITCH

Use with electrified locks, this equipment provides a unique way of bringing electrical current from the lock side of the door frame to the door. Power flows only when the door is closed. Stainless Steel trim



 72^{00}

ARMORED DOOR LOOP


For Use With Electric Locks

AK261

An easy way to bring electric current from the hinge side of a door frame to the door. 18" flexible armored cable. End brackets are deep drawn anodized aluminum to conceal wire connections.

5600





Accredited Lock Supply

www.acclock.com

•ELECTRONIC LOCKS

DOOR KEEPER

SWITCHES

EXIT DOOR ALARM PG-30

Top-of-the-line keypad-controlled narrow stile door alarm, simmilar to the PG21E, but also featuring the following advanced features:

Digital codes for Master, Management and Passage (used for Auto - Arming)

- 3 security levels for:
- a. High Security
- b. Unattended Operations
- c. Flexible control for delivery doors, etc.
- Audible low battery warning
- 3 programmable 95db siren styles: sweep, pulsed and steady
- Logo key is dual function test button

AKPG30MB Metallic Bronze 344.00
AKPG30MS Metallic Silver 344.00
AKPG30KPD Keypad for External 199.00

Control of PG30



CYLINDER FINGER PULL 711

An inexpensive door pull for use when outside key only access is required. **Less cylinder**

AK711-28 Aluminum Finish



OUTSIDE EMERGENCY PULL 22

To permit entrance from exterior roof or when outside key only access is required. For use with clapper design only.



AK22

9200

EXIT DOOR ALARM PILFERGARD MODEL PG-10


The original and industry-standard "anti-pilferage" exit door alarm for over 15 years. Budget-priced yet extremely effective against unauthorized use of emergency doors by both customers and employees. Doors can be safely maintained and unlocked as required by building and safety codes. Used by factories, chain stores, warehouses.

Less mortise, cylinder and key. Dimensions: 8 1/2" x 4 1/4" x 3 3/8" Weight: 3 lbs. 14 oz. (with battery) Finish: handsome gray aluminum

AKPG10 289.00 AKLL1 same w/strobe light 300.00

BATTERY PACK

For PG-10 & LL1 & 11A Exit Door Alarm



EXIT DOOR ALARM PILFERGARD MODEL PG21

A modern, high-tech annunciator that fits a variety of doors and motifs because of its sleek profile design. Even narrow stile doors easily accept the PG20.

Multi-purpose, easy-to-install, with selectable options for an unprecedented range of applications: magnetic contacts, automatic shutoff or continuous operation, immediate or 15-second delayed alarm sounding. Solid-state circuitry. Piercing 85dB alarm.

Packed with hardware mounting kit, template and warning signs. Less mortise cylinder and key. Rim cylinder for outside key control not included.

Slim-line, metallic-silver finish.Dim: 9" x 2 2/3" 2 1/2"

 AKPG21MS
 Silver
 289.00

 AKPG21MB
 Bronze
 289.00

 AKPG21MSS
 w/yellow strobe
 355.00

37⁰⁰

AKBP6

MODEL 103 FAIL SAFE WITH ALL KEEPERS

A compact unit designed for narrow stile doors. Comes complete with keepers for easy installation on all types of doors and windows - single, pairs, double acting or overhead.

When the lock is aligned with the keeper, the bolt projects into the keeper and locks the door. The bolt is retracted and the door unlocked by either a remote switch, a key switch, time programmer or other electrical contract which interrupts the power. Ideally suited for laundromats, lobby doors of public buildings and other unattended areas.

Dimensions: 1 3/4" x 6 3/4" (including keeper) Bolt diameter is 5/8" and projects 5/8"



AK103 (Fail unlocked) 349.00

AK103-12VDC

(Fail unlocked) 411.00

AK104RA

(Fail locked) 416.00