

PRODUCTS OVERVIEW

F-3066 Bluetooth module for the company independent development of intelligent wireless audio data transmission products, is the low cost High efficiency of double track wireless transmission scheme, module used Taiwan and jie sound chip, for module Provides the high quality sound and compatibility, the overall performance is optimized.F-3066 Bluetooth module from the drive Way, the customer only need to put the module access application products, electricity, connecting key, can quickly achieve.

Performance parameters:

Bluetooth specification: Bluetooth V3.0+EDR

Support Bluetooth protocol: AVRCP 1.0, GAVDP 1.0, AVDTP 1.0, A2DP 1.0,

Hands-Free Profile 1.5, Headset Profile v1.1

Working current: $\leq 30\text{mA}$

Temperature range: -40°C to $+80^{\circ}\text{C}$

Wireless transmission range: $> 10\text{m}$

Transmission power: CLASS 2 Max 4dBm

Sensitivity: [\$-80\text{dBm}@0.1\%BER\$](#)

Frequency range: 2.402GHz-2.480GHz

Audio performance: High performance stereo

Audio signal to noise ratio: $\geq 75\text{dB}$

Distortion: $\leq 0.1\%$

FCC Statement:

This equipment has been tested and found to comply with the limits for Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: Modifications to this product will void the user's authority to operate this equipment.

RF Radiation Exposure Statement:

1. This Transmitter must not be co - located or operating in conjunction with any other antenna or transmitter.
2. This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

FCC Information to OEM integrator

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user manual of the end product.

The user manual which is provided by OEM integrators for end users must include the following information in a prominent location.

1. To comply with FCC RF exposure compliance requirements, the antenna used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co - located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi - transmitter product procedures.
2. Only those antennas with same type and lesser gain filed under this FCC ID number can be used with this device.
3. The regulatory label on the final system must include the statement: "Contains FCC ID: 2AG2P-520 or using electronic labeling method as documented in KDB 784748.
4. The final system integrator must ensure there is no instruction provided in the user manual or customer documentation indicating how to install or remove the transmitter module except such device has implemented two - ways authentication between module and the host system