
MAGIC-X USB Wireless Adapter



User manual

MAGIC-X

Connect your Bluetooth or wired USB controllers to your Xbox Series X/S, Xbox One, PS3, Switch, PC Windows, macOS, NEOGEO mini, NEOGEO Arcade Stick Pro, PS Classic, SEGA MEGA DRIVE mini, SEGA Genesis Mini, SEGA Astro City Mini, Raspberry Pi, Steam entertainment system. If you find any issues or have any difficulty operating the device, please reach out to us at info@mayflash.com and we will be more than happy to help you out. Update to the latest firmware at www.mayflash.com

































Controller Compatibility

DualSense, DualShock 4, DualShock 3, Xbox Series X/S, Xbox One Bluetooth controllers, Xbox Elite Wireless Controller Series 2, Switch Pro, Switch Joy-Con, Wii Remote, Wii U Pro.

City Mini

Wired USB Controllers

DualSense, DualShock 4, DualShock 3, Xbox Bluetooth Controller, Switch Pro, ASTRO Gaming C40 TR Controller PlayStation 4, PlayStation 4 SCUF Vantage 2 Controller, SEGA MEGA DRIVE and SEGA Genesis Mini USB Controller Pads, Logitech rumble gamepad F510 and F310, PS Classic Controller, Switch Taiko Drum, PS4 Taiko Drum.

The wireless controller that comes from your console will become a wired controller by simply connecting a standard USB cable (with exception of Xbox 360 which requires an official Microsoft wired Xbox 360 controller). For best results, it is recommended that you use original Switch Controllers, or genuine Xbox or PlayStation controllers and quality certified USB cables.

Quick Start Guide

01 USB A-Male

Connect the adapter to your game console.



03 LED Indicators

System mode	Switch	Switch Pro	Xbox/mac0S	PS3/Raspberry Pi/ PC (Dinput)	Raspberry Pi/ PC/Steam (Xinput)	NEOGEO Arcade Stick Pro/ NEOGEO mini	PS Classic	SEGA MEGA DRIVE Mini/ SEGA Genesis Mini/ SEGA Astro City Mini	
LED Indicator	Red	Purple	Blue	Yellow	Green	White	Cyan	White	

- * LED Indicator blinks slowly: The Bluetooth is not connected yet.
- * LED Indicator blinks quickly: The Bluetooth is Pairing.
- * LED Indicator becomes solid: The connection is successful.
- * Switch Pro mode (LED is purple): Go to System Setting > Controller and Sensors > Turn on Pro Controller Wired Communication.
- * Bluetooth headset works for Switch mode (LED is red) and PS4 mode (LED is blue).

04 Button on the side of the adapter

05 Bluetooth Controllers Set Up

game console.

blinks slowly.

what we recommend:

- 6 LED Indicator

Pro Controller Wired

Communication

• Press the button shortly to pair the controllers and the adapter. The indicator blinks quickly.



• Connect the adapter into any spare USB port on your

To switch the modes, press and hold the button on the

side of the adapter for 3-5 seconds. The LED indicator

Turn on the Bluetooth controller, press the Button on the

Bluetooth controller. The LED indicator blinks quickly.

you can remove the USB cable and start to pair it again.

2. Turn off your Xbox Series S/X controller and turn it on again.

side of the adapter, and then press the pair button on your

LED indicator becomes solid when connection is successful.

* If the Bluetooth pairing failed, please connect the Bluetooth controller to the adapter using a USB cable (not

included in the packaging, you can purchase it separately). As soon as the controller is identified by the system,

* If you are having the issues connecting a Xbox Series S/X or Xbox Elite 2 controller to the MAGIC-X, this is

1. Disable or turn off any Bluetooth device (like your Smart TV or Set Top Box etc.) within range of the controller.

● The different game console systems can recognize the adapter automatically. If not, you can press and hold the button on the side of the adapter for 3-5 seconds to switch the mode vou need.






• Connect the adapter into any spare USB port on your game

4. The LED indicator becomes solid when connection is successful.

Please wait patiently until the LEDs stop blinking.





Using Bluetooth Headset (For Switch / LED Red and Xbox / LED Blue)

- Turn on your Bluetooth headset to enter into the pairing mode.
- 2 Press the pair button on the side of the adapter, LED indicator starts to blink rapidly, wait for a few seconds.

3. Pair your Xbox Series S/X controller with MAGIC-X again by pressing the button on the adapter and pair

patient! The connection may be disconnected shortly and then connected again during the pairing process.

button on your controller (LED indicator blinks quickly). The pairing process may take a few seconds. Please be

• LED becomes solid when the connection is successful.


- * Xbox mode works with both A2DP(High quality audio signals) and HFP(Audio and chatting) connections.
- * To use HFP connection on Xbox, press and hold the START + X/□ button on your controller.
- * To use A2DP connection on Xbox, press and hold the START + Y/\triangle button on your controller.
- * Switch mode (LED is Red) does not support 6-axis motion and vibration. If you need the 6-axis motion and vibration, please go to Switch Pro mode (LED is Purple).













Modify the Vibration Intensity

- Press and hold the Button R1/RB and R3 for 3-5 seconds until the controller keeps rumbling. (Please keep holding these two buttons until you finish the below whole process).
- To modify the vibration intensity, press the D-Pad "Up" or "Down".
- To guit the modification, release any button of R1/RB or R3 once you've got your preferred vibration intensity.
- There are 7 levels of the vibration intensity. The default one is 100%.









Adjust the Dead Zone

- Press and hold the Button START and D-Pad Left or D-Pad Right. Once the LED on the adapter starts to blink, you may release the Button D-Pad Left or D-Pad Right, BUT keep holding the Button START.
- To increase or decrease the dead zone, press the D-Pad "Up" or "Down".
- As soon as you get the right dead zone value, you may release the Button START to guit the process.
- There are 7 levels of the Dead Zone Value. The default one is Level 3

Level1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	
0%	2.5%	5%	7.5%	10%	12.5%	15%	1 /

You can know the Dead Zone Level by the times of the LED blinking during the adjusting process. For example, LED on the adapter blinks 3 times then stops when Dead Zone Level is Level 3.



Update the Software

If you are having problems with the adapter, you can follow the below instructions to update.

- Download the software from http://www.mayflash.com/Support and install it on your Windows system.
- Double click on the updater and leave the updater window open on your screen.
- Press and hold the button on the side of the adapter, and connect the USB from your adapter into any spare port on your PC. Wait for 3-5 seconds.
- As soon as the adapter has been recognized, you may release the button.
- Select "Update"
- O Do not disconnect the device until you are informed that the update is completed successfully

Additional Functions

- Only one Bluetooth controller is supported for one adapter.
- A wired USB controller and a wireless Bluetooth controller can be connected at the same time. but both of them have the same functions and can only play one game character.
- To switch A-B.B-A.X-Y.Y-X, press and hold the button "START" and "A" for 3 seconds. To switch A-A. B-B. X-X. Y-Y. press and hold the button "START" and "B" for 3 seconds. (This function is optional. It depends on the different controllers.







- The Touch Pad button on the PS4 Controller works as the Capture button of the Joy-Con or Switch Pro controller when you connect your PS4 controller to the Switch system by the adapter. Please see more details about the other controllers on the below "Controllers Buttons Table"
- To disconnect the controller and the adapter, press the button on the side of the adapter. But if you want to disconnect the Xbox Elite 2 and the adapter, you need to press and hold the HOME button on your controller to shut off the power.
- The adapter can remember up to 6 paired wireless controllers. But if your controller is a BLE device like Xbox Series X/S, then the adapter can only remember one.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

PS5 DualSense	\otimes	0	0	(1)	L1	R1	Create	OPTIONS	L3	R3	LS	RS	♣ P0V	L2	R2	₽ PS	Pressing Tpad
DualShock 4/macOS	8	0	0	۵	Li	R1	SHARE	OPTIONS	L3	R3	LS	RS	♣ P0V	L2	R2	(B) PS	Pressing Tpad
DualShock 3	8	0	0	۵	L1	R1	SELECT	START	L3	R3	LS	RS	♣ POV	L2	R2	♠ PS	SELECT+ START
Switch Pro	B	A	Ŷ	(X)	L	R	Θ	⊕	L3	R3	LS	RS	+ POV	ZL	ZR	⊕ номе	⊝ ÷.⊕ ©
Joy-Con	B	A	Ŷ	(X)	L	R	Θ	0	L3	R3	LS	RS	♦ POV	ZL	ZR	⊕ номе	⊖ _{or} ⊕
Xbox Series X/S	A	B	(X)	Ŷ	LB	RB	@view	MENU	L3	R3	LS	RS	+ POV	LT	RT	⊗ номе	⊜VIEW + ⊜ MENU
Xbox One	A	B	(X)	Ŷ	LB	RB	@view		L3	R3	LS	RS	∔ POV	LT	RT	⊗ HOME	⊜view + ⊜ menu
Xbox 360	A	B	(X)	(Ý)	LB	RB	@BACK	(D) START	L3	R3	LS	RS	♦ POV	LT	RT	⊗ номе	
PC-Xinput	1	2	3	4	(5)	6	7	8	9	10	X/Y Axis	X/Y Circle	POV	Z+	Z-	HOME	
PC-Dinput	3	2	4	1	(5)	6	9	10	(1)	(12)	X/Y Axis	Z Axis Circle	POV	(7)	8	(13)	
Wii U Pro	B	A	Ŷ	(X)	L	R	Θ	⊕	L3	R3	LS	RS	+ POV	ZL	ZR	(номе	⊝+⊕
Wii Classic Pro	(b)	(a)	ý	(X)	L	R	Θ	0			LS	RS	+ POV	ZL	ZR	⊕ номе	⊝÷⊕
Wii mote + Nunchuck	2	A	1	В	С		Θ	⊕			LS		+ POV	Z+		(номе	⊝⁺⊕
GENESIS mini Controller	₿	A				©		©START			♦ POV		♦ POV				
MEGA DRIVE mini Controller	₿	A	Ŷ	(X)	Ø	©	⊚море	©START			♦ POV		♦ POV				
PS4 Taiko Drum	8	0	0	۵	Li	R1		OPTIONS	Beat the Drum Left	Beat the Drum Right			♣ P0V	Beat the Drum Left	Beat the Drum Right	₽ PS	
Switch Taiko Drum	B	A	Ŷ	(X)	L	R	Θ	0	Beat the Drum Left	Beat the Drum Right			♣ POV	Beat the Drum Left	Beat the Drum Right	⊕ номе	Capture
PS Classic	8	0	0	۵	L1	R1	SELECT	©START					& POV	L2	R2		
NEOGEO mini	B	0	A	0			⊚ SELECT	©START			Q Joystick		Q Joystick				
					~	~								~	(m)		

Warning: Changes or modifications to this unit not expressly approved by the party onsible for compliance could void the user's authority to operate the equipment.

TE: This device complies with part 15 of the FCC Rules. Operation is subject to ollowing two conditions: (1) This device may not cause harmful interference, and this device must accept any interference received, including interference that may undesired operation.

Statement: This equipment has been tested and found to comply with the limits Class B digital device, pursuant to part 15 of the FCC Rules. These limits are ned to provide reasonable protection against harmful interference in a ential installation. This equipment generates, uses and can radiate radio nency energy and, if not installed and used in accordance with the instructions cause harmful interference to radio communications. However, there is no intee that interference will not occur in a particular installation. If this oment does cause harmful interference to radio or television reception, which be determined by turning the equipment off and on, the user is encouraged to try orrect the interference by one or more of the following measures: orient or relocate the receiving antenna.

- rease the separation between the equipment and receiver.
- nnect the equipment into an outlet on a circuit different from that to which the ver is connected.
- onsult the dealer or an experienced radio/TV technician for help.

Statement: This device complies with Part 15 of FCC Rules [and contains se-exempt transmitter(s) that comply with innovation, Science and Economic elopment Canada's licence-exempt RSS Standar(s)], Operation is subject to the wing two conditions: (1) This device may not cause interference; and

- his device must accept any interference received, including interference that may undesired operation
- digital apparatus complies with Canadian CAN ICES 3 (B)/NMB 3(B) device meets the exemption from the routine evaluation limits in section 2.5 of 102 and compliance with RSS 102 RF exposure, users can obtain Canadian mation on RF exposure and compliance.
- equipment complies with Canada radiation exposure limits set forth for an ontrolled environment.

ch: L'émetteur/récepteurexempt de licence contenu dans le présent appareil est orme aux CNR d'Innovation. Sciences et Développementéconomique Canada icables aux appareils radio exempts de licence. L'exploitation est autorisée aux conditions suivantes:

- appareil ne doit pas produire de brouillage, et
- appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage isceptible d'en compromettre le fonctionnement areil numérique du ciem conforme canadien neut 3 (b) / nmb 3 (b). ppareil est conforme à l'exemption des limites d'évaluation courante dans la
- on 2.5 du cnr 102 et conformité avec rss 102 de l'exposition aux rf, les ateurs peuvent obtenir des données canadiennes sur l'exposition aux champs rf