

DS-2CD5026G0

2 MP Indoor Smart Network Box Camera

DarkFighter.



The Hikvision DS-2CD5026G0 Indoor Smart Network Box Camera provides high definition output. It supports H.265+ video compression, which assures savings in bandwidth and storage. Darkfighter technology allows for viewing and recording in ultra low-light conditions.

With a WDR of 140 dB and Lightfighter technology, it provides superb image quality.

The camera can be equipped with up to eight different Hikvision lens options, which are installed on a standard CS mount.

Smart features, such as line crossing, intrusion, and scene change detection are also supported.

Available models:
DS-2CD5026G0

LightFighter.

- 1/2.5" (2 MP) Progressive Scan CMOS
- 1920 x 1080 Resolution @ 60 fps
- CS Lens Mount Options
- Ultra-Low Light, 0.002 Lux (with f/1.2 Lens), Darkfighter Technology
- H.265+, H.265, H.264+, H.264
- 5 Defined Streams and 5 Custom Streams
- 140dB WDR, Lightfighter Technology
- Alarm Input/Output
- 12 VDC Accessory Output
- MicroSD Card Slot Supports 256 GB
- 12 VDC and PoE (802.3af)

Specifications



| | |
|-------------------------------|---|
| DS-2CD502660 | |
| Camera | |
| Image Sensor | 1/1.8" [2 MP] progressive scan CMOS |
| Minimum Illumination | Color: 0.002 Lux @ (f/1.2, AGC on), B/W: 0.0002 lux @ (f/1.2, AGC on) |
| Shutter Speed | 1 s to 1/100,000 s |
| Slow Shutter | Yes |
| Auto-iris | DC drive |
| Day/Night | IR cut filter |
| Digital Noise Reduction | 3D DNR |
| WDR | 140 dB |
| Lens | |
| Lens Mount | CS Mount |
| Compression Standard | |
| Video Compression | Main stream:H.265+/H.265/H.264+/H.264; sub stream/third stream/fourth stream/fifth stream/custom stream: H.265+/H.265/H.264+/H.264/MJPEG |
| H.264 Type | Baseline profile/main profile/high profile |
| H.264+ | Main stream supported |
| H.265 Type | Main profile |
| H.265+ | Main stream supported |
| Video Bit Rate | 32 Kbps to 16 Mbps |
| Smart-Feature Set | |
| Behavior Analysis | Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection |
| Exception Detection | Scene change detection, audio exception detection, defocus detection |
| Face Detection | Yes |
| Statistics | Counting |
| Region of Interest | Four fixed regions for main stream, sub stream, third stream, fourth stream, and fifth stream, and dynamic face tracking |
| Image | |
| Maximum Resolution | 1920 x 1080 |
| Main Stream | 60 fps [1920 × 1080, 1280 × 960, 1280 × 720] |
| Sub Stream | 30 fps [704 × 480, 640 × 480] |
| Third Stream | 30 fps [1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480] |
| Fourth Stream | 30 fps [1920 × 1080, 1280 × 720, 704 × 480, 640 × 480] |
| Fifth Stream | 30 fps [704 × 480, 640 × 480] |
| Custom Stream | 30 fps [1920 × 1080, 1280 × 720, 704 × 480, 640 × 480]; up to 5 custom streams are supported |
| Image Enhancement | BLC, HLC, defog, 3D DNR, EIS |
| Image Setting | Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance are adjustable by client software or web browser |
| Target Cropping | Yes |
| SVC | H.264 and H.265 encoding |
| Day/Night Switch | Day/night/auto/schedule/triggered by alarm in |
| Picture Overlay | Logo picture can be overlaid on video with a 128 × 128 24-bit bmp format |
| Network | |
| Network Storage | Supports microSD/SDHC/SDXC card (256 GB) local storage and NAS (NFS,SMB/CIFS), ANR |
| Alarm Trigger | Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour |
| Security Measures | Password protection, HTTPS encryption, IEEE 802.1x port-based network access control, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF |
| General Function | One-key reset, anti-flicker, five streams and up to 5 custom streams, heartbeat, password protection, privacy mask, watermark, IP address filter |
| API | ONVIF (PROFILE S, PROFILE G), ISAPI, SDK |
| Simultaneous Live View | Up to 20 channels |
| User/Host | Up to 32 users. 3 user levels: administrator, operator and user |
| Client | iVMS-4200, Hik-Connect, iVMS-5200, Hik-Central |
| Web Browser | IE8+, Mozilla Firefox 30.0+, Google Chrome 31.0+, Safari 8.0+ |
| Interface | |
| Communication Interface | One-port RJ45 10M/100M/1000M Ethernet port; One RS-485 interface (half duplex, HIKVISION, Pelco-P, Pelco-D, self-adaptive) |
| Alarm | Two inputs; two outputs (alarm output supports up to 24 VDC, 1 A or 110 VAC, 500 mA) |
| Video Output | One Vp-p composite output (75 Ω/CVBS) |
| Power Output | 12 VDC, maximum 200 mA (supported by 12 VDC, 24 VA,C and PoE) |
| On-board storage | Built-in micro SD/SDHC/SDXC slot, up to 256 GB |
| BNC | CVBS analog output (4CIF resolution) |
| Reset Button | Yes |
| General | |
| Operating Conditions | -22° F to 140° F (-30° C to 60° C), humidity: 95% or less (non-condensation) |
| Power Supply | 12 VDC ± 20%, 24 VAC ± 20%, PoE (802.3af, class 3); terminal block for DC and AC input |
| Power Consumption and Current | 12 VDC ± 20%, 0.6 A, maximum 7 W; 24 VAC ± 20%, 0.3 A, maximum 7 W; PoE (802.3af, 36 V to 57 V), 0.1 A to 0.3 A |
| Material | Aluminum alloy |
| Dimensions | 5.61" × 2.75" × 2.68" [142.6 mm × 69.8 mm × 68 mm] |
| Weight | Approximately 1.52 lbs (690 g) |

Accessories

| | | | | | |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| HV3816D-8MPIR Manual Focusing 8 MP IR Lens | HV1140D-8MPIR Manual Focusing 8 MP IR Lens | HV3816P-8MPIR Manual Focusing 8 MP IR Lens | HV0733D-6MP Manual Focusing 6 MP Lens | HF3417D-12MPIR Manual Focusing 12 MP IR Lens | HV0415D-MP Vari-Focal Auto Iris DC Drive 3 MP Lens |

| | | | | | |
|---|--|---|---|---|---|
|  |  |  |  |  |  |
| HV1250D-MPIR Manual Focusing 3 MP IR Lens | HV1140P-8MPIR Manual Focusing 8 MP IR Lens | DS-1331HZ Indoor Box Camera Housing | DS-1332HZ Outdoor Box Camera Housing | PP2 Pendant Mount | WBS Box Camera Wall Mounting Bracket |

Dimensions

