

FEATURES:

- UL listed and CL2-rated for in-wall installations
- Perfect for use in or out of wall with a variety of speaker types including in-wall and in-ceiling.
- High-purity 99.996% oxygen-free copper conductors.
- Comes in an easy pull spool, Pulls and strips easily, reducing installation time
- Compatible with banana plugs and wall plates.
- Clearly distinguishable White, Yellow, Red and Black inner jackets for determining polarity.
- High quality, flame retardant PVC outer jacket.
- Multi-twist, rope lay braiding.

CL2 PVC Jacket

- Our CL2 Rated 2-Conductor Loud Speaker Cable comes wrapped in a sturdy PVC (Polyvinyl Chloride) Jacket, built to withstand high levels of stress, pulling, and pushing. CL2 rated speaker wires are made of the heat resistant material which makes them the most safe and permitted option for in-wall installations.

Strand Cable Design

- Designed for flexible, simple installations, this particular type of speaker cable is perfect for most installations where cable runs require several bends and twists in the line.

SPECIFICATION:

Awg		Awg	18#
No. of conductor		p,c	2C
Conductor	Material	---	Stranded bare copper
	Filler	---	-----
	Construction	No./mm	105/0.16±0.008mm
	Stranded diameter	mm	1.9mm
Insulation	Material	---	32P 60°C UL PVC
	Nom. Thickness	mm	0.35(Ref.)
	Diameter	mm	2.65±0.05mm
	Color	---	RD-01(168)/BK-01
Filler	Material	---	420DNYLON
Jacket	Material	---	60P 60°C UL PVC
	Min. Thickness	mm	0.75(Ref.)
	Nom. Thickness	mm	0.85(Ref.)
	O.D	mm	5.2±0.15mm
	Color	---	White WH-47 oil shine type PVC
Marking	KOA E360309 OR E360310 (UL) CM OR CL2 AUDIO CABLE 18AWG*2 STRANDED 001FT----100FT		

Configuration: