



NILES®



MP6

IN-WALL LOUDSPEAKER



6 1/2" 2-Way MP Multipurpose In-Wall Loudspeaker

- Tweeter can be rotated and pivoted
- Treated foam cone surround increases sensitivity and provides exceptional durability

SPECIFICATIONS SHEET

6 1/2" In-Wall Loudspeaker
MP6
6 1/2" 2-Way MP Multipurpose In-wall Loudspeaker

Tweeter can be rotated and pivoted

Model	Stock Number
-------	--------------

MP6R	FG00876
------	---------

MP6	FG00875
-----	---------



MP6 requires 6 Series Bracket Kit for installation. Use FG00320 or FG00898 (sold separately)

MP6R includes everything required for installation

Woofer Technology

- 6-1/2" Talc-filled polypropylene cone is light, strong and well damped to accommodate all program material
- Treated foam cone surround increases sensitivity and provides exceptional durability

Tweeter Technology

- Proprietary tweeter-adjustment mechanism ratchets in 1mm increments and then pivots for precise aiming of high frequencies
- 3/4" Kaladex® dome with fluid-cooling and ultra-wide dispersion for clear and detailed high-frequencies

Specifications

- Impedance: 8 ohm
- Recommended amplifier power: 10W to 75W
- Frequency response: 65Hz – 20kHz +/-3dB
- Sensitivity: 88dB for 2.83V pink noise
- Frame dimensions: 8 3/4" x 11 11/16" (22.2cm x 30cm)
- Hole cutout dimensions: 7 5/8" x 10 5/8" (19.4cm x 27cm)
- Depth behind wall: 3 5/8" (9.2cm) based on 1/2" drywall

Warranty: Lifetime limited

Shipping weight: 10 lbs. (4.5 Kg)