

CUTTING EDGE: ANOTHER WORLD FIRST FROM METABO!

With a choice of 4 blade options the tool-less Metabo Quick blade change system is a world first for hedge trimmers. It offers two distinct advantages from the off: on one hand, you can replace your blunt blade yourself without having to bring the whole machine in for servicing; on the other, you can cover several uses with one machine - trim large surfaces with a long blade, cover all your general jobs with a medium blade or choose a shorter blade for more delicate, intricate work. **Metabo. Work. Don't play.**







METABO IS SIMPLY A CUT ABOVE THE REST.

Once again Metabo are setting new standards in hedge trimming. In order to meet the varying demands of the hedge trimmer market we have divided our new models into three classes – a top, middle and standard class. The top class boasts a world first with its toolless "Quick" blade change system. The middle class incorporates the patented Metabo handle which increases the cutting reach by up to 50% compared to conventional designs (as does the

top class). Where as the standard class provides a compact light weight solution, while still retaining some the features and benefits of the upper classes. In essence Metabo hedge trimmers stand out in all three classes by virtue of their performance, ergonomics and innovation. Robust motors, laser cut diamond-ground blades and excellent features are just some of the reasons why they are the first choice for many professionals the world over.



The patented Metabo handle system (top & middle class)
offers 50% more reach by means of an extra switch on the back handle. You can reach higher without having to abandon the safe two-hand operation.



Safety lower blade
The 8-mm safety zone of the lower blade makes cutting even safer.





Safe two-hand operation and patented mechanical quick braking
This kicks in when one of the two hand switches are not depressed. This makes it virtually impossible for you to accidentally reach into the blade while it is running.



COMMON FEATURES

- Safety two-handed operation and patented mechanical quick braking (blade quick stop in 0.05 seconds)
- Safety lower blade
- Cleaner cut due to double ground blade teeth at 30° angle
- Especially sharp diamond-ground blade teeth
- Large hand guard
- Metabo S-automatic torque limiting clutch
- Quiet running and very good ergonomoy
- Cable strain relief
- Trigger-guard with twig feed



| | 450 Watt Hedge Trimmer HS 45 | 450 Watt Hedge Trimmer HS 55 | 450 Watt Hedge Trimmer HS 65 |
|---|---------------------------------|---------------------------------|---------------------------------|
| Comparative device characteristics | | | |
| Cutting strength | 18 mm | 18 mm | 18 mm |
| Cutting length | 450 mm | 550 mm | 650 mm |
| Blade clearance | 28 mm | 28 mm | 28 mm |
| Number of cuts at no load | 3.100 /min | 3.100 /min | 3.100 /min |
| Rated input power | 450 W | 450 W | 450 W |
| Weight (without mains cable) | 3,4 kg | 3,6 kg | 3,8 kg |
| Standard equipment | Trigger guard, container | Trigger guard, container | Trigger guard, container |
| Type | HS 45 | HS 55 | HS 65 |
| Order no. | 6.20016 | 6.20017 | 6.20018 ■ |

| Accessories | | Order no. |
|---|---|-----------|
|  | Hedge trimmer maintenance oil spray <ul style="list-style-type: none"> ■ Vegetable-based ■ Also suitable for the cordless hedge trimmer Hs A 8043 Maintenance, pump-spray-can, with 0.3 litre capacity | 6.30475 |
|  | Hedge trimmer maintenance oil, 1 litre <ul style="list-style-type: none"> ■ Vegetable-based ■ Also suitable for the cordless hedge trimmer Hs A 8043 | 6.30474 |

| | | |
|--|--|---------|
|  | Cable strain relief <ul style="list-style-type: none"> ■ For attaching between the machine power plug and the extension lead socket (prevents the plug of the power tool from accidentally being pulled out of the socket) | 6.31070 |
|  | Full-view safety goggles <ul style="list-style-type: none"> ■ Very comfortable full-view safety goggles. UV protection 2-1, coating on the lens: scratch-free on the outside and mist-free on the inside. | 6.31071 |

SAWS

SPECIAL-PURPOSE MACHINES

SYSTEMATIC ORGANISATION

GARDEN

WOOD-PROCESSING TECHNOLOGY


WATER-/PUMP TECHNOLOGY

WELDING TECHNOLOGY

COMPRESSED AIR SYSTEMS



COMMON FEATURES


- Up to 50% range increase due to patented Metabo handle system
- Safety two-handed operation and patented mechanical quick braking (blade quick stop in 0.05 seconds)
- Safety lower blade
- Cleaner cut due to double ground blade teeth at 30° angle
- Fatigue-proof operation due to ergonomic full grip bow-type handle design and optimum centre of gravity position
- Large hand guard
- Quiet running due to shear blades running in opposite direction
- Metabo S-automatic torque limiting clutch
- Quiet running and very good ergonomoy
- User-friendly guidance of machine exhaust in all working situations
- Cable strain relief
- Trigger-guard with twig feed



red dot
design award
winner 2007


| | 550 Watt Hedge Trimmer HS 8545 | 550 Watt Hedge Trimmer HS 8555 | 550 Watt Hedge Trimmer HS 8565 |
|---|-----------------------------------|-----------------------------------|-----------------------------------|
| Comparative device characteristics | | | |
| Cutting strength | 20 mm | 20 mm | 20 mm |
| Cutting length | 450 mm | 550 mm | 650 mm |
| Blade clearance | 26 mm | 26 mm | 26 mm |
| Number of cuts at no load | 3.200 /min | 3.200 /min | 3.200 /min |
| Rated input power | 550 W | 550 W | 550 W |
| Weight (without mains cable) | 3,6 kg | 3,8 kg | 4 kg |
| Standard equipment | Trigger guard, container | Trigger guard, container | Trigger guard, container |
| Type | HS 8545 | HS 8555 | HS 8565 |
| Order no. | 6.08545 | 6.08555 | 6.08565 |

| Accessories | | Order no. |
|--|---|-----------|
|  | Hedge trimmer maintenance oil spray ■ Vegetable-based ■ Also suitable for the cordless hedge trimmer Hs A 8043 Maintenance, pump-spray-can, with 0.3 litre capacity | 6.30475 |
|  | Hedge trimmer maintenance oil, 1 litre ■ Vegetable-based ■ Also suitable for the cordless hedge trimmer Hs A 8043 | 6.30474 |

| | | |
|---|---|----------------------|
|  | Cable strain relief ■ For attaching between the machine power plug and the extension lead socket (prevents the plug of the power tool from accidentally being pulled out of the socket) | Order no. 6.31070 |
|  NEW | Full-view safety goggles ■ Very comfortable full-view safety goggles. UV protection 2-1, coating on the lens: scratch-free on the outside and mist-free on the inside. | 6.31071 |

COMMON FEATURES

- Metabo "Quick": patented quick change of cutter bar without tools
- Up to 50% range increase due to patented Metabo handle system
- Especially high cutting output due to two-level reduced gear
- Safety two-handed operation and patented mechanical quick braking (blade quick stop in 0.05 seconds)
- Safety lower blade
- Cleaner cut due to double ground blade teeth at 30° angle
- Especially sharp diamond-ground blade teeth
- Fatigue-proof operation due to ergonomic full grip bow-type handle design and optimum centre of gravity position
- Large hand guard
- Quite running due to shear blades running in opposite direction
- Metabo S-automatic torque limiting clutch
- Quiet running and very good ergonomomy
- User-friendly guidance of machine exhaust in all working situations
- Cable strain relief
- Trigger-guard with twig feed



**FIRST OF ITS KIND
IN THE WORLD**
... with Metabo "quick"-blade
change, patented keyless quick
change system.



red dot
design award
winner 2007

| | 650 Watt Hedge Trimmer HS 8655 Quick | 650 Watt Hedge Trimmer HS 8665 Quick | 650 Watt Hedge Trimmer HS 8675 Quick |
|---|---|---|---|
| Comparative device characteristics | | | |
| Cutting strength | 26 mm | 26 mm | 26 mm |
| Cutting length | 460 mm | 560 mm | 660 mm |
| Blade clearance | 26 mm | 26 mm | 26 mm |
| Number of cuts at no load | 3.000 /min | 3.000 /min | 3.000 /min |
| Rated input power | 650 W | 650 W | 650 W |
| Weight (without mains cable) | 4,2 kg | 4,4 kg | 4,6 kg |
| Standard equipment | Trigger guard, container | Trigger guard, container | Trigger guard, container |
| Type | HS 8655 Quick | HS 8665 Quick | HS 8675 Quick |
| Order no. | 6.08655 | 6.08665 | 6.08675 |

Hedge trimming blade

- For quick replacement of blunt blades with sharp blades
- For trimming hedges with different blade lengths: large surfaces with long cutter bars; filigree profile cuts with short cutter bars
- All cutter bars fit on all hedge trimmers with "Quick" blade change

| | | Blade length mm | Order no. |
|--|-----|--------------------|--------------|
| | NEW | 450 | 6.24575 |
| | NEW | 550 | 6.24576 |
| | NEW | 650 | 6.24577 |
| | NEW | 750 | 6.24578 |

SAWS

SPECIAL-PURPOSE
MACHINESSYSTEMATIC
ORGANISATION

GARDEN

WOOD-PROCESSING
TECHNOLOGYWATER-/PUMP
TECHNOLOGYWELDING
TECHNOLOGYCOMPRESSED
AIR SYSTEMS






COMMON FEATURES

- Unique safety by the patented Metabo wrap spring chain brake (stop in 0.1 sec.)
- Saw chain with safety driving links
- Sturdy motor with high capacity reserve
- Break-proof housing made of reinforced fibre glass and heat-resistant polyamide
- Large hand guard
- Switch with safety lock lock to protect against unintentional start of the chain saw
- Bracing with support star
- Automatic chain lubrication
- Solid interchangeable stop clutch
- Chain catch pin in case the chain breaks
- Large surface for safe operation
- Easy chain change
- Auto-stop carbon brushes
- Combo-spanner in spanner case



Kt 1441

| | 1400 Watt Chain Saw Kt 1441 |
|---|---|
| Comparative device characteristics | |
| Torque | 10 Nm |
| Cutting length | 400 mm |
| Rated input power | 1.400 W |
| Output power | 800 W |
| Saw chain | |
| - Division | 9,35 mm |
| - Cutter shape | Low profile, Semi-chisel |
| - Thickness of drive links | 1,3 mm |
| - Number of drive links | 57 |
| No load chain speed | 10 m/s |
| Oil delivery rate adjustable | 5 - 10 cm ³ /min |
| Oil container volume | 0,2 l |
| Weight (without mains cable) | 4,2 kg |
| Standard equipment | |
| | Bracing, saw chain, contact safety device, 0.2 l chain saw adhesive oil, cable strain relief strap, combo-spanner |
| Type | Kt 1441 |
| Order no. | 6.01441 |

| Accessories | | Order no. |
|--|--|-----------|
|  | saw chain For Kt 1440 A; division: 3/8"; drive links; (as spare) | 6.31670 |
|  | Precision guide rail (as spare) | 6.31671 |
|  | Saw chain sharpening kit Consisting of file holder with Ø 4-mm round file (6.31438), flat file, depth gauge and brace cleaner | 6.31437 |
| | File holder with file File holder with Ø 4-mm round file (spare) | 6.31439 |
|  | Chain saw adhesive oil 1 litre, bio-degradable | 6.31433 |
| | 5 litre, bio-degradable | 6.31434 |
|  | Universal saw horse <ul style="list-style-type: none"> ▪ Stable construction made from galvanized, chromed steel ▪ Suitable for sawing with electric and motor chain saws. The machines can be attached on the right or left side of the saw horse. ▪ Safe working conditions - thanks to the restricted guidance of the chain-saw ▪ The distance between the saw's bracing and the wood to be sawn can be adjusted to suit the wood's thickness ▪ Suitable for cutting through logs up to 300 mm in diameter ▪ Adjustable length guide Working height: 75 cm Dimensions (folded): 87x82x6 cm Weight: 11 kg | 6.31430 |
|  | Full-view safety goggles <ul style="list-style-type: none"> ▪ Very comfortable full-view safety goggles. UV protection 2-1, coating on the lens: scratch-free on the outside and mist-free on the inside. | 6.31071 |

NEW