

Appendix C

User Manual

(Shall be added by Applicant)

Federal Communications Commission (FCC) Statement

This equipment (Trade name: EyeStar U2S, Model name: USC-1) has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Note:

Shielded interface cable with ferrite core installed on EyeStar U2S connector end must be used with this equipment.

Trade Name

Model Name

EyeStar U2S PC Camera (EyeStar 2 USB version)

USC-1

Caution

To assure continued FCC compliance:

- Any changes or modifications not approved by the guarantee of this device could void the user's authority to operate the equipment.
- The user must use shielded interface cable.
- FCC Label Compliance Statement:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Specification

Product	EyeStar U2S
Model number	USC-1
Type	Digital video camera
Hardware Interface	USB
Resolution	4CIF (704 X 576) VGA (640 X 480) CIF (352 X 288) SIF (320 X 240) QCIF (176 X 144) QSIF (160 X 120) SQIF (128 X 96)
Color Support	24 bit RGB 16 bit RGB
Speed of Scanning	30 frame/sec (QCIF) Maximum 15 frame/sec (CIF)
Optical view angle	56 degrees
Mechanical view angle	Vertical : 62 degrees