Magellan iCradle Instruction Booklet



BlueTooth® RESET on back

WARNING: Always press the unlock button whenever adjusting the retaining arm.

INSTALLATION

Please do not place your iPhone into the cradle until instructed to do so.

Assembly. Assemble the cradle as shown. Do not tighten the retaining ring.



Press the unlock button and raise the retaining arm all the way to the top.



Insert your iPhone into the cradle.



Slide your iPhone into the connector on the bottom of the cradle and then gently push your iPhone towards the cradle.

Press the unlock button and push down on the retaining arm to lock your iPhone in place.

Check for a gap between your iPhone and the cradle.



If there is a gap, you can slide the adjustment switch on the back to push out the adjustment block so that it rests against the back of your iPhone. (Please note, that if there is still a gap you will need to remove your iPhone. Then pull out the adjustment block, rotate it 180° and place it back in the cradle. This will increase the thickness of the adjustment block, providing for a snug fit.)

Mount the cradle in your vehicle.

Before mounting the cradle you should remove your iPhone by pressing the unlock button and raising the retaining arm.

When mounting the cradle in your vehicle please keep these important guidelines in mind...

- Check local vehicle laws regarding mounting devices on windshields. In some areas it is illegal to mount any device on your windshield.
- Make sure not to mount the cradle where it could be dislodged should your airbags deploy.
- Likewise, make sure that the power cable would not be dislodges should the airbags deploy.

Clean the area where the cradle will be placed. Dry the area throughly before continuing.

Press the cradle base firmly against the windshield or dash surface.

Push the suction cup arm down, locking the cradle to the surface.

Apply Power

Connect the USB end of the power cable to the cradle as shown. Connect the other end of the cable to a vehicle power receptacle.



Reinstall your iPhone into the cradle and adjust for proper viewing.

When making viewing adjustments **always** hold the assembly by the cradle and not your iPhone.

Make any final adjustments for proper viewing to the cradle and tighten the cradle retaining ring.

Set the cradle in landscape or portrait view

