## MONTANA WOODWORKS, INC.

## Assembly Instructions for Double Pedestal Table

Thank you very much for purchasing our heirloom quality double pedestal table. Should you have any questions or need to contact sales or support, please do not hesitate to contact our corporate offices at 888.889.3728 or via E-Mail at: <u>cs@montanawoodworks.com</u>

Before beginning assembly please take a few moments to read the instructions carefully, understanding each step. Likewise please also ensure that the hardware package contains the items as described here. Note: a ratcheting wrench can be a considerable timesaver during the assembly process.

Tools Needed: ½ " Wrench, Phillips Screw Driver

Parts List: (2) Pedestal Posts (4) Wooden Legs (4) Top Braces (1) Table Top

2 ¼" x 2 ¼" Top Cross Piece (1) 2 ¼" x 4 ¾ " Bottom Cross Piece

(3) 16 ½" Spindles

Hardware List: (22) 5/16" Course Thread Nuts (22) 5/16" Flat Washers

(4) Leg Levelers (8) 3" Wood Screws (Phillips)

STEPS: 1. Place pedestal posts upright on the floor. (Hole locations are the same. Either end up works.)

- 2. Attach 2 wooden legs to each post using 5/16" washers and nuts.
- 3. Screw Leg Levelers in each leg. Ensure they are completely seated.
- 4. Build center assembly by inserting the three spindles between top and bottom cross pieces.
- 5. Taking completed center piece assembled in step 4, insert the threaded studs into each pedestal posts being careful not to scratch the posts with exposed studs. Secure studs on top end of pedestal with 5/16" washers and nuts.
- 6. Carefully turn pedestal assembly over by reaching over pedestal assembly, grasping each cross piece and gently turn over so that legs are now resting on the floor.
- 7. Finish fastening center assembly using 5/16" washers and nuts.
- 8. Attach the four top braces to the pedestal posts ensuring they are even with top of pedestals.
- 9. Gently place table top face down on clean and padded surface being very careful not to scratch or dent it. Using technique described in step 6, turn pedestal assembly over carefully placing it onto the table top, aligning top braces with outline drawn on underside of table top.
- 10. Using 3" Phillips head screws, secure the top braces to the table top making certain that the braces are flush against table top.
- You are now ready to turn table over. With the assistance of another person, turn table upright. You may want to place a clean padded surface under the table edge to protect it from damage.
- 12. Adjust the four leg levelers on legs so that table is level and does not wobble.

## PROUDLY MADE IN THE U.S.A.

\*Pine requires a good sealant. We recommend two coats of varnish being applied per manufactures directions. The table may be stained prior to finishing with varnish.

