

- Open the Session Status tab in the Home page of the AP.
NOTE: An example of this page is shown in [Figure 137](#).

The screenshot shows a web browser window titled "Session Status [root] - Microsoft Internet Explorer". The browser's address bar is empty. The page has a navigation menu on the left with links: Home, Configuration, Statistics, Tools, Account, Quick Start, Copyright, and Logout. Below the menu, it says "Account: root" and "Level: ADMINISTRATOR". The main content area has tabs for "General Status", "Session Status", "Remote Subscribers", "Event Log", and "Network Interface". The "Session Status" tab is selected, displaying the title "Home ==> Session Status" and the text "2.4GHz - Access Point - 0a-00-3e-20-a5-36". Below this is a "Session Status List" section containing four entries, each starting with a LUID and MAC address, followed by detailed session information:

```

LUID: 002 : MAC: 0a-00-3e-20-00-32 State: IN SESSION (Encrypt Active)
Site Name : SM 10.40.14.121
Software Version : CANOPY 8.0 (Build 19) Mar 17 2006 16:46:09
Software Boot Version : CANOPYBOOT 3.0
FPGA Version : 071305 (DES Sched) P8
Session Timeout : 0, AirDelay 6 (approximately 0.06 miles (294 feet))
Session Count : 1, Reg Count 1, Re-Reg Count 0
RSSI (Avg/Last): 2059/2062 Jitter (Avg/Last): 2/2 Power Level (Avg/Last): -37/-37
Sustained Uplink Data Rate (APCAP): 3500 (kbit)
Uplink Burst Allocation (APCAP): 500000 (kbit)
Sustained Downlink Data Rate (APCAP): 3500 (kbit)
Downlink Burst Allocation (APCAP): 500000 (kbit)
Low Priority Uplink CIR (D): 0 (kbps) Low Priority Downlink CIR (D): 0 (kbps)
Rate : VC 18 Rate 1X1X

LUID: 003 : MAC: 0a-00-3e-20-a6-6f(Lite SM) State: IN SESSION (Encrypt Active)
Site Name : SM 10.40.14.147
Software Version : CANOPY 8.0 (Build 19) Mar 17 2006 16:46:09
Software Boot Version : CANOPYBOOT 3.0
FPGA Version : 022706 (DES Sched) P9
Session Timeout : 0, AirDelay 3 (approximately 0.03 miles (147 feet))
Session Count : 1, Reg Count 1, Re-Reg Count 0
RSSI (Avg/Last): 2056/2059 Jitter (Avg/Last): 4/2 Power Level (Avg/Last): -37/-37
Sustained Uplink Data Rate (DLCAP): 256 (kbit)
Uplink Burst Allocation (DLCAP): 768 (kbit)
Sustained Downlink Data Rate (DLCAP): 256 (kbit)
Downlink Burst Allocation (DLCAP): 768 (kbit)
Low Priority Uplink CIR (DL): 0 (kbps) Low Priority Downlink CIR (DL): 0 (kbps)
Rate : VC 19 Rate 2X2X

LUID: 004 : MAC: 0a-00-3e-20-a5-48 State: IN SESSION (Encrypt Active)
Site Name : Camera Client
Software Version : CANOPY 8.0 (Build 19) Mar 17 2006 16:46:09
Software Boot Version : CANOPYBOOT 3.0
FPGA Version : 022706 (DES Sched) P9
Session Timeout : 0, AirDelay 4 (approximately 0.04 miles (196 feet))
Session Count : 1, Reg Count 1, Re-Reg Count 0
RSSI (Avg/Last): 2059/2066 Jitter (Avg/Last): 5/7 Power Level (Avg/Last): -37/-37
Sustained Uplink Data Rate (APCAP): 20000 (kbit)
Uplink Burst Allocation (APCAP): 500000 (kbit)
Sustained Downlink Data Rate (APCAP): 20000 (kbit)
Downlink Burst Allocation (APCAP): 500000 (kbit)
Low Priority Uplink CIR (D): 0 (kbps) Low Priority Downlink CIR (D): 0 (kbps)
Rate : VC 20 Rate 2X2X

LUID: 005 : MAC: 0a-00-3e-20-00-2a State: IN SESSION (Encrypt Active)
Site Name : SM 10.40.14.103
Software Version : CANOPY 8.0 (Build 19) Mar 17 2006 16:46:09
Software Boot Version : CANOPYBOOT 3.0
FPGA Version : 071305 (DES Sched) P8
Session Timeout : 0, AirDelay 5 (approximately 0.05 miles (245 feet))
Session Count : 2, Reg Count 1, Re-Reg Count 1
RSSI (Avg/Last): 2059/2068 Jitter (Avg/Last): 2/2 Power Level (Avg/Last): -37/-37
Sustained Uplink Data Rate (APCAP): 3500 (kbit)
Uplink Burst Allocation (APCAP): 500000 (kbit)
Sustained Downlink Data Rate (APCAP): 3500 (kbit)
Downlink Burst Allocation (APCAP): 500000 (kbit)
Low Priority Uplink CIR (D): 0 (kbps) Low Priority Downlink CIR (D): 0 (kbps)
Rate : VC 21 Rate 1X1X

```

The browser's status bar at the bottom shows "Logged in as: root" and "Internet".

Figure 137: AP/SM link status indications in the AP Session Status tab

- Find the Session Count line under the MAC address of the SM.