


## B85M-E33 V2 (MS-7846v2.0) m-ATX Motherboard

Support Intel® Haswell processors for LGA 1150 socket





## **Motherboard Specification**

## **Processor Support** Connectors ■ Support Intel® Haswell processors for LGA 1150 socket ■ Back panel - 1 PS/2 mouse / keyboard port Base Clock - 4 USB 2.0 ports ■ 100 MHz - 2 USB 3.0 ports - 1 VGA port Chipset - 1 HDMİ port ■ Intel® B85 chipset 1 LAN port 3 flexible audio ports **Memory Support** On-Board - 1 USB 3.0 connector Support 2 DDR3 DIMMs1066/ 1333/ 1600 MHz up to 32GB max ■ Supports Dual-Channel mode - 2 USB 2.0 connectors - 1 Chassis Intrusion connector - 1 Front Panel Audio connector ■ Supports LAN 10/100/1000 Fast Ethernet by Realtek® RTL8111G - 1 TPM Module connector - 1 Serial connector ■ Chip integrated by Realtek® ALC887 ■ 1 PCIE x16 slot ■ Flexible 8-channel audio with jack sensing ■ 2 PCIE x1 slots ■ Compliant with Azalia 1.0 Spec Form Factor ■ 2 SATA 3Gb/s (SATA1~SATA2) ports by Intel® B85 ■ m-ATX (228 x 226 mm) ■ 2 SATA 6Gb/s (SATA3~SATA4) ports by Intel® B85 Feature on Focus ■ All Solid Cap design ■ 4 USB 3.0 ports by Intel® B85 ■ Click BIOS IV ■ M-Flash ■ Small Business Advantage ■ SATA 6Gb/s ■ USB 3 0 Mounting ■ 6 mounting holes

These specification is subject to change without prior notice.