

LBEE6ZZ1KD Installation Manual



FCC ID of this product is as follows.

FCC ID:VPYLB1KD

For OEM integration only – device cannot be sold to general public.
Therefore we will ask OEM to include the following statements required by FCC on the product and in the Installation manual Notice.

Contents

- 1. Supply Voltage
- 2. Theory of operation
- 3. Antenna
- 4. Notice

1. Supply Voltage

		min.	typ.	max.	unit
Specification Temperature Range		-40	+25	+85	deg.C
Specification Voltage	VDD	3.2	3.6	4.5	V
	VIO	1.62	1.8or3.3	3.63	V

2. Theory of Operation



Frequency of operation			Scan	Ad-hoc mode
2.4GHz	11b/g/n (HT20)	2412-2462MHz	Active	Yes
W52	11a/n (HT20) , 11ac(VHT20)	5180-5240MHz	Active	Yes
	11n (HT40) , 11ac(VHT40)	5190-5230MHz	Active	Yes
	11ac(VHT80)	5210MHz	Active	Yes
W53	11a/n (HT20) , 11ac(VHT20)	5260-5320MHz	Passive	No
	11n (HT40) , 11ac(VHT40)	5270-5310MHz	Passive	No
	11ac(VHT80)	5290MHz	Passive	No
W56	11a/n (HT20) , 11ac(VHT20)	5500-5720MHz	Passive	No
	11n (HT40) , 11ac(VHT40)	5510-5710MHz	Passive	No
	11ac(VHT80)	5530-5690MHz	Passive	No
W58	11a/n (HT20) , 11ac(VHT20)	5745-5825MHz	Active	Yes
	11n (HT40) , 11ac(VHT40)	5755-5795MHz	Active	Yes
	11ac(VHT80)	5775MHz	Active	Yes

Compliance with FCC requirement 15.407(c)
 Data transmission is always initiated by software, which is the passed down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets are initiated by the MAC. These are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets is being transmitted. In other words, this device automatically discontinue transmission in case of either absence of information to transmit or operational failure.

Frequency Tolerance: ± 20ppm

End users can not modify the software because F/W & driver are installed in device.



3. Antenna

■ Please perform the antenna design that followed the specifications of the antenna.

The concrete contents of a check are the following three points.

- 1) It is the same type as the antenna type of antenna specifications.
- 2) An antenna gain is lower than a gain given in antenna specifications.
- 3) The emission level is not getting worse.

	Antenna
Antenna type	2.4GHz Dipole Antenna 5GHz Dipole Antenna



4. Notice

For OEM integration only – device cannot be sold to general public.
Therefore we will ask OEM to include the following statements required by FCC/IC on the product and in the Installation manual Notice.
Please describe the following warning on the final product which contains this module.

Contains Transmitter Module FCC ID:VPYLB1KD

or

Contains FCC ID:VPYLB1KD

● Please describe the following warning to the manual.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC CAUTION
Changes or modifications not expressly approved by the party responsible for compliance could void the user’s authority to operate the equipment.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

※When the product is small, as for these words mentioned above, the posting to a manual is possible.

4. Notice

- When installing it in a mobile equipment. Please describe the following warning to the manual.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment and meets the FCC radio frequency (RF) Exposure Guidelines. This equipment should be installed and operated keeping the radiator at least 20cm or more away from person's body.

RF Exposure requirements are met when installed in mobile equipment.

This module cannot be installed in portable equipment without further testing and a change to FCC's grant of authorization.

Contact Murata regarding portable applications.

Note)

Portable equipment : Equipment for which the spaces between human body and antenna are used within 20cm.

Mobile equipment : Equipment used at position in which the spaces between human body and antenna exceeded 20cm.

4. Notice

This device is intended only for OEM integrators under the following conditions:

- 1)The antenna must be installed such that 20 cm is maintained between the antenna and users, and
- 2)The transmitter module may not be co-located with any other transmitter or antenna.
- 3)The use of an antenna with gain less than 2.37dBi (2.4GHz) and 2.93dBi (5GHz).

As long as 3 conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed

IMPORTANT NOTE: In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

End Product Labeling
This transmitter module is authorized only for use in device where the antenna may be installed such that 20 cm may be maintained between the antenna and users. The final end product must be labeled in a visible area with the following: "Contains FCC ID:VPYLB1KD". The grantee's FCC ID can be used only when all FCC compliance requirements are met.

Manual Information To the End User
The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.
The end user manual shall include all required regulatory information/warning as show in this manual.