MBM Triumph 4215 Semi-Automatic Cutter

Instruction Manual





→ 4215 SEMI-AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | patented, lever-activated, fast-action clamp | precision side guide | spindle-guided back gauge with calibrated crank | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | optional stand (shown) or cabinet

Dimensions (D x W x H): 27 % x 25 % x 14 % inches (41 % H with stand, 42 % H with cabinet), Shipping weight: 191 lbs. (217 with stand, 278 with cabinet).



FRONT SAFETY GUARD



The hinged, transparent front safety guard is electronically controlled.

DIGITAL DISPLAY



A digital measurement readout ensures exact positioning of back gauge.

FRONT BLADE CHANGE



The blade changing device covers edge of blade for safe handling.

→ TRIUMPH 4215

1 7 111101111 11 4210	
Cutting width	16 %
Cutting height	1 1/2"
Narrow cut	1 3/8"
Cutting length behind blade	15 1/16
Table length in front of blade	9''
Motor	3/5 h

Motor 3/5 hp
Power supply 115 V, 60 Hz

Dealer:



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com

