



Technical problems or questions: http://support.hidglobal.com Latest drivers and manuals: http://www.hidglobal.com/omnikey

OMNIKEY 5321 V2
OMNIKEY 5321 PAY
OMNIKEY 5321 CL SAM
OMNIKEY 5321 CLi V2
OMNIKEY 5321 CR V2

© 2009 HID Global Corporation - All rights reserved.











OMNIKEY® 5321 Smart Card Reader

This guide describes physical behaviour and conformities of the OMNIKEY® 5321 Family:

OMNIKEY 5321 V2: combined contactless and continues of the OMNIKE v9 5321 Pai
OMNIKEY 5321 PAY: Mastercard paypass® certified contactless smart card reader
OMNIKEY 5321 CL SAM: contactless smart card reader with built in SIM card holder
OMINKEY 5321 CL IV2: contactless smart card reader for HID iClass cards
OMNIKEY 5321 CR V2: IP67 conform contactless smart card reader

To install the OMNIKEY® 5321 follow the steps described. For further information, contact HID support: http://support.hidglobal.com/

Content

- Smart Card Reader
- Installation Guide

Find drivers and additional manuals for this reader and various operating systems at http://www.hidglobal.com/omnikey.

Overview

The OMNIKEY® 5321 is a PC-linked reader that reads 13.56 MHz (RFID) contactless smart cards. Depending on model this reader is also equipped with a contact interface, which reads/writes to virtually any contact smart card.

The OMNIKEY 5321 is a USB plug-and-play device. To connect the reader with your computer, plug the USB connector into your computers USB port.

When the reader is working, the LED on the right illuminates green. Consult the OMNIKEY User Guide for driver setup, if the reader is not working.

For contactless operation, hold the card next to the logo on the reader. For contact smart cards, insert the card with contacts facing up into the reader.

When the reader is exchanging data with a card (reading or writing) the LED on the right will blink red.

Specifications

Dimensions	Approx. 80 x 67 x 28 mm / 3.15" x 2,64" x 1,1"
Weight (incl. standing base)	Approx. 200gr / 7.1 ounces
Operating Temperature	0°-55°C / 32°-131°F
PC Connector Cable	180 cm / 70.9"
Meantime between Failure (MTBF)	500,000 Hours
Host Interface	USB 2.0 CCID (also supports USB 1.1)
Host Data Transmission Speed	12 Mbps (USB 2.0 Full Speed)
Power Supply	Bus powered

[.] IP67 = Dust tight, and protected against temporary immersion in water per IEC 60529 can vary depending on model









Conformance Information

CE Marking


The shipped version of this device complies with the requirements of the directives 2004/108/EC, 2006/95/EC and 1999/5/EC.



Declaration of Conformity (FCC ID SIYOK5321)

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions:





may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide

digital device, pursuant to Part 15 of the PCC Rules. These limits are designed to provi reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
 -- Connect the equipment into an outlet on a circuit different from that to which the receiver
- is connected.

 -- Consult the dealer or an experienced radio/TV technician for help.

Declaration of Conformity (5345A-OK5321)

This device complies with Industry Canada Radio Standards Specifications RSS-Gen Issue 2, Section 7.2.2 and RSS-210 Issue 7, Section 2.2, 2.6 (Category I Equipment). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device. This Class B digital apparatus complies with Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.













Manufacturer: Address:

OMNIKEY GmbH Am Klingenweg 6a 605396 Walluf GERMANY

OMNIKEY 5321 V2 OMNIKEY 5321 PAY OMNIKEY 5321 CLI V2 OMNIKEY 5321 CL SAM OMNIKEY 5321 CR V2

Directive of European Parliament and of the council on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity.

Conformity of the directives is assured through the application of the following standards:

Reference Number	Editio
EN 300330-2	V1.3.
EN 300330-1	V1.3.
ETSI EN 301489-1	V1.8.
ETSI EN 301489-3	V1.4.
EN 50364	2001
EN 60950-1	2006

This declaration certifies the conformity of the specified standards but contains no assurance of properties.

© 2009 HID Global Corporation - All rights reserved.





4