

# C-5000 ZOOM 5 megapixel CCD. Cool & compact. Intelligently designed.

**Designed-to-be-Digital** Combine a 5 megapixel CCD with our designed-to-be-digital lens for 3x optical/12x total seamless zoom capability. Print the most realistic digital images yet, up to 11" x 14".

Flexibility & Control Take your best shot with four exposure control modes, six scene program modes and one customizable MyMode preset. Connect up to 10 images into a single panoramic image.

Flash Options Extend the built-in flash range with the dedicated hot shoe for an external flash. Or, sync to a studio strobe.

**Auto-Connect USB Connect automatically** to nearly any computer with a USB port and download your images. **No software required** with most operating systems.

**Automatic Noise Reduction** Minimize that grainy-look and capture bright, vivid colors day or night by reducing random digital noise.

**QuickTime® Movies** Travel light and carry an exciting alternative to still images. Shoot 2-minute movies and e-mail to your friends.

**TruePic™ Technology** Produce smoother and clearer **color-accurate photos**, especially at lower resolutions.



#### **Package Contents**

CAMEDIA C-5000 Zoom Digital Camera, 32MB xD-Picture Card, LI-10B Li-Ion Battery and Charger, RM-2 Wireless Remote Control, Digital Camera Win/Mac USB Cable, Video Cable, Carrying Strap, Quick Start Guide, Printed Instruction Manual, CD-ROM:CAMEDIA Master Software, Windows 98 Rev 2 Driver, Camera Reference Manual, Warranty Card

#### System Requirements (for camera Auto-Connect USB)

Supported on USB-equipped Windows 2000 Pro, ME and XP computers. Windows 98 Rev 2 requires provided driver\* to be loaded for support. Macintosh requirements include Power Macintosh with built-in USB port and OS 8.6 - OS X 10.2. Mac OS 8.6 requires mass-storage driver 1.3.5 available at apple.com.

Downloading to computer without USB port possible with optional card readers.

## (for included CAMEDIA Master software)

System Requirements Windows® IBM PC/AT, Pentium or greater, Windows 98 second edition/ ME/2000 Pro, CD-ROM compatible drive, 64 MB RAM or greater, 120 MB minimum available HD space, USB port, Monitor with thousands of colors (millions of colors recommended).

> Macintosh® USB iMac, G3, G4 or greater, OS 8.6 - OS X 10.2, CD-ROM drive, 64 MB RAM or greater, 120 MB minimum available HD space, USB port, Monitor with thousands of colors (millions of colors recommended).

Check the Olympus website for updated information on system requirements for software and support.

\*Software driver supplied on enclosed CD.

### Memory Card Storage Capacity

	0 1 7		
Quality	Pixel Resolution	32MB xD-Picture Card (included)	128MB xD-Picture Card
TIFF	2560x1920 to 640x480	2, 33 shots	8, 135 shots
TIFF, SHQ, HQ	2560x1920	2, 8, 26 shots	8, 35, 106 shots
SQ1(High, Normal)	2048x1536, 1600x1200	13 - 66 shots	55 - 266 shots
SQ2(High, Normal)	1280x1960, 1024x768, 640x480	35 - 398 shots	142 - 1596 shots
HQ	320x240 15fps movie	32 sec. max per movie	32 sec. max per movie
SQ	160x120 15fps movie	140 sec. max per movie	140 sec. max per movie

All capacity figures are approximate.

A 5 megapixel CCD. Cool & compact. All the features, control and flexibility you want. Visit our website to see the amazing results.

olympusamerica.com/c-5000



©2003 Olympus America Inc. Olympus is a registered trademark of Olympus Optical Co., Ltd. (as of October 1, 2003 to be known as Olympus Corporation). All other trademarks and registered trademarks listed herein are the property of their respective holders. Specifications subject to change without notice. D1116-0803