

RF-MODULE
(Type: 444-59005)

User's Manual

Ver. 1.1

OLYMPUS CORPORATION

This manual describes the use, the functions and the performance of the Radio Frequency Identification System RF-MODULE. The system is so manufactured that it can not be repaired or replaced by the user; and therefore, if there are such needs, please contact Olympus Corporation or its agent. No service work should be started before the service person has read this manual.

Features:

This product uses radio frequency of 13.56 MHz to communicate with the tags; thus, it should conform to any relative laws and regulations of the country or the region. Authorization of the module or the printer into which the module is installed may be required in some countries or regions.

Cautions:

1. Use or store this product on the temperature and humidity conditions mentioned below, so as to maintain its operational reliability.
2. Use or store this product in an environment free of explosive gases, inflammable gases, corrosive gases, oils, organic solvents, dust, salt and metal powders.
3. Keep this product free of direct shock, strong vibration or sunshine.
4. To communicate with the tags, this product uses 13.56 MHz radio frequency, which may be interfered by radio waves (noises) emitted from a transceiver, a motor, a monitor, a power supply (including a power supply IC), etc. Please make sure that such interferences will not occur before using the product in a place near to these devices.
5. Take proper measures to avoid any possible electrostatic discharge to the product, which may damage the product.
6. After doing the wiring, make sure the connectors are fastened properly.

Warning:

Do not alter any part of the product.

Alteration of the printed wiring board, the antennas or the connecting cables of the module may damage the control board of the printer, and is an illegal act if it causes the modular transmitter emissions out of the limits provided by laws or regulations.

Specifications:

Dimensions	Less than 60 x 70 x 14.2 mm
Transmitting Frequency	13.56 MHz
Transmission field strength	Less than 500 μ V/m at 3m
Operating Temperature	0 to +50 deg.C
Storage Temperature	-20 to +60 deg.C
Operating Humidity	25 to 85% RH (Without condensation)
Supply voltage	5 V dc +/- 10%

Discarding the Product:

The product should be discarded as normal printed wiring boards. If you do not know how such boards should be discarded, ask Olympus Corporation , its agent or the government.

Notice about the law and the standard:

FCC ID: WK3RFAAA00

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Canada IC: 4763B-RFAAA00

Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

The user is cautioned that unauthorized changes or modifications not approved could void the user's authority to operate the equipment.