Panasonic

Operating Instructions

Cordless Telephone with Digital Answering Machine

Model No. KX-TGL430

KX-TGL432

KX-TGL433

KX-TG3683



Model shown is KX-TGL430.

Before initial use, see "Getting Started" on page 9.

Thank you for purchasing a Panasonic product.

Please read these operating instructions before using the unit and save them for future reference.

Consulte "Guía Rápida Española", página 54.

For assistance, visit our Web site: http://shop.panasonic.com/support for customers in the U.S.A.

Please register your product: http://shop.panasonic.com/support

Table of Contents

Introduction Model composition 3 Accessory information 3
Important Information For your safety .5 Important safety instructions .6 For best performance .6 Other information .7 Specifications .8
Getting Started Setting up 9 Controls 11 Display icons 12 Language settings 12 Date and time 13 Recording your greeting message 13 Other settings 13
Making/Answering Calls Making calls 14 Redialing 14 Answering calls 15 Useful features during a call 15 Intercom 17
Call Block Call block feature 18 Storing unwanted callers 18
PhonebookPhonebook20Speed dial22
Programming Menu list 23 Alarm 29 Silent mode 29 Baby monitor 30 Other programming 32 Registering a unit 32
Caller ID ServiceUsing Caller ID service
Answering System Answering system35

Turning the answering system on/off Greeting message	35
Listening to messagesAdvanced new message alerting features	
Remote operation	38
Useful Information	
Voicemail service	
Wall mounting	
Error messages	
Troubleshooting FCC and other information	
Guía Rápida Española	
Guía Rápida Española	54
Appendix	
Customer services Limited Warranty (ONLY FOR U.S.A.)	
Index	
Index	62

Model composition

Series	Model No.	Base unit	Handset	
Series	Woder No.	Part No.	Part No.	Quantity
KX-TGL430	KX-TGL430	KX-TGL430	KX-TGLA40	1
series	KX-TGL432	KX-TGL430	KX-TGLA40	2
	KX-TGL433	KX-TGL430	KX-TGLA40	3
	KX-TG3683	KX-TGL430	KX-TGLA40	3

Accessory information

Supplied accessories

		Quantity		
No.	Accessory item/Part number	KX-TGL430	KX-TGL432	KX-TGL433 KX-TG3683
1	AC adaptor/PNLV226-0X	1	1	1
2	Telephone line cord*1	1	1	1
3	Wall mounting adaptor/PNKL1061Z2	1	1	1
4	Rechargeable batteries*2	2	4	6
(5)	Handset cover*3/PNYNTGLA40BR	1	2	3
6	Charger/PNLC1070YB	-	1	2

- *1 PQJA10075Y (Black cord), PQJA10075Z (Transparent cord)
- *2 See page 4 for replacement battery information.
- *3 The handset cover comes attached to the handset.



















Introduction

Additional/replacement accessories

Please contact your nearest Panasonic dealer for sales information (page 59).


Accessory item	Model number/Specifications
Rechargeable batteries	HHR-4DPA*1 • To order, please visit http://shop.panasonic.com/support
	Battery type: - Nickel metal hydride (Ni-MH) - 2 x AAA (R03) size for each handset
Range extender	KX-TGA405*2
Key detector	KX-TGA20*3

- *1 Replacement batteries may have a different capacity from that of the supplied batteries.
- *2 By installing this unit, you can extend the range of your phone system to include areas where reception was previously not available. This product can be purchased online. Please visit our Web site: http://shop.panasonic.com/support
- *3 By registering the key detector (4 max.) to a Panasonic Digital Cordless Phone and attaching it to an easy-to-lose item in advance, you can locate and find the mislaid item to which the key detector is attached. Please visit our Web site: http://www.panasonic.com/tga20

Other information

- Design and specifications are subject to change without notice.
- The illustrations in these instructions may vary slightly from the actual product.

Expanding your phone system



For assistance, please visit http://shop.panasonic.com/support

For your safety

To prevent severe injury and loss of life/ property, read this section carefully before using the product to ensure proper and safe operation of your product.

MARNING

Power connection

- Use only the power source marked on the product.
- Do not overload power outlets and extension cords. This can result in the risk of fire or electric shock.
- Completely insert the AC adaptor/power plug into the power outlet. Failure to do so may cause electric shock and/or excessive heat resulting in a fire.
- Regularly remove any dust, etc. from the AC adaptor/power plug by pulling it from the power outlet, then wiping with a dry cloth. Accumulated dust may cause an insulation defect from moisture, etc. resulting in a fire.
- Unplug the product from power outlets if it emits smoke, an abnormal smell, or makes an unusual noise. These conditions can cause fire or electric shock. Confirm that smoke has stopped emitting and contact us at http://shop.panasonic.com/support
- Unplug from power outlets and never touch the inside of the product if its casing has been broken open.
- Never touch the plug with wet hands.
 Danger of electric shock exists.

Installation

- To prevent the risk of fire or electrical shock, do not expose the product to rain or any type of moisture.
- Do not place or use this product near automatically controlled devices such as automatic doors and fire alarms. Radio waves emitted from this product may cause such devices to malfunction resulting in an accident.

 Do not allow the AC adaptor or telephone line cord to be excessively pulled, bent or placed under heavy objects.

Operating safeguards

- Unplug the product from power outlets before cleaning. Do not use liquid or aerosol cleaners.
- Do not disassemble the product.
- Do not spill liquids (detergents, cleansers, etc.) onto the telephone line cord plug, or allow it to become wet at all. This may cause a fire. If the telephone line cord plug becomes wet, immediately pull it from the telephone wall jack, and do not use.

Medical

- Consult the manufacturer of any personal medical devices, such as pacemakers or hearing aids, to determine if they are adequately shielded from external RF (radio frequency) energy. (The product operates in the frequency range of 1.92 GHz to 1.93 GHz, and the RF transmission power is 115 mW (max.).)
- Do not use the product in health care facilities if any regulations posted in the area instruct you not to do so. Hospitals or health care facilities may be using equipment that could be sensitive to external RF energy.

♠ CAUTION

Installation and location

- Never install telephone wiring during an electrical storm.
- Never install telephone line jacks in wet locations unless the jack is specifically designed for wet locations.
- Never touch uninsulated telephone wires or terminals unless the telephone line has been disconnected at the network interface.
- Use caution when installing or modifying telephone lines.
- The AC adaptor is used as the main disconnect device. Ensure that the AC outlet is installed near the product and is easily accessible.

- This product is unable to make calls when:
 the handset batteries need recharging or
 - there is a power failure.

have failed.

Battery

- We recommend using the batteries noted on page 4. USE ONLY rechargeable Ni-MH batteries AAA (R03) size.
- Do not mix old and new batteries.
- Do not open or mutilate the batteries. Released electrolyte from the batteries is corrosive and may cause burns or injury to the eyes or skin. The electrolyte is toxic and may be harmful if swallowed.
- Exercise care when handling the batteries.
 Do not allow conductive materials such as rings, bracelets, or keys to touch the batteries, otherwise a short circuit may cause the batteries and/or the conductive material to overheat and cause burns.
- Charge the batteries provided with or identified for use with this product only, in accordance with the instructions and limitations specified in this manual.
- Only use a compatible base unit (or charger) to charge the batteries. Do not tamper with the base unit (or charger).
 Failure to follow these instructions may cause the batteries to swell or explode.

Attention:



A nickel metal hydride battery that is recyclable powers the product you have purchased.

Please call 1-800-8-BATTERY (1-800-822-8837) for information on how to recycle this battery.

Important safety instructions

When using your product, basic safety precautions should always be followed to reduce the risk of fire, electric shock, and injury to persons, including the following:

- Do not use this product near water for example, near a bathtub, washbowl, kitchen sink, or laundry tub, in a wet basement or near a swimming pool.
- Avoid using a telephone (other than a cordless type) during an electrical storm. There may be a remote risk of electric shock from lightning.
- 3. Do not use the telephone to report a gas leak in the vicinity of the leak.
- Use only the power cord and batteries indicated in this manual. Do not dispose of batteries in a fire. They may explode. Check with local codes for possible special disposal instructions.

SAVE THESE INSTRUCTIONS

For best performance

Base unit location/avoiding noise

The base unit and other compatible Panasonic units use radio waves to communicate with each other.

- For maximum coverage and noise-free communications, place your base unit:
 - at a convenient, high, and central location with no obstructions between the handset and base unit in an indoor environment.
 - away from electronic appliances such as TVs, radios, personal computers, wireless devices, or other phones.
 - facing away from radio frequency transmitters, such as external antennas of mobile phone cell stations. (Avoid putting the base unit on a bay window or near a window.)
- Coverage and voice quality depends on the local environmental conditions.

For assistance, please visit http://shop.panasonic.com/support

 If the reception for a base unit location is not satisfactory, move the base unit to another location for better reception.

Environment

- Keep the product away from electrical noise generating devices, such as fluorescent lamps and motors.
- The product should be kept free from excessive smoke, dust, high temperature, and vibration.
- The product should not be exposed to direct sunlight.
- Do not place heavy objects on top of the product.
- When you leave the product unused for a long period of time, unplug the product from the power outlet.
- The product should be kept away from heat sources such as heaters, kitchen stoves, etc. It should not be placed in rooms where the temperature is less than 0 °C (32 °F) or greater than 40 °C (104 °F). Damp basements should also be avoided.
- The maximum calling distance may be shortened when the product is used in the following places: Near obstacles such as hills, tunnels, underground, near metal objects such as wire fences, etc.
- Operating the product near electrical appliances may cause interference. Move away from the electrical appliances.

Routine care

- Wipe the outer surface of the product with a soft moist cloth.
- Do not use benzine, thinner, or any abrasive powder.

Other information

CAUTION: Risk of explosion if battery is replaced by an incorrect type. Dispose of used batteries according to the instructions.

Notice for product disposal, transfer, or return

 This product can store your private/ confidential information. To protect your privacy/confidentiality, we recommend that you erase information such as phonebook or caller list entries from the memory before you dispose of, transfer, or return the product.

Notice

- This product is designed for use in the United States of America. Sale or use of this product in other countries may violate local laws.
- Cet appareil est conçu pour être utilisé aux États-Unis d'Amérique. La vente ou l'emploi de cet appareil dans certains autres pays peut constituer une infraction à la législation locale.
- Este producto está diseñado para usarse en los Estados Unidos de América.
 La venta o el empleo de este producto en ciertos países puede constituir violación de la legislación local.
- ◆本產品專為美國使用而設。若在其他國家銷售或使用,可能會違反當地法例。
- ●この製品は、日本国外での使用を目的として設計されており、日本国内での使用は 法律違反となります。従って、当社では日本国内においては原則として修理などの サービスは致しかねます。

Specifications

• Standard:

DECT 6.0 (Digital Enhanced Cordless Telecommunications 6.0)

- Frequency range: 1.92 GHz to 1.93 GHz
- RF transmission power:

115 mW (max.)

- Power source:
 120 V AC, 60 Hz
- Power consumption:

Base unit:

Standby: Approx. 0.9 W Maximum: Approx. 3.8 W **Charger:**

Standby: Approx. 0.1 W Maximum: Approx. 1.8 W

Operating conditions:
 0 °C - 40 °C (32 °F - 104 °F), 20 % - 80 % relative air humidity (dry)

Setting up


Connections

■ Base unit

- ① Connect the AC adaptor to the unit by pressing the plug firmly.
- 2 Fasten the cord by hooking it.
- ③ Connect the AC adaptor to the power outlet.
- ④ Connect the telephone line cord to the unit, then to the single-line telephone jack (RJ11C) until you hear a click.
- (5) A DSL/ADSL filter (not supplied) is required if you have a DSL/ADSL service.

Note:

 Use only the supplied Panasonic AC adaptor PNLV226.



■ Charger


Connect the AC adaptor to the power outlet.



Battery installation

- USE ONLY rechargeable Ni-MH batteries AAA (R03) size (A).
- Do NOT use alkaline/manganese/Ni-Cd batteries.
- Confirm correct polarities (⊕, ⊖).






 Follow the directions on the display to set up the unit.

Battery charging

Charge for about 7 hours.

- Confirm "Charging" is displayed (A).
- When the batteries are fully charged, "Fully charged" is displayed.



Note when setting up

Note for connections

- The AC adaptor must remain connected at all times. (It is normal for the adaptor to feel warm during use.)
- The AC adaptor should be connected to a vertically oriented or floor-mounted AC outlet. Do not connect the AC adaptor to a ceiling-mounted AC outlet, as the weight of the adaptor may cause it to become disconnected.

During a power failure

The unit cannot be used to make or receive calls during a power failure. We recommend connecting a corded-type telephone that does not use an AC adaptor to your telephone line.

Note for battery installation

 Use the supplied rechargeable batteries.
 For replacement, we recommend using the Panasonic rechargeable batteries noted on page 4, 6.

Note for battery charging

 It is normal for the handset to feel warm during charging. Clean the charge contacts of the handset, base unit, and charger with a soft and dry cloth once a month. Before cleaning the unit, disconnect from power outlets and any telephone line cords. Clean more often if the unit is exposed to grease, dust, or high humidity.

Battery level

Icon	Battery level
	High
Ē	Medium
	Low
` \\	Needs charging.
Ō	Empty

Panasonic Ni-MH battery performance (supplied batteries)

Operation	Operating time
In continuous use	12 hours max.*1
Not in use (standby)	8 days max.*1

*1 If eco mode is on.

Note:

 Actual battery performance depends on usage and ambient environment.

Intelligent eco mode


This feature automatically reduces handset power consumption by suppressing handset transmission power when the handset is close to the base unit.

- When this feature is activated, ECO is displayed.
- Eco mode is turned off when the clarity booster is activated (page 16).

For assistance, please visit http://shop.panasonic.com/support

Controls

Handset



- Shoulder rest
- Ø Speaker
- [+]/[-] (VOL.: Volume up/down)
 - [\] (TALK)
 - [♣] (Speakerphone)
- Dial keypad (★: TONE)
- Õ Microphone
- ŏ Receiver
- Õ Display
- Õ [OFF]
- Charge contacts


■ Control type

(A) Soft keys

By pressing a soft key, you can select the feature shown directly above it on the display.

(B) Navigator key

- [A], [▼], [▼], or [►]: Scroll through various lists and items.
- [A] (Mute): Put the call on mute.
- [◄] ☐: View the phonebook entry.
 [▶] (Redial/CID) (Caller ID): View the redial list or caller list.
- 【▼】(Call Block): View the call block list.



- Charge contacts
- Speaker
- ĕ 60 0 [I◄◀] (Repeat) [►►I] (Skip)
- [►■] (PLAY/STOP)

Message indicator

- [+]/[-] (VOL.: Volume up/down)
- (ANSWER ON/OFF)
- ANSWER ON/OFF indicator ()
- (LOCATOR)
 - You can locate a misplaced handset by pressing [LOCATOR].
- ② [ERASE]

Display icons

Handset display items

Item	Meaning	
Ψ	Within base unit range	
¥	Out of base unit range	

Item	Meaning
	The line is in use. When flashing: The call is put on hold. When flashing rapidly: An incoming call is now being received.
ECO	Eco mode is on. (page 10)
NR	Noise reduction is set. (page 16)
EQ	Equalizer is set. (page 16)
母	Speakerphone is on. (page 14)
Ø	Ringer volume is off. (page 25)
Zzz	Silent mode is on. (page 29)
PRIV.	Call sharing mode is off. (page 27)
Ð	Alarm is on. (page 29)
0	Handset number
Ê	Battery level
/→)	Blocked call (page 18)
BOOST	Clarity booster is on. (page 16)
~	Baby monitor is activated. The name/number displayed next to the icon indicates the monitoring unit. (page 30)
In use	Answering system is being used by another handset.
Line in use	Someone is using the line.

Language settings

Display language

- (MENU)#110
- $[\ \ \]$: Select the desired setting. \rightarrow [SAVE] \rightarrow [OFF]

For assistance, please visit http://shop.panasonic.com/support

Voice announcement language

You can select the language used for the following features.

- Answering system guidance
- Talking Caller ID

The default setting is "English".

- 1 (MENU)#1112
- 2 [♣]: Select the desired setting. →
 [SAVE] → [OFF]

Date and time

- 1 [MENU]#101
- Enter the current month, date, and year by selecting 2 digits for each.
 Example: July 12, 2016
 0 7 12 16
- 3 [OK]
- 4 Enter the current hour and minute (12-hour clock format) by selecting 2 digits for each.

Example: 9:30 0 9 3 0

- 5 ★: Select "AM" or "PM".
- 6 [SAVE] \rightarrow [OFF]

Note

 When English is selected as the display language, 12-hour clock format is used.
 When Spanish is selected, 24-hour clock format is used.

Recording your greeting message

You can record your own greeting message instead of using a pre-recorded greeting message. See page 35 for details.

- 1 [MENU]#302
- 2 [♣]: "Yes" → [SELECT]
- 3 Record a greeting message. → [STOP] → [OFF]

Other settings

Dialing mode

If you cannot make calls, change this setting according to your telephone line service. The default setting is "Tone".

"Tone": For tone dial service.

"Pulse": For rotary/pulse dial service.

- 1 (MENU)#120
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

Making/Answering Calls

Making calls

- Lift the handset and then dial the phone number.
 - To correct a digit, press [CLEAR].
- 2 Press [\ /\sigma\) to make the call.
 - To make the call using the speakerphone, press and hold [1
 for a few seconds.
 - While talking, you can switch between the receiver and the speakerphone by pressing [].
- **3** When finished, press **[OFF]** or place the handset on the base unit or charger.

Note:

 In step 1, you can store the dialed phone number to the phonebook by pressing [SAVE].

Adjusting the receiver or speaker volume

Press [+] or [-] repeatedly while talking.

Pause (for PBX/long distance service users)

A pause is sometimes required when making calls using a PBX or long distance service. When storing a calling card access number and/or PIN in the phonebook, a pause is also needed (page 21).

Example: If you need to dial the line access number "9" when making outside calls with a PBX:

- 1 $9 \rightarrow [A]$ (Pause)
- 2 Dial the phone number. \rightarrow [$^{\sim}$ / $\stackrel{\triangleleft}{\sim}$]

Note:

A 3.5 second pause is inserted each time
 [A] (Pause) is pressed.

Redialing

Making a call using the redial list

The redial list displays up to 20 previously dialed phone numbers (48 digits max. each).

- 1 [►] (Redial/CID)
 - If there is a missed call, "Missed call" is displayed. To display the redial list, press [►] (Redial/CID) again.
- 2 (\$): Select the desired entry.

Redial mode

You can change the redial list display order.

- "Most dialed" (default): The most recently called item is displayed first. Subsequent items are displayed in order according to how frequently they are dialed. The number of times the item was dialed (example: is also displayed.
- "Recent dialed": Items are displayed in the order they were dialed.
- 1 [►] (Redial/CID)
 - If there is a missed call, "Missed call" is displayed. To display the redial list, press [►] (Redial/CID) again.
- 2 [MENU] → [♣]: "Redial mode" →
 [SELECT]
- 3 [♣]: Select the desired setting. → [SAVE] → [OFF]

Erasing a number in the redial list

- **1 (**►**)** (Redial/CID)
 - If there is a missed call, "Missed call" is displayed. To display the redial list, press [►] (Redial/CID) again.
- 2 [♣]: Select the desired entry. → [ERASE]

Erasing all numbers in the redial list

- 1 [►] (Redial/CID)
 - If there is a missed call, "Missed call" is displayed. To display the redial list, press [►] (Redial/CID) again.
- 2 [MENU] → [♣]: "Erase all"→
 [SELECT]
- 3 ($\$]: "Yes" \rightarrow [SELECT] \rightarrow [OFF]

Answering calls

- 1 When the unit rings, lift the handset.
 - To answer using the receiver Press [\^| \display].
- When you finish talking, press [OFF] or place the handset on the base unit or charger.

Any key answer: You can answer the call by pressing any dial key.

Auto talk: You can answer calls simply by lifting the handset (page 27).

Temporary handset ringer off: You can turn the ringer off temporarily by pressing and holding $\boxed{0}$ for a few seconds.

Adjusting the ringer volume

Handset

Press [+] or [-] repeatedly to select the desired volume.

• To turn the ringer off, press [—] repeatedly.

Base unit

Press [+] or [-] repeatedly to select the desired volume.

 To turn the ringer off, press and hold [-] until the unit beeps.

Useful features during a call

Hold

- 1 Press [MENU] during an outside call.
- 2 $[\buildrel \buildrel \$
- 3 To release hold, press [↑/♠].

Note:

 After holding for 10 minutes, the call is disconnected.

Mute

- 1 Press [A] (Mute) during a call.
- 2 To return to the call, press [A] (Mute).

Flash

Flash button allows you to use the special features of your host PBX such as transferring an extension call, or accessing optional telephone services.

Note:

To change the flash time, see page 27.

For call waiting or Call Waiting Caller ID service users

To use call waiting or Call Waiting Caller ID, you must first subscribe with your phone service provider.

This feature allows you to receive calls while you are already talking on the phone. If you receive a call while on the phone, you will hear a call waiting tone.

If you subscribe to both Caller ID and Call Waiting with Caller ID services, the 2nd caller's information is displayed on the unit that is in use after you hear the call waiting tone.

- 1 Press [ACCEPT] to answer the 2nd call.
- 2 To switch between calls, press (FLASH).

Making/Answering Calls

Note:

- [ACCEPT] and [FLASH] are soft keys visible on the display during a call.
- Please contact your phone service provider for details and availability of this service in your area.

Temporary tone dialing (for rotary/pulse service users)

Press ★ (TONE) before entering access numbers which require tone dialing.

Handset clarity booster

This feature can improve sound clarity when the handset is used in an area where there may be interference. During an outside call, this feature is turned on automatically when necessary.

 When this feature is turned on, BOOST is displayed.

Handset noise reduction

This feature allows you to hear the voice of the person you are talking to more clearly, by reducing the surrounding noise coming from the other party's telephone.

- 1 Press [MENU] while talking.
- 2 [♦]: "Noise reduction on" Or
 "Noise reduction off" →
 [SELECT]

Note:

- Depending on the environment where this handset is being used, this feature may not be effective.
- This feature is not available while using the speakerphone.

Handset equalizer

This feature clarifies the voice of the person you are talking to, producing a more natural-sounding voice that is easier to hear and understand.

- 1 Press [MENU] while talking.
- 2 (♣): "Equalizer" → [SELECT]

- 3 (*): Select the desired setting.
- 4 Press (OK) to exit.

Note:

- Depending on the condition and quality of your telephone line, this feature may emphasize existing line noise. If it becomes difficult to hear, turn this feature off
- This feature is not available while using the speakerphone.
- When both the "Equalizer" setting and noise reduction are activated, NR is shown on the display.

Call share

You can join an existing outside call.

To join the conversation, press [\[\] when the other unit is on an outside call.

Note:

- A maximum of 3 parties (including 1 outside party) can join a conversation using 2 extensions. (3-way conference)
- To prevent other users from joining your conversations with outside callers, turn call sharing mode off (page 27).

Transferring calls, conference calls

Outside calls can be transferred or a conference call with an outside party can be made between 2 handsets.

- 1 During an outside call, press [MENU].
- 2 [♣]: "Intercom" → [SELECT]
- 3 (♣): Select the desired unit. → [SELECT]
- 4 Wait for the paged party to answer.
 - If the paged party does not answer, press [BACK] to return to the outside
- To complete the transfer: Press [OFF].

To establish a conference call:

[MENU] → [♣]: "Conference" →

SELECT)

To leave the conference press

To leave the conference, press [OFF].
 The other 2 parties can continue the conversation.

For assistance, please visit http://shop.panasonic.com/support

Making/Answering Calls

 To put the outside call on hold: [MENU] → [♣]: "Hold" → [SELECT]

To resume the conference: [MENU]

→ [♣]: "Conference" → [SELECT]

To cancel the conference: [MENU] →
 [♠]: "Stop conference" →
 [SELECT]

You can continue the conversation with the outside caller.

Intercom

Intercom calls can be made between handsets.

Note:

- When paging unit(s), the paged unit(s) beeps for 1 minute.
- If you receive an outside call while talking on the intercom, the interrupt tone sounds.
 To finish intercom, press [OFF]. To answer the call, press [\(\sigma / \sigma \)]
- To change the ringer volume and ringer tone for intercom, see page 25.

Making an intercom call

- 1 [MENU] → [♣]: "Intercom" →
 [SELECT]
- 2 [♣]: Select the desired unit or "Voice paging". → [SELECT]
 - If you select "Voice paging", speak into the microphone after the beep. Your voice will be heard using the speakers of all handsets, until a handset user answers your page or until you press [OFF].
- 3 When you finish talking, press [OFF].

Note:

- You can also use the [INTERCOM] soft key, if displayed, to make intercom calls.
- You cannot use voice paging if a handset is in use. Try again later.

Answering an intercom call

1 Press [\(\sqrt{\pi} \) to answer the page.

2 When you finish talking, press [OFF].

Turning auto intercom on/off

This feature allows the handset to answer intercom calls automatically when it is called. You do not need to press [\(\ldots \) \(\ldots \)]. When this feature is set to "on", the monitoring handset for the baby monitor feature (page 30) will also answer baby monitor calls automatically. The default setting is "off".

- 1 (MENU)#273
- 2 [$\$]: Select the desired setting. \rightarrow [SAVE] \rightarrow [OFF]

Call Block

Call block feature

You can press the [▼] (Call Block) key in the following situations to disconnect the current call and add a phone number to the call block list:

- when an incoming call is being received
- when an incoming call is being recorded by the answering system
- when talking on an outside call

Once a phone number has been added to the call block list, the unit will block calls from that phone number in the future.

- Press [▼] (Call Block) under the situations shown above.
- Confirm the call block number and press [YES].
 - The call block number is stored in the call block list, "Caller blocked" is displayed, and then the call is disconnected.

Note:

- If the call has no phone number, the call is blocked but it is not stored in the call block list
- The call block feature is not available for intercom calls or calls received by call
- Blocked calls are logged in the caller list.

Storing unwanted callers

The unit can block calls by storing the desired items in the call block list beforehand (Caller ID subscribers only).

- "Block a single number": The unit blocks calls from specific phone numbers stored in the call block list.
- "Block range of numbers": The unit blocks calls that begin with a number stored in the call block list, such as a toll-free phone number prefix or certain area codes.
- "Block unknown CID": The unit blocks calls that have no phone number.

Single phone numbers and ranges of numbers can be stored in the call block list up to 250 items in total.

Blocking unwanted callers:

When a call is received, the unit rings once*1 while caller information is being received. If the caller's phone number matches an entry in the call block list, the unit emits no sound to the caller, and disconnects the call.

If you do not want this one ring to sound, select "No" in "Muting the first ring" (page 19).

Storing a single phone number

Important:

 We recommend storing 10 digits (including) the area code). If only 7 digits are stored, all numbers that have the same last 7 digits will be blocked.

Adding call blocked numbers from the caller list

- [▶] (Redial/CID)
 - If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.
- [\$]: Select the desired entry to be blocked. → [MENU]
 - To edit the number: (♣): "Edit" → [SELECT]

Press (EDIT) repeatedly until the phone number is shown in the 10-digit format. \rightarrow [SAVE] \rightarrow [\updownarrow]: "Call block" \rightarrow [SELECT] \rightarrow Go to step

- [♠]: "Save call block" → [SELECT]
- [♣]: "Yes" → [SELECT]
- Edit the phone number if necessary (24 digits max.). \rightarrow [SAVE] \rightarrow [OFF]

Adding call blocked numbers manually

- 【▼】(Call Block)
- [♣]: "Block a single number" → [SELECT]
- $[MENU] \rightarrow [\]$: "Add" $\rightarrow [SELECT]$
- Enter the phone number (24 digits max.). \rightarrow [SAVE] \rightarrow [OFF]

Storing a range of number

- 1 [▼] (Call Block)
- 2 [♣]: "Block range of numbers" →
 [SELECT]
- 3 [MENU] \rightarrow [\diamondsuit]: "Add" \rightarrow [SELECT]
- 4 Enter the desired number (2-8 digits). → [SAVE] → [OFF]

Blocking incoming calls that have no phone number

You can block calls when no phone number is provided, such as private callers or out of area calls.

- 1 [▼] (Call Block)
- 2 [♣]: "Block unknown CID" →
 [SELECT]
- 3 [♣]: Select the desired setting. → [SAVE] → [OFF]

Muting the first ring

This feature can mute the first ring when a call is received.

"אס": The first ring is muted for all calls.

"Yes": The first ring for all calls, including calls from blocked phone numbers, will be heard.

- 1 [▼] (Call Block)
- 2 [♣]: "One ring for blocked call"
 → [SELECT]
- 3 [♣]: Select the desired setting. → [SAVE] → [OFF]

Viewing/editing/erasing call block numbers

- 1 [▼] (Call Block)
- 2 [♠]: "Block a single number" or
 "Block range of numbers" →
 [SELECT]
- 3 (\$): Select the desired entry.
 - After viewing, press [OFF] to exit.

4 To edit a number: [EDIT] → Edit the number. → [SAVE] → [OFF] To erase a number: [ERASE] → [\$]: "Yes" → [SELECT]

Note:

 When editing, press the desired dial key to add digits and press [CLEAR] to erase digits

Erasing all call block numbers

1 [▼] (Call Block)

 \rightarrow [OFF]

- 2 [♠]: "Block a single number" OF
 "Block range of numbers" →
 [SELECT]
- 3 [MENU] → [♣]: "Erase all" →
 [SELECT]
- **4** [♣]: "Yes" → [SELECT]

Phonebook

Phonebook

You can add 100 names (16 characters max.) and phone numbers (24 digits max.) to the phonebook, and assign each phonebook entry to the desired group (page 20).

Important:

 All entries can be shared by any registered handset.

Adding phonebook entries

- 1 (◄) m → [MENU]
- 2 [♣]: "Add new entry" → [SELECT]
- 3 Enter the party's name. \rightarrow [OK]
- 4 Enter the party's phone number. → [OK]
- 5 [♣]: Select the desired group. → [SELECT] 2 times → [OFF]

Note:

- In step 3, you can switch the language for entering characters.
 - $\# \to [\diamondsuit]$: Select the desired language. \to [OK]

Entering characters

Press the dial key that corresponds to the desired character. Press repeatedly to scroll through the available characters. The following operations are also available.

Key	Operation
[*]	Switch between the uppercase and lowercase (A → a)
[∢] [►]	Move the cursor
[CLEAR]	Erase the character or number To erase all, press and hold it.

- To enter another character that is located on the same dial key, first press [►] to move the cursor to the next space.
- If you do not press any dial key within 2 seconds after entering a character, the

character is fixed and the cursor moves to the next space.

Storing a redial list number to the phonebook

Phone numbers of up to 24 digits can be stored in the phonebook.

- [►] (Redial/CID)
 - If there is a missed call, "Missed call" is displayed. To display the redial list, press [►] (Redial/CID) again.
- 2 ($\$]: Select the desired entry. \rightarrow [MENU]
- **3** [♣]: "Save" → [SELECT]
- **4** To store the name, continue from step 3, "Editing entries", page 21.

Storing caller information to the phonebook

1 [▶] (Redial/CID)

to step 4.

- If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.
- 2 [♠]: Select the desired entry. → [MENU]
 To edit the number: [♠]: "Edit" →
 - [SELECT]
 Press [EDIT] repeatedly until the phone number is shown in the desired format. → [SAVE] → [♣]:
 "Phonebook" → [SELECT] → Go
- 3 [♣]: "Save phonebook" → [SELECT]
- **4** Continue from step 3, "Editing entries", page 21.

Groups

Groups can help you find entries in the phonebook quickly and easily. You can change the names of groups assigned for phonebook entries ("Friends", "Family", etc.). By assigning different ringer tones for different groups of callers, you can identify who is calling (ringer ID), if you have subscribed to Caller ID service.

Changing group names/setting ringer

The default group name is "Group 1" to "Group 9".

- 1 (◄) m → [MENU]
- 2 [♣]: "Group" → [SELECT]
- 3 [♣]: Select the desired group. → [SELECT]
- 4 To change group names
 - [♠]: "Group name" → [SELECT] → Edit the name (10 characters max.). → [SAVE]

To set group ringer tone

- [♠]: Select the current setting of the group ringer tone. → [SELECT] → [♠]: Select the desired ringer tone. → [SAVE]
- **5** [OFF]

Finding and calling from a phonebook entry

- 1 [→]田
- 2 To scroll through all entries
 - [♣]: Select the desired entry.

To search by first character

- Press the dial key (0 to 9, or #)
 which contains the character you are
 searching for (page 20).
- (2) [\$\\$]: Scroll through the phonebook if necessary.

To search by group

- (GROUP)
- ② [♣]: Select the desired group. → [SELECT]
- ③ [♣]: Scroll through the phonebook if necessary.
- 3 [↑/\\

Editing entries

- 1 Find the desired entry (page 21).
- 2 [MENU] \rightarrow [\diamondsuit]: "Edit" \rightarrow [SELECT]
- 3 Edit the name if necessary. → [OK]
- 4 Edit the phone number if necessary. → [OK]

5 [♠]: Select the desired group (page 20).
 → [SELECT] 2 times → [OFF]

Erasing entries

Erasing an entry

- 1 Find the desired entry (page 21).
- 2 [MENU] \rightarrow [\diamondsuit]: "Erase" \rightarrow [SELECT]

Erasing all entries

- 1 (◄) m → [MENU]
 - [♣]: "Erase all" → [SELECT]
- **3** [♠]: "Yes" → [SELECT]

Chain dial

This feature allows you to dial phone numbers in the phonebook while you are on a call. This feature can be used, for example, to dial a calling card access number or bank account PIN that you have stored in the phonebook, without having to dial manually.

- 1 During an outside call, press [◄] □.
- 2 (\$): Select the desired entry.
- 3 Press [CALL] to dial the number.

Note:

- When storing a calling card access number and your PIN in the phonebook as one phonebook entry, press [A] (Pause) to add pauses after the number and PIN as necessary (page 14).

Phonebook

Speed dial

You can assign 1 phone number to each of the dial keys (1 to 9) on the handset.

Adding phone numbers to speed dial keys

- By entering phone numbers:
 - 1 Press and hold the desired speed dial key (1 to 9). → [ADD]
 - 2 [♣]: "Manual" → [SELECT]
 - 3 Enter the party's name (16 characters max.). → [OK]
 - 4 Enter the party's phone number (24 digits max.). → [OK] → [SELECT] → [OFF]
- From the phonebook:
 - 1 Press and hold the desired speed dial key (1 to 9). → [ADD]
 - 2 [♣]: "Phonebook" → [SELECT]
 - 3 [♠]: Select the desired entry. → [SAVE] → [OFF]

Note:

 If you edit a phonebook entry which is assigned to a speed dial key, the edited entry does not transfer to the speed dial key.

Editing an entry

- 1 Press and hold the desired speed dial key (1 to 9). → [MENU]
- 2 [♠]: "Edit" → [SELECT]
- 3 Edit the name if necessary. → [OK]
- 4 Edit the phone number if necessary. → [OK] → [SELECT] → [OFF]

Erasing an entry

- Press and hold the desired speed dial key (1 to 9). → [MENU]
- 2 [♣]: "Erase" → [SELECT]
- 3 (♣): "Yes" → [SELECT] → [OFF]

Viewing an entry/Making a call

- 1 Press and hold the desired speed dial key (11 to 19).
- 2 To make a call, press [¬/♠].

For assistance, please visit http://shop.panasonic.com/support

Menu list

To access the features, there are 2 methods.

- Scrolling through the display menus
 - 1 [MENU]
 - 2 Press [v] or [A] to select the desired main menu. \rightarrow [SELECT]
 - 3 Press [v] or [∆] to select the desired item from the next sub-menus. → [SELECT]
 - 4 Press (▼) or (▲) to select the desired setting. → (SAVE)
- Using the direct command code
 - 1 [MENU] → Enter the desired code.
 - Example: Press [MENU]#101.

 2 Select the desired setting. → [SAVE]

Note:

- To exit the operation, press [OFF].
- In the following table, < > indicates the default settings.
- In the following table, indicates the reference page number.
- Display menu order and sub-menu may vary depending on your model.

Display menu tree and direct command code table

Main menu: m "Phonebook"

Operation	Code	
Viewing the phonebook entry.	#280	21

Main menu: → "Caller list"

Operation	Code	Ġ
Viewing the caller list.	#213	33

Main menu: @ "Answering device"

Sub-menu 1	Sub-menu 2	Settings	Code	G
Play new message	_	_	#323	36
Play all message	-	_	#324	36
Erase all message*1	-	-	#325	37
Greeting	Record greeting*1	-	#302	35
	Check greeting	_	#303	36
	Pre-recorded*1 (Reset to pre-recorded greeting)	_	#304	35

Sub-menu 1	Sub-menu 2	Settings	Code	Œ
New message alert*1	Outgoing call - On/Off	On <off></off>	#338	37
	Outgoing call - Notification to	_		
	Outgoing call - Remote code	Activate <inactivate></inactivate>		
	Base unit beep	On <off></off>	#339	37
Settings	Ring count*1	Toll saver 2-7 rings <4 rings>	#211	40
	Recording time*1	<pre><3 min> 1 min Greeting only*2</pre>	#305	40
	Remote code*1	<111>	#306	39
	Screen call	<on></on>	#310	40
Answer on*1	-	-	#327	35
Answer off*1	_	_	#328	35

Main menu: ☑️ "Voicemail access"

Operation	Code	G
Listening to voicemail messages.	#330	41

Main menu: () "Intercom"

Operation	Code	Ġ
Paging the desired unit.	#274	17

Main menu: ⊕ "Set date & time"

Sub-menu 1	Sub-menu 2	Settings	Code	Ġ
Date and time*1	_	_	#101	13
Memo alarm	Alarm1-3	<off> Once Daily Weekly</off>	#720	29
Time adjustment*1,*3	-	<caller id<br="">auto> Manual</caller>	#226	_

Main menu: "" "Speed dial"

Operation	Code	G	ı
Viewing the speed dial entry.	#261	22	

Main menu: **▶** "Settings"

Sub-menu 1	Sub-menu 2	Settings	Code	
Ring adjustments	Ringer volume (Incoming)	Off-6 <6>	#160	-
	Intercom ringer volume (Handset)	1–6 <6>	#175	_
	Ringer tone (Incoming)*4,*5 (Handset)	<tone 1=""></tone>	#161	_
	Intercom ringer tone*4,*5 (Handset)	<tone 3=""></tone>	#163	_
	Silent mode - On/Off	On <off></off>	#238	29
	Silent mode - Start/End	<11:00 PM/ 06:00 AM>	#237	30
	Silent mode - Select group	Group 1 - 9	#241	30
Set date & time	Date and time*1	_	#101	13
	Memo alarm - Alarm1-3	<off> Once Daily Weekly</off>	#720	29
	Time adjustment*1,*3	<caller id<br="">auto> Manual</caller>	#226	-
Talking caller ID	Handset	<on> Off</on>	#162	33
	Base unit*1	On <off></off>	# X 162	

Sub-menu 1	Sub-menu 2	Settings	Code	G
Key detector	Change name*1	Detector1	#6561	-
setting*6 - 1:Add new		Detector2*8	#6562*8	
device (for		Detector3*8	#6563*8	
Detector1)*7		Detector4*8	#6564*8	
device (for	Registration	-	#6571	-
Detector2) - 3:Add new			#6572*8	
device (for			#6573*8	
Detector3)			#6574*8	
- 4:Add new device (for	Deregistration	-	#6581	-
Detector4)			#6582*8	
			#6583*8	
			#6584*8	
Call block*1	Block a single number	_	#217	18
	Block range of numbers	_		19
	Block unknown CID (CID: Caller ID)	Block <unblock></unblock>	#240	19
	One ring for blocked call	<yes></yes>	#173	19
Speed dial	_	_	#261	22
Record greeting*1	-	-	#302	35
Voicemail	Save VM access#*1 (VM: Voicemail)	_	#331	41
	VM tone detect*1	<on> Off</on>	#332	41
LCD contrast (Display contrast)	-	Level 1-4 <2>	#145	-
Handset name	_	-	#104	32
Display name	-	On <off></off>	#105	32
Redial mode	_	<most dialed=""> Recent dialed</most>	#659	14
Auto intercom	_	On <off></off>	#273	17
Key tone	-	<on></on>	#165	-

For assistance, please visit http://shop.panasonic.com/support

Sub-menu 1	Sub-menu 2	Settings	Code	Ġ
Caller ID edit (Caller ID number auto edit)	-	<on> Off</on>	#214	34
Auto talk*9	_	On <off></off>	#200	15
Set tel line	Set dial mode*1	<tone> Pulse</tone>	#120	13
	Set flash time*1,*10	80 ms 90 ms 100 ms 110 ms 160 ms 200 ms 250 ms 300 ms 400 ms 600 ms <700 ms> 900 ms	#121	15
	Set line mode*1,*11	A 	#122	-
Call sharing*1	_	<on> Off</on>	#194	16
Registration	Register handset	_	#130	32
	Deregistration*2	_	#131	32
Change language	Display	<english> Español</english>	#110	12
	Announcement*1	<english> Español</english>	#112	13

Main menu: ? "Customer support"

Operation	Code	G
Displaying customer support Web address.	#680	_

Main menu: (3) "Baby monitor"

Sub-menu 1	Sub-menu 2	Settings	Code	Ġ
On/Off	_	On <off></off>	#268	30
Sensitivity level	-	Low <middle> High</middle>	#269	31

Main menu: (1) "Key detector"*6

Sub-menu 1	Sub-menu 2	Settings	Code	Ġ
Search	-	-	#655	-
Battery check	-	_		

- *1 If you program these settings using one of the units, you do not need to program the same item using another unit.
- *2 This menu is not displayed when scrolling through the display menus. It is only available in direct command code.
- *3 This feature allows the unit to automatically adjust the date and time each time caller information including date and time is received.
 - To turn this feature on, select "Caller ID auto". To turn this feature off, select "Manual". (Caller ID subscribers only)
 - To use this feature, set the date and time first (page 13).
- *4 If you subscribe to a distinctive ring service (such as IDENTA-RING), select a tone (tone 1 to 2). If you select a melody, you cannot distinguish lines by their ringers.
- *5 The preset melodies in this product are used with permission of © 2009 Copyrights Vision Inc.
- *6 This setting is available when you have the key detector (KX-TGA20). Read the installation manual for more information on the key detector.
- *7 For models with supplied key detectors, the display shows "1: Detector1".
- *8 If you register 2 or more key detectors.
- *9 If you subscribe to a Caller ID service and want to view the caller's information after lifting up the handset to answer a call, turn off this feature.
- *10 The flash time depends on your telephone exchange or host PBX. Contact your PBX supplier if necessary. The setting should stay at "700 ms" unless pressing [FLASH] fails to pick up the waiting call.
- *11 Generally, the line mode setting should not be changed. This setting automatically maintains receiver volume at the proper level depending on the current telephone line condition. Set the line mode to "a" if telephone line condition is not good.

Alarm

An alarm sounds at the set time for 1 minute and is repeated 5 times at 5 minute intervals (snooze function). A text memo can also be displayed for the alarm. A total of 3 separate alarm times can be programmed for each handset. You can set one of 3 different alarm options (once, daily, or weekly) for each alarm time.

Important:

- Make sure the unit's date and time setting is correct (page 13).
- 1 (MENU)#720
- 2 [♠]: Select the desired alarm. → [SELECT]
- 3 [♣]: Select the desired alarm option. → [SELECT]

"off"

Turns alarm off. Go to step 10.

"Once"

An alarm sounds once at the set time.

"Daily"

An alarm sounds daily at the set time. Go to step 5.

"Weekly"

Alarm sounds weekly at the set time(s).

- 4 Proceed with the operation according to your selection in step 3.
 - Once:

Enter the desired month and date. → [OK]

- Weekly:
 - $\{\$]: Select the desired day of the week and press (SELECT). \rightarrow [OK]
- 5 Set the desired time.
- 6 \mathbb{R} : Select "AM" or "PM". \rightarrow [OK]
- 7 Enter a text memo (10 characters max.). → [OK]

- [♠]: Select the desired alarm tone. →
 [SELECT]
 - We recommend selecting a different ringer tone from the one used for outside calls
- 9 (♣): Select the desired snooze setting.→ [SAVE]
- 10 [SELECT] \rightarrow [OFF]

Note:

- Press (STOP) to stop the alarm completely.
- When the handset is in use, the alarm will not sound until the handset is in standby mode.
- Press any dial key or [SNOOZE] to stop the sound but keep the snooze function activated.
- If you want to make an outside call when the snooze function is activated, please stop the snooze function before making the call.

Silent mode

Silent mode allows you to select a period of time during which the handset and/or base unit will not ring for outside calls. This feature is useful for time periods when you do not want to be disturbed, for example, while sleeping. Silent mode can be set for each unit. Using the phonebook's group feature (page 20), you can also select groups of callers whose calls override silent mode and ring the unit (Caller ID subscribers only).

Important:

- Make sure the unit's date and time setting is correct (page 13).
- If you have set the alarm, the alarm sounds even if the silent mode is turned on.

Turning silent mode on/off

- 1 (MENU)#238
- 2 [♠]: Select the desired setting. → [SAVE]
 - If you select "Off", press [OFF] to exit.

- 3 Enter the desired hour and minute you wish to start this feature.
- 4 ★: Select "AM" or "PM". → [OK]
- 5 Enter the desired hour and minute you wish to end this feature.
- 6 ★: Select "AM" or "PM".
- 7 $[SAVE] \rightarrow [OFF]$

Changing the start and end time

- 1 (MENU)#237
- 2 Continue from step 3, "Turning silent mode on/off", page 29.

Selecting groups to bypass silent mode

- 1 (MENU)#241
- 2 [♣]: Select your desired groups. → [SELECT]
 - "✓" is displayed next to the selected group numbers.
 - To cancel the selected group:
 [♠]: Select the group. → Press
 [SELECT] again. "✓" disappears.
- 3 [SAVE] \rightarrow [OFF]

Baby monitor

This feature allows you to listen in on a room where another handset is located, allowing you to easily monitor from different areas of the house or even while away from home. The monitored handset (placed in a baby's room, for example) will automatically call the monitoring handset or the phone number stored when it detects sound.

Important:

30

- Before using this feature, we recommend that you test this feature and adjust the baby monitor sensitivity as needed, especially if you plan to monitor from outside.
- This feature should not be used as a substitute for a medical or caregiver's supervision. It is the caregiver's

responsibility to stay close enough to handle any eventuality.

Note:

- If the unit is connected to a PBX system, you cannot set the baby monitor.
- During the monitoring mode, battery consumption is faster than usual. We recommend leaving the monitored handset on the base unit or charger.
- The monitored handset never rings while it is being monitored. If the base unit is placed near the monitored handset, we recommend turning off the base unit ringer volume (page 25).

Setting the baby monitor

Perform the setting operation with the handset to be monitored (for example, the handset placed in a baby's room).

To monitor with a unit

The internal baby monitor feature is available between handsets.

- 1 (MENU)#268
- 2 [♣]: "on" → [SELECT]
- 3 [♣]: Select the desired unit's number to monitor with. → [SAVE]
 - "Baby monitor" will be displayed.
 - The registered unit's name/number is displayed.

Note:

 When this feature is on, another handset can hear the monitored handset by making an intercom call.

To monitor from outside

If you enable this feature, the unit will call a pre-programmed phone number when the handset detects sound. After you answer the call, you can listen in on the room where the handset is located.

- From the phonebook:
 - 1 (MENU)#268
 - 2 (♠): "on" → [SELECT]

- 3 [♣]: Select "Outgoing call" to monitor from outside. → [ADD]
- 4 (♣): "Phonebook" → [SELECT]
- 5 [♣]: Select the phonebook entry. → [SAVE]
 - "Baby monitor" will be displayed.

Note:

- If you edit a phonebook entry which is assigned for monitoring, the edited entry does not transfer to the monitor.
- By entering phone numbers:
 - 1 [MENU]#1216181
 - 2 (♣): "on" → [SELECT]
 - 3 [♣]: Select "Outgoing call" to monitor from outside. → [ADD]
 - 4 [♣]: "Manual" → [SELECT]
 - 5 Enter the desired name. \rightarrow [OK]
 - 6 Enter the desired number. → [OK] → [SELECT]
 - "Baby monitor" will be displayed.

Note:

The registered name/number is displayed.

Turning off the baby monitor

The monitored handset cannot be used while baby monitor is set to "on".

- Press [MENU] on the handset being monitored.
- 2 $[\dfrac{1}{2}]$: "On/Off" \rightarrow [SELECT]
- 3 ($\$): "off" \rightarrow [SELECT] \rightarrow [OFF]

Editing an outside monitoring number

- Press [MENU] on the handset being monitored.
- 2 ($\$): "On/Off" \rightarrow [SELECT]
- 3 ($\ \$): "on" \rightarrow [SELECT]
- **4** [♣]: Select the outside line.
- 5 [MENU] → [♣]: "Edit" → [SELECT]
- 6 Edit the name if necessary. → [OK]
- 7 Edit the phone number if necessary. → [OK] → [SELECT]

Erasing an outside monitoring number

- Press [MENU] on the handset being monitored.
- 2 [♣]: "On/Off" → [SELECT]
- 4 (*): Select the outside line.
- 5 [MENU] \rightarrow [\updownarrow]: "Erase" \rightarrow [SELECT]

Baby monitor sensitivity

You can adjust the sensitivity of the baby monitor. Increase or decrease the sensitivity to adjust the sound level needed to trigger the baby monitor feature.

- This feature cannot be set during a monitoring call.
- Press [MENU] on the handset being monitored.
- 2 [♣]: "Sensitivity level" →
 [SELECT]
- 3 [♠]: Select the desired setting. → [SAVE] → [OFF]

Answering the baby monitor

When monitoring with a handset:

 The monitoring unit will answer calls automatically when the auto intercom feature is set to "on" (page 17).

Note:

- If you receive an outside call when communicating with the monitored handset, the interrupt tone sounds. To answer the call, press [OFF], then press [~/*].
- When monitoring from outside: Answer the call.

If you want to respond from your monitoring phone, press #1 using tone dialing.
You can turn off the baby monitor feature by pressing #0.

Noto:

 The unit disconnects the call automatically after 2 minutes.

Other programming

Changing the handset name

The default handset name is "Handset 1" to "Handset 6". You can customize the name of each handset ("Bob", "Kitchen", etc.). This is useful when you make intercom calls between handsets. To display the handset name in standby mode, turn on the handset name display feature (page 32).

- 1 (MENU)#104
- 2 Enter the desired name (10 characters max.). → [SAVE] → [OFF]

Displaying the handset name

You can select whether or not the handset name is displayed in standby mode. The default setting is "off".

- 1 (MENU)#105
- 2 [♠]: Select the desired setting. → [SAVE] → [OFF]

Registering a unit

Operating additional units

Additional handsets

Up to 6 handsets can be registered to the base unit.

Important:

 See page 4 for information on the available model.

Registering a handset to the base unit

The supplied handset and base unit are pre-registered. If for some reason the handset is not registered to the base unit, re-register the handset.

- 1 Handset: [MENU]#[1]3[0]
- 2 Base unit: Press and hold [LOCATOR] for about 5 seconds.
 - If all registered handsets start ringing, press [LOCATOR] again to stop, then repeat this step.
- 3 Handset: Press [OK], then wait until a long beep sounds.

Deregistering a handset

A handset can cancel its own registration to the base unit, or other handsets registered to the same base unit. This allows the handset to end its wireless connection with the system.

- 1 (MENU)#131
 - All handsets registered to the base unit are displayed.
- 2 [♣]: Select the handset you want to cancel. → [SELECT]
- 3 (♣): "Yes" → [SELECT] → [OFF]

Using Caller ID service

Important:

 This unit is Caller ID compatible. To use Caller ID features, you must subscribe to a Caller ID service. Contact your phone service provider for details.

Caller ID features

When an outside call is being received, the caller information is displayed.

Caller information for the last 50 callers is logged in the caller list from the most recent call to the oldest.

- If the unit cannot receive caller information, the following is displayed:
 - "Out of area": The caller dials from an area which does not provide a Caller ID service
 - "Private caller": The caller requests not to send caller information.
 - "Long distance": The caller makes a long distance call.
- If the unit is connected to a PBX system, caller information may not be properly received. Contact your PBX supplier.

Missed calls

If a call is not answered, the unit treats it as a missed call. The display shows "Missed call".

Note:

- Even when there are unviewed missed calls, "Missed call" disappears from the standby display if the following operation is performed by one of the units:
 - A handset is replaced on the base unit or charger.
 - Pressing [OFF] on a handset.

Phonebook name display

When caller information is received and it matches a phone number stored in the phonebook, the stored name in the phonebook is displayed and logged in the caller list.

Talking Caller ID

Handset / Base unit

This feature lets you know who is calling without looking at the display.

To use this feature, you must:

- subscribe to a Caller ID service of your phone service provider.
- turn this feature on (page 25).
 When caller information is received, the handsets and/or base unit announce the caller's name or phone number received from your phone service provider following every ring.
- Name pronunciation may vary. This feature may not pronounce all names correctly.
- Caller ID service has a limit of how many characters can be displayed. If the caller's name is too long, the unit may not be able to display or announce the entire name.

Phonebook name announcement

When caller information is received and it matches a phone number stored in the phonebook, the stored name in the phonebook is announced.

Caller list

Important:

 Make sure the unit's date and time setting is correct (page 13).

Viewing the caller list and calling back

- 1 [►] (Redial/CID)
 - If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.
- Press (▼) to search from the most recent call, or (▲) to search from the oldest call.
- To call back, press [↑/♠].
 To exit, press [OFF].

Caller ID Service

Note:

 If the entry has already been viewed or answered. "✓" is displayed.

Editing a caller's phone number

You can edit a phone number in the caller list by removing its area code and/or the long distance code "1".

- **1** [▶] (Redial/CID)
 - If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.
- 2 (♣): Select the desired entry. → [MENU]
- 3 [♠]: "Edit" → [SELECT]
- 4 Press [EDIT] repeatedly until the phone number is shown in the desired format.
- 5 **[→ /**♠]

Caller ID number auto edit feature

Once you call back an edited number, the unit which was used to call back remembers the area code and format of the edited number. The next time someone calls from the same area code, caller information is customized by the unit as follows:

- When the call is being received, the Caller ID number is displayed in the same format as the edited number.
- After the call has ended, the caller's phone number is displayed in the same format as the edited number, when reviewed from the caller list.

For example, you can use this feature to set the unit to ignore the area code of callers in your area, so that you can call these local numbers using caller information without dialing the area code.

To activate this feature, you must edit an entry in the caller list, then call that number. After that, phone numbers from that caller's area code are edited automatically.

This feature can be set for each unit (page 27). The default setting is "on".

Note:

34

 Phone numbers from the 4 most recently edited area codes are automatically edited.

Erasing selected caller information

- 1 [►] (Redial/CID)
 - If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.
- 2 (\$): Select the desired entry.
- 3 [ERASE] \rightarrow [\diamondsuit]: "Yes" \rightarrow [SELECT] \rightarrow [OFF]

Erasing all caller information

- 1 [►] (Redial/CID)
 - If the redial list is displayed, press [►] (Redial/CID) again to switch to the caller list.

Answering system

The answering system can answer and record calls for you when you are unavailable to answer the phone.

You can also set the unit to play a greeting message but not to record caller messages by selecting "Greeting only" as the recording time setting (page 40).

Important:

 Make sure the unit's date and time setting is correct (page 13).

Memory capacity (including your greeting message)

The total recording capacity is about 17 minutes. A maximum of 64 messages can be recorded.

Note:

- When message memory becomes full:
 - "Messages full" is shown on the handset display.
 - The ANSWER ON/OFF indicator (
 on the base unit flashes rapidly if the
 answering system is turned on.
 - If you use the pre-recorded greeting message, the unit automatically switches to another pre-recorded greeting message asking callers to call again later.
 - If you recorded your own greeting message, the same message is still announced to callers even though their messages are not recorded.

Turning the answering system on/off

Base unit

Press [ANSWER ON/OFF] to turn on/off the answering system.

Handset

1 To turn on: [MENU]#327

To turn off: [MENU]#328

OFF)

Note for base unit and handset:

 When the answering system is turned on, the ANSWER ON/OFF indicator (on the base unit lights up.

Greeting message

When the unit answers a call, a greeting message is played to callers. You can use either:

- your own greeting message
- a pre-recorded greeting message

Recording your greeting message

- 1 (MENU)#302
- 2 ($\$]: "Yes" \rightarrow [SELECT]
- 3 After a beep sounds, hold the handset about 20 cm (8 inches) away and speak clearly into the microphone (2 minutes max.).
- 4 Press [STOP] to stop recording. → [OFF]

Using a pre-recorded greeting message

The unit provides 2 pre-recorded greeting messages:

- If you reset to pre-recorded greeting or do not record your own greeting message, the unit plays a pre-recorded greeting asking callers to leave a message.
- If the message recording time (page 40) is set to "Greeting only", callers' messages are not recorded and the unit plays a different pre-recorded greeting message asking callers to call again.

Resetting to a pre-recorded greeting message

Use this procedure to erase your greeting message and use a pre-recorded one.

Answering System

- 1 [MENU]#[3]0[4]
- 2 [YES] → [OFF]

Playing back the greeting message

- 1 [MENU]#303
- 2 To exit, press [OFF].

Listening to messages

Important:

- If your phone service provider offers voicemail service, the voicemail service may answer calls before the base unit's built-in answering system has a chance to answer calls and record messages. In this case, messages you expect to be recorded by the answering system will be recorded on the voicemail service. For more information, see "For landline voicemail service subscribers" (page 40).
- When using the base unit or handset to listen to messages, the noise reduction feature (page 16) is activated automatically in spite of the setting (INT is not displayed).

Using the base unit

When new messages have been recorded, **[►■]** on the base unit flashes.

Press [►■] (PLAY).

- During playback, [►■] on the base unit lights.
- If new messages have been recorded, the base unit plays back new messages.
- If there are no new messages, the base unit plays back all messages.

Operating the answering system during playback

Key	Operation
[+] or [-]	Adjust the speaker volume

Key	Operation
[144]	Repeat message*1
[>> 1]	Skip message
[►■] (STOP)	Stop playback
[ERASE]	Erase currently playing message

*1 If pressed within the first 5 seconds of a message, the previous message is played.

Erasing all messages

Press [ERASE] 2 times while the unit is not in use.

Using the handset

When new messages have been recorded, "New message" is displayed.

- 1 To listen to new messages: [MENU]#323
 To listen to all messages: [MENU]#324
- When finished, press [OFF].

Note:

- To switch to the receiver, press [\(^\left\)/\(^\left\)].
- You can also use the [PLAY] soft key, if displayed, to play new messages.

Operating the answering system

[MENU] \rightarrow [\updownarrow]: "Answering device" \rightarrow [SELECT]

Key	Operation
[+] or [-]	Adjust the receiver/speaker volume (during playback)
1 or [◄]	Repeat message (during playback)*1
2 or [►]	Skip message (during playback)
3	Enter the "Settings" menu
4	Play new messages
5	Play all messages
6	Play greeting message

For assistance, please visit http://shop.panasonic.com/support

Key	Operation
76	Record greeting message
8	Turn answering system on
[PAUSE]	Pause message*2
9 or [STOP]	Stop recording Stop playback
0	Turn answering system off
¥4 *3	Erase currently playing message
* 5	Erase all messages
 ★ 6	Reset to a pre-recorded greeting message

- *1 If pressed within the first 5 seconds of a message, the previous message is played.
- *2 To resume playback:
 - [♣]: "Playback" → [SELECT]
- *3 You can also erase as follows:

 [PAUSE] → [♠]: "Erase" →

 [SELECT] → [♠]: "Yes" → [SELECT]

Calling back (Caller ID subscribers only)

- 1 Press [PAUSE] during playback.
- 2 [♣]: "Call back" → [SELECT]

Editing the number before calling back

- 1 Press [PAUSE] during playback.
- 2 [♣]: "Edit & Call" → [SELECT]

Erasing all messages

- 1 (MENU)#325

Advanced new message alerting features

Audible message alert

This feature allows the base unit to beep to inform you of a new message arrival when new messages are recorded. The base unit beeps 2 times every minute until you listen to the messages, if the "Base unit beep" setting is turned on. The default setting is "Off".

- 1 (MENU)#339
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

New message alert by a call

This feature allows you to receive a notification by phone when new messages are recorded. The base unit calls a phone number you specify. You can then operate the answering system remotely to listen to the new message.

To use this feature, you must:

- store a phone number to which the unit makes the call to.
- turn on the new message alert setting.
 After you answer the new message alert call, you can listen to messages from that call (page 38).

Important:

 A new message alert is stopped 1 minute after the unit starts to call. The unit will not retry the call even if the call is not answered.

Storing a phone number to which the unit makes an alert call

- From the phonebook:
 - 1 (MENU)#338
 - 2 [♣]: "Notification to" →
 [SELECT] → [ADD]
 - 3 [♣]: "Phonebook" → [SELECT]
 - **4** [♠]: Select the desired phonebook entry. → [SAVE] → [OFF]

Answering System

- By entering a phone number:
 - 1 [MENU]#338

 - 3 [♠]: "Manual" → [SELECT]
 - 4 Enter the desired name (16 characters max.). → [OK]
 - 5 Enter the desired number (24 digits max.). → [OK] → [SELECT] → [OFF]

Turning on/off the new message alert setting

- 1 (MENU)#338
- 2 [♣]: "On/Off" → [SELECT]
- 3 [♣]: Select the desired setting. → [SAVE] → [OFF]

Editing the set phone number

- 1 [MENU]#338
- 2 (♣): "Notification to" → [SELECT]
- 3 [MENU] \rightarrow [\updownarrow]: "Edit" \rightarrow [SELECT]
- 4 Edit the name if necessary (16 characters max.). → [OK]
- 5 Edit the phone number if necessary (24 digits max.). → [OK] → [SELECT] → [OFF]

Erasing the set phone number

- 1 [MENU]#338
- 2 [♠]: "Notification to" → [SELECT]
- 3 [MENU] \rightarrow [$\stackrel{\blacktriangle}{\bullet}$]: "Erase" \rightarrow [SELECT]
- - The new message alert setting is turned off.

Activating/inactivating the remote access code to play messages

If you activate this feature, you must enter the remote access code (page 39) to play the new message from the new message alert call. This is so that unauthorized parties

cannot listen to your messages. The default setting is "Inactivate".

- "Inactivate": You can listen to the message by pressing 4 to play new messages (without entering the remote access code).
- "Activate": You must enter your remote access code and then press 4 to play new message.
 - 1 [MENU]#338
 - 2 (♣): "Remote code" → [SELECT]
 - 3 [♣]: Select the desired setting. → [SAVE] → [OFF]

Listening to messages

After you answer the new message alert, you can listen to the messages as follows.

■ When the remote access code is set to "Inactivate":

Press 4 to play the new message during the announcement.

- When the remote access code is set to "Activate":
 - 1 Enter the remote access code (page 39) during the announcement.
 - **2** Press **4** to play the new message.

Note:

- Within 10 seconds after listening to new messages, you can press # 9 during the call to turn off the new message alert by a call feature.
- Even if the unit makes a new message alert call, the handset redial list does not show the record.

Remote operation

Using a touch-tone phone, you can call your phone number from outside and access the unit to listen to messages or change answering system settings. The unit's voice guidance prompts you to press certain dial keys to perform different operations.

Answering System

Remote access code

A 3-digit remote access code must be entered when operating the answering system remotely. This code prevents unauthorized parties from listening to your messages remotely. The default setting is "111".

Important:

- To prevent unauthorized access to this product, we recommend that you regularly change the remote code.
- (MENU)#306
- Enter the desired 3-digit remote access $code. \rightarrow [SAVE] \rightarrow [OFF]$

Deactivating remote operation

Press x in step 2 on "Remote access code", page 39.

The entered remote access code is deleted.

Using the answering system remotely

- Dial your phone number from a touch-tone phone.
- After the greeting message starts, enter your remote access code.
- Follow the voice guidance prompts as necessary or control the unit using remote commands (page 39).
- When finished, hang up.

Voice guidance

■ When the English voice guidance is selected

During remote operation, the unit's voice guidance starts and prompts you to press 1 to perform a specific operation, or press

- [2] to listen to more available operations.
- When the Spanish voice guidance is selected

To start the voice guidance, press [9]. The voice guidance announces the available remote commands (page 39).

Note:

• If you do not press any dial keys within 10 seconds after a voice guidance prompt, the unit disconnects your call.

Remote commands

You can press dial keys to access certain answering system functions without waiting for the voice guidance to prompt you.

Key	Operation
1	Repeat message (during playback)*1
2	Skip message (during playback)
4	Play new messages
5	Play all messages
9	Stop playback*2 Start voice guidance*3
0	Turn answering system off
* 4	Erase currently playing message
* 5	Erase all messages
*#	End remote operation (or hang up)

- If pressed within the first 5 seconds of a message, the previous message is
- For English voice guidance only
- For Spanish voice guidance only

Turning on the answering system remotely

- Dial your phone number from a touch-tone phone.
- Let the phone ring 15 times.
 - A long beep is heard.
- Enter your remote access code within 10 seconds after the long beep.
 - The greeting message is played back.
 - You can either hang up, or enter your remote access code again and begin remote operation (page 38).

Answering System

Answering system settings

Call screening

While a caller is leaving a message, you can listen to the call through the unit's speaker. To adjust the speaker volume, press [+] or [-] repeatedly.

You can answer the call by pressing [\(\frac{1}{4} \)] on the handset.

Call screening can be set for each handset. The default setting is "on".

- 1 (MENU)#310
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

Number of rings before the unit answers a call

You can change the number of times the phone rings "Ring count" before the unit answers calls. You can select 2 to 7 rings, or "Toll saver".

The default setting is "4 rings".

"Toll saver": The unit's answering system answers at the end of the 2nd ring when new messages have been recorded, or at the end of the 5th ring when there are no new messages. If you call your phone from outside to listen to new messages (page 39), you know that there are no new messages when the phone rings for the 3rd time. You can then hang up without being charged for the call.

- 1 (MENU)#211
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

For landline voicemail service subscribers

If you subscribe to a flat-rate service package that includes Caller ID, call waiting, voicemail, and unlimited local/regional/long distance calls, please note the following:

 To use the voicemail service provided by your phone service provider rather than the

- unit's answering system, turn off the answering system (page 35).
- To use this unit's answering system rather than the voicemail service provided by your phone service provider, please contact your phone service provider to deactivate your voicemail service.

If your phone service provider cannot do this:

- Set this unit's "Ring count" setting so that this unit's answering system answers calls before the voicemail service of your phone service provider does. It is necessary to check the number of rings required to activate the voicemail service provided by your phone service provider before changing this setting.
- Change the number of rings of the voicemail service so that the answering system can answer the call first. To do so, contact your phone service provider.

Caller's recording time

You can change the maximum message recording time allowed for each caller. The default setting is "3 min".

- 1 [MENU]#305
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

Selecting "Greeting only"

You can select "Greeting only" which sets the unit to announce a greeting message to callers but not record messages.

Select "Greeting only" in step 2 on "Caller's recording time". page 40.

Note:

- When you select "Greeting only":
 - If you do not record your own message, the unit will play the pre-recorded greeting-only message asking callers to call again later.
 - If you use your own message, record the greeting-only message asking callers to call again later (page 35).

Voicemail service

Voicemail is an automatic answering service offered by your phone service provider. After you subscribe to this service, your phone service provider's voicemail system answers calls for you when you are unavailable to answer the phone or when your line is busy. Messages are recorded by your phone service provider, not your telephone. Please contact your phone service provider for details of this service.

Important:

 To use the voicemail service provided by your phone service provider rather than the unit's answering system, turn off the answering system (page 35). For details, see page 40.

Storing the voicemail (VM) access number

In order to listen to your voicemail messages, you must dial your phone service provider's voicemail access number. Once you have stored your voicemail access number, you can dial it automatically (page 41).

- 1 [MENU]#331
- Enter your access number (24 digits max.). → [SAVE] → [OFF]

Note:

 When storing your voicemail access number and your mailbox password, press
 [A] (Pause) to add pauses (page 14) between the access number and the password as necessary. Contact your phone service provider for the required pause time.

Example:



To erase the voicemail access number

- 1 (MENU)#331
- Press and hold [CLEAR] until all digits are erased. → [SAVE] → [OFF]

Voicemail (VM) tone detection

Your phone service provider sends special signals (sometimes called "voicemail tones" or "stutter tones") to the unit to let you know you have new voicemail messages. If you hear a series of dial tones followed by a continuous dial tone after you press [, you have new voicemail messages. Soon after you hang up a call or after the phone stops ringing, your unit checks the phone line to see if new voicemail messages have been recorded. Turn this feature off when:

Tutti tilis leature on when.

- You do not subscribe to voicemail service.
- Your phone service provider does not send voicemail tones.
- Your phone is connected to a PBX.
 If you are not sure which setting is required, contact your phone service provider.

Turning VM tone detection on/off

The default setting is "on".

- 1 [MENU]#332
- 2 [♣]: Select the desired setting. → [SAVE] → [OFF]

Listening to voicemail messages

When new messages have been recorded, "Voicemail msg. via phone co." is displayed if message indication service is available.

- 1 (MENU)#330
 - The speakerphone turns on.
- 2 Follow the pre-recorded instructions.
- 3 When finished, hang up.

Note:

 You can also use the [ACCESS] soft key, if displayed, to play new voicemail messages.

 If the handset still indicates there are new messages even after you have listened to all new messages, turn it off by pressing and holding # until the handset beeps.

Wall mounting

Note:

 Make sure that the wall and the fixing method are strong enough to support the weight of the unit.

Base unit

 Lead the AC adaptor cord and telephone line cord through the hole in the wall mounting adaptor in the direction of the arrow.




Tuck the telephone line cord inside the wall mounting adaptor (1). Connect the AC adaptor cord and telephone line cord (2)

AC adaptor cord




Insert the hooks on the wall mounting adaptor into holes (**(A)**) and (**(B)**) on the base unit.



For assistance, please visit http://shop.panasonic.com/support

42


4 Adjust the adaptor to hold the base unit, then push it in the direction of the arrow until it clicks into place.






- Mount the unit on a wall then slide down to secure in place.
 - AC adaptor cord
 - This product is compliant with the following wall phone plate sizes (2 types).
 - **B** 83 mm (3 ¹/₄ inches)
 - **6** 102 mm (4 inches)


Fit the slots of the unit onto the corresponding wall phone plate tabs for (①) and (②) respectively.





To remove the wall mounting adaptor


While pushing down the release levers (1), remove the adaptor (2).



Charger

Drive the screws (4) (not supplied) into the wall

B 27.2 mm (1 ¹/₁₆ inches)



Error messages

Display message	Cause/solution
Ask phone company for VM access #	You have not stored the voicemail access number. Store the number (page 41).
Base no power Or No link. Re- connect base AC adaptor.	Confirm the base unit's AC adaptor is connected to the unit and the power outlet correctly. The handset has lost communication with the base unit. Move closer to the base unit and try again. Unplug the base unit's AC adaptor to reset the unit. Reconnect the adaptor and try again. The handset's registration may have been canceled. Re-register the handset (page 32).
Busy	 The called unit is in use. Other units are in use and the system is busy. Try again later. The handset you are using is too far from the base unit. Move closer and try again.
Check tel line	The supplied telephone line cord has not been connected yet or not connected properly. Check the connections (page 9).
Error!!	Recording was too short. Try again.
Invalid	 There is no handset registered to the base unit matching the handset number you entered. The handset is not registered to the base unit. Register the handset (page 32).
Requires subscription to Caller ID.	You must subscribe to a Caller ID service. Once you receive caller information after subscribing to a Caller ID service, this message will not be displayed.
Use rechargeable battery.	 A wrong type of battery such as alkaline or manganese was inserted. Use only the rechargeable Ni-MH batteries noted on page 4, 6.

Troubleshooting

If you still have difficulties after following the instructions in this section, disconnect the base unit's AC adaptor, then reconnect the base unit's AC adaptor. Remove the batteries from the handset, and then insert them into the handset again.

General use

Problem	Cause/solution
The handset does not turn on even after installing charged batteries.	Place the handset on the base unit or charger to turn on the handset.
The unit does not work.	 Make sure the batteries are installed correctly (page 9). Fully charge the batteries (page 10). Check the connections (page 9). Unplug the base unit's AC adaptor to reset the unit. Reconnect the adaptor and try again. The handset has not been registered to the base unit. Register the handset (page 32).
I cannot hear a dial tone.	The base unit's AC adaptor or telephone line cord is not connected. Check the connections. Disconnect the base unit from the telephone line and connect the line to a known working telephone. If the working telephone operates properly, contact our service personnel to have the unit repaired. If the working telephone does not operate properly, contact your phone service provider.
The base unit beeps.	New messages have been recorded. Listen to the new messages (page 36).

Menu list

Problem	Cause/solution
The display is in a language I cannot read.	Change the display language (page 12).
I cannot register a handset to a base unit.	 The maximum number of handsets (6) is already registered to the base unit. Cancel unused handset registrations from the base unit (page 32).

Battery recharge

Problem	Cause/solution
The handset beeps and/or flashes.	Battery charge is low. Fully charge the batteries (page 10).

For assistance, please visit http://shop.panasonic.com/support

TGL43x (en) _1006_ve003. pdf

46

Problem	Cause/solution
I fully charged the batteries, but - still flashes, - is displayed, or - the operating time seems to be shorter.	 Clean the battery ends (⊕, ⊝) and the charge contacts with a dry cloth and charge again. It is time to replace the batteries (page 9).

Making/answering calls, intercom

Problem	Cause/solution
y is displayed.	 The handset is too far from the base unit. Move closer. The base unit's AC adaptor is not properly connected. Reconnect AC adaptor to the base unit. The handset is not registered to the base unit. Register it (page 32).
Noise is heard, sound cuts in and out.	You are using the handset or base unit in an area with high electrical interference. Re-position the base unit and use the handset away from sources of interference. Move closer to the base unit. If you use a DSL/ADSL service, we recommend connecting a DSL/ADSL filter between the base unit and the telephone line jack. Contact your DSL/ADSL provider for details.
The handset or base unit does not ring.	 The ringer volume is turned off. Adjust the ringer volume (page 15, 25). Silent mode is turned on. Turn it off (page 29).
I cannot make a call.	The dialing mode may be set incorrectly. Change the setting (page 13).
I cannot make long distance calls.	Make sure that you have long distance service.

Caller ID/Talking Caller ID

Problem	Cause/solution
Caller information is not displayed.	You must subscribe to Caller ID service. Contact your phone service provider for details. If your unit is connected to any additional telephone equipment such as a Caller ID box or cordless telephone line jack, plug the unit directly into the wall jack. If you use a DSL/ADSL service, we recommend connecting a DSL/ADSL filter between the base unit and the telephone line jack. Contact your DSL/ADSL provider for details. The name display service may not be available in some areas. Contact your phone service provider for details. Other telephone equipment may be interfering with this unit. Disconnect the other equipment and try again.

Problem	Cause/solution
Caller information is displayed or announced late.	 Depending on your phone service provider, the unit may display or announce the caller's information at the 2nd ring or later. Move closer to the base unit.
Caller information is not announced.	 The handset or base unit's ringer volume is turned off. Adjust it (page 15, 25). The Talking Caller ID feature is turned off. Turn it on (page 25). The number of rings for the answering system is set to "2 rings" or "Toll saver". Select a different setting (page 40). If the base unit and another handset are having an intercom call, your handset does not announce caller information.
The caller list/incoming phone numbers are not edited automatically.	The Caller ID number auto edit feature is turned off. Turn it on and try again (page 27). You need to call back the edited number to activate Caller ID number auto edit.
I cannot dial the phone number edited in the caller list.	The phone number you dialed might have been edited incorrectly (for example, the long distance "1" or the area code is missing). Edit the phone number with another pattern (page 34).
Time on the unit has shifted.	Incorrect time information from incoming Caller ID changes the time. Set the time adjustment to "Manual" (off) (page 25).
The 2nd caller's information is not displayed during an outside call.	In order to use Caller ID, call waiting, or Call Waiting Caller ID (CWID), you must first contact your phone service provider and subscribe to the desired service. After subscribing, you may need to contact your phone service provider again to activate this specific service, even if you already subscribed to both Caller ID and Call Waiting with Caller ID services (CWID).

Answering system

Problem	Cause/solution
The unit does not record new messages.	The answering system is turned off. Turn it on (page 35). The message memory is full. Erase unnecessary messages (page 36, 37). The recording time is set to "Greeting only". Change the setting (page 40). Your phone service provider's voicemail service may be answering your calls before the unit's answering system can answer your calls. Change the unit's number of rings setting (page 40) to a lower value, or contact your phone service provider. The answering system will not answer incoming calls while the other devices such as handsets are engaged in a call.
I cannot operate the answering system remotely.	The remote access code is not set. Set the remote access code (page 39). You are entering the wrong remote access code. If you have forgotten your remote access code, enter the remote access code setting to check your current code (page 39). The answering system is turned off. Turn it on (page 39).
The unit does not emit the specified number of rings.	If the ring once setting is turned off (page 19), the number of rings decreases by 1 from the specified number of rings.

Voicemail

Problem	Cause/solution
"Voicemail msg. via phone co." is shown on the handset display. How do I remove this message from the display?	• This notification is displayed when your phone service provider's voicemail service (not the unit's answering system) has recorded a message for you. Typically you can remove this notification from the display by listening to the message. To listen to the message, dial the voicemail number provided by your phone service provider (for most cases, this will be your own phone number), and follow the voice instructions. Depending on your phone service provider, you may need to remove all messages from your voice mailbox to remove the notification. You can also remove this notification by pressing and holding ## until the unit beeps.

Liquid damage

Problem	Cause/solution
Liquid or other form of moisture has entered the handset/base unit.	Disconnect the AC adaptor and telephone line cord from the base unit. Remove the batteries from the handset and leave to dry for at least 3 days. After the handset/base unit are completely dry, reconnect the AC adaptor and telephone line cord. Insert the batteries and charge fully before use. If the unit does not work properly, contact an authorized service center.

Caution:

• To avoid permanent damage, do not use a microwave oven to speed up the drying process.

FCC and other information

This equipment complies with Part 68 of the FCC rules and the requirements adopted by the ACTA. On the bottom of this equipment is a label that contains, among other information, a product identifier in the format US:ACJ--------

If requested, this number must be provided to the telephone company.

- Registration No.....(found on the bottom of the unit)
- Ringer Equivalence No. (REN)......0.1B

A plug and jack used to connect this equipment to the premises wiring and telephone network must comply with the applicable FCC Part 68 rules and requirements adopted by the ACTA. A compliant telephone cord and modular plug is provided with the product. It is designed to be connected to a compatible modular jack that is also compliant.

The RFN is used to determine the number of devices that may be connected to a telephone line. Excessive RENs on a telephone line may result in the devices not ringing in response to an incoming call. In most but not all areas, the sum of RENs should not exceed five (5.0). To be certain of the number of devices that may be connected to a line, as determined by the total RENs, contact the local telephone company. For products approved after July 23, 2001, the REN for the product is part of the product identifier that has the format US:AAAEQ##TXXXX. The digits represented by ## are the REN without a decimal point (e.g., 03 is a REN of 0.3).

If this equipment causes harm to the telephone network, the telephone company will notify you in advance that temporary discontinuance of service may be required. But if advance notice isn't practical, the telephone company will notify the customer as soon as possible. Also, you will be

advised of your right to file a complaint with the FCC if you believe it is necessary.

The telephone company may make changes in its facilities, equipment, operations or procedures that could affect the operation of the equipment. If this happens the telephone company will provide advance notice in order for you to make necessary modifications to maintain uninterrupted service.

If trouble is experienced with this equipment, for repair or warranty information, please contact a Factory Service Center or other Authorized Servicer. If the equipment is causing harm to the telephone network, the telephone company may request that you disconnect the equipment until the problem is resolved.

Connection to party line service is subject to state tariffs. Contact the state public utility commission, public service commission or corporation commission for information.

If your home has specially wired alarm equipment connected to the telephone line, ensure the installation of this equipment does not disable your alarm equipment. If you have questions about what will disable alarm equipment, consult your telephone company or a qualified installer.

This equipment is hearing aid compatible as defined by the FCC in 47 CFR Section 68.316.

When you hold the phone to your ear, noise might be heard in your Hearing Aid. Some Hearing Aids are not adequately shielded from external RF (radio frequency) energy. If noise occurs, use an optional headset accessory or the speakerphone option (if applicable) when using this phone. Consult with your audiologist or Hearing Aid

manufacturer about the availability of Hearing Aids which provide adequate shielding to RF energy commonly emitted by digital devices.

WHEN PROGRAMMING EMERGENCY NUMBERS AND(OR) MAKING TEST CALLS TO EMERGENCY NUMBERS:

- 1) Remain on the line and briefly explain to the dispatcher the reason for the call.
- Perform such activities in the off-peak hours, such as early morning or late evenings.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Privacy of communications may not be ensured when using this phone.

CAUTION:

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this device.

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Some cordless telephones operate at frequencies that may cause interference to nearby TVs and VCRs. To minimize or prevent such interference, the base of the cordless telephone should not be placed near or on top of a TV or VCR. If interference is experienced, move the cordless telephone further away from the TV or VCR. This will often reduce or eliminate interference.

FCC RF Exposure Warning:

- This product complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- To comply with FCC RF exposure requirements, the base unit must be installed and operated 20 cm (8 inches) or more between the product and all person's body.
- This product may not be collocated or operated in conjunction with any other antenna or transmitter.
- For body-worn operation, the handset must be used only with a non-metallic accessory. Use of other accessories may not ensure compliance with FCC RF exposure requirements.

Notice:

 FCC ID can be found inside the battery compartment or on the bottom of the units.

For assistance, please visit http://shop.panasonic.com/support

52


Compliance with TIA-1083 standard:


Telephone handsets identified with this logo have reduced noise and interference when used with T-Coil equipped hearing aids and cochlear implants.





Guía Rápida Española

Guía Rápida Española










57



Customer services

Shop Accessories!

for all your Panasonic gear

http://shop.panasonic.com/support

Get everything you need to get the most out of your Panasonic products

Accessories & Parts for your Camera, Phone, A/V products, TV, Computers & Networking, Personal Care, Home Appliances, Headphones, Batteries, Backup Chargers & more...

Customer Services Directory

For Product Information, Operating Assistance, Parts, Owner's Manuals, Dealer and Service info go to http://shop.panasonic.com/support

For the hearing or speech impaired TTY: 1-877-833-8855

As of June 2015

Limited Warranty (ONLY FOR U.S.A.)

Panasonic Products Limited Warranty

Limited Warranty Coverage (For USA Only)

If your product does not work properly because of a defect in materials or workmanship, Panasonic Corporation of North America (referred to as "the warrantor") will, for the length of the period indicated on the chart below, which starts with the date of original purchase ("warranty period"), at its option either (a) repair your product with new or refurbished parts, (b) replace it with a new or a refurbished equivalent value product, or (c) refund your purchase price. The decision to repair, replace or refund will be made by the warrantor.

Product or Part Name	Parts	Labor
Telephone	One (1) Year	One (1) Year

During the "Labor" warranty period there will be no charge for labor. During the "Parts" warranty period, there will be no charge for parts. This Limited Warranty excludes both parts and labor for non-rechargeable batteries, antennas, and cosmetic parts (cabinet). This warranty only applies to products purchased and serviced in the United States. This warranty is extended only to the original purchaser of a new product which was not sold "as is".

Mail-In Service--Online Repair Request

Online Repair Request

To submit a new repair request and for quick repair status visit our Web Site at http://shop.panasonic.com/support

When shipping the unit, carefully pack, include all supplied accessories listed in the Owner's Manual, and send it prepaid, adequately insured and packed well in a carton box. When shipping Lithium Ion batteries please visit our Web Site at

http://shop.panasonic.com/support as Panasonic is committed to providing the most up to date information. Include a letter detailing the complaint, a return address and provide a daytime phone number where you can be reached. A valid registered receipt is required under the Limited Warranty.

IF REPAIR IS NEEDED DURING THE WARRANTY PERIOD, THE PURCHASER WILL BE REQUIRED TO FURNISH A SALES RECEIPT/PROOF OF PURCHASE INDICATING DATE OF PURCHASE, AMOUNT PAID AND PLACE OF PURCHASE. CUSTOMER WILL BE CHARGED FOR THE REPAIR OF ANY UNIT RECEIVED WITHOUT SUCH PROOF OF PURCHASE.

Limited Warranty Limits and Exclusions

This warranty ONLY COVERS failures due to defects in materials or workmanship, and DOES NOT COVER normal wear and tear or cosmetic damage. The warranty ALSO DOES NOT COVER damages which occurred in shipment, or failures which are caused by products not supplied by the warrantor, or failures which result from accidents, misuse, abuse, neglect, mishandling, misapplication, alteration, faulty installation, set-up adjustments, misadjustment of consumer controls, improper maintenance, power line surge, lightning damage, modification, introduction of sand, humidity or liquids, commercial use such as hotel, office, restaurant, or other business or rental use of the product, or service by anyone other than a Factory Service Center or other Authorized Servicer, or damage that is attributable to acts of God.

THERE ARE NO EXPRESS WARRANTIES EXCEPT AS LISTED UNDER "LIMITED WARRANTY COVERAGE".

THE WARRANTOR IS NOT LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THIS PRODUCT, OR ARISING OUT OF ANY BREACH OF THIS WARRANTY.

(As examples, this excludes damages for lost time, travel to and from the servicer, loss of or damage to media or images, data or other memory or recorded content. The items listed are not exclusive, but for illustration only.)

ALL EXPRESS AND IMPLIED WARRANTIES, INCLUDING THE WARRANTY OF MERCHANTABILITY, ARE LIMITED TO THE PERIOD OF THE LIMITED WARRANTY.

Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the exclusions may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. If a problem with this product develops during or after the warranty period, you may contact your dealer or Service Center. If the problem is not handled to your satisfaction, then write to:

Consumer Affairs Department Panasonic Corporation of North America 661 Independence Pkwy Chesapeake, VA 23320

PARTS AND SERVICE, WHICH ARE NOT COVERED BY THIS LIMITED WARRANTY, ARE YOUR RESPONSIBILITY.

As of June 2015

Index

Groups: 20 Handset Index Deregistration: 32 Name: 32 3-way conference: 16 Registration: 32 A Additional handset: 32 Hold: 15 Alarm: 29 Intercom: 17 Answering calls: 15 Κ Key detector: 26, 28 Answering system Key tone: 26 Call screening: 40 Erasing messages: 36, 37, 39 L Line mode: 27 Greeting message: 35 M Making calls: 14 Greeting only: 40 Missed calls: 33 Listening to messages: 36, 39 Mute: 15 New message alerting: 37 Noise reduction: 16 Number of rings: 40 P Pause: 14 Recording time: 40 Phonebook: 20 Remote access code: 39 Power failure: 10 Remote operation: 38 Redialing: 14 R Ring count: 40 Ringer ID: 21 Toll saver: 40 Ringer tone: 25 Turning on/off: 35 Rotary/pulse service: 16 Auto intercom: 17 S Auto talk: 15, 27 Silent mode: 29 Speed dial: 22 Baby monitor: 30 SP-PHONE (Speakerphone): 14 Battery: 9, 10 Booster (Clarity booster): 16 Talking Caller ID: 33 Temporary tone dialing: 16 Call block: 18 Time adjustment: 25 One ring for blocked call: 19 Transferring calls: 16 Call share: 16, 27 Troubleshooting: 46 Call waiting: 15 TTY: 59 Call Waiting Caller ID: 15 Caller ID number auto edit: 27, 34 VM (Voicemail): 41 Caller ID service: 33 Voice announcement language: 13 Caller list: 33 Voice paging: 17 Caller list edit: 34 Voicemail: 40, 41 Chain dial: 21 Volume CID (Caller ID): 33 Receiver: 14 Conference calls: 16 Ringer (Base unit): 15 Control type: 11 Ringer (Handset): 15, 25 Customer support: 27 Speaker: 14 Date and time: 13 W Wall mounting: 42 Dialing mode: 13 Direct command code: 23 Display Contrast: 26 Language: 12 Eco mode: 10

62

Equalizer: 16 Error messages: 45 Flash: 15. 27

Notes

63

IMPORTANT!

If your product is not working properly. . .

- (1) Reconnect AC adaptor to the base unit.
- 2 Check if telephone line cord is connected.
- (3) Use rechargeable Ni-MH batteries. (Alkaline/Manganese/Ni-Cd batteries CANNOT be used.)
- (4) Read troubleshooting page in the Operating Instructions.



Visit our Web site: http://shop.panasonic.com/support

FAQ and troubleshooting hints are available.

For your future reference

We recommend keeping a record of the following information to assist with any repair under warranty.

Serial No.	Date of purchase	
(found on the bottom of the base unit)		
Name and address of dealer		

Attach your purchase receipt here.

Panasonic Corporation of North America

Two Riverfront Plaza, Newark, NJ 07102-5490

© Panasonic System Networks Co., Ltd. 2015

Printed in Vietnam



PNQX7766ZA

PNQX7766ZA TT1115MG0