


**Class I, Div. 1 and 2
Groups C,D
Class II, Div. 1 and 2
Groups E,F,G‡
Class III**

A-51® HID Mounting Hoods and Fixture Units

Copper-Free Aluminum Fixture with Gray Epoxy Finish. Mounting Hoods in Aluminum and Malleable Iron.*

UL 1598, 844

Type Mounting	Hub Size (Inches)	Catalog Number	
Mounting Hoods			
	Pendant		
	One Hub	1/2	AAP-50
	Rigid or Flexible Mounting	3/4 1	AAP-75 AAP-100
	Ceiling		
	Four Hubs, Three Close-Up Plugs	1/2 3/4 1	AAC-50 AAC-75 AAC-100
		Long Bracket	
Four Hubs, Three Close-Up Plugs		1/2 3/4 1	AALB-50 AALB-75 AALB-100
		Short Bracket	
	Two Hubs, One Close-Up Plug	1/2 3/4	AASB-50 AASB-75
		25° Stanchion (Not UL Listed)	
One Hub		1-1/4 or 1-1/2†	AAN-150†
Fixture Units without Ballasts			
 	100-250 Watt‡		
	100-250W MV; and 175-250W MH		AAU-2MVNS
	400 Watt		
400W MV and MH		AAU-4MVNS	

*Pendant and stanchion mounting hoods are copper-free aluminum. Ceiling and bracket types are malleable iron with aluminum thread adapters. †1-1/2" tapped hub furnished with 1-1/2" to 1-1/4" reducer. ‡250MH and MV fixture with or without reflector and 400W MV fixture with reflector suitable for Class I, Groups C and D; and Class II, Groups E and F only.




**Class I, Div. 1 and 2
Groups C,D
Class II, Div. 1 and 2
Groups E,F,G‡
Class III**

UL 1598, 844

A-51® Factory Sealed HID Fixtures Without Ballasts: 100W-400W; Explosionproof, Dust-Ignitionproof

Mercury Vapor, and Metal Halide Mogul Base Lamps. Suitable for use in Wet Locations.

U.S. Pat 3,675,007 Pat. Can. 1972

	Type Mounting	Hub Size (Inches)	Catalog Number	
	Pendant One Hub Rigid or Flexible Mounting			
		100-250 Watt‡	1/2	AP2550MV
		175, 250W MH;	3/4	AP2575MV
		100, 175, 250W MV.	1	AP25100MV
		400 Watt	1/2	AP4050MV
		400W MV and MH	3/4	AP4075MV
		1	AP40100MV	
	Ceiling Four Hubs and Three Close-Up Plugs			
		100-250 Watt‡	1/2	AC2550MV
		175, 250W MH;	3/4	AC2575MV
		100, 175, 250W MV	1	AC25100MV
		400 Watt	1/2	AC4050MV
		400W MV and MH	3/4	AC4075MV
		1	AC40100MV	
	25° Stanchion One Hub			
		100-250 Watt‡		
		175, 250W MH;	1-1/4 or 1-1/2*	AN25150MV
		100, 175, 250W MV		
400 Watt				
400W MV and MH	1-1/4 or 1-1/2*	AN40150MV		

‡250W MH and MV fixture with or without reflector and 400W MV fixture with reflector suitable for Class I, Groups C and D, and Class II, Groups E and F only. *1-1/2" tapped hub furnished with a 1-1/2" to 1-1/4" reducer.