





# PROTEK Double-Hinged, UL and NEMA Type 4, 4X or

Catalog Number: PTHW362428G2A US List Price (USD): \$3,914.00

#### **Bulletin Number:**

DWDH2



#### Model Code:

23657

## Ship Wt. Std. Pkg. (lbs):

• 195.0

#### Interchangeable:

False

## Industry Standards:

UL 508A Listed; File Number E61997 cUL Listed per CSA C22.2 No. 94; File Number E619967 Solid Door: Type 4 and 12 Window Door: Type 12 Solid Door, Stainless Steel: Type 4, 4X and 12 NEMA / EEMAC: Type 4, 4X or 12 IEC 60529, IP66 or IP55, IK 10

# **Description**

PROTEK Double-Hinged cabinets are an excellent, off-the-shelf choice for mounting 19-in. rack, panel-mounted devices or other electronic equipment. The cabinets are designed to provide both front and rear access to 19-in. rack-mounted equipment. They provide protection against water, dirt, corrosive agents and other contaminants.

## Application:

PROTEK Double-Hinged cabinets are an excellent, off-the-shelf choice for mounting 19-in. rack, panel-mounted devices or other electronic equipment. The cabinets are designed to provide both front and rear access to 19-in. rack-mounted equipment. They provide protection against water, dirt, corrosive agents and other contaminants. PROTEK is an excellent choice for applications where space is at a premium and the only option is wall mounting. PROTEK comes in a broad range of sizes, materials and configurations to meet many demanding applications.

## Features:

- Front and rear access to 19-in. rack equipment provided by three-part design: door, center section and wall section
- Solid door provides complete physical and visual protection
- Window door, made of scratch-resistant safety glass, provides visual monitoring of internal equipment while maintaining equipment protection
- All seams are fully welded and ground smooth
- · Doors, center section and wall section are provided with ground studs to facilitate proper bonding and grounding of the cabinet
- Premium seamless, foam-in-place gasket prevents contaminants from entering the cabinet
- · Keylocking wing knob is included on painted steel cabinet, providing access control to the cabinet; two keys are included with each
- Stainless steel cabinet is provided with a quarter-turn slotted latch
  One set of plated, self-grounding, tapped 10-32 rack angles per EIA universal spacing standards, which can be adjusted front-toback, is provided with each center section of the cabinet; additional tapped- or square-hole rack angles can be added to the cabinet to provide additional mounting
- Ön 28-in. (700 mm) wide enclosures, a 4-in. vertical cable manager with composite fingers is provided on hinge side of cabinet
- · Wall section welded panel studs which accommodate standard panels (steel and wood available), can be ordered separately

#### **Specifications:**

- Doors made of 16 gauge; center and wall sections made of 14 gauge steel. Stainless steel enclosures made from Type 304 stainless steel
- Window made of .25-in. thick, scratch- and impact-resistant safety glass
- Rack angles made of plated 12 gauge steel

- M6 ground studs on door, center and wall sections are masked from paint
  Twenty 10-32 screws included with cabinet
  Foam-in-place gasket made of durable polyurethane

## Finish:

- Pretreated steel coated with RAL 7035 light-gray, low-gloss, lightly textured polyester powder paint
   Stainless steel is provided with a smooth-grain finish

# Load Ratings:

- Center hinged section:
  Height: Maximum Load Rating
  16 in.: 175 lb./79.4 kg
  24 in.: 250 lb./113.4 kg
  36 in.: 300 lb./136.1 kg
  48 in.: 350 lb./158.8 kg
  60 in.: 400 lb./181.4 kg

# Accessories:

- Locks and handlesPanels (steel and wood)
- Grounding kits
  Power Distribution Units (PDUs)
- Rack angles

# **Technical Data**

# PROTEK Double-Hinged, UL and NEMA Type 4, 4X or 12

**Catalog Number** PTHW362428G2A

**Rack Units** 19 F in. 25.65 S in. 1.11 Q in. 15.38 P in. 30.75 CP3220 Optional Steel Panel Optional Wood Panel CP3220W

Additional Rack Angles a PTRA36T or PTRA36S

Description Solid Door AC

## **Documents**



Instruction Manual



3D STEP CAD



2D DXF CAD



**Spec Sheet** 



**Dimension Drawing** 

# Accessories

|                         | Keylocking Quarter-Turn Wing Knob | PTWK     |  |
|-------------------------|-----------------------------------|----------|--|
| DU36<br>EHP PTU368      | Handle Options                    | DL36     |  |
| DU36<br>ELHP<br>PPIJS68 | Handle Options                    | EPL4     |  |
| DJ36<br>ELHP PTI368     | Handle Options                    | ELHP     |  |
|                         | Single-Sided Shelf                | ESH1915V |  |
|                         | Single-Sided Shelf                | ESH1915  |  |
|                         | Single-Sided Shelf                | ESH1917  |  |
|                         | Rack-Mount Steel Shelf            | EMSV1918 |  |
|                         | Rack-Mount Steel Shelf            | EMS1918  |  |
|                         | Pole-Mount Kit                    | CPMK24   |  |
|                         | Cage Nut Package                  | P1032CN  |  |
|                         | Screw Packages                    | AS1032   |  |
|                         | CONCEPT Panels                    | CP3220   |  |
|                         | PROTEK Rack Angles                | PTRA36S  |  |
|                         | PROTEK Rack Angles                | PTRA36T  |  |