

Simpler Installation

Meets Proven Reliability

Electrical Markets

3M™ Cold Shrink QS4 Integrated Splice



The new 3M™ Cold Shrink QS4 Integrated Splice Kit is a premier offering that utilizes our field-proven 3M™ Cold Shrink QS-III Splice Body with additional features that make installation quick and easy. This exciting new product integrates all of the layers of a shielded power cable splice into one compact joint. With this splice, 3M is introducing our new easy-to-use yellow core and new re-jacketing tube. We incorporated our smooth-edged shield sock (non-fraying ends) with optional customizable ground braid.

Product Features and Benefits

Simpler Installation

Integrated Design: The challenge of installation in tight spaces can be solved with this product's shorter parking space. With few components, the installation process is simplified.

Easy-Pulling Installation Core: The new, easier-unwinding, smooth-edged yellow core provides for a simpler installation of the splice with less effort, and less wear and tear on the hands.

Efficient Re-jacketing: The QS4's integrated re-jacketing eliminates additional core and reduces the overall parking space required during installation. The yellow slider sleeve eliminates the need for messy grease to help the installation of the re-jacketing tube.

Customizable Grounding: Some configurations of the new splice come with a factory-installed ground braid that can be customized for specific application needs or work practices, reducing field prep time.

Smooth-Edged Shielding: The smooth-edged shield sock means virtually no fraying or sharp edges to deal with during installation.

Proven Reliability

Built upon 3M's field-proven QS-III Cold Shrink splice body, the QS4 splice is specifically designed for the rigors of the IEEE electrical system. Every splice is factory-tested.

Additional Features

The sock is short circuit tested for 10 cycles at 40kA.

The sock is equivalent to a 1/6 neutral on a 1000 kcmil cable or a 1/3 neutral on a 750 kcmil cable.

Cold Shrink
TECHNOLOGY
Pioneers

Kit Customization Available

3M

The Jacketed Concentric Neutral (JCN) inline splice kits below are designed for joining Jacketed Concentric Neutral (JCN) and Flat Strap Neutral power cables. The splice includes an integrated 7 AWG ground braid for attaching to an external ground wire (ground braid does not extend beyond the end of the re-jacketing after installation).

3M™ Cold Shrink QS4 Integrated Splice (JCN)



Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-15-JCN-2-4/0	051128-60171	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	None
QS4-15-JCN-4/0-500	051128-60173	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG - 500 kcmil (95 - 240 mm ²)	None
QS4-15-JCN-350-750	051128-60175	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-15-JCN-500-1000	051128-60177	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
25/28 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-25-JCN-1-250	051128-60179	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG - 250 kcmil (50 - 120 mm ²)	None
QS4-25-JCN-350-750	051128-60181	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-25-JCN-500-1000	051128-60183	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
35 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-35-JCN-1/0-350	051128-60185	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	None
QS4-35-JCN-350-1000	051128-60187	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 1000 kcmil (185 - 500 mm ²)	None



3M™ Cold Shrink QS4 Integrated Splice with Shearbolt Connector (JCN)

Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-15JCN-QCI-2-4/0	051128-60172	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	QCI 2 - 250
QS4-15JCN-QCI-4/0-500	051128-60174	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG - 500 kcmil (95 - 240 mm ²)	QCI 4/0 - 600
QS4-15JCN-QCI-350-750	051128-60176	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-15JCN-QCI-500-1000	051128-60178	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
25/28 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-25JCN-QCI -1-250	051128-60180	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG - 250 kcmil (50 - 120 mm ²)	QCI 2 - 250
QS4-25JCN-QCI -350-750	051128-60182	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-25JCN-QCI-500-1000	051128-60184	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
35 kV Jacketed Concentric Neutral (JCN) and Flat Strap Neutral Cables				
QS4-35JCN-QCI-1/0-350	051128-60186	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	QCI 1/0 - 350
QS4-35JCN-QCI-350-750	051128-60188	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-35JCN-QCI-500-1000	051128-60189	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000

The Shielded Power (SP) inline splice kits below are designed for joining Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) power cables. The splice includes a 4 AWG, 4 foot long integrated ground braid for attaching to an external ground (factory installed ground braid extends approximately 4 feet beyond the end of the re-jacketing after installation).

3M™ Cold Shrink QS4 Integrated Splice (SP)



Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-15SP-2-4/0-BCA	051128-60568	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	None
QS4-15SP-4/0-500-BCA	051128-60570	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG - 500 kcmil (95 - 240 mm ²)	None
QS4-15SP-350-750-BCA	051128-60531	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-15SP-500-1000-BCA	051128-60533	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
25/28 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-25SP-1-250-BCA	051128-60572	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG - 250 kcmil (50 - 120 mm ²)	None
QS4-25SP-350-750-BCA	051128-60574	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-25SP-500-1000-BCA	051128-60576	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
35 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-35SP-1/0-350-BCA	051128-60578	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	None
QS4-35SP-350-1000-BCA	051128-60580	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 1000 kcmil (185 - 500 mm ²)	None



3M™ Cold Shrink QS4 Integrated Splice with Shearbolt Connector (SP)

Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-15SP-QCI-2-4/0-BCA	051128-60569	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	QCI 2 - 250
QS4-15SP-QCI-4/0-500-BCA	051128-60571	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG - 500 kcmil (95 - 240 mm ²)	QCI 4/0 - 600
QS4-15SP-QCI-350-750-BCA	051128-60532	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-15SP-QCI-500-1000-BCA	051128-60534	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
25/28 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-25SP-QCI-1-250-BCA	051128-60573	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG - 250 kcmil (50 - 120 mm ²)	QCI 2 - 250
QS4-25SP-QCI-350-750-BCA	051128-60575	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-25SP-QCI-500-1000-BCA	051128-60577	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
35 kV Jacketed Concentric Neutral (JCN), Flat Strap Neutral, Tape Shield and Longitudinally Corrugated (LC) Cables				
QS4-35SP-QCI-1/0-350-BCA	051128-60579	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	QCI 1/0 - 350
QS4-35SP-QCI-350-750-BCA	051128-60581	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-35SP-QCI-500-1000-BCA	051128-60582	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000

The Tape Shielded (TS) inline splice kits below are designed for joining Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) power cables. The splice includes a separate 7 AWG U-shaped ground braid that can be attached to the shield with a constant force spring for external grounding.

3M™ Cold Shrink QS4 Integrated Splice (TS)

Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-15TS-2-4/0	051128-60190	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	None
QS4-15TS-4/0-500	051128-60192	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG - 500 kcmil (95 - 240 mm ²)	None
QS4-15TS-350-750	051128-60194	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-15TS-500-1000	051128-60196	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
25/28 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-25TS-1-250	051128-60198	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG- 250 kcmil (50 - 120 mm ²)	None
QS4-25TS-350-750	051128-60200	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	None
QS4-25TS-500-1000	051128-60202	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	None
35 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-35TS-1/0-350	051128-60204	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	None
QS4-35TS-350-1000	051128-60206	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 1000 kcmil (185 - 500 mm ²)	None

3M™ Cold Shrink QS4 Integrated Splice with Shearbolt Connector (TS)

Product	UPC	Primary Insulation O.D. Range	Conductor Size	Connector
15 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-15TS-QCI-2-4/0	051128-60191	0.64 - 1.01" (16,3 - 25,7 mm)	2 - 4/0 AWG (35 - 95 mm ²)	QCI 2 - 250
QS4-15TS-QCI-4/0-500	051128-60193	0.84 - 1.38" (21,3 - 35,1 mm)	4/0 AWG- 500 kcmil (95 - 240 mm ²)	QCI 4/0 - 600
QS4-15TS-QCI-350-750	051128-60195	1.04 - 1.70" (26,4 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-15TS-QCI-500-1000	051128-60197	1.08 - 1.70" (27,4 - 43,2 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
25/28 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-25TS-QCI-1-250	051128-60199	0.84 - 1.36" (21,3 - 34,5 mm)	1 AWG - 250 kcmil (50 - 120 mm ²)	QCI 2 - 250
QS4-25TS-QCI-350-750	051128-60201	1.10 - 1.70" (27,9 - 43,2 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-25TS-QCI-500-1000	051128-60203	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000
35 kV Tape Shield, Wire Shield, UniShield® and Longitudinally Corrugated (LC) Cables				
QS4-35TS-QCI-1/0-350	051128-60205	1.07 - 1.70" (27,2 - 43,2 mm)	1/0 AWG - 350 kcmil (60 - 185 mm ²)	QCI 1/0 - 350
QS4-35TS-QCI-350-750	051128-60207	1.24 - 2.07" (31,5 - 52,6 mm)	350 - 750 kcmil (185 - 325 mm ²)	QCI 350 - 750
QS4-35TS-QCI-500-1000	051128-60208	1.24 - 2.07" (31,5 - 52,6 mm)	500 - 1000 kcmil (240 - 500 mm ²)	QCI 500 - 1000

3M is a trademark of 3M Company.

3M products shown with a flag in this brochure are manufactured in the USA as of OCTOBER, 2013. 3M products offered on a government contract that require country of origin representation must be certified by 3M Trade Compliance. Contact customer service at 800-245-3573 to request a certificate.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



Electrical Markets Division

6801 River Place Blvd.
Austin, TX 78726-9000
800 245 3573
Fax 800 245 0329
www.3M.com/electrical

Please recycle. Printed in USA.
© 3M 2014. All rights reserved.
80-6016-0710-6C