

**Information Sheet**  
**NIMBUS - PBT2 series**  
**Tightening Torque Values**

Cat. No. *	Wire range			Torque (in-lbs)	Wire O.D. (Max) ** (Inches)
	Class B/C Copper Wires	Class B Aluminum Wires	Class H, I, K, M, DLO Copper Wires		
PBT2-xx-250-F	250kcmil - 6 AWG	250kcmil - 6 AWG	H, I, K 4/0 AWG - 6 AWG, M 2/0 AWG - 6 AWG, DLO 3/0 AWG - 6 AWG	335	0.740
PBT2-xx-350-F	350kcmil - 6 AWG	350kcmil - 6 AWG	H, I, K 250kcmil - 6 AWG, M 4/0 AWG - 6 AWG, DLO 262kcmil - 6 AWG	275	0.850
PBT2-xx-600-F	600kcmil - 4 AWG	600kcmil - 4 AWG	H, I, K 350kcmil - 4 AWG, M 4/0 AWG - 4 AWG, DLO 373kcmil - 4 AWG	500	1.100
PBT2-xx-750-F	750kcmil - 4/0 AWG	750kcmil - 4/0 AWG	H, I, K 500kcmil - 3/0 AWG, M 4/0 AWG - 3/0 AWG, DLO 535kcmil - 3/0 AWG	500	1.190

\* xx = Number of conductor openings from 4 to 12

\*\* Upsize to larger Cat. No. if Max. OD of wire (including insulation) exceeds this dimension