



Rittal – Ri4Power Form 2-4




Including
innovations 2009

Low-voltage switchgear
for maximum flexibility

Ri4Power – structured system solutions for the reliable, fast assembly of low-voltage switchgear systems for machines, plant, and buildings. Rittal Ri4Power is the new name in low-voltage switchgear and distribution enclosures under a single roof – in accordance with the worldwide standard (IEC 60 439-1 and IEC 61 439-1/-2).

Ri4Power



Form 1

Low-voltage switchgear without form separation

ISV

Distribution enclosures

Software

Planning, configuration, selection

Form 2-4

Low-voltage switchgear with form separation

Top enclosure system TS 8 in conjunction with busbar systems up to 5500 A as a modular solution.

Applications:

- Process industry
- Water supply/disposal
- Building distribution
- Chemical industry
- Mechanical engineering
- Small power plants
- Wind power



Form 2-4, system examples

from page 9

Complete examples of the principal panel types:

• Circuit-breaker section	9
• Coupling section.....	13
• Outgoing section	17
• Cable chamber.....	21
• Switch-disconnector-fuse section.....	25

Form 2-4 enclosures

from page 28

TS 8 Top enclosure system – System platform of infinite possibilities for Ri4Power Form 2-4

• Benefits of the TS 8 system platform	29
• SV-TS 8 modular enclosures	30
• SV-TS 8 cable chamber enclosures	33
• SV-TS 8 switch-disconnector-fuse enclosures.....	36
• SV-TS 8 busbar enclosures	38

Form 2-4 enclosure system accessories

from page 39

The modular system for fast, perfect, individual configuration. Please also refer to Catalogue 32.

• Enclosure configuration (overview)	39
• Side panels, base/plinths	39
• Baying, front trim panels, cross members	41
• Partial doors, locks	43
• Roof plates, cable entry.....	44
• Front trim panels and assembly kit for switch-disconnector-fuse section.....	46

Form 2-4 compartment

from page 48

TS 8-compatible components for simple assembly of compartments

• System benefits, compartment configuration (overview)	50
• Side panel modules, covers	51
• Compartment divider, mounting bracket	53
• Partial mounting plates	56
• Support frame, punched rails, accessories	56

Form 2-4 busbar systems

from page 62

Tested safety, infinite solution diversity, rapid assembly with RiLine60, Maxi-PLS and Flat-PLS

• System benefits of RiLine60	63
• RiLine60 bar systems, system components, adaptors.....	65
• System benefits of Maxi-PLS and Flat-PLS.....	83
• Maxi-PLS bar systems, system components, connection components	84
• Flat-PLS bar systems, system components, connection components.....	90
• Accessories for RiLine60, Maxi-PLS and Flat-PLS	100

Form 2-4 technical information

from page 115

Detailed dimensions, diagrams and other important information for reliable project-planning

• Regulations and information regarding busbar systems.....	115
• Short-circuit resistance diagrams.....	116
• Rated currents	120
• Planning and configuration of Ri4Power systems	122
• Maxi-PLS, Flat-PLS system components, connection components, dimensions SV-TS 8 enclosures.....	125
• System data	134
• Busbar screw connections to DIN 43 673	141

Form 2-4: Universal in best form



Process industry

- Sewage treatment plant
- Heavy industry (mining, iron, steel)
- Cement works
- Waste disposal industry
- Paper industry
- Chemicals, petrochemicals
- Pharmaceutical industry

Industrial plants

- Automotive industry
- Mechanical engineering
- Shipbuilding, marine engineering

Energy generation

- Small power plants
- Wind and solar power
- Biomass power plants

Buildings, infrastructure

- Schools
- Banks
- Insurance companies
- Data centres
- Football stadiums
- Hospitals
- Festival halls and exhibition buildings
- Airports



1 Circuit-breaker section

- For switchgear from all well-known manufacturers such as Siemens, ABB, Mitsubishi, Moeller, Merlin Gerin, Terasaki
- Use of air and moulded case circuit-breakers

See page 9.

2 Coupling section

- Combination of a circuit-breaker section with a space-saving busbar riser
- Separation into individual busbar sections to boost equipment availability

See page 13.

3 Outgoing section

- Flexible design of the interior installation
- Fully insulated distribution busbars with extensive connection system

See page 17.

4 Cable chamber

- Available from a field width of 300 mm
- Optional cable entry from above or below
- Flexible installation with Rittal system accessories


See page 21.

NEW

5 Switch-disconnector-fuse section

- For switchgear from Jean Müller, Moeller, ABB, Siemens
- Alternatively also suitable for installation of equipment modules from Jean Müller.

See page 25.



Ri4Power Form 2-4 – An individual system for the configuration of type-tested low-voltage switchgear with inner form separation. The flexible combination of Ri4Power field types supports optimum configuration for your applications.



Form 2-4: Switchgear with a high level of safety



1 Cable connection

- Tested connection system
- Clear arrangement of the cable connection points
- Contacting system with no drilling required
- Space-optimised configuration, even for smaller rated currents

2 Busbar infeed

- An extensive range of accessories to cover the busbar
- Fully insulated busbar connection
- Connection accessories for every type of conductor

3 Side busbar riser

- Connection accessories for every type of conductor
- Unobstructed access to the busbar compartment from the front
- For the side infeed of compartments



4 Modular outgoing section

- Safe compartmentalisation
- Logically structured layout of functional units
- Access control, thanks to lockable partial doors
- Combination of control units and power outlet within one enclosure is supported

5 Cable chamber enclosure

- Various options for structured cable routing
- Safe shielding from the compartments
- Solid shielding from the main busbar system


Tested safety

- Type-tested to the internationally valid standard IEC 60 439-1
- Design verification to IEC 61 439-1/-2
- Tests with ASTA certification
- Tested accidental arcing protection to IEC 61 641
- Protection category up to IP 54
- Prevention of accidental arcing

Ri4Power Form 2-4 offers the best possible operator protection. Thanks to extensive busbar insulation and sub-division of the compartments, the occurrence and spread of accidental arcs is largely prevented.







Circuit-breaker section



The circuit-breaker section is used as the feed to switchgear and the output of large currents from switchgear. Busbar systems up to 5500 A with Maxi-PLS or Flat-PLS **are dimensioned and individually configured according to requirements.** The integrated modular concept and high manufacturing quality ensure **fast, time-saving configuration.** The Ri4Power Form 2-4 system is suitable for circuit-breakers from all well-known manufacturers such as Siemens, ABB, Mitsubishi, Moeller, Merlin Gerin and Terasaki. Finally, the compartment divider is assembled, ensuring optimum access to all connection points throughout the entire assembly process.

Note:
Use these examples of a circuit-breaker section to give you ideas. The following information and tools will make project planning easier:

- For diagrams and lists of parts with model numbers for this example, please see page 10/11.
- Software **Rittal Power Engineering** from Version 4.0, see page 123.



Example of a comprehensive circuit-breaker section design with Ri4Power Form 2-4.

Terminal space

- 1** Stepped, assembly-friendly arrangement of the connection bars.
- 2** Cable connection system for optimum connection of all conductor types.
- 3** Flexible positioning of the bars in the connection space thanks to the modular side panel system.

Circuit-breakers

- 4** Circuit-breakers available as fixed or rack-mounted, allowing a choice of positioning.
- 5** Connection systems for ACB air circuit-breakers from all well-known manufacturers (Siemens, ABB, Mitsubishi, Moeller, Merlin Gerin, Terasaki).
- 6** Modular configuration of the compartments, for circuit-breakers and function groups, in accordance with your requirements.

Busbar system

- 7** Maxi-PLS up to 4000 A, alternatively Flat-PLS up to 5500 A.
- 8** Main busbar system 3- or 4-pole.
- 9** Busbar mounting options include: Roof, base or rear panel area, both top and bottom.
- 10** "Section to section connection system" for all busbar systems, with no drilling required.


Form 2-4 system example 1

Circuit-breaker section, component overview




The components required for a circuit-breaker section are comprised of the enclosure, the enclosure system accessories, the compartment and the busbar systems.

Enclosure



Enclosure system accessories




Rittal Power Engineering


The software Rittal Power Engineering from V4.0 is highly recommended for easy, fast configuration of section types and systems. This continuously updated, graphics-oriented software tool supports customer-specific configuration and automatically produces bills of materials, CAD drawings and order lists of equipment and sections. The export interfaces mean that data and drawings are easily transmitted to other programs such as Word or Excel, or to EPLAN Electric P8.

See page 123.

Compartment



Busbar systems



Form 2-4 system example 1

Circuit-breaker section, parts list



Configuration parameters:

Enclosure dimensions
W x H x D: 800 x 2200 x 800 mm,
with base/plinth 200 mm

Roof plate IP 54
Front trim panel IP 2X
Form 4b

Busbar system top
Maxi-PLS 3200, 4-pole,
in roof area,
without cover

PE busbar design 80 x 10 mm

For air circuit-breaker (ACB)
Mitsubishi AE, 3200 A,
4-pole, rack-mounted,
positioned behind the door,
with cable connection system
Maxi-PLS 3200 A, 4-pole

Functional space divider, vented.

Enclosure		Qty.	P. of	Model No.	Page
1	SV-TS 8 modular enclosure, W/H/D: 800 x 2200 x 800 mm	1	1	9670.828	32

Enclosure system accessories

2	Base/plinth components, front and rear, 200 mm high	1	1	8602.800	40
3	Base/plinth trim, side, 200 mm high	1	1	8602.080	40
4	Front trim panel kit, IP 2X, W/H: 800 x 300/100 mm	1	1	9672.038	42
5	Horizontal roof frame bar, W: 800 mm	1	2	9672.008	44
6	Cross member for functional space divider, W: 800 mm	3	5	9671.008	42
7	Solid roof plate, W/D: 800 x 800 mm	1	1	9671.688	44
8	Partial door, W/H: 800 x 600 mm	3	1	9671.186	43
9	Lock with double-bit insert	6	1	9671.130	43


Compartment

10	Functional space side panel module, H/D: 200 x 800 mm	12	6	9673.082	51
11	Functional space side panel module, H/D: 150 x 800 mm	2	6	9673.085	51
12	Functional space side panel module connection space, H/D: 450 x 800 mm	2	2	9673.089	51
13	Mounting bracket for functional space divider for enclosure depth 800 mm	4	8	9673.408	53
14	Mounting bracket for ACB + functional space divider for enclosure depth 800 mm	2	2	9673.428	53
15	Air circuit-breaker support rail Form 2-4 for enclosure width 800 mm	2	2	9673.008	54
	Mounting kit for air circuit-breaker	1	1	9660.970	54
16	Functional space divider for busbar system gland, vented, W/D: 800 x 800 mm	3	4	9673.478	55
	Gland plate for functional space divider, W: 800 mm	3	4	9673.508	55
17	Partial mounting plate, W/H: 800 x 600 mm	1	1	9673.686	56
18	Stacking insulator	25	6	9660.200	105
19	Support rail for stacking insulator for enclosure width 800 mm	5	2	9676.198	105

Busbar systems

20	Busbar support Maxi-PLS 3200	6	3	9650.000	86
	Busbar support Maxi-PLS 3200	2	1	9659.000	86
21	End support Maxi-PLS 3200	6	6	9650.010	86
	End support Maxi-PLS 3200	2	2	9659.010	86
22	System attachment, Maxi-PLS 3200, 4-pole, in roof area	2	2	9650.080	86
23	Busbars Maxi-PLS 3200 691 mm	4	1	9650.231	86
24	Busbars Maxi-PLS 3200 799 mm	4	1	9650.251	86
25	Connection bracket for Maxi-PLS 3200, 3-pole, 3 x 100 x 10 mm, for D: 800 mm	2	1	9659.483	87
	Connection bracket for Maxi-PLS 3200, for N, 3 x 100 x 10 mm, for D: 800 mm	2	1	9659.484	87
26	U contact makers Maxi-PLS 3200, W: 100 mm	3	3	9650.180	87
	U contact maker Maxi-PLS 3200, W: 100 mm	1	1	9659.180	87
	Sliding blocks Maxi-PLS 3200, M12	8	15	9650.990	87
27	Connection kit, top, for ACB, design code 828F8J1H8H6F16	1	1	9676.910	88
28	Connection kit, bottom, for ACB, design code 828F8J1H8H6F16	1	1	9676.912	88
	Screw connection for connection bracket	2	8	9676.963	104
29	Busbars 80 x 10 mm, 792 mm	1	2	9661.180	109
30	PE/PEN combination angles, flat, 40 x 10 mm	2	4	9661.240	109





Coupling section



Note:


Use these examples of a coupling section to give you ideas. The following information and tools will make your individual project planning easier:

- For diagrams and lists of parts with model numbers for this example, please see page 14/15.
- Software **Rittal Power Engineering** from Version 4.0, see page 123.

Disconnecting and connecting main busbar systems in a low-voltage switchgear is the task of a coupling section. For plant with several incomers, this prevents total failure and helps to reduce costs in the event of a malfunction. Similarly, the requirements governing overall short-circuit resistance may be reduced.

Overall, the investment, operating and maintenance costs are reduced, while reliability is increased. In the event of servicing, individual busbar sections can be de-energised without having to switch off the entire system.

The coupling section is a combination of a circuit-breaker section with a busbar riser optionally arranged on the left or right. The large number of identical parts and work stages therefore also translates into **convincing cost and time benefits during assembly.**



Example of a comprehensive coupling section design with Ri4Power Form 2-4.

Coupling switch

- 1** Connection systems for ACB air circuit-breakers from all well-known manufacturers (Siemens, ABB, Mitsubishi, Moeller, Merlin Gerin, Terasaki).
- 2** The same system architecture as the circuit-breaker section reduces the number of different items and the required assembly work.
- 3** Other system accessories facilitate virtually any variant, tailored to the required application.

Busbar riser

- 4** Version with Maxi-PLS or alternatively Flat-PLS.
- 5** Space-saving, modular and flexible arrangement of the busbar riser (on the left, alternatively on the right, or on both sides).

Busbar configuration

- 6** Main busbar routing in the rear. Alternatively, other positions are also supported.
- 7** Option of using the other compartments separately. Flexible design with standard items e.g. for controlling and monitoring the coupling switch.
- 8** Individual selection of the roof plate and front trim panel allows process-optimised population of the switchgear.


Form 2-4 system example 2

Coupling section, component overview




The components required for a coupling section are comprised of the enclosure, the enclosure system accessories, the compartment and the busbar systems.

Enclosure



Enclosure system accessories




Rittal Power Engineering


The software Rittal Power Engineering from V4.0 is highly recommended for easy, fast configuration of section types and systems. This continuously updated, graphics-oriented software tool supports customer-specific configuration and automatically produces bills of materials, CAD drawings and order lists of equipment and sections. The export interfaces mean that data and drawings are easily transmitted to other programs such as Word or Excel, or to EPLAN Electric P8.

See page 123.

Compartment



Busbar systems



Form 2-4 system example 2

Coupling section, parts list



Configuration parameters:

Enclosure dimensions
W x H x D: 800 x 2200 x 800 mm,
200 x 2200 x 800 mm,
with base/plinth 200 mm

Roof plate IP2X vented
Front trim panel IP 2X vented
Form 4b

Busbar system top
Maxi-PLS 2000, 4-pole,
in rear area,
without cover

PE busbar design 80 x 10 mm

For air circuit-breakers (ACB)
ABB, E2, 2500 A,
static installation, 4-pole,
positioned behind the door

Busbar system, bottom
Maxi-PLS 2000, 4-pole,
directly underneath the
circuit-breaker

Functional space divider, vented

Enclosure		Qty.	P. of	Model No.	Page
1	SV-TS 8 mdoular enclosure, W/H/D: 800 x 2200 x 800 mm	1	1	9670.828	32
2	SV-TS 8 busbar enclosure, W/H/D: 200 x 2200 x 800 mm	1	1	9670.228	38

Enclosure system accessories					
3	Base/plinth components, front and rear, 200 mm high	1	1	8602.000	40
4	Base/plinth trim, side, 200 mm high	1	1	8602.080	40
5	Front trim panel kit, IP 2X, W/H: 800 x 100 mm	1	1	9671.038	41
6	Cross member for functional space divider, W: 800 mm	6	5	9671.008	42
7	Roof plate, vented, IP 2X, W/D: 800 x 800 mm	1	1	9659.535	44
	Partial door, W/H: 800 x 200 mm	1	1	9671.182	43
	Partial door, W/H: 800 x 300 mm	2	1	9671.183	43
8	Partial door, W/H: 800 x 600 mm	2	1	9671.186	43
9	Lock with double-bit insert	7	1	9671.130	43
	Baying connectors, external	6	6	8800.490	41
	Angular baying bracket TS/TS	4	4	8800.430	41

Compartment					
10	Punched section w. mounting flange for coupling set section, for encl. width 800 mm	2	2	9674.058	59
11	TS punched section with mounting flange, 23 x 73 mm, for enclosure width 800 mm	1	4	8612.580	Cat. 32, 995
12	Functional space side panel module, H/D: 200 x 800 mm	13	6	9673.082	51
13	Functional space side panel module, H/D: 100 x 800 mm	2	6	9673.081	51
14	Functional space side panel module, H/D: 200 x 600 mm	4	6	9673.062	51
15	Functional space side panel module, H/D: 100 x 600 mm	2	6	9673.061	51
16	Mounting bracket for functional space divider for enclosure depth 800 mm	2	8	9673.408	53
17	Mounting bracket for functional space divider for enclosure depth 600 mm	6	8	9673.406	53
18	Mounting bracket for ACB + functional space divider for enclosure depth 800 mm	2	2	9673.428	53
19	Air circuit-breaker support rail Form 2-4 for enclosure width 800 mm	2	2	9673.008	54
	Mounting kit for air circuit-breaker	1	1	9660.970	54
20	Functional space divider, vented, W/D: 800 x 600 mm	3	4	9673.485	54
21	Functional space divider for busbar system gland, vented, W/D: 800 x 800 mm	2	4	9673.478	55
	Gland plate for functional space divider, W: 800 mm	2	4	9673.508	55
22	Partial mounting plate, W/H: 800 x 200 mm	1	1	9673.682	56
	Partial mounting plate, W/H: 800 x 300 mm	2	1	9673.683	56
23	Stacking insulator	5	6	9660.200	105
24	Support rail for stacking insulator for enclosure width 800 mm	1	2	9676.198	105
25	Mini-TS profile, 17 x 15.5 mm, L: 137.5 mm	2	12	9673.920	57
26	Mini-TS profile, 17 x 15.5 mm, L: 487.5 mm	2	12	9673.953	57
27	Frame connector piece for Mini-TS profile	4	24	9673.901	58
28	Corner connector for Mini-TS profile	2	10	9673.902	58
29	Coupling set mounting kit for enclosure depth 800 mm	1	1	9674.198	59

Busbar systems					
	Busbar support Maxi-PLS 2000	24	3	9640.000	84
30	Busbar support Maxi-PLS 2000, suitable for top-mounting	8	3	9640.160	84
31	End support Maxi-PLS 2000	4	6	9640.010	84
32	System attachment Maxi-PLS 2000/4, rear section, frame chassis	2	2	9640.098	84
	System attachment Maxi-PLS 2000/4, in the roof area	2	2	9640.088	84
33	System attachment Maxi-PLS 2000/4, coupling section	6	2	9649.078	84
34	Busbars Maxi-PLS 2000 725 mm	4	1	9640.241	84
35	Busbars Maxi-PLS 2000 799 mm	4	1	9640.251	84
36	Busbars Maxi-PLS 2000, special length 1299 mm	1	1	9640.368	on request
	Busbars Maxi-PLS 2000, special length 1399 mm	1	1	9640.368	on request
	Busbars Maxi-PLS 2000, special length 1499 mm	1	1	9640.368	on request
	Busbars Maxi-PLS 2000, special length 1599 mm	1	1	9640.368	on request
37	Connection bracket for Maxi-PLS 1600/2000, 3-pole, 2 x 100 x 10 mm	1	1	9640.473	85
	Connection bracket for Maxi-PLS 1600/2000, for N, 2 x 100 x 10 mm	1	1	9640.474	85
38	Connection kit, top, for ACB, design code 828D9A2G4H6D26	1	1	9676.910	88
39	Connection kit, bottom, for ACB, design code 828D9A2G4H6D26	1	1	9676.912	88
	Terminal studs for connector kit	8	8	9676.976	103
	Screw connection for connection bracket	8	8	9676.962	104
40	U contact makers Maxi-PLS 2000, W: 100 mm	8	3	9640.180	85
	Corner bracket Maxi-PLS 2000	4	1	9640.700	102
	Sliding blocks Maxi-PLS 2000, M10	16	15	9640.980	85
	Connection kit Maxi-PLS 2000/3, coupling set in the rear section	1	1	9660.313	102
	Connection kit Maxi-PLS 2000/N, coupling set in the rear section	1	1	9660.314	102
41	Busbars 80 x 10 mm, 992 mm	1	2	9661.100	109
42	PE/PEN combination angles, flat, 40 x 10 mm	2	4	9661.240	109





Form 2-4 system example 3

Outgoing section




Installation of switchgear, power supply outlets or controllers – the **application areas of the outgoing section are very versatile**. With multifunctional components, the individual compartments may be quickly assembled and configured to suit your requirements. The busbar distributor system may be positioned adjacent to, behind or directly in the compartments and is easily and safely connected to the main busbar systems using system components.

The benefits are convincing, both in terms of assembly and during subsequent operation: Simple project planning, fast assembly, flexible adaptation and a high level of safety.

Note:

Use these examples of an outgoing section to give you ideas. The following information and tools will make project planning easier:

- For diagrams and lists of parts with model numbers for this example, please see page 18/19.
- Software **Rittal Power Engineering** from Version 4.0, see page 123.



Example of a comprehensive outgoing section design with Ri4Power Form 2-4.

Distributor busbars

- 1** RiLine60 is ideal for small rated currents. Alternatively, for higher currents, Maxi-PLS or Flat-PLS may be used for the main busbar.
- 2** Simple insulation and cover with standard parts.
- 3** T-connection kits for connecting main and distribution busbar systems.

Compartments with power outlet

- 4** Interior installation individual, flexible and tailored to your requirements.
- 5** Distribution busbar arrangement of the indoor busbar system, alternatively:
 - Behind the compartments/partial mounting plates
 - At the side adjacent to the modular outgoing section to the side infeed into the compartments.
- 6** RiLine60 circuit-breaker adaptor for time-saving, maintenance-friendly installation of circuit-breakers up to 630 A.

Compartments with control units

- 7** Use of control units to your individual requirements.
- 8** For all well-known brands of switchgear from Siemens, ABB, Mitsubishi, Moeller, Merlin Gerin, Terasaki.
- 9** Space-optimised configuration thanks to graduation of the compartment heights.
- 10** Rittal system accessories provide comprehensive installation and numerous design variants depending on the intended application.


Form 2-4 system example 3

Outgoing section, component overview




The components required for an outgoing section are comprised of the enclosure, the enclosure system accessories, the compartment and the busbar systems.

Enclosure



Enclosure system accessories




Rittal Power Engineering


The software Rittal Power Engineering from V4.0 is highly recommended for easy, fast configuration of section types and systems. This continuously updated, graphics-oriented software tool supports customer-specific configuration and automatically produces bills of materials, CAD drawings and order lists of equipment and sections. The export interfaces mean that data and drawings are easily transmitted to other programs such as Word or Excel, or to EPLAN Electric P8.

See page 123.

Compartment



Busbar systems



Form 2-4 system example 3

Outgoing section, parts list



Configuration parameters:

Enclosure dimensions
W x H x D: 600 x 2200 x 600 mm,
with base/plinth 200 mm

Roof plate IP 54, solid
Front trim panel IP 54, solid
Form 4a

Main busbar system
RiLine60, PLS 1600, 4-pole,
in rear section, top,
with busbar cover

PE busbar design 30 x 10 mm

Distributor busbar system
RiLine60, PLS 1600, 4-pole,
in compartment (indoor),
with cover

Functional space divider for
RiLine60, solid

Device-specific design of the
compartments and adaptors

Enclosure	Qty.	P. of	Model No.	Page
1 SV-TS 8 modular enclosure, W/H/D: 600 x 2200 x 600 mm	1	1	9670.626	32

Enclosure system accessories

2 Base/plinth components, front and rear, 200 mm high	1	1	8602.600	40
3 Base/plinth trim, side, 200 mm high	1	1	8602.060	40
4 Front trim panel kit IP 54, W/H: 600 x 100 mm	1	1	9671.016	41
5 Cross member for functional space divider, W: 600 mm	7	5	9671.006	42
6 Solid roof plate, W/D: 600 x 600 mm	1	1	9671.666	44
Partial door, W/H: 600 x 150 mm	1	1	9671.161	43
7 Partial door, W/H: 600 x 300 mm	2	1	9671.163	43
Partial door, W/H: 600 x 400 mm	1	1	9671.164	43
Partial door, W/H: 600 x 600 mm	1	1	9671.166	43
Partial door, W/H: 600 x 250 mm	1	1	9671.167	43
8 Lock with double-bit insert	7	1	9671.130	43

Compartment configuration

9 Functional space side panel module, H/D: 100 x 425 mm	2	6	9673.051	51
10 Functional space side panel module, H/D: 200 x 425 mm	1	6	9673.052	51
11 Functional space side panel module, H/D: 150 x 425 mm	1	6	9673.055	51
Functional space side panel module, H/D: 100 x 600 mm	4	6	9673.061	51
12 Functional space side panel module, H/D: 200 x 600 mm	6	6	9673.062	51
Functional space side panel module, H/D: 150 x 600 mm	1	6	9673.065	51
Functional space side panel module with gland plate, H/D: 200 x 425 mm	1	6	9673.152	51
Functional space side panel module with gland plate, H/D: 150 x 425 mm	1	6	9673.155	51
13 Functional space side panel module with gland plate, H/D: 200 x 600 mm	6	6	9673.162	51
Functional space side panel module with gland plate, H/D: 150 x 600 mm	1	6	9673.165	51
14 Mounting bracket for functional space divider for enclosure depth 425 mm	6	8	9673.405	53
15 Mounting bracket for functional space divider for enclosure depth 600 mm	8	8	9673.406	53
16 Functional space divider for RiLine60, solid, W/D: 600 x 401 mm	7	4	9673.450	55
Partial mounting plate, W/H: 600 x 150 mm	1	1	9673.661	56
17 Partial mounting plate, W/H: 600 x 300 mm	2	1	9673.663	56
Partial mounting plate, W/H: 600 x 400 mm	1	1	9673.664	56
18 Partial mounting plate, W/H: 600 x 600 mm	1	1	9673.666	56
Partial mounting plate, W/H: 600 x 250 mm	1	1	9673.667	56
19 Support frame for DIN rail-mounted devices, W: 600 mm, 2-row	1	1	9674.762	56
20 Mini-TS profile, 17 x 15.5 mm, L: 62.5 mm	2	12	9673.915	57
21 Mini-TS profile, 17 x 15.5 mm, L: 437.5 mm	2	12	9673.952	57
22 Frame connector piece for Mini-TS profile	4	24	9673.901	58
23 Corner connector for Mini-TS profile	2	10	9673.902	58

Busbar systems

24 RiLine60 busbar support PLS 1600 PLUS	7	4	9342.004	76
25 RiLine60 end cover for PLS 1600 PLUS	1	2	9342.074	76
26 Busbar PLS 1600 A, 495 mm long	4	3	3527.000	68
27 RiLine60 base tray for PLS 1600 PLUS	2	2	9342.134	77
28 RiLine60 cover section, L: 1100 mm	2	2	9340.214	77
RiLine60 support panel	14	5	9340.224	77
Circuit-breaker component adaptor 160 A, 690 V, outlet at bottom, 3-pole	1	1	9342.510	72
29 Circuit-breaker component adaptor 160 A, 690 V, outlet at bottom, 4-pole	2	1	9342.514	80
Circuit-breaker component adaptor 250 A, 690 V, outlet at bottom, 4-pole	2	1	9342.614	80
Circuit-breaker component adaptor 630 A, 690 V, outlet at bottom, 3-pole	3	1	9342.710	73
Insert strip, W: 25 mm, for SV 9342.700/710	4	4	9342.720	113
30 Busbar, 30 x 10 mm, for enclosure width 600 mm	1	2	9661.360	109
31 PE/PEN combination angles, 30 x 10 mm	2	4	9661.230	109
32 System attachment for RiLine60 for enclosure width 600 mm	1	1	9674.006	103
33 T-connector RiLine60, 1600 A, 4-pole, indoor, PLS 1600	1	1	9675.166	100
34 Distribution busbar PLS 1600, indoor, for enclosure height 2200 mm	4	1	9675.242	102





Form 2-4 system example 4

Cable chamber




The distribution of cables into and out of the individual compartments is the task of the cable chamber. Depending on the main busbar system chosen, **cable entry may be either from below, above, or below and above.** There are various cable entry glands to choose from for the roof plate. The main busbar system is covered in a contact hazard-proof way, depending on the type and configuration. Ri4Power Form 2-4 offers every conceivable option for designing PE and N distribution busbars. In each case, **the panel builder's requirements are effectively met to**

Note:

Use these examples of a cable chamber to give you ideas. The following information and tools will make project planning easier:

- For diagrams and lists of parts with model numbers for this example, please see page 22/23.
- Software **Rittal Power Engineering** from Version 4.0, see page 123.

perfection.



Example of a comprehensive cable chamber design with Ri4Power Form 2-4.

SV-TS 8 cable chamber enclosure

- 1 Roof plate for cable gland plates, cable entry glands.
- 2 Cover of the main busbar system.
- 3 Mini-TS profiles as an auxiliary construction.
- 4 Main busbar system with RiLine60, alternatively with Maxi-PLS or Flat-PLS.

PE and N distributor busbars

- 5 Busbar supports for PE and N distribution busbars.
- 6 Distribution busbar to match the enclosure heights.
- 7 Supporting structure of Mini-TS sections for individual attachment.

PE/PEN, cable entry, base/plinth

- 8 PE/PEN busbar tailored to the enclosure width. Configurable in various cross-sections.
- 9 PE/PEN combination angles for attaching the PE busbar and incorporating the TS 8 enclosure into the protective measure.
- 10 C rails for cable attachment, alternatively cable clamp rail from right-angle profile.
- 11 Gland plates divided in the depth.
- 12 Base/plinth components, front and rear base/plinth trim, side.


Form 2-4 system example 4

Cable chamber, component overview




The components required for a cable chamber are comprised of the enclosure, the enclosure system accessories, the compartment and the busbar systems.

Enclosure



Enclosure system accessories




Rittal Power Engineering


The software Rittal Power Engineering from V4.0 is highly recommended for easy, fast configuration of section types and systems. This continuously updated, graphics-oriented software tool supports customer-specific configuration and automatically produces bills of materials, CAD drawings and order lists of equipment and sections. The export interfaces mean that data and drawings are easily transmitted to other programs such as Word or Excel, or to EPLAN Electric P8.

See page 123.

Compartment



Busbar systems



Form 2-4 system example 4

Cable chamber, parts list



Configuration parameters:

Enclosure dimensions
W x H x D: 400 x 2200 x 600 mm,
with base/plinth 200 mm

Roof plate for cable gland plates
Form 4a

Main busbar system RiLine60,
PLS 1600, 4-pole,
in rear section, top,
with cover

PE busbar design 30 x 10 mm

PE/N distribution busbar version
PE + N

PE 30 x 10 mm

N 30 x 10 mm

Cable clamp rail

C rail

Enclosure		Qty.	P. of	Model No.	Page
1	SV-TS 8 cable chamber enclosure, W/H/D: 400 x 2200 x 600 mm	1	1	9670.436	35

Enclosure system accessories

2	Base/plinth components, front and rear, 200 mm high	1	1	8602.400	40
3	Base/plinth trim, side, 200 mm high	1	1	8602.060	40
4	Roof plate for cable gland plates, W/D: 400 x 600 mm	1	1	9671.546	44
5	ISV cable entry gland, M25/32/40/50/63	1	1	9665.760	45
6	ISV cable entry gland, with entry fittings	1	1	9665.780	45
7	ISV cable entry gland, solid	1	4	9665.785	45
8	Support rail for TS 8, W: 600 mm	4	2	9676.196	105


Compartment

9	Cover plate for main busbar system, W: 400 mm	1	2	9673.540	52
10	Mini-TS profile, 17 x 15.5 mm, L: 62.5 mm	2	12	9673.915	57
11	Mini-TS profile, 17 x 15.5 mm, L: 262.5 mm	2	12	9673.940	57
12	Mini-TS profile, 17 x 15.5 mm, L: 487.5 mm	2	12	9673.953	57
13	Mini-TS profile, 17 x 15.5 mm, L: 462.5 mm	5	12	9673.960	57
14	Mini-TS profile, 17 x 15.5 mm, L: 662.5 mm	1	12	9673.980	57
15	Frame connector piece for Mini-TS profile	17	24	9673.901	58
16	Corner connector for Mini-TS profile	2	10	9673.902	58
17	T-connector piece for Mini-TS profile	3	24	9673.903	58

Busbar systems

18	RiLine60 busbar support PLS 1600 PLUS	2	4	9342.004	76
19	RiLine60 end cover for PLS 1600 PLUS	1	2	9342.074	76
20	Busbar PLS 1600 A, 495 mm long	4	3	3527.000	68
21	RiLine60 base tray for PLS 1600 PLUS	1	2	9342.134	77
22	RiLine60 cover section, L: 1100 mm	1	2	9340.214	77
	RiLine60 support panel	2	5	9340.224	77
23	Busbar, 30 x 10 mm, for enclosure width 400 mm	1	2	9661.340	109
24	PE/PEN combination angles, 30 x 10 mm	2	4	9661.230	109
25	System attachment for RiLine60 for enclosure width 400 mm	1	1	9674.004	103
26	Distribution busbar 30 x 10 mm, indoor, for enclosure height 2200 mm	2	1	9675.222	102
27	Busbar support N/PE, 2-pole	7	4	9340.040	110





Form 2-4 system example 5

Switch-disconnector-fuse section



The distribution of electrical power with fused switchgear can be achieved compactly and variably with a switch-disconnector-fuse section.

Thanks to the modular Ri4Power configuration system the installation of switch-disconnector-fuse sections sizes 00 to 3 from **Jean Müller or ABB/Siemens** can be fully prepared.

With the device modules from Jean Müller, live-interchangeable control units may also be integrated into the switch-disconnector-fuse section.

The distribution busbars are selectively and economically dimensioned according to requirements. **The main and the distribution busbar system can be configured for short-circuit resistance of up to 100 kA.**

Internal sub-division in the switch-disconnector-fuse section is from Form 1 to Form 4b, depending on customer requirements, thanks to the optional selection of components.

Note:

Use these examples of a switch-disconnector-fuse section to give you ideas. The following information and tools will make project planning easier:

- For diagrams and lists of parts with Model Numbers for this example, please see page 26/27.
- **Rittal Power Engineering** software from Version 4.1, see page 123.



Example of a comprehensive switch-disconnector-fuse section design with Ri4Power Form 2-4.

Busbar system

- 1** Accommodates standard commercially available flat copper bars from 50 x 10 to 100 x 10 mm for rated currents up to 2100 A.
- 2** Connection of the distribution busbars with terminal block, no drilling required.
- 3** Flexible busbar support arrangement on a 25 mm pitch pattern for optimum switch-disconnector-fuse configuration.

Switchgear area

Individual interior configuration for:

- 4** a) Jean Müller Sasil switch-disconnector-fuses, Jean Müller device modules
- 5** b) ABB SlimLine switch-disconnector-fuses/Siemens 3NJ62 switch-disconnector-fuses
- 6** Variable positioning of ventilation trim panels between switch-disconnector-fuses according to manufacturer's instructions.

Cable connection space

- 7** Upgradable to Form 4b with device-specific terminal space covers.
- 8** Application-specific design of PE and N for the distribution busbar system.
- 9** Optional contact hazard protection even without form separation.


Form 2-4 system example 5

Switch-disconnector-fuse section, component overview




The components required for a switch-disconnector-fuse section are comprised of the enclosure, the enclosure system accessories, the compartment and the busbar systems.

Enclosure



Enclosure system accessories




Rittal Power Engineering



The software Rittal Power Engineering from V4.1 is highly recommended for easy, fast configuration of panel types and systems. This continuously updated, graphics-oriented software tool supports customer-specific configuration and automatically produces bills of materials, CAD drawings and order lists of equipment and panels. The export interfaces mean that data and drawings are easily transmitted to other programs such as Word or Excel, or to EPLAN Electric P8.

See page 123.

Compartment



Busbar systems



Form 2-4 system example 5

Switch-disconnector-fuse section, component list



Configuration parameters:

Enclosure dimensions
W x H x D: 1200 x 2200 x 800 mm,
with base/plinth 200 mm

Roof plate IP 2X vented
Front trim panel IP 2X vented
Form 4b

Busbar system top
Flat-PLS 100, 4-pole,
4 x 100 x 10 mm,
reinforced,
in roof section with cover

PE busbar design 80 x 10 mm

For Jean Müller (JM) NH switch-
disconnector-fuses, type Sasil

Enclosure		Qty.	P. of	Model No.	Page
1	SV-TS 8 switch-disconnector-fuse enclosure, W/H/D: 1200 x 2200 x 800 mm	1	1	9670.128	37

Enclosure system accessories					
2	Base/plinth components, front and rear, 200 mm high	1	1	8602.200	40
3	Base/plinth trim, side, 200 mm high	1	1	8602.080	40
4	Front trim panels, switch-disconnector-fuse section, top 350 mm/bottom 150 mm	1	1	9674.340	46
5	Assembly kit for switch-disconnector-fuse section JM, H: 2200 mm	1	1	9674.352	46
6	Maxi-PLS roof plate, vented, W/D: 1200 x 800 mm, 50 mm high, RAL 7035	1	1	9659.555	44
	Baying connector, external	6	6	8800.490	41
	Angular baying bracket TS/TS	4	4	8800.430	41
7	Support rails for TS 8, W/D: 800 mm	4	2	9676.198	105

Compartment					
8	Divider panel, switch-disconnector-fuse section JM/ABB, H/D: 2200 x 800 mm	1	1	9674.328	60
9	Dividing plate for switch-disconnector-fuse section for JM	2	1	9674.346	60
10	Contact hazard protection, switch-disconnector-fuse section, W/D: 1200 x 800 mm	1	1	9674.368	60
11	Functional space side panel module, H/D: 200 x 800 mm	9	6	9673.082	51

Busbar systems					
12	Busbar support Flat-PLS 100 suitable for stabiliser bar	12	1	9676.021	91
13	System attachment for busbar support Flat-PLS 100, in roof/bases, 3-/4-pole, D: 800 mm	3	2	9674.184	90
14	Busbar stabiliser bar, 4-pole	3	2	9676.025	91
15	Busbars E-Cu, 100 x 10 x 2400 mm	8	3	3590.010	110
	Busbar claws up to 4 x 100 x 10 mm, 1-pole	12	1	9676.016	93
16	Contact piece for Flat-PLS, 4 bars, W: 60 mm	4	1	9676.546	96
17	Connection bracket, switch-disconnector-fuse section, Flat-PLS 100, L1 – 3, D: 800 mm	1	1	9674.457	108
	Connection bracket, switch-disconnector-fuse section, Flat-PLS 100, N, D: 800 mm	1	1	9674.458	108
18	End support for switch-disconnector-fuse section, 3-/4-pole, bar width: 100 mm	1	1	9674.430	106
19	Busbar support for switch-disconnector-fuse section, 3-/4-pole, bar width: 100 mm	6	1	9674.410	106
20	Distributor bar for switch-disconnector-fuse section, W/H: 100/2200 mm	4	1	9674.420	106
21	Terminal block, distribution busbar for switch-disconnector-fuse section, 80/100 mm	4	1	9674.488	108
22	Cover for distribution busbar, switch-disconnector-fuse section JM, enclosure height: 2000/2200 mm	1	1	9674.380	107
	Punched rail for distribution busbar cover, switch-disconnector-fuse section JM, enclosure height: 2000/2200 mm	1	1	9674.381	107
23	Busbar support up to 1600 A, 3-pole, 185 mm bar centre distance for busbars E-Cu 50 x 10 to 80 x 10 mm	2	2	3052.000	Cat. 32, 391
24	Distribution busbar for switch-disconnector-fuse section, W/H: 80/2000 mm	1	1	9674.408	106
25	Busbars, 1192 x 80 x 10 mm, for enclosure width 1200 mm	1	2	9661.120	109
26	PE/PEN combination angles, flat, E-Cu 40 x 10 mm	2	4	9661.240	109




Top enclosure, top flexibility, top efficient: TS 8

With the TS 8 enclosure system, every enclosure is a specialist – however exceptional the task. By combining Ri4Power and busbar components with general system accessories, it is possible to create infinite possibilities in the separation of Form 2-4 – the TS 8 system punching is the key.

System platform TS 8 Top enclosure system



The enclosure system with the efficiency of infinite possibilities. Unbeatable in terms of space utilisation, bayability, interior installation and fast assembly.



Universal interior installation: Frame sections, slotted on a 25 mm pitch pattern. Two symmetrical levels for maximum space utilisation in the width and depth.



Uninhibited access from all sides: Doors are possible at the front, rear and sides. 4-point hinge and lock system.



Bayable on all sides: Around corners, to the front, rear, left, right and if necessary, even upwards.

Ri4Power configuration



Ri4Power system solutions are based on the TS 8 Top enclosure system. Winning features: Compatibility with all power distribution components.



The proven TS 8 pitch pattern is used for many Ri4Power Form 2-4 components, thus enabling the use of TS 8 system accessories.



Undoubtedly convincing – **RiLine60:** effective space utilisation, extensive safety back-ups, all-round contact hazard protection, safe and fast contacting.



Low voltage switchgear with **Maxi-PLS and Flat-PLS.** Future-oriented, type-tested modular systems offer exceptional fast assembly and safety.

Standard accessories



Rittal system accessories for individuality, perfection and speed when solving your tasks.



Base/plinth components (front and rear) combined with trim panels (side) or used to link two base/plinths.




Quick assembly: Door-operated switch and lights – simply fit and secure – and it's done.



Roof plate options for every type of cable entry and ventilation.

Form 2-4 enclosures

SV-TS 8 modular enclosures (height 1800 mm)



Modular enclosure frame for installation with partial doors and internal separation.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm

Surface finish:

Enclosure frame: Dipcoat-primed
Rear panel: Dipcoat-primed, powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54, depending on the roof plate, front trim panels and side panel.

Supply includes:

Enclosure frame with rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 130.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	400	600	800	Page
Height (H) mm		1800	1800	1800	
Depth (T) mm		600	600	600	
Model No. SV	1	9670.486	9670.686	9670.886	
Weight (kg)		42.0	53.0	58.0	

Base/plinth						
1 Components front and rear	Height 100 mm	1 set	8601.400	8601.600	8601.800	40
	Height 200 mm	1 set	8602.400	8602.600	8602.800	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	40


Also required												
3 Side panels for protection category	IP 55	2	8186.235	8186.235	8186.235	39						
	IP 2X	2	9671.986	9671.986	9671.986	39						
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.996	39					
4 Roof plates for protection category	IP 55	1	9671.646	9671.666	9671.686	44						
	IP 43	1	9671.746	9671.766	9671.786	44						
	IP 2X	1	9671.446	9660.235	9660.245	44						
Roof plates for cable entry gland							1	9671.546	9665.903	9671.586	44	
5 Front trim panels for protection category	IP 54	1 set	9671.014	9671.016	9671.018	41						
	IP 2X	1 set	9671.034	9671.036	9671.038	41						
	Upgrade kit for front panels IP 2X	IP 43	1 set	9671.044	9671.046	9671.048	41					
Partial doors for clearance height with front trim panel 100/100 mm							1	9671.156	9671.176	9671.196	43	
5 Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	9672.014	9672.016	9672.018	42						
	IP 2X	1 set	9672.034	9672.036	9672.038	42						
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	9672.024	9672.026	9672.028	42						
	IP 2X	1 set	9672.044	9672.046	9672.048	42						
Upgrade kit for front trim panels 300/100 mm IP 2X							IP 43	1 set	9672.054	9672.056	9672.058	42
Partial doors for clearance height with front trim panel 300/100 mm							1	–	–	–		
Partial doors for modular configuration							1	■	■	■	43	
Angular baying brackets							4		8800.430		41	
Baying connectors, external							6		8800.490		41	

Accessories	
Enclosure configuration	39 – 46
Compartment configuration	50 – 61
Components	65 – 114

¹⁾Pack sufficient for 1 pack of side panels.

Form 2-4 enclosures

SV-TS 8 modular enclosures (height 2000 mm)



Modular enclosure frame for installation with partial doors and internal separation.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm

Surface finish:

Enclosure frame: Dipcoat-primed
Rear panel: Dipcoat-primed, powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54, depending on the roof plate, front trim panels and side panel.

Supply includes:

Enclosure frame with rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 130.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	400	600	800	400	600	800	Page
Height (H) mm		2000	2000	2000	2000	2000	2000	
Depth (T) mm		600	600	600	800	800	800	
Model No. SV	1	9670.406	9670.606	9670.806	9670.408	9670.608	9670.808	
Weight (kg)		43.8	54.0	59.2	43.8	53.7	64.2	

Base/plinth									
1 Components front and rear	Height 100 mm	1 set	8601.400	8601.600	8601.800	8601.400	8601.600	8601.800	40
	Height 200 mm	1 set	8602.400	8602.600	8602.800	8602.400	8602.600	8602.800	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	8601.080	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	8602.080	8602.080	8602.080	40

Also required									
3 Side panels for protection category	IP 55	2	8106.235	8106.235	8106.235	8108.235	8108.235	8108.235	39
	IP 2X	2	9671.906	9671.906	9671.906	9671.908	9671.908	9671.908	39
	Upgrade kit for side panels IP 2X	2 sets ¹⁾	9671.996	9671.996	9671.996	9671.998	9671.998	9671.998	39
4 Roof plates for protection category	IP 55	1	9671.646	9671.666	9671.686	9671.648	9671.668	9671.688	44
	IP 43	1	9671.746	9671.766	9671.786	9671.748	9671.768	9671.788	44
	IP 2X	1	9671.446	9660.235	9660.245	9671.448	9659.525	9659.535	44
5 Front trim panels for protection category	IP 54	1 set	9671.014	9671.016	9671.018	9671.014	9671.016	9671.018	41
	IP 2X	1 set	9671.034	9671.036	9671.038	9671.034	9671.036	9671.038	41
	Upgrade kit for front panels IP 2X	1 set	9671.044	9671.046	9671.048	9671.044	9671.046	9671.048	41
Partial doors for clearance height with front trim panel 100/100 mm	IP 43	1	9671.158	9671.178	9671.198	9671.158	9671.178	9671.198	43
5 Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	9672.014	9672.016	9672.018	9672.014	9672.016	9672.018	42
	IP 2X	1 set	9672.034	9672.036	9672.038	9672.034	9672.036	9672.038	42
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	9672.024	9672.026	9672.028	9672.024	9672.026	9672.028	42
	IP 2X	1 set	9672.044	9672.046	9672.048	9672.044	9672.046	9672.048	42
Upgrade kit for front trim panels 300/100 mm IP 2X	IP 43	1 set	9672.054	9672.056	9672.058	9672.054	9672.056	9672.058	42
Partial doors for clearance height with front trim panel 300/100 mm		1	9671.156	9671.176	9671.196	9671.156	9671.176	9671.196	43
Partial doors for modular configuration		1	■	■	■	■	■	■	43
Angular baying brackets		4	8800.430						41
Baying connectors, external		6	8800.490						41


Accessories	
Enclosure configuration	39 – 46
Compartment configuration	50 – 61
Components	65 – 114

¹⁾ Pack sufficient for 1 pack of side panels.

System examples Page 9 – 27

Form 2-4 enclosures

SV-TS 8 modular enclosures (height 2200 mm)



Modular enclosure frame for installation with partial doors and internal separation.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm

Surface finish:

Enclosure frame: Dipcoat-primed
Rear panel: Dipcoat-primed, powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54, depending on the roof plate, front trim panels and side panel.

Supply includes:

Enclosure frame with rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 130.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	400	600	800	400	600	800	Page
Height (H) mm		2200	2200	2200	2200	2200	2200	
Depth (T) mm		600	600	600	800	800	800	
Model No. SV	1	9670.426	9670.626	9670.826	9670.428	9670.628	9670.828	
Weight (kg)		43.2	54.0	59.4	46.1	55.8	66.0	

Base/plinth									
1 Components front and rear	Height 100 mm	1 set	8601.400	8601.600	8601.800	8601.400	8601.600	8601.800	40
	Height 200 mm	1 set	8602.400	8602.600	8602.800	8602.400	8602.600	8602.800	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	8601.080	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	8602.080	8602.080	8602.080	40

Also required									
3 Side panels for protection category	IP 55	2	8126.235	8126.235	8126.235	8128.235	8128.235	8128.235	39
	IP 2X	2	9671.926	9671.926	9671.926	9671.928	9671.928	9671.928	39
	Upgrade kit for side panels IP 2X	2 sets ¹⁾	9671.996	9671.996	9671.996	9671.998	9671.998	9671.998	39
4 Roof plates for protection category	IP 55	1	9671.646	9671.666	9671.686	9671.648	9671.668	9671.688	44
	IP 43	1	9671.746	9671.766	9671.786	9671.748	9671.768	9671.788	44
	IP 2X	1	9671.446	9660.235	9660.245	9671.448	9659.525	9659.535	44
Roof plates for cable entry gland		1	9671.546	9665.903	9671.586	9671.548	9671.568	9671.588	44
5 Front trim panels for protection category	IP 54	1 set	9671.014	9671.016	9671.018	9671.014	9671.016	9671.018	41
	IP 2X	1 set	9671.034	9671.036	9671.038	9671.034	9671.036	9671.038	41
	Upgrade kit for front panels IP 2X	1 set	9671.044	9671.046	9671.048	9671.044	9671.046	9671.048	41
Partial doors for clearance height with front trim panel 100/100 mm		1	9671.150	9671.170	9671.190	9671.150	9671.170	9671.190	43
5 Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	9672.014	9672.016	9672.018	9672.014	9672.016	9672.018	42
	IP 2X	1 set	9672.034	9672.036	9672.038	9672.034	9672.036	9672.038	42
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	9672.024	9672.026	9672.028	9672.024	9672.026	9672.028	42
	IP 2X	1 set	9672.044	9672.046	9672.048	9672.044	9672.046	9672.048	42
Upgrade kit for front trim panels 300/100 mm IP 2X	IP 43	1 set	9672.054	9672.056	9672.058	9672.054	9672.056	9672.058	42
Partial doors for clearance height with front trim panel 300/100 mm		1	9671.158	9671.178	9671.198	9671.158	9671.178	9671.198	43
Partial doors for modular configuration		1	■	■	■	■	■	■	43
Angular baying brackets		4	8800.430						41
Baying connectors, external		6	8800.490						41


Accessories									
Enclosure configuration									39 – 46
Compartment configuration									50 – 61
Components									65 – 114

¹⁾ Pack sufficient for 1 pack of side panels.

System examples Page 9 – 27

Form 2-4 enclosures

SV-TS 8 cable chamber enclosures (height 1800 mm)



Enclosure frame for the management of incoming and outgoing cables. The use of a roof plate with cable gland plates additionally allows cables to be fed in from above.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm
Door: 2.0 mm

Surface finish:

Enclosure frame:
Dipcoat-primed
Door and rear panel:
Dipcoat-primed,
powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54,
depending on the roof plate and the side panel.

Supply includes:

Enclosure frame with door, rear panel and gland plates.



Accessories:

System accessories,
see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings,
see page 131.

Technical information,
see page 134 – 140.

Width (B) mm	Packs of	300	400	600	Page
Height (H) mm		1800	1800	1800	
Depth (T) mm		600	600	600	
Model No. SV	1	9670.396	9670.496	9670.696	
Weight (kg)		47.0	49.5	62.0	

Base/plinth						
1 Components front and rear	Height 100 mm	1 set	8601.915	8601.400	8601.600	40
	Height 200 mm	1 set	8602.915	8602.400	8602.600	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	40
Also required						
3 Side panels for protection category	IP 55	2	8186.235	8186.235	8186.235	39
	IP 2X	2	9671.986	9671.986	9671.986	39
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.996
4 Roof plates for protection category	IP 55	1	9671.636	9671.646	9671.666	44
	IP 43	1	9671.736	9671.746	9671.766	44
	Roof plates for cable entry gland	1	9671.536	9671.546	9665.903	44
Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	–	9672.014	9672.016	42
	IP 2X	1 set	–	9672.034	9672.036	42
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	–	9672.024	9672.026	42
	IP 2X	1 set	–	9672.044	9672.046	42
Upgrade kit for front trim panels 300/100 mm IP 2X	IP 43	1 set	–	9672.054	9672.056	42
Partial doors for clearance height with front trim panel 300/100 mm		1	–	–	–	
Angular baying brackets		4		8800.430		41
Baying connectors, external		6		8800.490		41


Accessories	
Enclosure configuration	39 – 46
Compartment configuration	50 – 61
Components	65 – 114

Lock systems	
Standard double-bit lock may be exchanged for a lock with security cylinder/T handles, see page 43.	

¹⁾Pack sufficient for 1 pack of side panels.

Form 2-4 enclosures

SV-TS 8 cable chamber enclosures (height 2000 mm)



Enclosure frame for the management of incoming and outgoing cables. The use of a roof plate with cable gland plates additionally allows cables to be fed in from above.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm
Door: 2.0 mm

Surface finish:

Enclosure frame:
Dipcoat-primed
Door and rear panel:
Dipcoat-primed,
powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54,
depending on the roof plate and the side panel.

Supply includes:

Enclosure frame with door, rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 131.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	300	400	600	300	400	600	Page
Height (H) mm		2000	2000	2000	2000	2000	2000	
Depth (T) mm		600	600	600	800	800	800	
Model No. SV	1	9670.316	9670.416	9670.616	9670.318	9670.418	9670.618	
Weight (kg)		48.5	53.8	69.4	50.4	55.9	74.0	

Base/plinth									
1 Components front and rear	Height 100 mm	1 set	8601.915	8601.400	8601.600	8601.915	8601.400	8601.600	40
	Height 200 mm	1 set	8602.915	8602.400	8602.600	8602.915	8602.400	8602.600	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	8601.080	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	8602.080	8602.080	8602.080	40

Also required									
3 Side panels for protection category	IP 55	2	8106.235	8106.235	8106.235	8108.235	8108.235	8108.235	39
	IP 2X	2	9671.906	9671.906	9671.906	9671.908	9671.908	9671.908	39
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.996	9671.998	9671.998	39
4 Roof plates for protection category	IP 55	1	9671.636	9671.646	9671.666	9671.638	9671.648	9671.668	44
	IP 43	1	9671.736	9671.746	9671.766	9671.738	9671.748	9671.768	44
	Roof plates for cable entry gland		1	9671.536	9671.546	9665.903	9671.538	9671.548	44
Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	9672.013	9672.014	9672.016	9672.013	9672.014	9672.016	42
	IP 2X	1 set	9672.033	9672.034	9672.036	9672.033	9672.034	9672.036	42
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	9672.023	9672.024	9672.026	9672.023	9672.024	9672.026	42
	IP 2X	1 set	9672.043	9672.044	9672.046	9672.043	9672.044	9672.046	42
Upgrade kit for front trim panels 300/100 mm IP 2X	IP 43	1 set	9672.053	9672.054	9672.056	9672.053	9672.054	9672.056	42
Partial doors for clearance height with front trim panel 300/100 mm		1	9671.126	9671.156	9671.176	9671.126	9671.156	9671.176	43
Angular baying brackets		4				8800.430			41
Baying connectors, external		6				8800.490			41


Accessories		
Enclosure configuration		39 – 46
Compartment configuration		50 – 61
Components		65 – 114

Lock systems	
Standard double-bit lock may be exchanged for a lock with security cylinder/T handles, see page 43.	

¹⁾Pack sufficient for 1 pack of side panels.

Form 2-4 enclosures

SV-TS 8 cable chamber enclosures (height 2200 mm)



Enclosure frame for the management of incoming and outgoing cables. The use of a roof plate with cable gland plates additionally allows cables to be fed in from above.

Material:

Sheet steel
Enclosure frame, rear panel and gland plates: 1.5 mm
Door: 2.0 mm

Surface finish:

Enclosure frame:
Dipcoat-primed
Door and rear panel:
Dipcoat-primed,
powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 54,
depending on the roof plate and the side panel.

Supply includes:

Enclosure frame with door, rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 131.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	300	400	600	300	400	600	Page
Height (H) mm		2200	2200	2200	2200	2200	2200	
Depth (T) mm		600	600	600	800	800	800	
Model No. SV	1	9670.336	9670.436	9670.636	9670.338	9670.438	9670.638	
Weight (kg)		47.8	57.3	75.8	50.6	61.0	80.7	

Base/plinth									
1 Components front and rear	Height 100 mm	1 set	8601.915	8601.400	8601.600	8601.915	8601.400	8601.600	40
	Height 200 mm	1 set	8602.915	8602.400	8602.600	8602.915	8602.400	8602.600	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.060	8601.080	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.060	8602.080	8602.080	8602.080	40
Also required									
3 Side panels for protection category	IP 55	2	8126.235	8126.235	8126.235	8128.235	8128.235	8128.235	39
	IP 2X	2	9671.926	9671.926	9671.926	9671.928	9671.928	9671.928	39
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.996	9671.998	9671.998	39
4 Roof plates for protection category	IP 55	1	9671.636	9671.646	9671.666	9671.638	9671.648	9671.668	44
	IP 43	1	9671.736	9671.746	9671.766	9671.738	9671.748	9671.768	44
	Roof plates for cable entry gland		1	9671.536	9671.546	9665.903	9671.538	9671.548	9671.568
Front trim panels, top 300 mm/ bottom 100 mm for protection category	IP 54	1 set	9672.013	9672.014	9672.016	9672.013	9672.014	9672.016	42
	IP 2X	1 set	9672.033	9672.034	9672.036	9672.033	9672.034	9672.036	42
Front trim panels, top 100 mm/ bottom 300 mm for protection category	IP 54	1 set	9672.023	9672.024	9672.026	9672.023	9672.024	9672.026	42
	IP 2X	1 set	9672.043	9672.044	9672.046	9672.043	9672.044	9672.046	42
Upgrade kit for front trim panels 300/100 mm IP 2X	IP 43	1 set	9672.053	9672.054	9672.056	9672.053	9672.054	9672.056	42
Partial doors for clearance height with front trim panel 300/100 mm		1	9671.128	9671.158	9671.178	9671.128	9671.158	9671.178	43
Angular baying brackets		4	8800.430						41
Baying connectors, external		6	8800.490						41


Accessories	
Enclosure configuration	39 – 46
Compartment configuration	50 – 61
Components	65 – 114

Lock systems	
Standard double-bit lock may be exchanged for a lock with security cylinder/T handles, see page 43.	

¹⁾Pack sufficient for 1 pack of side panels.

Form 2-4 enclosures

SV-TS 8 switch-disconnector-fuse enclosure (height 2000 mm)



Enclosure frame for assembly with mounting kit and distribution busbar system to install switch-disconnector-fuses from Jean Müller Sasil or ABB SlimLine. Optionally with inner separation in a modular design up to Form 4b.

Material:

Sheet steel
Enclosure frame, roof, rear panel and gland plates: 1.5 mm
Door: 2.0 mm

Surface finish:

Enclosure frame: Dipcoat-primed
Door, roof and rear panel: Dipcoat-primed, powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 3X, depending on the roof plate, front trim panels and side panel.

Supply includes:

Enclosure frame prepared for the installation of switch-disconnector-fuse section components with door, roof, rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 132.



Technical information, see page 134 – 140.

Width (B) mm	Packs of	1000	1200	1000	1200	Page	
Height (H) mm		2000	2000	2000	2000		
Depth (T) mm		600	600	800	800		
Model No. SV	1	9670.006	9670.106	9670.008	9670.108		
Weight (kg)		97.0	116.0	104.0	123.0		
Base/plinth							
1 Components front and rear	Height 100 mm	1 set	8601.000	8601.200	8601.000	8601.200	40
	Height 200 mm	1 set	8602.000	8602.200	8602.000	8602.200	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.080	8602.080	40
Also required							
3 Side panels for protection category	IP 55	2	8106.235	8106.235	8108.235	8108.235	39
	IP 2X	2	9671.906	9671.906	9671.908	9671.908	39
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.998	9671.998
4 Front trim panels, top 350 mm/ bottom 150 mm for protection category	IP 3X	1 set	9674.340	9674.340	9674.340	9674.340	46
	Front trim panels, top 150 mm/ bottom 350 mm for protection category	IP 3X	1 set	9674.342	9674.342	9674.342	9674.342
Contact hazard protection, cable chamber		1 set	9674.362	9674.366	9674.364	9674.368	60
Angular baying brackets		4	8800.430				41
Baying connectors, external		6	8800.490				41
Accessories							
5 Roof plates for protection category	IP 2X	1	9660.255	9660.265	9659.545	9659.555	44
	Roof plates with pressure relief function ²⁾	1	9660.955	9660.965	–	–	44
Enclosure configuration							39 – 46
Compartment configuration							50 – 61
Components							65 – 114

¹⁾ Pack sufficient for 1 pack of side panels.

²⁾ Other sizes available on request.

SV-TS 8 switch-disconnector-fuse enclosure (height 2200 mm)



Enclosure frame for assembly with mounting kit and distribution busbar system to install switch-disconnector-fuses from Jean Müller Sasil or ABB SlimLine. Optionally with inner separation in a modular design up to Form 4b.

Material:

Sheet steel
Enclosure frame, roof, rear panel and gland plates: 1.5 mm
Door: 2.0 mm

Surface finish:

Enclosure frame:
Dipcoat-primed
Door, roof and rear panel:
Dipcoat-primed, powder-coated in textured RAL 7035 on the outside
Gland plates: Zinc-plated

Protection category:

Up to IP 3X, depending on the roof plate, front trim panels and side panel.

Supply includes:

Enclosure frame prepared for the installation of switch-disconnector-fuses with door, roof, rear panel and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 132.

Technical information, see page 134 – 140.


Width (B) mm	Packs of	1000	1200	1000	1200	Page	
Height (H) mm		2200	2200	2200	2200		
Depth (T) mm		600	600	800	800		
Model No. SV	1	9670.026	9670.126	9670.028	9670.128		
Weight (kg)		102.0	122.0	109.0	129.0		
Base/plinth							
1 Components front and rear	Height 100 mm	1 set	8601.000	8601.200	8601.000	8601.200	40
	Height 200 mm	1 set	8602.000	8602.200	8602.000	8601.200	40
2 Trim panels sides	Height 100 mm	1 set	8601.060	8601.060	8601.080	8601.080	40
	Height 200 mm	1 set	8602.060	8602.060	8602.080	8602.080	40
Also required							
3 Side panels for protection category	IP 55	2	8126.235	8126.235	8128.235	8128.235	39
	IP 2X	2	9671.926	9671.926	9671.928	9671.928	39
	Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.998	9671.998
4 Front trim panels, top 350 mm/ bottom 150 mm for protection category	IP 3X	1 set	9674.340	9674.340	9674.340	9674.340	46
	Front trim panels, top 150 mm/ bottom 350 mm for protection category	IP 3X	1 set	9674.342	9674.342	9674.342	9674.342
Contact hazard protection, cable chamber		1 set	9674.362	9674.366	9674.364	9674.368	60
Angular baying brackets		4	8800.430				41
Baying connectors, external		6	8800.490				41
Accessories							
5 Roof plates for protection category	IP 2X	1	9660.255	9660.265	9659.545	9659.555	44
	Roof plates with pressure relief function ²⁾	1	9660.955	9660.965	–	–	44
Enclosure configuration							39 – 46
Compartment configuration							50 – 61
Components							65 – 114

¹⁾ Pack sufficient for 1 pack of side panels.

²⁾ Other sizes available on request.

Form 2-4 enclosures

SV-TS 8 busbar enclosures (width 200 mm)



Empty enclosure for baying to TS 8 enclosures, to accommodate vertical busbar systems.

Material:

Sheet steel enclosure frame with front trim panel, rear panel and roof plate and gland plate: 1.5 mm

Surface finish:

Enclosure frame, gland plate, roof plate:
Dipcoat-primed and powder-coated in textured RAL 7035
Rear panel, front trim panel:
Dipcoat-primed and powder-coated in textured RAL 7035

Protection category:

Up to IP 55

Supply includes:

Enclosure frame with front trim panel, rear panel, roof and gland plates.



Accessories:

System accessories, see Cat. 32, page 890.

Standard:

Type-tested in accordance with IEC 60 439-1.
Design verification in accordance with IEC 61 439-1/-2.

Detailed drawings, see page 133.

Technical information, see page 134 – 140.

Width (B) mm	Packs of	200	200	200	200	Page
Height (H) mm		2000	2200	2000	2200	
Depth (T) mm		600	600	800	800	
Model No. SV	1	9670.206	9670.226	9670.208	9670.228	
Weight (kg)		34.0	36.6	37.5	40.0	

Base/plinth²⁾

Also required

1) Side panels for protection category	IP 55	2	8106.235	8126.235	8108.235	8128.235	39
	IP 2X	2	9671.906	9671.926	9671.908	9671.928	39
Upgrade kit for side panels IP 2X	IP 43	2 sets ¹⁾	9671.996	9671.996	9671.998	9671.998	39
2) Coupling set mounting kit		1 set	9674.196	9674.196	9674.198	9674.198	59
	Angular baying brackets	4		8800.430			41
Baying connectors, external		6		8800.490			41

Accessories

Compartment configuration	50 – 61
Components	65 – 114


¹⁾ Pack sufficient for 1 pack of side panels.

²⁾ The busbar enclosure is on one base/plinth together with the main enclosure, i.e. please select a base/plinth for the main enclosure which is 200 mm wider.


Form 2-4 enclosure system accessories

Enclosure configuration

SV-TS 8 modular section



SV-TS 8 cable chamber section



Accessory components for external mounting on a modular or cable chamber enclosure. The required components should be selected depending on the required function. We highly recommend the Rittal Power Engineering software for easier selection – see page 123.

Accessory components	Page
1 Side panels	39
2 Front trim panels	41/42/46
3 Roof frame bars/cross members	42/44
4 Roof plates	44
5 Cable entry glands	45
6 Partial doors	43
7 Locks	43
8 Base/plinth components, front and rear	40
9 Base/plinth trim, side	40



Side panels

for TS

Easy positioning on the frame with the location aid. Six enclosure panel holders with earthing insert ensure automatic potential equalisation and higher EMC protection. Earthing bolts with contact surface are integrated.

Material:


Sheet steel, 1.5 mm

Surface finish:

Textured RAL 7035

Supply includes:

Assembly parts.



For enclosures		Version	Packs of	Model No. SV
Height mm	Depth mm			
1800	600	IP 55 sealed	2	8186.235
2000	600		2	8106.235
2200	600		2	8126.235
2000	800		2	8108.235
2200	800		2	8128.235
1800	600	IP 2X with ventilation hole	2	9671.986
2000	600		2	9671.906
2200	600		2	9671.926
2000	800		2	9671.908
2200	800		2	9671.928



Accessories:

IP 43 upgrade kit for side panels

For enclosure depth mm	Version	Packs of	Model No. SV
600	for side panels	2 sets	9671.996
800	IP 2X	2 sets	9671.998

Pack sufficient for 1 pack of side panels.

Form 2-4 enclosure system accessories

Enclosure configuration




Base/plinth components front and rear

Sheet steel for TS, CM, TP, PC-TS, IW, FR(i), TE
Base/plinth component consisting of one trim panel and two pre-configured corner pieces. In 200 mm high base/plinth components, one trim panel is divided into two for cable entry.

Material:
Sheet steel, spray-finished
Cover caps plastic RAL 9005/7035

Supply includes:
1 set =
2 base/plinth components, 4 cover caps,
4 screws and captive nuts M12
for mounting on the enclosure.



+ Accessories:

Base mounting plate SO 2817.000,
see Cat. 32, page 896.
Filter mat for vented variants,
see Cat. 32, page 898.


Detailed drawing,
see Cat. 32, page 894.

German patent no. 198 60 408

For enclosure width mm	Version	Colour		Model No. TS	
		RAL 7022	RAL 7035	100 mm high	200 mm high
300	solid	–	■	8601.905	8602.905
	solid	■	–	8601.915	8602.915
400	solid	■	–	8601.400	8602.400
500	solid	■	–	8601.500	8602.500
600	solid	■	–	8601.600	8602.600
	solid	–	■	8601.605¹⁾	8602.605
	vented	–	■	7825.601²⁾	–
800	vented with designer cover	–	■	7825.603	–
	solid	■	–	8601.800	8602.800
	solid	–	■	8601.805³⁾	8602.805
	vented	–	■	7825.801⁴⁾	–
850	solid	■	–	8601.850	8602.850
1000	solid	■	–	8601.000	8602.000
1100	solid	■	–	8601.300	8602.100
1200	solid	■	–	8601.200	8602.200
1600	solid	■	–	8601.920	8602.920

¹⁾ Variant in RAL 9005: TS 8601.602
²⁾ Variant in RAL 9005: DK 7825.605

³⁾ Variant in RAL 9005: TS 8601.802
⁴⁾ Variant in RAL 9005: DK 7825.805




Base/plinth trim, side

Sheet steel for TS, CM, TP, PC-TS, IW, FR(i), TE
For mounting between the base/plinth components. At 200 mm height, two 100 mm base/plinth trims may be used. Base/plinth trim (100 mm high) may be installed rotated through 90° in order to stabilise bayed base/plinth components.

Material:
Sheet steel, spray-finished

Supply includes:
1 set =
2 base/plinth trim panels, including parts for
attaching to the base/plinth components.



! Also required:

Base/plinth baying brackets TS 8601.100,
see Cat. 32, page 896,
when mounting base/plinth trim panels rotated
through 90°.

+ Accessories:

Assembly bolts for base/plinth,
see Cat. 32, page 896.

Detailed drawing,
see Cat. 32, page 894.


For enclosure depth mm	Colour		Model No. TS	
	RAL 7022	RAL 7035	100 mm high	200 mm high
300	■	–	8601.030	8602.030
400	■	–	8601.040	8602.040
500	■	–	8601.050	8602.050
600	■	–	8601.060	8602.060
	–	■	8601.065	8602.065
800	■	–	8601.080	8602.080
	–	■	8601.085¹⁾	8602.085
900	–	■	8601.095²⁾	8602.095
1000	–	■	8601.015³⁾	8602.015
1200	–	■	8601.025⁴⁾	8602.025

¹⁾ Variant in RAL 9005: TS 8601.086
²⁾ Variant in RAL 9005: TS 8601.092

³⁾ Variant in RAL 9005: TS 8601.010
⁴⁾ Variant in RAL 9005: TS 8601.026

Form 2-4 enclosure system accessories

Enclosure configuration



Angular baying bracket

for TS/TS

The robust connection when transporting bayed enclosure suites.

Screw-fastening either

- Horizontally and vertically with 8 screws
 - Horizontally with 2 screws and M8 threaded blocks, vertically with 4 screws
- is supported.

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Assembly parts.

Packs of	Model No. TS
4	8800.430



Baying connector, external

for TS/TS

For mounting on the vertical enclosure sections.

Simply position on the outside and screw-fasten either from the inside or outside.

Material:


Sheet steel, zinc-plated, passivated or stainless steel 1.4301 (AISI 304)

Supply includes:

Assembly parts.

Version	Packs of	Model No. TS
Sheet steel	6	8800.490
Stainless steel	6	8700.000

German patent no. 197 37 668



Front trim panels

for TS

Required as an upper and lower height filler when partial doors are used.

Height: 100 mm.

Material:

Sheet steel, 2 mm

Surface finish:

Textured RAL 7035

Supply includes:

2 front trim panels, including assembly parts.



Also required:

Cross member, see page 42.



Version	Packs of	Model No. SV			
		For enclosure width			
		300 mm	400 mm	600 mm	800 mm
IP 54 sealed	1 set	9671.013	9671.014	9671.016	9671.018
IP 2X with ventilation hole	1 set	9671.033	9671.034	9671.036	9671.038
Accessories					
Upgrade kit IP 43 for front trim panel IP 2X	1 set	9671.043	9671.044	9671.046	9671.048

Form 2-4 enclosure system accessories

Enclosure configuration



Front trim panels

for TS (busbar compartment)

Required to conceal a 300 mm high busbar compartment and for using partial doors as an upper and lower height filler.

Height of busbar compartment cover: 300 mm.
Height of front trim panel opposite: 100 mm.

Material:

Sheet steel, 2 mm

Colour:

Textured RAL 7035

Supply includes:

2 front trim panels, including assembly parts.



Also required:

Roof frame bars, see page 44.
Cross members, see page 42.



Accessories:

Upgrade kit IP 43

for front trim panels IP 2X with ventilation hole

For enclosure width mm	Packs of	Model No. SV
300	1 set	9672.053
400	1 set	9672.054
600	1 set	9672.056
800	1 set	9672.058
1000	1 set	9672.050¹⁾
1200	1 set	9672.052¹⁾

¹⁾ Delivery times available on request.

For enclosure width mm	Height of front trim panels		Packs of	Model No. SV	
	top mm	bottom mm		Version	
				IP 54 sealed	IP 2X with ventilation hole
300	300	100	1 set	9672.013	9672.033
300	100	300	1 set	9672.023	9672.043
400	300	100	1 set	9672.014	9672.034
400	100	300	1 set	9672.024	9672.044
600	300	100	1 set	9672.016	9672.036
600	100	300	1 set	9672.026	9672.046
800	300	100	1 set	9672.018	9672.038
800	100	300	1 set	9672.028	9672.048
1000	300	100	1 set	9672.010¹⁾	9672.030¹⁾
1000	100	300	1 set	9672.020¹⁾	9672.040¹⁾
1200	300	100	1 set	9672.012¹⁾	9672.032¹⁾
1200	100	300	1 set	9672.022¹⁾	9672.042¹⁾

¹⁾ Delivery times available on request.



Cross members

for TS

For use as sealing member between:

- Front trim panels
- Trim panels
- Partial doors

Material:

Sheet steel, 1 mm

Colour:

RAL 7035

Supply includes:


Assembly parts and sealing material.



For enclosure width mm	Packs of	Model No. SV
300	5	9671.003
400	5	9671.004
600	5	9671.006
800	5	9671.008

Form 2-4 enclosure system accessories

Enclosure configuration



Partial doors

for TS, without lock

Door hinges with non-drilled internal fastening. Door may be optionally hinged on the right or left.

Material:

Sheet steel, 2 mm

Surface finish:

Textured RAL 7035

Supply includes:

Hinges and assembly parts.



Also required:

Locks,
see page 43.
Cross members,
see page 42.



Height mm	No. of locks required	Packs of	Model No. SV			
			For enclosure width			
			300 mm	400 mm	600 mm	800 mm
150	1	1	–	9671.141	9671.161	9671.181
200	1	1	–	9671.142	9671.162	9671.182
250	1	1	–	9671.147	9671.167	9671.187
300	1	1	–	9671.143	9671.163	9671.183
400	1	1	–	9671.144	9671.164	9671.184
600	2	1	–	9671.146	9671.166	9671.186
800	2	1	–	9671.148	9671.168	9671.188
1000	3	1	–	9671.140	9671.160	9671.180
1600	3	1	9671.126	9671.156	9671.176	9671.196
1800	3	1	9671.128	9671.158	9671.178	9671.198
2000	3	1	9671.120	9671.150	9671.170	9671.190



Perforated mounting strip

for partial doors

For retrospective external mounting on SV partial doors. The perforated mounting strips have a 25 mm pitch pattern of holes and may be used for individual mountings on the rear side of the door, e.g. cable ducts, hose holders etc.

Material:

Sheet steel, 1 mm


Surface finish:

Sheet steel, zinc-plated, passivated

Supply includes:

Assembly parts.

For partial door height mm	Hole diameter of the perforated strip mm	Packs of	Model No. SV			
			For enclosure width mm			
			300	400	600	800
150 – 800	4.5	10	–	9671.204	9671.206	9671.208
Length mm			–	298	498	698



Locks

For installation in partial doors or in exchange for AE cam locks.

Material:

Housing made of fibreglass-reinforced plastic, bolt made of PA

Colour:

RAL 7035

Supply includes:

Housing, lock insert, bolt including assembly parts.

Version	Packs of	Model No. SV
1 With double-bit insert	1	9671.130
2 With cylinder insert, lock no. 3524 E	1	9671.132
3 With T handle	1	9671.134
4 With T handle and lock insert, lock no. 3524 E	1	9671.135
5 Fastener lug with end stop ¹⁾	2	9671.138

¹⁾ Must be used if the twist lock cannot be locked on the TS 8 frame.



5



Form 2-4 enclosure system accessories

Enclosure configuration



Roof frame strips, horizontal for TS

Required as sealing bar between 300 mm high front trim panels and partial doors.

Material:
Sheet steel, 1.5 mm

Colour:
RAL 7035

Supply includes:
Assembly parts and sealing material.

For enclosure width mm	Width mm	Packs of	Model No. SV
300	208	2	9672.003
400	308	2	9672.004
600	508	2	9672.006
800	708	2	9672.008
1000	908	2	9672.000¹⁾
1200	1108	2	9672.002¹⁾

¹⁾ Delivery times available on request.



Roof plates for TS

For SV-TS 8 modular and cable chamber enclosures without roof plate and in exchange for the standard roof plate for other TS enclosures.

Material:
Sheet steel, 1.5 mm

Surface finish:
Textured RAL 7035

Supply includes:
Assembly parts.



Also required:

Cable entry gland, see page 45.

No. of cable entry glands required	
For roof plate	Quantity required
SV 9671.536	2
SV 9671.546	3
SV 9665.903	4
SV 9671.586	8
SV 9671.538	2
SV 9671.548	4
SV 9671.568	8
SV 9671.588	8



For enclosures			Model No. SV				
Width mm	Depth mm	Packs of	Version				
			IP 55 sealed	IP 43 with ventilation hole	IP 2X with ventilation hole	For cable entry gland	With pressure relief valve
300	600	1	9671.636	9671.736	–	9671.536	–
400	600	1	9671.646	9671.746	9671.846	9671.546	9671.446¹⁾
600	600	1	9671.666	9671.766	9660.235	9665.903	9660.935¹⁾
800	600	1	9671.686	9671.786	9660.245	9671.586	9660.945¹⁾
1000	600	1	–	–	9660.255	–	9660.955
1200	600	1	–	–	9660.265	–	9660.965
300	800	1	9671.638	9671.738	–	9671.538	–
400	800	1	9671.648	9671.748	9671.848	9671.548	9671.448¹⁾
600	800	1	9671.668	9671.768	9659.525	9671.568	9671.468¹⁾
800	800	1	9671.688	9671.788	9659.535	9671.588	9671.488¹⁾
1000	800	1	–	–	9659.545	–	³⁾
1200	800	1	–	–	9659.555	–	³⁾
Build height mm			0	93	72	0 ²⁾	25

¹⁾ Delivery times available on request.

²⁾ Build height depending on the cable entry gland.


³⁾ Other sizes available on request.

Form 2-4 enclosure system accessories


Enclosure configuration




1




2



3



4



5

Cable entry glands

- Including seal
- External dimensions 250 x 160 mm
- Protection category IP 55

Material:


SV 9665.750 to 9665.780

Insulating material RAL 7032

SV 9665.785

Sheet steel, spray-finished in RAL 7035

Version	Packs of	Model No. SV
1 14 x M25/32	1	9665.750
2 2 x M25/32/40, 1 x M32/40/50, 2 x M40/50/63	1	9665.760
3 With sealing membranes 32 x dia. 7 – 16 mm, 4 x dia. 10 – 20 mm, 3 x dia. 14 – 26 mm	1	9665.770
4 With entry glands up to 66 mm diameter	1	9665.780
5 Solid	4	9665.785



Cut-out dimensions for
SV 9665.750 to SV 9665.785

Form 2-4 enclosure system accessories

Enclosure configuration



Front trim panels

for switch-disconnector-fuse section

The front trim panels cover above and below the mounting area of the NH switch-disconnector-fuses on the door front. With integral vent openings, protection categories IP 3X/IP 2X of the switch-disconnector-fuse section are achieved.

Material:

Sheet steel, 2 mm

Colour:

Textured RAL 7035

Supply includes:

2 front trim panels, assembly parts.




Front trim panels height mm		Packs of	Model No. SV
top	bottom		Version
338	136	1 set	IP 3X ¹⁾ with ventilation hole 9674.340
136	338	1 set	9674.342

¹⁾ For IP 2X the inner perforated plate must be removed.



Also required:

Assembly kit for switch-disconnector-fuse section, see page 46.



Assembly kit

for switch-disconnector-fuse section

Assembly kit for the installation of switch-disconnector-fuses and attachment of the distribution busbar system. Depending on the switch-disconnector-fuses to be used from ABB or Jean Müller, the required assembly kits are selected according to the enclosure height.

Material:

Section corner piece left/right, sheet steel, zinc-plated, 2 mm

Trim panel left/right, sheet steel, 2 mm, spray-finished

Colour:

Textured RAL 7035

Supply includes:

2 section corner pieces, 2 trim panels, assembly parts.



For make/switch-disconnector-fuse	For enclosure height mm	Packs of	Model No. SV
Jean Müller SASIL	2000	1 set	9674.350
Jean Müller SASIL	2200	1 set	9674.352
ABB SlimLine	2000	1 set	9674.356
ABB SlimLine	2200	1 set	9674.358



Also required:

Divider panel for switch-disconnector-fuse section, see page 60.





Perfection down to the smallest detail

Time-saving system assembly, form-separated interior installation, innovative module components, and an extensive range of accessories. Rittal Ri4Power Form 2-4 is a modular system for the time-optimised configuration of form-separated low-voltage switchgear. Fresh approaches in installation technology and multifunctional components now mean that the internal separation of a low-voltage switchgear can be installed with just a few operations. The TS 8 Top enclosure system, as the system platform for Ri4Power Form 2-4, offers infinite possibilities, and provides the ideal solution to suit your requirements, however specific.

Side panel modules



The side panel modules form the basic element for internal installation.



One-person assembly: Locate components into the TS 8 pitch pattern, and release. Both hands are now free for the next installation step.



The **modular installation concept** enables optimum utilisation of the assembly area, thanks to compartment heights in small increments (150, 200, 250 mm, etc.).



The **proven TS 8 pitch** is used for many Ri4Power components and so permits the use of TS 8 system accessories.

Partial doors and cross members



Simple assembly and high quality standards characterise the new partial door system.



Thanks to the new design, the **cross member** may also be retro-fitted.



Fitting accuracy and precision are prerequisites for modular technology.



The **hinge** of the partial doors is mounted on the TS 8 frame **without any holes needing to be drilled**.

Mini-TS profile



Mini-TS profile – the TS pitch in the smallest dimension. An extension of the assembly spectrum for small and medium loads.



The **three assembly sides of the Mini-TS profile** ensure the versatility and fast assembly technology of the TS 8 enclosure profile at all times, whatever the location.



The **connector pieces** always provide an attachment point at every position in the 25 mm pitch, irrespective of the mounting angle used.




The **small size** means the Mini-TS bars can be mounted without conflict in the internal and external mounting level of the TS 8 enclosure.

Form 2-4 compartment


Compartment configuration

Modular outgoing section with distribution busbar system


Inside the compartment




Behind the compartment




Compartment layout




Busbar space separation (only required with main busbar systems in the rear area)




Cable chamber



Coupling section




Circuit-breaker section



Accessory components for the configuration of modular or cable chamber enclosures. The required components are selected depending on the required compartments and system configuration.

We highly recommend the Rittal Power Engineering software for an explanation of the selection process – see page 123.

Accessory components	Page
1 Functional space side panel modules	51
2 Mounting bracket for functional space divider	53
3 Functional space divider	54/55
4 Partial mounting plates including angle brackets	56
5 Cross members	42
6 Partial doors	43
7 Locks	43
8 Mini-TS profiles 17 x 15.5 mm	57
9 Frame connector piece (external mounting level)	58
10 Corner connector	58
11 Cover plates	52
12 Air circuit-breaker support bar	54
13 Stacking insulator	105
14 Support bar for packing insulator	105
15 Functional space side panel modules for cable connection space	51
16 Mounting bracket for functional space divider and air circuit-breaker support bar	53
Support frame for DIN rail-mounted devices	56
17 Punched rails, RiLine distribution busbar system	61
18 Accessories for coupling set	59
Accessories for switch-disconnector-fuses	60






Functional space side panel modules

for TS

For internal separation as a side divider panel for compartments, for mounting in the TS pitch pattern. Prepared for the attachment of mounting brackets for horizontal functional space dividers or mounting plates with two M40 knockouts for cable entry. Two TS system punchings allow the use of additional TS accessories.

The side panel modules for reduced compartment depth and an auxiliary construction using the Mini-TS profiles can be used to provide a separate enclosure space in the side panel area, e.g. for the provision of a busbar system. Version with plastic plate has prepunched knockouts for cable entry.



Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.




Accessories:

Mini-TS extrusions and connector pieces, see page 57, 58.

Gland plates, see page 51.

Height mm	Configuration with plastic gland plate	Packs of	Model No. SV		
			For compartment depth		
			425 mm	600 mm	800 mm
100	–	6	9673.051	9673.061	9673.081
150	–	6	9673.055	9673.065	9673.085
150	■	6	9673.155	9673.165	9673.185
200	–	6	9673.052	9673.062	9673.082
200	■	6	9673.152	9673.162	9673.182
600	–	2	–	9673.066	9673.086
600	■	2	–	9673.166	9673.186



Gland plates

To seal additional cable entries.

Material:

PVC, 3 mm
fire protection corresponding to UL 94-V0

Colour:

RAL 7004

Supply includes:

Assembly parts.

For side panel modules height mm	Packs of	Model No. SV
150	10	9673.195
200/600	10	9673.192



Functional space side panel modules

for TS (cable connection space)

For mounting a Maxi-PLS cable connection busbar system in a TS enclosure.

Material:

Sheet steel, zinc-plated, passivated, 2 mm

Supply includes:

Assembly parts.

Height mm	Packs of	Model No. SV	
		For enclosure depth	
		600 mm	800 mm
450	2	9673.069	9673.089
Suitable for cable connection busbar system			
Maxi-PLS	Number of poles		
1600/2000	3-pole	■	■
1600/2000	4-pole	■	■
3200	3-pole	■	■
3200	4-pole	–	■



Also required:

2 functional space side panel modules with height 150 mm, see page 51.
End support, see page 84/86.

Form 2-4 compartment

Compartment configuration



Cover plates

for rear busbar system in the cable chamber

To separate an area of the cable chamber enclosure for a rear-mounted busbar system. Attachment requires an auxiliary construction made from Mini-TS profiles, to which the cover plates are attached and fastened.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



Also required:

Frame connector piece (4 x SV 9673.901), see page 58.
 Corner connector (2 x SV 9673.902), see page 58.
 Mini-TS profiles for SV 9673.5X0 (2 x SV 9673.915, 2 x SV 9673.953), see page 57.
 Mini-TS profiles for SV 9673.5X2 (2 x SV 9673.920, 2 x SV 9673.983), see page 57.

For enclosure depth mm	For enclosure width mm	Width mm	Height mm	Depth mm	Packs of	Model No. SV
600	300	297	540	170.5	2 sets	9673.530¹⁾
600	400	397	540	170.5	2 sets	9673.540¹⁾
600	600	597	540	170.5	2 sets	9673.560¹⁾
600/800	300	297	837	245.5	1 set	9673.532²⁾
600/800	400	397	837	245.5	1 set	9673.542²⁾
600/800	600	597	837	245.5	1 set	9673.562²⁾

¹⁾ Suitable for RiLine60 and Maxi-PLS 1600/2000

²⁾ Suitable for RiLine60, Maxi-PLS 1600/2000/3200 and Flat-PLS

Terminal box Form 4b

for modular outgoing section

To shield the connections (terminals) of the functional space, busbar chamber and cable chamber to Form 4b, IEC 60 439-1. The terminal boxes are externally mounted on the functional space side panel modules in the cable chamber, to match the heights of the compartments. The terminal box is prepared for mounting of a clamping strip and the introduction of lines and cables.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.

Note:

For installation of the terminal boxes, the width of the cable chamber must be at least 400 mm!

For compartment height mm	For enclosure width mm ¹⁾	Packs of	Model No. SV
150	400/600	1 set	9674.701
200	400/600	1 set	9674.702
250	400/600	1 set	9674.707
300	400/600	1 set	9674.703
400	400/600	1 set	9674.704
600	400/600	1 set	9674.706

¹⁾ Enclosure width of the cable chamber



Also required:

Functional space side panel modules, see page 51.

Compartment configuration



Mounting bracket

for functional space divider

The mounting bracket is fastened to the TS frame or between a frame section and an auxiliary construction.

It is suitable both for fastening to a side panel module and also directly to the TS frame. The functional space dividers can be inserted into the installation openings provided.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



For compartment depth mm	Length mm	Packs of	Model No. SV
425	427	8	9673.405 ¹⁾
600	552	8	9673.406
800	752	8	9673.408

¹⁾ In conjunction with vertical busbar space separation.



Mounting bracket

for functional space divider (inner mounting level)

The mounting bracket is secured to a TS punched section with mounting flange 23 x 73 mm.

The functional space dividers can be inserted into the installation openings provided.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



For compartment depth mm	Length mm	Packs of	Model No. SV
600	544.5	8	9673.416
800	744.5	8	9673.418



Also required:

TS punched section with mounting flange, 23 x 73 mm, see Cat. 32, page 995.



Mounting bracket

for functional space divider and air circuit-breaker support bar

The mounting bracket is attached to a side panel module. The functional space dividers can be inserted into the installation openings provided.

The air circuit-breaker support bar may be attached to the upper level.

Material:

Sheet steel, zinc-plated, passivated, 2 mm

Supply includes:

Assembly parts.



For compartment depth mm	Length mm	Packs of	Model No. SV
600	552	2	9673.426
800	752	2	9673.428



Also required:

Functional space side panel modules, see page 51.
Air circuit-breaker support bar, see page 54.

Form 2-4 compartment

Compartment configuration



Air circuit-breaker support bar

For the configuration of air circuit-breakers (ACB) in compartments. The air circuit-breaker support bar is attached to a mounting bracket for functional space dividers and air circuit-breaker support bar.

Material:

Sheet steel, zinc-plated, passivated, 2.5 mm

Supply includes:

Assembly parts.



For enclosure width mm	Length mm	Packs of	Model No. SV
400	351	2	9673.004
600	551	2	9673.006
800	751	2	9673.008



Also required:

Mounting bracket for functional space divider and air circuit-breaker support bar see page 53.
Attachment set for air circuit-breaker installation, see page 54.



Attachment set

for air circuit-breaker installation

For attaching air circuit-breakers (ACB) to air circuit-breaker support bars.

Material:

Sheet steel, zinc-plated

Supply includes:

4 threaded plates (M8).

Packs of	Model No. SV
1 set	9660.970



Functional space divider

for TS

For the horizontal separation of compartments. In combination with the side panel modules, produces a separation in accordance with Form 3 or 4. Two mounting brackets are required to install the functional space divider.

Material:

Sheet steel, zinc-plated, passivated, 1.25 mm



Also required:


Mounting bracket, see page 53.
Cross members, see page 42.



For enclosure width mm	For compartment depth mm	Width mm	Depth mm	Packs of	Model No. SV	
					Version	
					Vented ¹⁾	Solid ²⁾
300	600	206	588	4	–	9673.431
300	800	206	788	4	–	9673.432
400	425	306	445	4	9673.444	9673.440
400	600	306	588	4	9673.445	9673.441
400	800	306	788	4	9673.448	9673.449
600	425	506	445	4	9673.464	9673.460
600	600	506	588	4	9673.465	9673.461
600	800	506	788	4	9673.468	9673.469
800	425	706	445	4	9673.484	9673.480
800	600	706	588	4	9673.485	9673.481
800	800	706	788	4	9673.488	9673.489

¹⁾ With ventilation holes

²⁾ Derating of 5% with enclosure protection category IP 2X or less, in relation to the rated currents of the selected busbar system.



Functional space divider

for TS, prepared for RiLine60 busbar systems

For the horizontal separation of compartments with integrated RiLine60 multi-terminal busbar system. In combination with the side panel modules, produces a separation in accordance with Form 3 or 4. Two mounting brackets are required to install the functional space divider.

Material:

Sheet steel, zinc-plated, passivated, 1.25 mm



Also required:

Mounting bracket, see page 53.
Cross members, see page 42.



For enclosure width mm	For compartment depth mm	Width mm	Depth mm	Position of the busbar system in the compartment	Packs of	Model No. SV	
						Version	
						Vented ¹⁾	Solid ³⁾
400	401	306	413	–	4	9673.434 ²⁾	9673.430 ²⁾
600	401	506	413	–	4	9673.454	9673.450
800	401	706	413	Right	4	9673.474	9673.470
800	401	706	413	Left	4	9673.475	9673.471

¹⁾ With ventilation holes

²⁾ Only for use with a 3-pole bar system.

³⁾ Derating of 5% with enclosure protection category IP 2X or less, in relation to the rated currents of the selected busbar system.



Functional space divider

for TS, prepared for the entry of vertical busbar systems

For the horizontal separation of compartments with vertical busbars. In combination with the side panel modules, produces a separation in accordance with Form 3 or 4. Two mounting brackets are required to install the functional space divider.


Material:

Sheet steel, zinc-plated, passivated, 1.25 mm



Also required:

Mounting bracket, see page 53.
Cross members, see page 42.
Gland plate, see page 55.



For enclosure width mm	For compartment depth mm	Width mm	Depth mm	Width of entry (B) mm	Depth of entry (T) mm	Packs of	Model No. SV	
							Version	
							Vented ¹⁾	Solid ²⁾
400	600	306	588	212	201	4	9673.436	9673.437
400	800	306	788	212	201	4	9673.438	9673.439
600	600	506	588	412	201	4	9673.456	9673.457
600	800	506	788	412	201	4	9673.458	9673.459
800	600	706	588	612	201	4	9673.476	9673.477
800	800	706	788	612	201	4	9673.478	9673.479

¹⁾ With ventilation holes

²⁾ Derating of 5% with enclosure protection category IP 2X or less, in relation to the rated currents of the selected busbar system.



Gland plate

To shroud the opening for the vertical busbar systems.

For enclosure width mm	Width mm	Height mm	Packs of	Model No. SV
400	250	223.5	4	9673.504
600	450	223.5	4	9673.506
800	650	223.5	4	9673.508

Form 2-4 compartment

Compartment configuration



Partial mounting plates

With and without duct, for TS

For direct attachment to the functional space side panel modules.

- Universal internal installation with switchgear and control devices.

- Additional mounting levels.

In combination with functional space dividers and side panel modules, internal separation in accordance with Form 2, 3 or 4 is possible.



Material:

Sheet steel, zinc-plated, passivated, 2 mm

Supply includes:

Angle brackets and assembly parts.

For the version with cable entry:

Additional square cut-out with insulating plates for sealing the cut-out.



Also required:

Functional space side panel modules, see page 51.

For enclosure width mm	For compartment height mm	Width mm	Height mm	Packs of	Model No. SV	
					With duct	Without duct
400	150	302	143	1	9673.651	9673.641
400	200	302	193	1	9673.652	9673.642
400	250	302	243	1	9673.657	9673.647
400	300	302	293	1	9673.653	9673.643
400	400	302	393	1	9673.654	9673.644
400	600	302	593	1	–	9673.646
400	800	302	793	1	–	9673.648
400	1000	302	993	1	–	9673.640
600	150	502	143	1	9673.671	9673.661
600	200	502	193	1	9673.672	9673.662
600	250	502	243	1	9673.677	9673.667
600	300	502	293	1	9673.673	9673.663
600	400	502	393	1	9673.674	9673.664
600	600	502	593	1	–	9673.666
600	800	502	793	1	–	9673.668
600	1000	502	993	1	–	9673.660
800	150	702	143	1	9673.691	9673.681
800	200	702	193	1	9673.692	9673.682
800	250	702	243	1	9673.697	9673.687
800	300	702	293	1	9673.693	9673.683
800	400	702	393	1	9673.694	9673.684
800	600	702	593	1	–	9673.686
800	800	702	793	1	–	9673.688
800	1000	702	993	1	–	9673.680



Support frame

for DIN rail-mounted devices

Support frame set for accepting DIN rail-mounted devices (e.g. MCBs). The support rails are fastened with two mounting brackets to the side panel modules. The cover is fastened to the support frame with knurled screws.

In combination with functional space dividers, partial mounting plates and side panel modules, separation in accordance with Form 2, 3 or 4 is possible.

Material:

Support frame: Sheet steel, zinc-plated, passivated, 1.5 mm

Cover: Sheet steel, spray-finished, 1.5 mm

Supply includes:

- 2 support rails,
- 2 mounting brackets,
- 1 front trim panel with cut-out, incl. assembly parts.

For enclosure width mm	For compartment height mm	No. of pitch units 17.5 mm	Packs of	Model No. SV
600	150	1 x 24	1 set	9674.761
600	300	2 x 24	1 set	9674.762
600	600	3 x 24	1 set	9674.763
600	600	4 x 24	1 set	9674.764
800	150	1 x 36	1 set	9674.781
800	300	2 x 36	1 set	9674.782
800	600	3 x 36	1 set	9674.783
800	600	4 x 36	1 set	9674.784



Also required:

Functional space side panel modules, see page 51.

Partial mounting plates, see page 56.

Compartment configuration



Mini-TS profiles 17 x 15.5 mm for TS

Mounting angle with TS pitch on three sides. Suitable for

- building an auxiliary construction for dividing the busbar space,
- individual use as mounting frame for low and medium loads,
- fastening to the internal or external mounting level of the TS 8 enclosure.


Material:

Sheet steel, zinc-plated, passivated, 1.5 mm




Also required:

Frame connector piece, see page 58.
T-connector piece, see page 58.
Corner connector, see page 58.



Installation situation with busbar system in the top rear section



Installation situation with busbar system in the bottom rear section

For horizontal busbar space separation		Packs of	Model No. SV
For compartment depth mm	Length mm		
425	62.5	12	9673.915
600	137.5	12	9673.920

For vertical separation with busbar system in the top rear section		Packs of	Model No. SV
For compartment height mm	Length mm		
350	337.5	12	9673.942
400	387.5	12	9673.943
450	437.5	12	9673.952
500	487.5	12	9673.953
550	537.5	12	9673.962
600	587.5	12	9673.963
650	637.5	12	9673.972
700	687.5	12	9673.973
750	737.5	12	9673.982
800	787.5	12	9673.983

For vertical separation with busbar system in the bottom rear section		Packs of	Model No. SV
For compartment height mm	Length mm		
350	412.5	12	9673.951
400	462.5	12	9673.960
450	512.5	12	9673.961
500	562.5	12	9673.970
550	612.5	12	9673.971
600	662.5	12	9673.980
650	712.5	12	9673.981
700	762.5	12	9673.990
750	812.5	12	9673.991
800	862.5	12	9673.995

For external mounting level		Packs of	Model No. SV
For enclosure width/depth mm	Length mm		
300	162.5	12	9673.930
400	262.5	12	9673.940
500	362.5	12	9673.950
600	462.5	12	9673.960
800	662.5	12	9673.980

For internal mounting level		Packs of	Model No. SV
For enclosure width/depth mm	Length mm		
300	212.5	12	9673.931
400	312.5	12	9673.941
500	412.5	12	9673.951
600	512.5	12	9673.961
800	712.5	12	9673.981

Form 2-4 compartment

Compartment configuration



Frame connector piece

for Mini-TS profile

Mounting part with integral M4 threads for attaching the Mini-TS profile to the horizontal and vertical TS frame section (external level). The frame adaptor piece can be used as a self-holding construction aid in the TS pitch and fastened with a screw to the frame. Can also be used for fastening other sections with TS pitch.

Material:

Die-cast zinc

Supply includes:

Assembly parts.

Packs of	Model No. SV
24	9673.901



T-connector piece

for Mini-TS profile

Mounting part with integrated M4 threads for fastening the Mini-TS profile to the

- horizontal and vertical TS chassis,
- Mini-TS profile,
- vertical TS frame section (internal level).

The T-connector piece can be used as a self-holding construction aid in the TS pitch and fastened with a screw to the frame. Can also be used for fastening other sections with TS pitch.

Material:

Die-cast zinc

Supply includes:

Assembly parts.

Packs of	Model No. SV
24	9673.903



Corner connector

for Mini-TS profile

Mounting part with integrated M4 threads for connecting two Mini-TS profiles at an angle of 90° at the corner. Required for building the auxiliary construction for the busbar space separation.

Material:

Die-cast zinc

Supply includes:

Assembly parts.

Packs of	Model No. SV
10	9673.902



Coupling set mounting kit

for busbar enclosure or riser

The mounting kit is used as a base support for a vertical Maxi-PLS busbar system/Flat-PLS busbar system.

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Support plate and punched section with mounting flange, assembly parts.

With the version for 300 and 400 mm enclosure widths, additionally with insulating plate for the installation of Flat-PLS.



For enclosure width mm	For enclosure depth mm	Packs of	Model No. SV
200	600	1 set	9674.196¹⁾
200	800	1 set	9674.198¹⁾
300	600	1 set	9674.036
300	800	1 set	9674.038
400	600	1 set	9674.046
400	800	1 set	9674.048

¹⁾ Only suitable for Maxi-PLS.



Also required:

End support, see page 84/86.



Punched sections with mounting flanges

for coupling section

The punched section with mounting flange for coupling set is needed for assembling a Maxi-PLS or Flat-PLS busbar system directly beneath or above the circuit-breaker. This punched section with mounting flange may be used without conflict in conjunction with the functional space side panel modules. It is attached to the outer level of the TS 8 enclosure system, but thanks to the PS punchings allows a mounting level as in the roof or base frame, thereby facilitating the use of busbar system attachment for the roof/base section.

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Assembly parts.



For enclosure width mm	For enclosure depth mm	Packs of	Model No. SV
600	600	2	9674.056
800	800	2	9674.058



Also required:

System attachment for Maxi-PLS 1600/2000, see page 84.

System attachment for Maxi-PLS 3200, see page 86.

System attachment for Maxi-PLS 60 and 100, see page 90.

Form 2-4 compartment

Compartment configuration



Divider panel

for switch-disconnector-fuse section

The divider panel is required for interior configuration of the switch-disconnector-fuse section, and divides the connection space from the functional space. Depending on the chosen position of the main busbar system, the divider panel is fitted in the prepared switch-disconnector-fuse enclosures. The prepared cut-outs are suitable for the connection of switch-disconnector-fuse Jean Müller Sasil and ABB SlimLine.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



For main busbar system in the roof section

For enclosure height mm	For enclosure depth mm	Packs of	Model No. SV
2000	600	1	9674.306
2000	800	1	9674.308
2200	600	1	9674.326
2200	800	1	9674.328

For main busbar system in the rear section, top or bottom

For enclosure height mm	For enclosure depth mm	Packs of	Model No. SV
2000	600	1	9674.305
2000	800	1	9674.307
2200	600	1	9674.325
2200	800	1	9674.327



Dividing plate

for switch-disconnector-fuse section

Dividing plate to divide the busbar chamber and NH switch-disconnector-fuse chamber (compartment). The design of the divider plate must be matched to the chosen make of the NH switch-disconnector-fuse and the installation position.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



Mounting position	Make of NH switch-disconnector-fuse	Packs of	Model No. SV
Top/bottom	Jean Müller SASIL	1	9674.346
Top/bottom	ABB SlimLine	1	9674.348



Also required:

Assembly kit for switch-disconnector-fuse section, see page 46.



Contact hazard protection, cable chamber

for switch-disconnector-fuse section

The contact hazard protection cover plate shields the main busbar in the cable chamber, enabling the safe connection of cables and lines. Suitable for Maxi-PLS and Flat-PLS busbar systems in the roof section. Contact hazard protection for main busbars in the rear section available on request.

Material:

Sheet steel, zinc-plated, passivated, 1.5 mm

Supply includes:

Assembly parts.



For main busbar system in the roof section

For enclosure width mm	For enclosure depth mm	Packs of	Model No. SV
1000	600	1 set	9674.362
1000	800	1 set	9674.364
1200	600	1 set	9674.366
1200	800	1 set	9674.368



Also required:

Divider panel for switch-disconnector-fuse section, see page 60.

Assembly parts

for RiLine60 distribution busbar systems

The following accessory components must be used for mounting a type-tested vertical distribution busbar system behind the compartment:



Mounting rails 23 x 23 mm

For installing a vertical RiLine60 distribution busbar system on the vertical enclosure section.

Material:

Sheet steel, zinc-plated, passivated

Length mm	For enclosures WHD mm	Packs of	Model No. PS
295	400	12	4169.000
495	600	12	4171.000
695	800	12	4172.000



Also required:

Mounting bracket and U nuts, see page 61.



Mounting bracket

For mounting the mounting rails on the TS frame.

Material:

Die-cast zinc

Supply includes:


24 screws 5.5 x 13 mm.

Packs of	Model No. TS
24	8800.370



Also required:

U nuts (recommendation: M6), see page 61.



U nuts


For fastening the mounting rails to the bracket and fastening the busbar holder to the mounting rails.

Thread	Packs of	Model No. PS
M5	20	4157.000
M6	20	4179.000



Accessories:

Multi-tooth screws M6 x 12 mm (for PS 4179.000), see Catalogue 32, page 1011.



Safe, flexible and fast – Rittal busbar technology

Time-saving assembly, diverse application options, individual modularity and a high level of operational safety – these are the benefits of the Rittal RiLine60 busbar systems. Simply insert the bars, secure – and it's done!

This is how quickly a variety of copper cross-sections may be mounted in the support. Simple assembly and safe contacting, coupled with a broad selection of connection and component support adaptors and fuse elements are the prerequisites for efficient assembly and operation.

Safety




Rittal busbar systems use proven and tested system components to provide a high level of safety.



Fully-insulated busbar system with finger-safe **contact hazard protection**, also at the connection points.



Increased arcing safety thanks to **busbar system installed without any base points** and busbar holders with arcing fault prevention.



All plastic materials used for the busbar system are **self-extinguishing** (fire behaviour in accordance with UL 94-V0).

Busbar system



Rittal busbar systems – **modular and compact.**



Each rated current, each construction form and each required short-circuit resistance has a busbar system appropriate for the enclosure.



Pre-assembled **busbar connection adapters** ensure simple, safe handling.



As well as enabling you to optimise your assembly, the **tested component adapters** and the alternative indoor busbar system also saves valuable installation and servicing time.

Fuse elements



Simple planning, compact designs, fast assembly, reliable contacting.




Bus-mounting fuse bases for snap-on mounting. The three-pole components ensure reliable-contact, shake-proof connection with the busbars.



RiLine NH fuse-switch-disconnector. The contact swivel feet have one outstanding function: The cable outlet can be switched from bottom to top in a matter of seconds.




NH fuse-switch-disconnector. With a build width of just 50 mm, it sets new standards in compact, space-saving configuration.




Modular outgoing section with distribution busbar system


Inside the compartment




Behind the compartment




Flat copper busbar system



PLS busbar system



Cable chamber




Busbar components for the configuration of modular sections or cable chambers with a busbar system. Components must be selected depending on the required rated current and the associated system components. Connection and cover components should be selected according to requirements. We highly recommend the Rittal Power Engineering software for an explanation of the selection process – see page 123.

Components	Page
1 Busbar supports (3-pole)	66
2 System components (3-pole)	67
3 PLS busbar supports (3-pole)	68
4 PLS system components (3-pole)	69
5 Busbar connection adaptors (3-pole)	70/71
6 Circuit-breaker component adaptor (3-pole)	72/73
1 Busbar supports (4-pole)	74
2 System components (4-pole)	75
3 Busbar supports PLUS (4-pole)	76
4 PLS system components (4-pole)	77
5 Busbar connection adaptors (4-pole)	78/79
6 Circuit-breaker component adaptor (4-pole)	80
7 Busbars	110
8 PE/PEN combination angle	109
9 Busbar supports (2-pole)	110
10 Busbar connectors	111
11 System attachments	103
12 Distribution busbars	102
13 T-connection kits	100/101
PLS busbar connectors	111
PLS expansion connectors	111
Busbar cover section	110
Base isolators	109
14 Busbar for PE/PEN	109

Form 2-4 busbar systems

Busbar supports (3-pole)



Material:

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:
RAL 7035

**Short-circuit protection
diagram,**
see page 116.

Technical information
for the calculation
of rated currents,
see page 120.

1 With attachment
holes on the outside

2 With attachment
holes on the inside

Version	Packs of	1 External attachment	2 Internal attachment	Page
Number of poles		3-pole	3-pole	
Bar centre distance		60 mm	60 mm	
For busbars E-Cu		12 x 5/10 mm ¹⁾ , 15 x 5 – 30 x 10 mm		
Tightening torque				
● Assembly screw (M5 x 16)		3 – 5 Nm	3 – 5 Nm	
● Cover attachment		1 – 3 Nm	1 – 3 Nm	
Model No. SV	4	9340.010	9340.000	
Accessories				
3 End covers for contact hazard protection on the sides	2	9340.070	9340.070	
Spacers for SV 9340.000/010	12	9340.090	9340.090	113

¹⁾ If 12 x 5/10 mm busbars are used, the spacer SV 9340.090 is additionally required.

Busbars E-Cu


To DIN EN 13 601.
Length: 2400 mm/bar.

Dimensions mm	Packs of	Model No. SV	Page
12 x 5	6	3580.000	110
12 x 10	6	3580.100	
15 x 5	6	3581.000	
15 x 10	6	3581.100	
20 x 5	6	3582.000	
20 x 10	6	3585.000	
25 x 5	6	3583.000	
30 x 5 ¹⁾	6	3584.000 ²⁾	
30 x 10 ¹⁾	6	3586.000 ²⁾	
Accessories			
Busbar cover section (length 1 m/each)	10	3092.000	110
Busbar connector for E-Cu			
4 12 x 5 – 15 x 10 mm (single connection)	3	9350.075	111
5 20 x 5 – 30 x 10 mm (single connection)	3	9320.020	111
6 20 x 5 – 30 x 10 mm (bayed connection) ³⁾	3	9320.030	111

¹⁾ Other busbar lengths, see page 109.

²⁾ Tin-plated version available on request.

³⁾ From enclosure to enclosure.



1 Base tray

For rear contact hazard protection of the flat bar assembly.

Length (L) mm	Packs of	Model No. SV
500	2	9340.100
700	2	9340.110
900	2	9340.120
1100	2	9340.130
2400	1	9340.170

2 Cover section

May be cut to length as required; for clip-on mounting to the base tray.

Length (L) mm	Packs of	Model No. SV
700	2	9340.200
1100	2	9340.210

Base tray and cover section

Material:


Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Note:

If the cover section is mounted from the front, the support panel (SV 9340.220) is needed for stability.



Base tray infill

For rear contact hazard protection when connecting the busbars from enclosure to enclosure.

Material:

Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Packs of	Model No. SV
2	9340.140

Supply includes:

Assembly parts.



Support panel

for cover section

To prevent side access to the cover section. The support panel also provides additional stability. Recommended mounting distance ≤ 500 mm.


Material:

Polyamide (PA 6.6).
Continuous operating temperature max. 105°C.
Fire protection corresponding to UL 94-V0.

Colour:




RAL 7035

Packs of	Model No. SV
5	9340.220



Form 2-4 busbar systems

PLS busbar supports (3-pole)



1 Rittal PLS 800

2 Rittal PLS 1600

Material:

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:

RAL 7035

**Short-circuit protection
diagram,**
see page 116.

Technical information
for the calculation
of rated currents,
see page 120.

For Rittal system	Packs of	1 PLS 800	2 PLS 1600
Number of poles		3-pole	3-pole
Bar centre distance		60 mm	60 mm
Tightening torque		3 – 5 Nm	3 – 5 Nm
• Assembly screw (M5 x 20)		0.7 Nm	0.7 Nm
• Busbar anti-slip guard			
Model No. SV	4	9341.000	9342.000
Accessories			
3 End covers for contact hazard protection on the sides	2	9341.070	9342.070

PLS special busbars

made from E-Cu


For Rittal system	Packs of	PLS 800	PLS 1600	Page
Cross-section		300 mm ²	900 mm ²	
Bar thickness		5 mm	10 mm	
Length mm	For enclosure width mm	Model No. SV		
		E-Cu	E-Cu, tin-plated	E-Cu
495	600 ¹⁾	3	3524.000 3524.200²⁾	3527.000 3527.200²⁾
695	800 ¹⁾	3	3525.000 3525.200²⁾	3528.000 3528.200²⁾
895	1000 ¹⁾	3	3525.010 3525.210²⁾	3528.010 3528.210²⁾
1095	1200 ¹⁾	3	3526.000 3526.200²⁾	3529.000 3529.200²⁾
2400	variable	1	3509.000 3509.200²⁾	3516.000 3516.200²⁾
Accessories				
4 PLS busbar connector (single connection)	3	3504.000	3514.000	111
5 PLS busbar connector (bayed connection) ³⁾	3	3505.000	3515.000	111
6 PLS expansion connectors ⁴⁾	3	9320.060	9320.070	111

¹⁾ For Rittal TS 8/ES enclosure systems.

²⁾ Delivery times available on request.

³⁾ From enclosure to enclosure.

⁴⁾ Two PLS rail connectors (single connection) are required to fit one expansion connector.



1 Base tray

For rear contact hazard protection of the PLS busbar assembly.

Length (L) mm	Packs of	Model No. SV For system	
		PLS 800	PLS 1600
500	2	9341.100	9342.100
700	2	9341.110	9342.110
900	2	9341.120	9342.120
1100	2	9341.130	9342.130
2400	1	9341.170	9342.170
Height (H) mm		32	43

2 Cover section

May be cut to length as required; for clip-on mounting to the base tray.

Length (L) mm	Packs of	Model No. SV
700	2	9340.200
1100	2	9340.210

Base tray and cover section

Material:


Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Note:

If the cover section is mounted from the front, the support panel (SV 9340.220) is needed for stability.



Base tray infill

For rear contact hazard protection when connecting the busbars from enclosure to enclosure.

Material:

Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

For system	Height (H) mm	Packs of	Model No. SV
PLS 800	32	2	9341.140
PLS 1600	43	2	9342.140

Supply includes:

Assembly parts.



Support panel

for cover section

To prevent side access to the cover section. The support panel also provides additional stability. Recommended mounting distance ≤ 500 mm.


Material:

Polyamide (PA 6.6).
Continuous operating temperature max. 105°C.
Fire protection corresponding to UL 94-V0.

Colour:






RAL 7035

Packs of	Model No. SV
5	9340.220



Form 2-4 busbar systems

Busbar connection adaptors (3-pole)



Material:

Chassis

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Cover

ABS,
fire protection corresponding to UL 94-V0.

Colour:

RAL 7035



Supply includes:

Cover.

Version (3-pole)	Packs of	1	2	3	4	Page
Rated current up to		63 A	125 A	250 A	800 A	
Rated operating voltage		690 V~	690 V~	690 V~	690 V~	
Connection of round conductors						
• Fine wire with wire end ferrule		2.5 – 10 mm ²	10 – 25 mm ²	35 – 120 mm ²	95 – 185 mm ²	
• Multi-wire		2.5 – 16 mm ²	16 – 35 mm ²	35 – 120 mm ²	95 – 300 mm ²	
• Solid		2.5 – 16 mm ²	–	–	–	
Clamping area for laminated copper bars		–	10 x 7.8 mm	18.5 x 15.5 mm	33 x 20 mm	
Tightening torque						
• Assembly screw		2 Nm	2 Nm	4 – 6 Nm	6 Nm	
• Terminal screw		2.5 Nm	2 – 3 Nm	12 Nm	12 – 14 Nm	
For bar thickness		5/10 mm	5/10 mm	5/10 mm	5/10 mm	
Outlet at top/bottom						
Model No. SV	1	–	9342.220	9342.250	9342.280	
Outlet at top						
Model No. SV	1	9342.200	9342.230	9342.260	9342.290	
Outlet at bottom						
Model No. SV	1	9342.210	9342.240	9342.270	9342.300	
Accessories						
Laminated copper bars		–	■	■	■	112

Form 2-4 busbar systems

Busbar connection adaptors (3-pole)



Material:

Chassis

SV 3439.010

Fibreglass-reinforced, thermoplastic polyester (PBT). Continuous operating temperature max. 140°C. Fire protection corresponding to UL 94-V0.

SV 9342.310/.320

Polyamide (PA 6.6), 25% fibreglass-reinforced. Continuous operating temperature max. 130°C. Fire protection corresponding to UL 94-V0.

Cover

ABS, fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Supply includes:

Cover.



SV 3439.010

When connecting round conductors 300 mm² with ring terminal, the terminal clamps fitted as standard in the busbar connection adaptors must be replaced with screws and/or bolts M10.

Version (3 x 1-pole)	Packs of	1	2	3	Page
Rated current up to		600 A	800 A	1600 A	
Rated operating voltage		690 V~	690 V~	690 V~	
Outlet		top/bottom	top/bottom	top/bottom	
Connection of round conductors					
• Fine wire with wire end ferrule		35 – 240 mm ²	95 – 185 mm ²	–	
• Multi-wire		35 – 240 mm ²	95 – 300 mm ²	–	
Clamping area for laminated copper bars					
• For 5 mm bar thickness		24 x 21 mm	33 x 27 mm	65 x 27 mm	
• For 10 mm bar thickness		24 x 21 mm	33 x 22 mm	65 x 22 mm	
Tightening torque					
• Assembly screw		15 – 20 Nm	–	–	
• Terminal screw		15 Nm	12 – 14 Nm	15 – 20 Nm	
For bar thickness		5/10 mm	5/10 mm	5/10 mm	
Model No. SV	1 set	3439.010	9342.310	9342.320	
Accessories					
Laminated copper bars		■	■	■	112

Form 2-4 busbar systems


Component adaptors 100 A/circuit-breaker component adaptors 125 A, 160 A (3-pole)



1 SV 9342.400
SV 9342.410

2 SV 9342.540

3 SV 9342.500



2 SV 9342.550

3 SV 9342.510

Material:

Chassis

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:

RAL 7035

Scope of supply

Circuit-breaker component adaptor:

Terminal cover and sliding
blocks for switchgear attachment.

Version	Packs of	1 Component adaptor	2 Circuit-breaker component adaptor	3 Circuit-breaker component adaptor	Page
Construction width		72 mm	90 mm	90 mm	
Length		210 mm	225 mm	215 mm	
Rated current up to		100 A	125 A	160 A	
Rated operating voltage		690 V~	690 V~		
Connection clamp		Box terminal	Box terminal		
Connection of round conductors		10 – 35 mm ²	35 – 120 mm ²		
Clamping area for laminated copper bars		10 x 7.8 mm	18.5 x 15.5 mm		
Tightening torque					
• Terminal screw		2 – 3 Nm	12 Nm		
• Rail attachment		2 Nm	4 – 6 Nm		
• Switchgear attachment		1.5 Nm	1.5 Nm		
For switchgear make/model	ABB	MS497	S2, T1, T2		
	Allen Bradley	–	140 – CMN		
	GE	–	FD		
	Merlin Gerin	–	NS80, NSC100		
	Mitsubishi	–	–		
	Moeller Electric	PKZ2 ¹⁾	NZM1		
	Siemens	S3	–		
	Telemecanique	GV3 ¹⁾	–		
	Terasaki	–	S125, E125		
Universal application	■ ¹⁾	–			
For bar thickness		5/10 mm	5/10 mm		
Cable outlet at the top ²⁾ Model No. SV	1	9342.400	9342.540	9342.500	
Cable outlet at the bottom ²⁾ Model No. SV	1	9342.410	9342.550	9342.510	

Accessories


Support rail Width 72 mm, height 15 mm	5	9320.120	–	–	113
Sliding blocks	6	–	9342.560	9342.560	113
Connection bracket		–	■	■	114

¹⁾ Mounting only possible with support rail SV 9320.120.


²⁾ Switch outlet or outgoing cable.

Form 2-4 busbar systems


Circuit-breaker component adaptors 250 A/630 A (3-pole)




1 SV 9342.600



2 SV 9342.700



1 SV 9342.610



2 SV 9342.710

Material:

Chassis

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:

RAL 7035

Supply includes:

Terminal cover and sliding
blocks for switchgear attach-
ment.

Version	Packs of	1	2	Page
Construction width		105 mm	140 mm	
Length		240 mm	324 mm	
Rated current up to		250 A	630 A	
Rated operating voltage		690 V~	690 V~	
Connection clamp		Box terminal	Screw terminal M10	
Connection of round conductors		35 – 120 mm ²	max. 150 mm ² 2)	
Clamping area for laminated copper bars		18.5 x 15.5 mm	32 x 10 mm	
Tightening torque				
● Terminal screw		12 Nm	30 – 32 Nm	
● Rail attachment		4 – 6 Nm	12 – 14 Nm	
● Switchgear attachment		1.5 Nm	2.5 Nm	
For switchgear make/model	ABB	S3, T3, T4	S5, T5	
	Allen Bradley	140 U – J	140 U – L	
	GE	FE	–	
	Merlin Gerin	NS(X)100, NS(X)160, NS(X)250	NS(X)400, NS(X)630	
	Mitsubishi	NF125-SGW, NF125-HGW, NF160-SGW, NF160-HGW	NF400-SEW, NF400-HEW, NF400-REW, NF600-SEW, NF600-HEW, NF600-REW	
	Moeller Electric	NZM2	NZM3	
	Siemens	VL160X, VL160, VL250	VL400, VL630 ³⁾	
	Telemecanique	GV7	–	
Terasaki	S160, S250, E250, H125, L125, H160, L160, H250, L250	E400, S400, H400, L400, E630, S630		
For bar thickness		5/10 mm	5/10 mm	
Cable outlet at the top ¹⁾ Model No. SV	1	9342.600	9342.700	
Cable outlet at the bottom ¹⁾ Model No. SV	1	9342.610	9342.710	

Accessories

3 Insert strip 25 mm to extend the construction width from 140 mm to 190 mm	4 (1 set)	–	9342.720	113
Sliding blocks	6	9342.640	–	113
Connection bracket		■	■	114



1) Switch outlet or outgoing cable.

2) With ring terminal.

3) Also required: Insert strip 25 mm (SV 9342.720).

Form 2-4 busbar systems

Busbar supports (4-pole)



Material:

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:
RAL 7035

**Short-circuit protection
diagram,**
see page 117.

Technical information
for the calculation
of rated currents,
see page 120.

1 With attachment holes
on the inside

Version	Packs of	1	Page
Number of poles		4-pole	
Bar centre distance		60 mm	
For busbars E-Cu		12 x 5/10 mm ¹⁾ , 15 x 5 – 30 x 10 mm	
Tightening torque			
● Assembly screw (M5 x 25)		3 – 5 Nm	
● Cover attachment		1 – 3 Nm	
Model No. SV	4	9340.004	
Accessories			
2 End covers for contact hazard protection on the sides	2	9340.074	
Spacers for SV 9340.004	12	9340.090	113

¹⁾ If 12 x 5/10 mm busbars are used, the spacer SV 9340.090 is additionally required.

Busbars E-Cu

To DIN EN 13 601.
Length: 2400 mm/bar.

Dimensions mm	Packs of	Model No. SV	Page
12 x 5	6	3580.000	110
12 x 10	6	3580.100	
15 x 5	6	3581.000	
15 x 10	6	3581.100	
20 x 5	6	3582.000	
20 x 10	6	3585.000	
25 x 5	6	3583.000	
30 x 5 ¹⁾	6	3584.000 ²⁾	
30 x 10 ¹⁾	6	3586.000 ²⁾	
Accessories			
Busbar cover section (length 1 m/each)	10	3092.000	110
Busbar connector for E-Cu			
3 12 x 5 – 15 x 10 mm (single connection)	3	9350.075	111
4 20 x 5 – 30 x 10 mm (single connection)	3	9320.020	111
5 20 x 5 – 30 x 10 mm (bayed connection) ³⁾	3	9320.030	111


¹⁾ Other busbar lengths, see page 109.

²⁾ Tin-plated version available on request.

³⁾ From enclosure to enclosure.

Form 2-4 busbar systems

System components (4-pole)



1 Base tray

For rear contact hazard protection of the flat bar assembly.

Length (L) mm	Packs of	Model No. SV
1100	2	9340.134

2 Cover section

May be cut to length as required; for clip-on mounting to the base tray.

Length (L) mm	Packs of	Model No. SV
1100	2	9340.214

Base tray and cover section

Material:

Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Note:

If the cover section is mounted from the front, the support panel (SV 9340.224) is needed for stability.



Support panel

for cover section

To prevent side access to the cover section. The support panel also provides additional stability. Recommended mounting distance ≤ 500 mm.


Material:

Polyamide (PA 6.6).
Continuous operating temperature max. 105°C.
Fire protection corresponding to UL 94-V0.

Colour:



RAL 7035

Packs of	Model No. SV
5	9340.224



Form 2-4 busbar systems

Busbar supports PLUS (4-pole)



1 Rittal 30 x 10 PLUS 2 Rittal PLS 1600 PLUS

Material:

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

**Short-circuit protection
diagram,**
see page 117.

Technical information
for the calculation
of rated currents,
see page 120.

Colour:

RAL 7035

For system	Packs of	1 Rittal 30 x 10 PLUS	2 Rittal PLS 1600 PLUS
Number of poles		4-pole	4-pole
Bar centre distance		60 mm	60 mm
For busbars E-Cu 30 x 10 mm		■	–
For PLS special busbars (PLS 1600)		–	■
Tightening torque			
● Assembly screw (M6 x 20)		3 – 5 Nm	3 – 5 Nm
● Cover attachment		5 – 7 Nm	5 – 7 Nm
Model No. SV	4	9342.014	9342.004
Accessories			
3 End covers for contact hazard protection on the sides	2	9342.074	9342.074

Busbars made from E-Cu

Detailed drawing:
SV 9661.300 to .380, see page 109.

For system	Rittal 30 x 10 PLUS			Page	Rittal PLS 1600 PLUS			Page
Size	30 x 10 mm				–			
Cross-section (bar thickness)	–				900 mm ² (10 mm) ¹⁾			
For enclosure width mm	Length mm	Packs of	Model No. SV		Length mm	Packs of	Model No. SV	
300 ²⁾	265	2	9661.330	109	–	–	–	
400 ²⁾	365	2	9661.340	109	–	–	–	
600 ²⁾	565	2	9661.360	109	495	3	3527.000	68
800 ²⁾	765	2	9661.380	109	695	3	3528.000	68
1000 ²⁾	965	2	9661.300	109	895	3	3528.010	68
1200 ²⁾	1165	2	9661.320	109	1095	3	3529.000	68
Variable	2400	6	3586.000	110	2400	1	3516.000	68

Accessories

4 PLS busbar connector (single connection)	–	–	–		–	3	3514.000	111
5 PLS busbar connector (bayed connection) ³⁾	–	–	–		–	3	3515.000	111
6 PLS expansion connectors ⁴⁾	–	–	–		–	3	9320.070	111
Baying bracket for SV 9661.300 to .380 (bayed connection)	95	4	9661.350	109	–	–	–	
Busbar connector for SV 3586.000	Single connection	–	3	9320.020	111	–	–	
	Baying connection ³⁾	–	3	9320.030	111	–	–	
Busbar cover section	1000	10	3092.000	110	–	–	–	

¹⁾ PLS special busbars (1600 A). To order tin-plated version, please add extension .2X0 to the Model No. Delivery times available on request.


²⁾ For Rittal TS 8/ES enclosure systems.

³⁾ From enclosure to enclosure.

⁴⁾ Two PLS rail connectors (single connection) are required to fit one expansion connector.

Form 2-4 busbar systems

System components (4-pole)



1 Base tray

For rear contact hazard protection of the busbar assembly PLUS.

Length (L) mm	Packs of	Model No. SV
1100	2	9342.134

2 Cover section

May be cut to length as required; for clip-on mounting to the base tray.

Length (L) mm	Packs of	Model No. SV
1100	2	9340.214

Base tray and cover section

Material:

Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Note:

If the cover section is mounted from the front, the support panel (SV 9340.224) is needed for stability.



Support panel for cover section

To prevent side access to the cover section. The support panel also provides additional stability. Recommended mounting distance ≤ 500 mm.


Material:

Polyamide (PA 6.6).
Continuous operating temperature max. 105°C.
Fire protection corresponding to UL 94-V0.

Colour:




RAL 7035

Packs of	Model No. SV
5	9340.224



Form 2-4 busbar systems

Busbar connection adaptors (4-pole)



Material:

Chassis

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Cover

ABS,
fire protection corresponding
to UL 94-V0.

Colour:

RAL 7035

Supply includes:

Cover.



Version (4-pole)	Packs of	1	2	Page
Rated current up to		125 A	250 A	
Rated operating voltage		690 V~	690 V~	
Connection of round conductors				
● Fine wire with wire end ferrule		10 – 25 mm ²	35 – 120 mm ²	
● Multi-wire		16 – 35 mm ²	35 – 120 mm ²	
Clamping area for laminated copper bars		10 x 7.8 mm	18.5 x 15.5 mm	
Tightening torque				
● Assembly screw		2 Nm	4 – 6 Nm	
● Terminal screw		2 – 3 Nm	12 Nm	
For bar thickness		5/10 mm	5/10 mm	
Outlet at top/bottom	1	9342.224	9342.254	
Model No. SV				
Outlet at top	1	9342.234	9342.264	
Model No. SV				
Outlet at bottom	1	9342.244	9342.274	
Model No. SV				

Accessories


Laminated copper bars		■	■	112
-----------------------	--	---	---	-----

Form 2-4 busbar systems

Busbar connection adaptors (4-pole)



1 SV 9342.310 with SV 9342.314



2 SV 9342.320 with SV 9342.324


Material:
Chassis
 Polyamide (PA 6.6),
 25% fibreglass-reinforced.
 Continuous operating
 temperature max. 130°C.
 Fire protection corresponding
 to UL 94-V0.
Cover
 ABS,
 fire protection corresponding
 to UL 94-V0.

Colour:
 RAL 7035
Supply includes:
 Cover.


Version	Packs of	1	2	Page
Rated current up to		800 A	1600 A	
Rated operating voltage		690 V~	690 V~	
Outlet		top/bottom	top/bottom	
Connection of round conductors				
● Fine wire with wire end ferrule		95 – 185 mm ²	–	
● Multi-wire		95 – 300 mm ²	–	
Clamping area for laminated copper bars				
● For 5 mm bar thickness		33 x 27 mm	65 x 27 mm	
● For 10 mm bar thickness		33 x 22 mm	65 x 22 mm	
Tightening torque		12 – 14 Nm	15 – 20 Nm	
For bar thickness		5/10 mm	5/10 mm	
Busbar connection adaptors (3 x 1-pole) Model No. SV	A 1 set	9342.310	9342.320	
Also required				
Connection adaptor (expansion set for 4-pole configuration)	B 1	9342.314	9342.324	
Accessories				
Laminated copper bars		■	■	112

Form 2-4 busbar systems


Circuit-breaker component adaptors 160 A/250 A (4-pole)




1 SV 9342.504



2 SV 9342.604



1 SV 9342.514



2 SV 9342.614

Material:

Chassis

Polyamide (PA 6.6),
25% fibreglass-reinforced.
Continuous operating
temperature max. 130°C.
Fire protection corresponding
to UL 94-V0.

Colour:

RAL 7035


Supply includes:

Terminal cover and sliding
blocks for switchgear attach-
ment.

Version	Packs of	1	2
Construction width		120 mm	140 mm
Length		277 mm	310 mm
Rated current up to		160 A	250 A
Rated operating voltage		690 V~	690 V~
Connection clamp		Box terminal	Box terminal
Connection of round conductors		35 – 120 mm ²	35 – 120 mm ²
Clamping area for laminated copper bars		18.5 x 15.5 mm	18.5 x 15.5 mm
Tightening torque			
● Terminal screw		12 Nm	12 Nm
● Rail attachment		4 – 6 Nm	4 – 6 Nm
● Switchgear attachment		1.5 Nm	1.5 Nm
For switchgear make/model	ABB	T1 (160 A), T2 (160 A)	T3S (250 A), T4V (315 A)
	Merlin Gerin	NSC100	NS(X)100, NS(X)160, NS(X)250
	Moeller Electric	NZM1-4 (125 A)	NZM2-4 (250 A)
	Siemens	–	VL160X, VL160, VL250
For bar thickness		5/10 mm	5/10 mm
Cable outlet at the top ¹⁾ Model No. SV	1	9342.504	9342.604
Cable outlet at the bottom ¹⁾ Model No. SV	1	9342.514	9342.614

¹⁾ Switch outlet or outgoing cable.





Two systems for optimum performance

Ingeniously simple assembly of low-voltage distributors and switchgear in the heavy current range.

The Rittal Maxi-PLS system components are supplied ready to assemble. All modules are standardised and batch-produced to ensure cost-effectiveness. One new addition to the range is the Flat-PLS, a busbar system for standard, commercially available flat bars. Whether you opt for Maxi-PLS or Flat-PLS – Ri4Power systems are the ideal links between power supply and power distribution, even down to the tiniest piece of equipment.

Form 2-4 busbar systems

Maxi-PLS and Flat-PLS up to 5500 A

Maxi-PLS



Standardised Maxi-PLS busbars in a super-compact design with an ingeniously simple attachment system.



Thanks to the **perfect system technology** and tailored dimensional pitch pattern, Maxi-PLS supports and bars ensure precise-fit, simple and fast installation.



With the aid of sliding blocks or studs, the **four attachment levels** of the Maxi-PLS busbars enable infinitely variable attachment and ...



... contacting of round conductors, laminated flat copper, connection brackets and connection kits.

Flat-PLS



System configuration analogous to Maxi-PLS with standard, commercially available flat copper bars.



Flat-PLS busbar support. **Multi-variant dimensioning** of the busbars with just two supports. Also suitable for aluminium and copper-plated aluminium bars.



Longitudinal connectors for Flat-PLS. For connecting Flat-PLS busbar systems, no drilling required. Adapted to your requirements.



All-round contact hazard protection for busbars and for connection kits. Also for preventive protection against accidental arcing.

Connection components




System packages for all commercially available air circuit-breakers.



Connected to Maxi-PLS and Flat-PLS busbars using standardised components on the **connection tailored to the respective air circuit-breaker.**




The combination of **isolator chassis, contact makers and connection brackets** forms the heart of the connection.



Type-tested to IEC 60 439-1, with ASTA certification. Design verification to IEC 61 439-1/-2. Special testing to EN 61 641/ IEC 61 641.

Form 2-4 busbar systems

System components, Maxi-PLS 1600/2000



Material:

Busbar support, end support,
end cover: PA 6.6
System attachment:
Stainless steel
Cover section: Hard PVC

Note:

Busbars for
PE/PEN combinations,
see page 109.

Detailed drawing,

see page 125.

Maxi-PLS system components			3-pole		4-pole	
			Packs of	Model No. SV	Packs of	Model No. SV
1	Busbar support	3	9640.000	3 + 1	9640.000 9649.000	
2	Busbar support, suitable for top mounting	3	9640.160	3	9640.160	
3	End support	6	9640.010	6 + 2	9640.010 9649.010	
4	System attachment for installing the busbar supports.					
	For application	For enclosure depth mm	Bar centre distance mm			
	In the roof/base section	600	100	2	9640.080	
		800	100	2	9640.088	
	Vertical coupling set	600	100	2	9649.076	
		800	100	2	9649.078	
	Rear section top/bottom	–	100	2	9640.098	
	Rear section (185 mm)	–	185	2	9640.150	
6	Cover section for clip-on mounting on the Maxi-PLS busbars, length 1000 mm.					
7	Longitudinal connector E-Cu for simple baying connection of Maxi-PLS busbars. Incl. sliding blocks, bolts, washers and nuts.					
	End cover for clip-on mounting on the end surface of Maxi-PLS busbars.			6 + 2	9640.060 9649.060	
5	Maxi-PLS busbars E-Cu (special lengths available on request).					
	Length mm	For enclosure width mm	For application ¹⁾	3/4-pole 1600 A	3/4-pole 2000 A	
	491	600	A	1	9640.206	
	525	600	B	1	9640.216	
	599	600	C	1	9640.226	
	691	800	A	1	9640.236	
	725	800	B	1	9640.246	
	799	800	C	1	9640.256	
	891	1000	A	1	9640.266	
	925	1000	B	1	9640.276	
	999	1000	C	1	9640.286	
	1091	1200	A	1	9640.296	
	1125	1200	B	1	9640.306	
	1199	1200	C	1	9640.316	
	2400	–	–	3	9640.365	
	2400	–	–	–	9649.360	


¹⁾ A = Cable connection system with end support

B = Left-hand or right-hand end enclosure in a switchgear installation

C = Bayed enclosure with sections bayed on the left and right

Form 2-4 busbar systems

Connection components, Maxi-PLS 1600/2000



Detailed drawing,
see page 126.


Maxi-PLS connection components			3-pole		4-pole	
			Packs of	Model No. SV	Packs of	Model No. SV
1 Connection bracket E-Cu Transition from the main busbar system to the connection kits ¹⁾ .						
For enclosure depth mm	Width mm	Number of brackets per phase				
600/800	60	1	1 set	9640.433	1 set	9640.433 + 9640.434
	60	2	1 set	9640.443	1 set	9640.443 + 9640.444
	60	3	1 set	9640.453	1 set	9640.453 + 9640.454
	100	2	1 set	9640.473	1 set	9640.473 + 9640.474
	100	3	1 set	9640.483	1 set	9640.483 + 9640.484
2 Isolator chassis for isolated routing of the connection brackets. Material: PA 6.6, black, including assembly parts.						
Bar centre distance mm	For connection bracket width mm					
100	60		1 set	9640.020	1 set	9649.020
3 U contact maker E-Cu for contacting the connection brackets to the Maxi-PLS busbars. Including sliding blocks.						
60 mm width			3	9640.170	3 + 1	9640.170 9649.170
100 mm width			3	9640.180	3	9640.180
4 Connection clamp for the connection of round conductors (Cu/Al) 95 to 300 mm ² (single-wire and multi-wire). Including assembly parts.						
50 mm width			1	9640.325	1	9640.325
5 Connection plates for the connection of laminated flat copper bars. Including assembly parts.						
Maximum clamping area	2 x 10 x 32 x 1 mm		3	9640.330	3	9640.330
	2 x 10 x 63 x 1 mm		3	9640.340	3	9640.340
	2 x 10 x 100 x 1 mm		3	9640.350	3	9640.350
6 Terminal stud for connecting cables with ring terminals. Including sliding blocks.						
Thread	M12	Length 30 mm	3	9640.370	3	9640.370
	M16	Length 30 mm	3	9640.380	3	9640.380
7 Sliding blocks for sliding into the Maxi-PLS busbar section at the sides.						
Thread	M8	Length (L) 20 mm	15	9640.970	15	9640.970
	M10	Length (L) 25 mm	15	9640.980	15	9640.980
8 Sliding nuts for retrospective insertion into the Maxi-PLS busbar section.						
Thread	M6		15	9640.900	15	9640.900
	M8		15	9640.910	15	9640.910
	M10		15	9640.920	15	9640.920
Threaded bolts for individual connection options ²⁾ . Including plain washers, spring lock washers and nuts.						
Thread	M6	Length 35 mm	6	9640.930	6	9640.930
	M8	Length 35 mm	6	9640.940	6	9640.940
	M10	Length 80 mm	6	9640.960	6	9640.960

¹⁾ For the assembly of connection brackets to Maxi-PLS busbars without using contact makers (e.g. for cable connection system), please choose sliding blocks SV 9640.980 (3-pole = 6 pcs., 4-pole = 8 pcs.).

²⁾ Sliding blocks or sliding nuts are additionally required for attachment.

Form 2-4 busbar systems

System components, Maxi-PLS 3200



Material:

Busbar support, end support,
end cover: PA 6.6
System attachment:
Stainless steel
Cover section: Hard PVC

Note:

PE/PEN combination/busbars,
see page 109.

Detailed drawing,

see page 125.

Maxi-PLS system components		3-pole		4-pole	
		Packs of	Model No. SV	Packs of	Model No. SV
1	Busbar support	3	9650.000	3 + 1	9650.000 9659.000
2	Busbar support, suitable for top mounting	3	9650.160	3	9650.160
3	End support	6	9650.010	6 + 2	9650.010 9659.010
4	System attachment for installing the busbar supports.				
	For application	For enclosure depth mm	Bar centre distance mm		
	In the roof/base section	600	150	2	9650.100
		800	150	2	9650.080
	Vertical coupling set	600	150	2	9650.076
		800	150	2	9659.078
	Rear section top/bottom	–	150	2	9650.098
	Rear section (185 mm)	–	185	2	9650.150
6	Cover section for clip-on mounting on the Maxi-PLS busbars, length 1000 mm.	5	9650.050	5	9650.050
7	Longitudinal connector E-Cu for simple baying connection of the Maxi-PLS busbars. Including sliding blocks, bolts, washers and nuts.	3	9650.190	3 + 1	9650.190 9659.190
	End cover for clip-on mounting on the end surface of Maxi-PLS busbars.	6	9650.060	6 + 2	9650.060 9659.060
	Stabiliser to increase short-circuit resistance (I_{cw} up to 124 kA).	4 ²⁾	9650.140	–	–
5	Maxi-PLS busbars E-Cu (special lengths available on request).				
	Length mm	For enclosure width mm	For application ¹⁾		3200 A
	491	600	A	1	9650.201
	525	600	B	1	9650.211
	599	600	C	1	9650.221
	691	800	A	1	9650.231
	725	800	B	1	9650.241
	799	800	C	1	9650.251
	891	1000	A	1	9650.261
	925	1000	B	1	9650.271
	999	1000	C	1	9650.281
	1091	1200	A	1	9650.291
	1125	1200	B	1	9650.301
	1199	1200	C	1	9650.311
	2400	–	–	3	9650.360
	2400	–	–	4	9659.360

¹⁾ A = Cable connection system with end support


B = Left-hand or right-hand end enclosure in a switchgear installation

C = Bayed enclosure with sections bayed on the left and right

²⁾ Modules for two complete stabilisers

Form 2-4 busbar systems

Connection components, Maxi-PLS 3200



Detailed drawing, see page 126.



Maxi-PLS connection components			3-pole		4-pole	
			Packs of	Model No. SV	Packs of	Model No. SV
1 Connection bracket E-Cu Transition from the main busbar system to the connector kits ¹⁾ .						
For enclosure depth mm	Width mm	Number of brackets per phase				
600	60	1	1 set	9650.400	–	–
	60	2	1 set	9650.410	–	–
	60	3	1 set	9650.420	–	–
	100	2	1 set	9650.470	–	–
	100	3	1 set	9650.480	–	–
800	120	3	1 set	9650.487	–	–
	60	1	1 set	9659.403	1 set	9659.403 + 9659.404
	60	2	1 set	9659.413	1 set	9659.413 + 9659.414
	60	3	1 set	9659.423	1 set	9659.423 + 9659.424
	100	2	1 set	9659.473	1 set	9659.473 + 9659.474
	100	3	1 set	9659.483	1 set	9659.483 + 9659.484
	120	3	1 set	9659.493	1 set	9659.493 + 9659.494
2 Isolator chassis for isolated routing of the connection brackets. Material: PA 6.6, black, including assembly parts.						
Bar centre distance mm		For connection bracket width mm				
150		60	1 set	9650.020	1 set	9659.020
150		100	1 set	9650.030	1 set	9659.030
3 U contact maker E-Cu for contacting the connection brackets to the Maxi-PLS busbars. Including sliding blocks.						
60 mm width			3	9650.170	3 + 1	9650.170 9659.170
100 mm width			3	9650.180	3 + 1	9650.180 9659.180
4 Connection clamp for the connection of round conductors (Cu/Al) 95 to 300 mm ² (single-wire and multi-wire). Including assembly parts.						
50 mm width			1	9650.325	1	9650.325
5 Connection plates for the connection of laminated flat copper bars. Including assembly parts.						
2 x 10 x 32 x 1 mm			3	9650.330	3	9650.330
Maximum clamping area 2 x 10 x 63 x 1 mm			3	9650.340	3	9650.340
2 x 10 x 100 x 1 mm			3	9650.350	3	9650.350
6 Terminal stud for connecting cables with ring terminals. Including sliding blocks.						
Thread	M12	Length 32 mm	3	9650.370	3	9650.370
	M16	Length 32 mm	3	9650.380	3	9650.380
7 Sliding blocks for sliding into the Maxi-PLS busbar section at the sides.						
Thread	M10	Length (L) 25 mm	15	9650.980	15	9650.980
	M12	Length (L) 35 mm	15	9650.990	15	9650.990
8 Sliding nuts for retrospective insertion into the Maxi-PLS busbar section.						
Thread	M6		15	9650.900	15	9650.900
	M10		15	9650.910	15	9650.910
	M12		15	9650.920	15	9650.920
Threaded bolts for individual connection options ²⁾ . Including plain washers, spring lock washers and nuts.						
Thread	M6	Length 35 mm	6	9650.930	6	9650.930
	M10	Length 35 mm	6	9650.940	6	9650.940
	M12	Length 80 mm	6	9650.960	6	9650.960

¹⁾ For the assembly of connection brackets to Maxi-PLS busbars without using contact makers (e.g. for cable connection system), please choose sliding blocks SV 9650.990 (3-pole = 6 pcs., 4-pole = 8 pcs.).

²⁾ Sliding blocks or sliding nuts are additionally required for attachment.

Form 2-4 busbar systems

Connection components, Maxi-PLS/Flat-PLS



Connector kits

For connecting air circuit-breakers (ACB) to Maxi-PLS/Flat-PLS busbar systems in SV-TS 8 modular enclosures. Please include the design code of the specification below in the order text for your connector kit. We highly recommend the Rittal Power Engineering software for easier configuration of the connector kits – see page 123.

Model No. SV	Design code													
	a	b	c	d	e	f	g	h	i	j	k	l	m	n
Top	9676.910													
Bottom	9676.912													

Material:
E-Cu

Note:
Please quote the complete design code on all enquiries and orders.

! Also required:




M10/M12 screw connections, see page 104.
Terminal studs Maxi-PLS, see page 103.
Screw connections Flat-PLS, see page 104.

Enclosure

a	Width mm	400 4	600 6	800 8	1000 0	Selection <input type="checkbox"/>
	b	Height mm	1800 8	2000 0	2200 2	Selection <input type="checkbox"/>
c			Depth mm	600 6	800 8	Selection <input type="checkbox"/>

Form 2-4 busbar systems

Connection components, Maxi-PLS/Flat-PLS



Air circuit-breakers

f	Brand	ABB	A	Selection <input type="checkbox"/>	
		Mitsubishi	J		
		Merlin Gerin	M		
		Siemens/Moeller	S		
		Terasaki	D		
	Various	V			
g	Size	1/none	1	Selection <input type="checkbox"/>	
		2	2		
		3	3		
		4	4		
h	Rated current	630 A	A	Selection <input type="checkbox"/>	
		800 A	B		
		1000 A	C		
		1250 A	D		
		1600 A	E		
		2000 A	F		
		2500 A	G		
		3200 A	H		
		4000 A	I		
i	No. of poles/ version	Static	3-pole	3	Selection <input type="checkbox"/>
			4-pole	4	
	Rack-mounted	3-pole	6		
		4-pole	8		
j	Position	Behind the door	H	Selection <input type="checkbox"/>	
		In front of the door (in door cut-out)	V		
k	Compartment height directly underneath the circuit-breaker	0 mm	0	Selection <input type="checkbox"/>	
		150 mm	1		
		200 mm	2		
		250 mm	3		
		300 mm	4		
		400 mm	5		
		600 mm ¹⁾	6		
		800 mm	7		
1000 mm	8				
n ²⁾	Compartment height of circuit-breaker	600 mm	6	Selection <input type="checkbox"/>	
		800 mm	7	<input type="checkbox"/>	
		1000 mm	8	<input type="checkbox"/>	

Underneath the air circuit-breaker

d	Busbar type			Selection <input type="checkbox"/>	
	Maxi-PLS	1600	3-pole		A
			4-pole		B
		2000	3-pole		C
			4-pole		D
		3200	3-pole		E
			4-pole		F
	Flat-PLS	60 2 bars	3-pole		G
			4-pole		H
		60 4 bars	3-pole		I
			4-pole		J
		100 2 bars	3-pole		K
4-pole			L		
100 4 bars	3-pole	M			
	4-pole	N			
e	Busbar system configuration			Selection <input type="checkbox"/>	
	in rear section, Form 1 ¹⁾				5
	in the base section				6
	in the lower rear section				7
	as cable connection system				8
directly underneath the circuit-breaker			9		

Above the air circuit-breaker

i	Busbar type			Selection <input type="checkbox"/>	
	Maxi-PLS	1600	3-pole		A
			4-pole		B
		2000	3-pole		C
			4-pole		D
		3200	3-pole		E
			4-pole		F
	Flat-PLS	60 2 bars	3-pole		G
			4-pole		H
		60 4 bars	3-pole		I
			4-pole		J
		100 2 bars	3-pole		K
4-pole			L		
100 4 bars	3-pole	M			
	4-pole	N			
m	Busbar system configuration			Selection <input type="checkbox"/>	
	in the roof section				1
	in the top rear section				2
	as cable connection system, connection space height 600 mm				3
	directly above the circuit-breaker				4
	in rear section, Form 1 ¹⁾				5
	as cable connection system connection space height 800 mm				8
	as cable connection system connection space height 1000 mm				9

¹⁾ Standard height in Form 1
²⁾ For Form 1 please select a 6

Form 2-4 busbar systems

Flat-PLS



Busbar support Flat-PLS

for flat copper busbars

For the configuration of busbar systems from flat copper bars. For mounting on a system attachment or directly on the mounting plate. Also suitable for aluminium and copper-plated aluminium bars.

Max. permissible tolerance of bar width (60/100 mm) ± 0.3 mm, bar thickness (10 mm) ± 0.15 mm.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced. Continuous operating temperature max. 130°C. Fire protection corresponding to UL 94-V0.

Colour: RAL 9005

Short-circuit protection diagrams, see page 118.

Current carrying capacity, see page 121.

Supply includes: Assembly parts.


Note:

The internal use of busbar supports may be rotated through 90° so that the busbars **3** may be upright or horizontal **4** for installation purposes.

Busbars, see page 110.

+ Accessories:

System attachments for Flat-PLS, see page 90.
End cover, see page 92.
Filler piece, see page 92.
Spacer, see page 92.



System	For busbars up to	A mm	B mm	C mm	D mm	E mm	F	Md ²⁾ Nm	G mm	Packs of	Model No. SV
1 Flat-PLS 60	4 x 60 x 10 mm	127.5	60	120	70	50	M8	8	100	1	9676.002¹⁾
2 Flat-PLS 100	4 x 100 x 10 mm	162.5	100	165	90	55	M10	9	125	1	9676.004¹⁾

¹⁾ With a bar width of < 60/100 mm the spacer should be used.

²⁾ When using only 1, 2 or 3 bars, the vacant bar slots should be closed using the filler pieces.

³⁾ Rated torque



System attachments for Flat-PLS

For the assembly of 3- or 4-pole busbar systems of flat copper bars.

For mounting on the TS frame or punched section with mounting flange.

Material:

Stainless steel

Supply includes:

Assembly parts.

For busbar support Flat-PLS 60

For application	For enclosure depth mm	Bar centre distance mm	For assembly		Packs of	Model No. SV
			3-pole	4-pole		
1 In the roof section/ base section	600	120	■	■	2	9674.162
	800	120	■	■	2	9674.182
Vertical coupling set	600	120	■	■	2	9674.172
	800	120	■	■	2	9674.192
Rear section ^{1) 2)}	–	120	■	■	2	9674.122
Rear section ³⁾	–	185	■	–	2	9674.152
2 Single-pole assembly, for mounting on the TS 8 frame	–	–	–	–	2	9674.102

For busbar support Flat-PLS 100

For application	For enclosure depth mm	Bar centre distance mm	For assembly		Packs of	Model No. SV
			3-pole	4-pole		
1 In the roof section/ base section	600	165	■	–	2	9674.164
	800	165	■	■	2	9674.184
Vertical coupling set	600	165	■	–	2	9674.174
	800	165	■	■	2	9674.194
Rear section ^{1) 2)}	–	165	■	■	2	9674.124
Rear section ³⁾	–	185	■	–	2	9674.154
2 Single-pole assembly, for mounting on the TS 8 frame	–	–	–	–	2	9674.104

¹⁾ For mounting between the TS 8 roof frame and TS punched section with mounting flange.

²⁾ In conjunction with form separation, may only be used in 800 mm deep TS enclosures.

³⁾ For mounting between two TS punched sections with mounting flanges.



Busbar support Flat-PLS

for flat copper bar, suitable for stabiliser bar

For the configuration of busbar systems from flat copper bars with increased short-circuit resistance. For mounting on a system attachment or directly on the mounting plate.

Also suitable for aluminium and copper-plated aluminium bars.

Max. permissible tolerance of bar width (60/100 mm) ± 0.3 mm, bar thickness (10 mm) ± 0.15 mm.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced. Continuous operating temperature max. 130°C. Fire protection corresponding to UL 94-V0.

Colour:

RAL 9005

Short-circuit protection diagrams,

see page 118.

Current carrying capacity,

see page 121.

Supply includes:

Assembly parts.

Note:

The internal busbar support insert may be rotated through 90° to allow upright or flat installation of the busbars.

Busbars,

see page 110.




Also required:

System attachments for Flat-PLS, see page 90.
Busbar stabiliser bar, see page 91.



Accessories:

End cover, see page 92.
Filler piece, see page 92.
Spacer, see page 92.



System	For busbars up to	A mm	B mm	C mm	D mm	E mm	F	Md ²⁾ Nm	G mm	Packs of	Model No. SV
Flat-PLS 60	4 x 60 x 10 mm	130	60	120	70	50	M8	10	100	1	9676.020 ¹⁾
Flat-PLS 100	4 x 100 x 10 mm	170	100	165	90	55	M10	12	125	1	9676.021 ¹⁾

¹⁾ With a bar width of < 60/100 mm the spacer should be used.

When using only 1, 2 or 3 bars, the vacant bar slots should be closed using the filler pieces.

²⁾ Rated torque



Busbar stabiliser bars

for busbar support Flat-PLS

For the configuration of busbar systems from flat copper bars with increased short-circuit resistance. For mounting in conjunction with system attachment and Flat-PLS busbar support for stabiliser bar.

Material:

Stainless steel



Also required:

System attachments for Flat-PLS, see page 90.



Accessories:


Busbar claw, see page 93.



For system	For busbar supports	Bar centre distance mm	System assembly	Packs of	Model No. SV
Flat-PLS 60	SV 9676.020	120	3-pole	2	9676.022
			4-pole	2	9676.023
Flat-PLS 100	SV 9676.021	165	3-pole	2	9676.024
			4-pole	2	9676.025
		185	3-pole	2	9676.027

Form 2-4 busbar systems

Flat-PLS



End covers

for busbar support Flat-PLS

Inserted into the Flat-PLS busbar supports for electric shockproof covering of the busbar ends.

Material:

Polyamide (PA 6.6).
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 9005



For system	For busbar supports		Packs of	Model No. SV
Flat-PLS 60	SV 9676.002	SV 9676.020	2	9676.006
Flat-PLS 100	SV 9676.004	SV 9676.021		



Filler pieces

for busbar support Flat-PLS

To cover open chambers in busbar supports when using only 1, 2 or 3 bars per conductor or when using a busbar support as an end support.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced.
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 9005



Note:

If only 2 busbars are used per support, the bars should be inserted as shown in the left-hand picture, in order to ensure the usability of connection brackets and connector kits.

For system	For busbar supports ³⁾		Packs of	Model No. SV
Flat-PLS 60 ¹⁾	SV 9676.002	SV 9676.020	16	9676.008
Flat-PLS 100 ²⁾	SV 9676.004	SV 9676.021		

¹⁾ Two required per chamber.

²⁾ Three required per chamber.

³⁾ When using a busbar support as an end support, eight are required per support.



Spacers

for busbar support Flat-PLS

When using smaller busbar widths, the spacer piece should be inserted into the chambers of the support to compensate for width differences.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced.
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 9005



Note:

The spacers should always be inserted into the support base, so that the busbars are as close as possible to the support lid (see left-hand picture).

For system	E-Cu Dimensions	Required number of spacers per chamber	Packs of	Model No. SV
Flat-PLS 60	40 x 10 mm	2	16	9676.007
	50 x 10 mm	1		
Flat-PLS 100	80 x 10 mm	2		



Busbar claws

for Flat-PLS

For the assembly of busbar systems from flat copper bars with increased short-circuit resistance or for the mechanical stabilisation of busbar stacks. For use on free busbar lengths > 300 mm in order to achieve the specified short-circuit resistance levels.

Material:

Stainless steel.

Accessories: Sheet steel, zinc-plated, passivated

Supply includes:

Assembly parts.



Accessories:

Covers for busbar claws, see page 93.

Detailed drawing, see page 127.



For system	For busbar width mm	Screw	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60	2 x 60 x 10 mm	M10 x 80	15	1	9676.011
	3 x 60 x 10 mm	M10 x 80	15	1	9676.012
	4 x 60 x 10 mm	M10 x 80	15	1	9676.013
Flat-PLS 100	2 x 100 x 10 mm	M10 x 120	15	1	9676.014
	3 x 100 x 10 mm	M10 x 120	15	1	9676.015
	4 x 100 x 10 mm	M10 x 120	15	1	9676.016
Flat-PLS	2 x B x 10 mm ¹⁾	Without screw ²⁾	15	1	9676.017
	3 x B x 10 mm ¹⁾	Without screw ³⁾	15	1	9676.018
	4 x B x 10 mm ¹⁾	Without screw ³⁾	15	1	9676.019

¹⁾ For the version without screw, the relevant screw must additionally be ordered according to the relevant busbar width B.

²⁾ Required number of screws per busbar claw: 1

³⁾ Required number of screws per busbar claw: 2

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 60	15	8	9676.806	104
	50	M10 x 70	15	8	9676.807	104
	60	M10 x 80	15	8	9676.808	104
	80	M10 x 100	15	8	9676.810	104
	100	M10 x 120	15	8	9676.812	104



Covers

for busbar claws

For contact hazard protection of the busbar claws. The cover terminates flush with the cover sections of the Flat-PLS system.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced. Continuous operating temperature max. 130°C. Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035



Accessories:


Cover section, see page 94.



For system	No. of bars per conductor	For busbar claw			Packs of	Model No. SV
		SV 9676.011	SV 9676.014	SV 9676.017 SV 9676.832		
Flat-PLS 60/ Flat-PLS 100	2	SV 9676.011	SV 9676.014	SV 9676.018	8	9676.046
	3	SV 9676.012	SV 9676.015	SV 9676.018	8	9676.047
	4	SV 9676.013	SV 9676.016	SV 9676.019	8	9676.048

Form 2-4 busbar systems

Flat-PLS



Cover sections

for Flat-PLS

For contact hazard protection of the Flat-PLS busbar system and connector kits for open air circuit-breakers. The cover sections may also be used outside of Flat-PLS for covering standard, commercially available flat copper bars. Edge cover sections should always be combined with side cover sections when assembling the cover.

Material:

Thermally modified hard PVC.
Continuous operating temperature max. 95°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035

Detailed drawing,

see page 127.



	For system	No. of bars per conductor	For busbar width mm	Length mm	Packs of	Model No. SV
1	Edge cover section for bar systems with no space between the bars	1	–	1000	10	9676.041
		2	–	1000	10	9676.042
		3	–	1000	10	9676.043
2	Edge cover section for bar systems with 10 mm space between the bars	2	–	1000	10	9676.052
		3	–	1000	10	9676.053
		4	–	1000	10	9676.054
3	Side cover section for bar systems, to match the edge cover sections	–	60	1000	10	9676.056
		–	80	1000	10	9676.058
		–	100	1000	10	9676.059



Direct connection terminals

for Flat-PLS

For the direct connection of round conductors 95 – 300 mm² (single-wire and multi-wire). The mounting accessories supplied loose may be used to mount the connection terminal on the Flat-PLS busbar system without the need for drilling.

Material:

Brass alloy,
nickel-plated surface finish

Supply includes:

Assembly parts.

Detailed drawing,

see page 128.

Max. rated current with 300 m²
at 20°K = 630 A
at 70°K = 1300 A

For system	For busbar width mm	Screw	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60	60	M10 x 120	20	1	9676.731
Flat-PLS 100	100	M10 x 160	20	1	9676.733
Flat-PLS	B ¹⁾	Without screw	20	1	9676.730

¹⁾ For the version without screw, the relevant screw must additionally be ordered according to the relevant busbar width B.

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 100	20	8	9676.810	104
	50	M10 x 110	20	8	9676.811	104
	60	M10 x 120	20	8	9676.812	104
	80	M10 x 140	20	8	9676.814	104
	100	M10 x 160	20	8	9676.816	104



Connection plates with studs M12/16

for Flat-PLS

For connecting ring terminals to a Flat-PLS busbar system with 2 – 4 bars per conductor. The mounting accessories supplied loose may be used to mount the connection terminal on a Flat-PLS busbar system without the need for drilling.

Material:

E-Cu, nickel-plated

Supply includes:

Assembly parts.



Also required:

Screw connections Flat-PLS, see page 104.

Detailed drawing,

see page 128.



For system	Terminal studs	Stud length mm	Rated torque Terminal stud Nm	Rated torque Screw M10 Nm	Packs of	Model No. SV
Flat-PLS	M12	30	40	20	1	9676.700
Flat-PLS	M16	30	40	20	1	9676.704

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 60	20	8	9676.806	104
	50	M10 x 70	20	8	9676.807	104
	60	M10 x 80	20	8	9676.808	104
	80	M10 x 100	20	8	9676.810	104
	100	M10 x 120	20	8	9676.812	104



Connection plates with studs M10

for Flat-PLS

For connecting ring terminals to a Flat-PLS busbar system with 2 – 4 bars per conductor. The straight-through screws and the mounting accessories supplied loose may be used to mount the connection terminal on a Flat-PLS busbar system without the need for drilling.

Material:

E-Cu, nickel-plated

Supply includes:

Assembly parts.



Also required:

Screw connections Flat-PLS, see page 104.

Detailed drawing,

see page 128.

For system	Terminal stud	Rated torque Screw M10 Nm	Packs of	Model No. SV
Flat-PLS	M10	20	1	9676.710
	2 x M10	20	1	9676.714

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 80	20	8	9676.808	104
	50	M10 x 90	20	8	9676.809	104
	60	M10 x 100	20	8	9676.810	104
	80	M10 x 120	20	8	9676.812	104
	100	M10 x 140	20	8	9676.814	104

Form 2-4 busbar systems

Flat-PLS



Connection plates for laminated copper bars

for Flat-PLS

For connecting laminated copper bars up to 2 x 10 x 100 x 1.0 mm (Flexibar) to a Flat-PLS busbar system with 2 – 4 bars per conductor. The mounting accessories supplied loose may be used to mount the copper bar on a Flat-PLS busbar system without the need for drilling.

Material:

Infill plate: E-Cu, nickel-plated
Top: Stainless steel

Supply includes:

Assembly parts.

Laminated copper bars,

see page 112.

Detailed drawing,

see page 128.

For system	For busbar width mm	For laminated copper bars up to	Screw	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60	60	2 x 10 x 32 x 1 mm	2 off M10 x 115	20	1	9676.741
Flat-PLS 60	60	2 x 10 x 63 x 1 mm	2 off M10 x 115	25	1	9676.742
Flat-PLS 60	60	2 x 10 x 100 x 1 mm	2 off M10 x 115	30	1	9676.743
Flat-PLS 100	100	2 x 10 x 32 x 1 mm	2 off M10 x 150	20	1	9676.744
Flat-PLS 100	100	2 x 10 x 63 x 1 mm	2 off M10 x 150	25	1	9676.745
Flat-PLS 100	100	2 x 10 x 100 x 1 mm	2 off M10 x 150	30	1	9676.746
Flat-PLS	B ¹⁾	2 x 10 x 32 x 1 mm	Without screws	20	1	9676.747 ²⁾
Flat-PLS	B ¹⁾	2 x 10 x 63 x 1 mm	Without screws	25g	1	9676.748 ²⁾
Flat-PLS	B ¹⁾	2 x 10 x 100 x 1 mm	Without screws	30	1	9676.749 ²⁾

¹⁾ For the version without screw, the relevant screw must additionally be ordered according to the relevant busbar width B.

²⁾ Version without assembly screws.

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 90	20/25/30	8	9676.809	104
	50	M10 x 100	20/25/30	8	9676.810	104
	80	M10 x 130	20/25/30	8	9676.813	104



Contact makers

for Flat-PLS

For connecting connection brackets and connector kits of flat copper bars to Flat-PLS busbar systems; no drilling required
For connecting the connection brackets or a connector kit to the main busbar system, a suitable screw connector kit should be ordered separately.

Material:

E-Cu

Supply includes:

Contact maker, assembly aid for Flat-PLS with 60 or 100 mm bar width¹⁾, assembly parts.

Note:

Nickel-plated version of the contact maker for connecting aluminium bars available on request.




Also required:

Screw connections Flat-PLS²⁾, see page 104.

Detailed drawing,

see page 127.



For system	For busbar width (B) mm	No. (n) of bars per conductor	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60 + Flat-PLS 100	60	2	20	1	9676.526
	60	3 or 4	20	1	9676.546
	80	2	20	1	9676.528
	80	3 or 4	20	1	9676.548
	100	2	20	1	9676.520
	100	3 or 4	20	1	9676.540

¹⁾ If alternative main busbar widths are used, the screws supplied loose with the mounting aid cannot be used.

²⁾ Required screw length for attaching the connection bracket:

Length of screw connection = (no. of bars of the connection bracket x 10 mm) + width of main busbar system + 40 mm.

Required screw length for attaching the connector kits to main busbar systems in the rear section:

Length of screw connection = (no. of bars of connector kits x 10 mm) + width of main busbar system + 40 mm + sum total of distances between the bars of the connector kits.



Connection bracket

for Flat-PLS

For connecting connection brackets and connector kits of flat copper bars to Flat-PLS busbar systems; no drilling required.

Material:
E-Cu

Supply includes:
Connection bracket without assembly parts.



Also required:

Contact maker, see page 96.
Connector kit for Flat-PLS, see page 88.
Screw connections for Flat-PLS¹⁾, see page 104.
M12 screw connections for connection brackets, see page 104.

For system Flat-PLS	For conductor	No. of bars per conductor	Bar width of connection bracket	Packs of	Model No. SV	Packs of	Model No. SV	
				For enclosure depth 600 mm		For enclosure depth 800 mm		
for connecting connector kits of air circuit-breakers to a Flat-PLS 60 main bar system in the roof section, base section, directly above or below the air circuit-breaker	L1, L2, L3	1	60	1 set	9676.201	1 set	9676.221	
	N			1 set	9676.202	1 set	9676.222	
	L1, L2, L3	2		1 set	9676.203	1 set	9676.223	
	N			1 set	9676.204	1 set	9676.224	
	L1, L2, L3	3		1 set	9676.205	1 set	9676.225	
	N			1 set	9676.206	1 set	9676.226	
	L1, L2, L3	2	100	1 set	9676.213	1 set	9676.233	
	N			1 set	9676.214	1 set	9676.234	
	L1, L2, L3	3		1 set	9676.215	1 set	9676.235	
	N			1 set	9676.216	1 set	9676.236	
	L1, L2, L3	3		120	1 set	9676.217	1 set	9676.237
	N				1 set	9676.218	1 set	9676.238
L1, L2, L3	1	60	1 set		9676.301	1 set	9676.321	
N			–		–	1 set	9676.322	
L1, L2, L3	2		1 set		9676.303	1 set	9676.323	
N			–		–	1 set	9676.324	
L1, L2, L3	3		1 set	9676.305	1 set	9676.325		
N			–	–	1 set	9676.326		
L1, L2, L3	2	100	1 set	9676.313	1 set	9676.333		
N			–	–	1 set	9676.334		
L1, L2, L3	3		1 set	9676.315	1 set	9676.335		
N			–	–	1 set	9676.336		
L1, L2, L3	3		120	1 set	9676.317	1 set	9676.337	
N				–	–	1 set	9676.338	

¹⁾ Screw length = (no. of bars x 10 mm) + bar width of main busbar + 40 mm.
No. of screws per bracket: for 2 bars, per conductor of the main busbar system: 2, for 3/4 bars, per conductor of the main busbar system: 4



Connector kits

for Flat-PLS

For connecting air circuit-breakers (ACB) to Flat-PLS busbar systems in SV-TS 8 modular enclosures. Please include the design code for the relevant specification in the order text for your connector kit.

We highly recommend the Rittal Power Engineering software for easier configuration of the connector kits – see page 123.

Note:

Model No. design code, see page 88.

Material:

E-Cu

Supply includes:
Connection bracket.



Also required:

M12 screw connections for connection brackets, see page 104.
Screw connections Flat-PLS, see page 104.

Form 2-4 busbar systems

Flat-PLS



Longitudinal connector

for Flat-PLS

For connecting Flat-PLS busbar systems, no drilling required.

Material:

E-Cu

Supply includes:

Assembly parts.

Note:

Nickel-plated version of the longitudinal connector for connecting aluminium bars available on request.

Detailed drawing,

see page 127.



For system	No. of bars per conductor	For busbar width mm	Screw	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60	2	60	M10 x 100	20	1	9676.626
	3 or 4	60	M10 x 100	20	1	9676.646
Flat-PLS 100	2	80	M10 x 120	20	1	9676.628
	3 or 4	80	M10 x 120	20	1	9676.648
	2	100	M10 x 140	20	1	9676.620
Flat-PLS	3 or 4	100	M10 x 140	20	1	9676.640
	2	B ¹⁾	Without screw	20	1	9676.621²⁾ 3)
	3 or 4	B ¹⁾	Without screw	20	1	9676.641²⁾ 4)

¹⁾ For the version without screw, the relevant screw must additionally be ordered according to the relevant busbar width B.

²⁾ Design as for SV 9676.620/SV 9676.640, but without assembly screws.

³⁾ Number of screws: 4

⁴⁾ Number of screws: 8

Accessories	For busbar width B mm	Screw	Rated torque Nm	Packs of	Model No. SV	Page
Screw connections for Flat-PLS busbar systems	40	M10 x 80	20	8	9676.808	104
	50	M10 x 90	20	8	9676.809	104



Angular connector

for Flat-PLS busbar systems

For connecting horizontal and vertical Flat-PLS busbar systems.

Material:

E-Cu

Supply includes:

Bracket.

Note:

No. of corner brackets required for applications

- 3-pole = 3
- 4-pole = 4



Also required:

Screw connections for Flat-PLS busbar system¹⁾, see page 104.

Claw with threaded insert, see page 104.

For systems	Bar population up to	For enclosure depth mm	No. of brackets	Packs of	Model No. SV
Flat-PLS 60	2 x 40 x 10 mm	600/800	2 x 40 x 10 mm	1	9675.842
Flat-PLS 60	2 x 60 x 10 mm	600/800	3 x 40 x 10 mm	1	9675.843
Flat-PLS 60/100	4 x 40 x 10 mm or 2 x 100 x 10 mm	600/800	2 x 80 x 10 mm	1	9675.882
Flat-PLS 60	4 x 60 x 10 mm	600/800	3 x 80 x 10 mm	1	9675.883
Flat-PLS 100	4 x 80 x 10 mm	600/800	2 x 100 x 10 mm	1	9675.892
Flat-PLS 100	4 x 100 x 10 mm	600/800	3 x 100 x 10 mm	1	9675.893

¹⁾ Required length of screw connection = (no. of brackets x 10 mm) + bar width of main busbar system + 20 mm.



Cable connection system

for Maxi-PLS/Flat-PLS

The type-tested cable connection system facilitates fast, cost-optimised assembly while guaranteeing the very highest level of security. Thanks to the sliding block system, the connection components may be moved around as required, for simple, manageable connection of cables and lines.

In conjunction with the connection brackets and connection kits of Ri4Power system technology, the complete assembly of air circuit-breaker sections is simple and requires minimal installation time.

Cable connection systems are dimensioned according to

- Rated current for incoming/outgoing circuit
- Enclosure dimensions
- Number of poles in the connection
- Type and number of cables or lines

For rated current of cable connection system		Packs of	For enclosure width mm				Page
			600	800	1000	1200	
			Model No. SV				
up to 2000 A	Cable connection bar	1	9640.206	9640.236	9640.266	9640.296	84
	End supports	6	9640.010	9640.010	9640.010	9640.010	84
	Terminal studs M12	3	9640.370				85
	Terminal studs M16	3	9640.380				85
	Direct connection terminal	1	9640.325				85
up to 3200 A	Cable connection bar	1	9640.201	9640.231	9640.261	9640.291	84
	End supports	6	9640.010	9640.010	9640.010	9640.010	84
	Terminal studs M12	3	9640.370				85
	Terminal studs M16	3	9640.380				85
	Direct connection terminal	1	9640.325				85
up to 4000 A	1 Cable connection bar	1	9650.201	9650.231	9650.261	9650.291	86
	2 End supports	6	9650.010	9650.010	9650.010	9650.010	86
	3 Terminal studs M12	3	9650.370				87
	Terminal studs M16	3	9650.380				87
	4 Direct connection terminal	1	9650.325				87

Additionally required

Side panel module for cable connection space	For enclosure depth 600 mm	2	9673.069	51
	For enclosure depth 800 mm	2	9673.089	51

For more connection accessories, see page 85 or 87.

Order example

Cable connection for 2500 A, 4-pole, for enclosure W x H x D 800 x 2000 x 800 mm:
Designed for 6 cables, 240 mm² per conductor, with ring terminals for studs M12

	Required quantity	Model No. SV
Side panel module for cable connection space (D = 800 mm)	2	9673.089
Cable connection bar	4	9640.231
End supports	8	9640.010
Terminal studs M12	24	9640.370

Form 2-4 busbar systems

Accessories



T-connector kits

for Maxi-PLS/RiLine60 bar systems

For connecting horizontal Maxi-PLS main busbar systems to vertical RiLine60 distribution busbar systems in the modular outgoing section.

Material:

E-Cu

Supply includes:

Assembly parts.



Also required:

Distribution busbars, see page 102.

Main busbar system	Distribution busbar system	Packs of	Model No. SV			
			For enclosure depth mm			
			600		800	
			3-pole	4-pole	3-pole	4-pole
In the roof section/ base section	Behind the compartment					
Maxi-PLS 1600/2000	Cu 30 x 10/5 mm	1 set	9675.303	9675.304	9675.303	9675.304
Maxi-PLS 3200	Cu 30 x 10/5 mm	1 set	9675.311	–	9675.313	9675.314
Maxi-PLS 1600/2000	PLS 1600	1 set	9675.306	9675.307	9675.306	9675.307
Maxi-PLS 3200	PLS 1600	1 set	9675.315	–	9675.316	9675.317
In the roof section/ base section	In the compartment (indoors)					
Maxi-PLS 1600/2000	Cu 30 x 10/5 mm	1 set	9675.321	9675.322	9675.323	9675.324
Maxi-PLS 3200	Cu 30 x 10/5 mm	1 set	9675.331	–	9675.333	9675.334
Maxi-PLS 1600/2000	PLS 1600	1 set	9675.325	9675.328	9675.326	9675.327
Maxi-PLS 3200	PLS 1600	1 set	9675.335	–	9675.336	9675.337
In the rear section top/bottom	Behind the compartment					
Maxi-PLS 1600/2000	Cu 30 x 10/5 mm	1 set	9675.343	9675.344	9675.343	9675.344
Maxi-PLS 3200	Cu 30 x 10/5 mm	1 set	–	–	9675.353	9675.354
Maxi-PLS 1600/2000	PLS 1600	1 set	9675.346	9675.347	9675.346	9675.347
Maxi-PLS 3200	PLS 1600	1 set	–	–	9675.356	9675.357
In the rear section top/bottom	In the compartment (indoors)					
Maxi-PLS 1600/2000	Cu 30 x 10/5 mm	1 set	9675.361	9675.362	9675.363	9675.364
Maxi-PLS 3200	Cu 30 x 10/5 mm	1 set	–	–	9675.373	9675.374
Maxi-PLS 1600/2000	PLS 1600	1 set	9675.365	9675.368	9675.366	9675.367
Maxi-PLS 3200	PLS 1600	1 set	–	–	9675.376	9675.377



T-connector kits

for Rittal RiLine60 busbar systems

For connecting horizontal RiLine60 main busbar systems to vertical RiLine60 distribution busbar systems.

Material:

E-Cu

Supply includes:

Assembly parts.



Also required:

Distribution busbars, see page 102.

Main busbar system	Distribution busbar system	Packs of	Model No. SV	
			3-pole	4-pole
Behind the compartment				
PLS 1600	Cu 30 x 10/5 mm	1 set	9675.130	9675.140
Cu 30 x 10/5 mm	Cu 30 x 10/5 mm	1 set	9675.133	9675.143
PLS 1600	PLS 1600	1 set	9675.136	9675.146
Inside the compartment				
PLS 1600/Cu 30 x 10/5 mm	Cu 30 x 10/5 mm	1 set	9675.153¹⁾	9675.163¹⁾
PLS 1600	PLS 1600	1 set	9675.156¹⁾	9675.166¹⁾

¹⁾ Only suitable for enclosure depth 600 mm.



T-connector kits

for Flat-PLS/RiLine60 bar systems

For connecting horizontal Flat-PLS main busbar systems to vertical RiLine60 distribution busbar systems in the modular outgoing section.

Material:

E-Cu

Supply includes:

Sets of screws for connection to distribution busbar system.



Also required:

Distribution busbar, see page 102.
 Spacer rolls SV 9676.503¹⁾, see page 103.
 Screw connections for Flat-PLS¹⁾ 2), see page 104.
 Claw with threaded insert M10¹⁾, see page 104.



Main busbar system	Distribution busbar system	Packs of	Model No. SV			
			For enclosure depth mm			
			600		800	
			3-pole	4-pole	3-pole	4-pole
In the roof section/ base section	Behind the compartment					
Flat-PLS 60	Cu 30 x 10/5 mm	1 set	9675.501	9675.502	9675.503	9675.504
Flat-PLS 100	Cu 30 x 10/5 mm	1 set	9675.511	–	9675.513	9675.514
Flat-PLS 60	PLS 1600	1 set	9675.505	9675.508	9675.506	9675.507
Flat-PLS 100	PLS 1600	1 set	9675.515	–	9675.516	9675.517
In the roof section/ base section	In the compartment (indoors)					
Flat-PLS 60	Cu 30 x 10/5 mm	1 set	9675.521	9675.522	9675.523	9675.524
Flat-PLS 100	Cu 30 x 10/5 mm	1 set	9675.531	–	9675.533	9675.534
Flat-PLS 60	PLS 1600	1 set	9675.525	9675.528	9675.526	9675.527
Flat-PLS 100	PLS 1600	1 set	9675.535	–	9675.536	9675.537
In the rear section top/bottom	Behind the compartment					
Flat-PLS 60	Cu 30 x 10/5 mm	1 set	–	–	9675.543	9675.544
Flat-PLS 100	Cu 30 x 10/5 mm	1 set	–	–	9675.553	9675.554
Flat-PLS 60	PLS 1600	1 set	–	–	9675.546	9675.547
Flat-PLS 100	PLS 1600	1 set	–	–	9675.556	9675.557
In the rear section top/bottom	In the compartment (indoors)					
Flat-PLS 60	Cu 30 x 10/5 mm	1 set	–	–	9675.563	9675.564
Flat-PLS 100	Cu 30 x 10/5 mm	1 set	–	–	9675.573	9675.574
Flat-PLS 60	PLS 1600	1 set	–	–	9675.566	9675.567
Flat-PLS 100	PLS 1600	1 set	–	–	9675.576	9675.577

¹⁾ For main busbar system with 2 or 3 bars, 1 spacer roll, 1 screw connection and 1 claw should be ordered per pole.

²⁾ For main busbar systems with 4 bars, 2 spacer rolls, 2 screw connections and 2 claws should be ordered per pole.

Accessories	For busbar width B mm	Screws for connecting a T-connection kit for						Page
		Cu 30 x 10/5 mm			PLS 1600			
		Packs of	Screw	Model No.	Packs of	Screw	Model No.	
Screw connections for Flat-PLS busbar systems	40	8	M10 x 90	9676.809	8	M10 x 100	9676.810	104
	50	8	M10 x 100	9676.810	8	M10 x 110	9676.811	104
	60	8	M10 x 110	9676.811	8	M10 x 120	9676.812	104
	80	8	M10 x 130	9676.813	8	M10 x 140	9676.814	104
	100	8	M10 x 150	9676.815	8	M10 x 160	9676.816	104

Form 2-4 busbar systems

Accessories



Distribution busbars

Prepared for the connection of T-connector kits. The lengths are adapted for applications in TS 8 enclosures.

Material:
E-Cu

For main busbar system with RiLine60 and distribution busbar system behind the compartment	For distribution busbar system in the compartment (indoors)	Packs of	Version			
			Cu 30 x 10 mm		PLS 1600	
For enclosure height mm			Length mm	Model No. SV	Length mm	Model No. SV
1800	–	1	1210	9675.218	1150	9675.238
2000	–	1	1410	9675.210	1350	9675.230
2200	1800 ¹⁾	1	1610	9675.212	1550	9675.232
–	2000 ¹⁾	1	1810	9675.220	1750	9675.240
–	2200 ¹⁾	1	2010	9675.222	1950	9675.242

¹⁾ Also suitable as a vertical busbar for PE/PEN/N.



Corner bracket

E-Cu

- For connecting horizontal Maxi-PLS busbar systems in the roof/base section to vertical busbar systems.
- For 90° connection of two Maxi-PLS busbars in the rear area.
- May be used for individual installation.

Material:
E-Cu

Supply includes:
Bracket, threaded bolts, nuts, washers.

Note:
No. of corner brackets required for applications

- 3-pole = 3
- 4-pole = 4

For Maxi-PLS	Packs of	3/4-pole			Page
		1600	2000	3200	
No. of brackets per phase		2 x 60 x 10 mm	3 x 60 x 10 mm	3 x 80 x 10 mm	
Model No. SV	1	9640.705	9640.700	9650.700	
Also required					
Sliding blocks	15	9640.980 ¹⁾	9640.980 ¹⁾	9650.990 ¹⁾	85/87

¹⁾ Quantity required per corner bracket: 4



Connector kits

for busbar riser

For connecting horizontal Maxi-PLS busbar systems in the rear section to vertical busbar systems.

Material:
E-Cu

Supply includes:
Bracket.

! Also required:

Terminal studs for connector kits and connection brackets, see page 103.

Sliding blocks

For Maxi-PLS	Packs of	Model No. SV	Page
1600/2000	15	9640.980 ¹⁾	85
3200	15	9650.990 ¹⁾	87

¹⁾ Quantity required per connector kit: 4

For Maxi-PLS	For enclosure depth mm	No. of brackets per phase	Packs of	Model No. SV	
				for 3-pole	for 4-pole
1600	600/800	2	1 set	9660.318	9660.318 + 9660.319
2000	600/800	3	1 set	9660.313	9660.313 + 9660.314
3200	600	3	1 set	9660.363	–
3200	800	3	1 set	9660.368	9660.368 + 9660.369




Spacer rolls

for Maxi-PLS and flat copper bars

For use as a universal spacer.

Material:

E-Cu



Diameter (D) mm	Cu bar – Cu bar		Maxi-PLS – Cu bar		Flat-PLS – Cu bar		Packs of	Model No. SV
	Cross-section size mm ²	Max. rated current A	Contact area mm ²	Max. rated current A	Contact area mm ²	Max. rated current A		
30	550	1100	360	800	380	850	4	9676.503
40	1100	2200	780	1600	670	1400	4	9676.504
50	1800	3400	1380	2800	990	2000	4	9676.505



System attachments

for RiLine60 main busbar system

System attachment with M5 and M6 threaded holes in a 50 mm pitch for the rear assembly of a RiLine60 main busbar system up to 1600 A. For locating into the TS frame.

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Assembly parts.

Note:

RiLine60 busbar systems, see page 66 – 76.

For enclosure width mm	Width mm	Height mm	Packs of	Model No. SV
300	238.5	362	1	9674.003
400	338.5	362	1	9674.004
600	538.5	362	1	9674.006
800	738.5	362	1	9674.008



Terminal studs

for connector kits and connection brackets

Special bolt for attaching a connector kit or connection bracket with and without U contact maker to a Maxi-PLS busbar section.

May be used for 3- and 4-pole connector kits.

Supply includes:

8 nuts and 8 washers.

Note:

For a connector kit bar width of 120 mm, 2 packs are required per connector kit.

No. of bars per phase when using		Packs of	For Maxi-PLS 1600/2000		For Maxi-PLS 3200	
with U contact maker	without U contact maker ¹⁾		Screw design	Model No. SV	Screw design	Model No. SV
–	1	8	M10 x 35	9676.971	M12 x 40	9676.981
–	2	8	M10 x 45	9676.972	M12 x 50	9676.982
1	3	8	M10 x 55	9676.973	M12 x 60	9676.983
2	–	8	M10 x 70	9676.976	M12 x 70	9676.986
3	–	8	M10 x 80	9676.977	M12 x 80	9676.987

¹⁾ Sliding blocks – see page 85/87 – additionally required.

Form 2-4 busbar systems

Accessories



Screw connections

for connection brackets

For connecting connection brackets and a connector kit.

May be used for 3- and 4-pole connector kits.

Material:

Steel screws, zinc-plated, passivated

Supply includes:

8 nuts and 16 washers.

Note:

For a bar width of 120 mm, 2 packs are required per connector kit.

For systems	Screw design	Rated torque Nm	No. of bars per phase	Packs of	Model No. SV
Maxi-PLS 1600/2000/3200	M10 x 40	20	1	8	9676.966
	M10 x 60	20	2	8	9676.967
	M10 x 80	20	3	8	9676.968
Maxi-PLS 1600/2000/3200 and Flat-PLS 60 + 100	M12 x 40	40	1	8	9676.961
	M12 x 60	40	2	8	9676.962
	M12 x 80	40	3	8	9676.963



Screw connections

for Flat-PLS busbar systems

For attaching connection brackets and connector kits, with and without contact makers, to Flat-PLS busbar systems.

Material:

Stainless steel

Supply includes:

Allen screw,
spring lock washer and
plain washer.

For systems	Screw design	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60 + 100	M10 x 60	20	8	9676.806
	M10 x 70	20	8	9676.807
	M10 x 80	20	8	9676.808
	M10 x 90	20	8	9676.809
	M10 x 100	20	8	9676.810
	M10 x 110	20	8	9676.811
	M10 x 120	20	8	9676.812
	M10 x 130	20	8	9676.813
	M10 x 140	20	8	9676.814
	M10 x 150	20	8	9676.815
	M10 x 160	20	8	9676.816
	M10 x 170	20	8	9676.817
	M10 x 190	20	8	9676.819



Claw with nut M10

for Flat-PLS

Double claw with nut M10. Used in combination with screw connections for the mechanical connection of connection components such as angular connectors.

Material:

Stainless steel

Supply includes:


8 claws.



Also required:

Screw connectors for Flat-PLS, see page 104.

For systems	Insert nut	Rated torque Nm	Packs of	Model No. SV
Flat-PLS 60 + 100	M10	20	8	9676.832



Stacking insulator

To support the connection kits top/bottom for circuit-breakers. Easily retro-fitted.


Supply includes:
Assembly parts.

Packs of	Model No. SV
6	9660.200



Also required:

Support rail for stacking insulator, see page 105.



Support rails

for stacking insulator

For attaching to the outer mounting level of the TS 8 enclosure and for the configuration of stacking insulators. C rail may also be used as cable management bar.

Material:
Sheet steel, zinc-plated, passivated

Supply includes:
Assembly parts.

For enclosure width mm	Packs of	Model No. SV
400	2	9676.194
600	2	9676.196
800	2	9676.198



Stabiliser

for connection kit

To increase short-circuit resistance of the connection kits to 100 kA, 1 sec.

2 stabilisers are required per connection kit.
May be used for 3- and 4-pole connector kits.
Fitted in addition to the stacking insulators.

Material:
Tapped rod: Fibreglass-reinforced plastic

Supply includes:
2 stabilisers
Assembly parts.

For enclosure width mm	Packs of	Model No. SV
400	2	9676.184
600	2	9676.186
800	2	9676.188

Form 2-4 busbar systems

Accessories



Busbar support

for switch-disconnector-fuse section

Busbar support for the distribution busbar system of the switch-disconnector-fuse section, to assemble the distribution busbar. The busbar supports are mounted on the section corner pieces of the assembly kit.

Material:

Fibreglass-reinforced plastic

Supply includes:

Mounting bracket and screws.



Number of poles	For bars mm	Packs of	Model No. SV
3/4-pole	50 x 10	1	9674.415
3/4-pole	60 x 10	1	9674.416
3/4-pole	80 x 10	1	9674.418
3/4-pole	100 x 10	1	9674.410



Also required:

Assembly kit for switch-disconnector-fuse section, see page 46.

End support for switch-disconnector-fuse section, see page 106.

Distribution busbar for switch-disconnector-fuse section, see page 106.



End support

for switch-disconnector-fuse section

End support for the distribution busbar system of the switch-disconnector-fuse section, for vertical support of the distribution system with infeed from above.

The end support is secured to the section corner piece of the assembly kit.

Material:

Fibreglass-reinforced plastic

Supply includes:

Mounting bracket and screws.



Number of poles	For bars mm	Packs of	Model No. SV
3/4-pole	50 x 10	1	9674.435
3/4-pole	60 x 10	1	9674.436
3/4-pole	80 x 10	1	9674.438
3/4-pole	100 x 10	1	9674.430



Also required:

Assembly kit for switch-disconnector-fuse section, see page 46.

Distribution busbar for switch-disconnector-fuse section, see page 106.



Distribution busbar

for switch-disconnector-fuse section

Distribution busbar to fit the Ri4Power main busbar systems Maxi-PLS and Flat-PLS for installation in the switch-disconnector-fuse sections.

Material:

E-Cu



Also required:

Busbar support for switch-disconnector-fuse section, see page 106.

End support for switch-disconnector-fuse section, see page 106.

Terminal block distribution busbar, see page 108.



Dimensions mm	Length mm	Packs of	Model No. SV	Length mm	Packs of	Model No. SV
	For enclosure height 2000 mm			For enclosure height 2200 mm		
50 x 10	1632.5	1	9674.405	1832.5	1	9674.425
60 x 10	1632.5	1	9674.406	1832.5	1	9674.426
80 x 10	1632.5	1	9674.408	1832.5	1	9674.428
100 x 10	1632.5	1	9674.400	1832.5	1	9674.420



Distribution busbar cover

for Jean Müller switch-disconnector-fuse section

Busbar cover as kit for covering the distribution busbar system of a switch-disconnector-fuse section, designed to install devices from Jean Müller. The 150 mm high busbar and cable connection space covers shield the busbar compartment from the functional space and the cable connection compartment so that it is safe from probe contact, with a protection category of IP 20. The internal separation significantly enhances personal safety of the switchgear, and is a pre-requisite for all work when the system is live. For systems from Form 2a and above, this cover is compulsory.

Material:
PVC, black

Supply includes:

Busbar cover and cable connection space cover for enclosure height 2000 mm and 2200 mm.

Packs of	Model No. SV
1 set	9674.380



Also required:

Punched rail cover, distribution busbar, see page 107.



Punched rail cover, distribution busbar

for Jean Müller switch-disconnector-fuse section

Required for mounting the distribution busbar cover. The cover modules are inserted into the punched rail and create form-fit separation of the busbar compartment from the functional space and cable chamber. Suitable for use in enclosures with height 2000 mm and 2200 mm. For systems from Form 2a and above, this cover is compulsory.

Material:
Sheet steel, zinc-plated, passivated

Supply includes:

2 punched rails.

Packs of	Model No. SV
1 set	9674.381

Note:

For 1 switch-disconnector-fuse section, 1 pack of punched rails is required.



Distribution busbar cover

for ABB/Siemens switch-disconnector-fuse section

Busbar cover to cover the distribution busbar system of a switch-disconnector-fuse section, designed to install equipment from ABB (model SlimLine) or Siemens (model 3NJ62).

The 200 mm high busbar compartment covers shield the busbar compartment from the functional space so that it is safe from probe contact, with a protection category of IP 20. The internal separation significantly enhances personal safety of the switchgear, and is a pre-requisite for all work when the system is live. For systems from Form 2a and above, this cover is compulsory.

Material:
PVC, black

Note:

The distribution busbar cover for switch-disconnector-fuse sections from ABB/Siemens may be ordered from ABB under order number NHP 407062R000X.

For enclosure height 2000 mm, a height of 1500 mm should be covered, and for enclosure height 2200 mm, a height of 1700 mm should be covered.



Form 2-4 busbar systems

Accessories



Connection bracket

for switch-disconnector-fuse section

For connecting Maxi-PLS or Flat-PLS main busbar systems to distribution busbar systems of the switch-disconnector-fuse sections, no drilling required.

Material:
E-Cu

Supply includes:
Assembly parts.



Also required:

Maxi-PLS contact makers, 60 mm, see page 85/87.
Flat-PLS contact makers, 60 mm, see page 96.
Terminal block distribution bar, see page 108.

For system	For application	For conductor	Packs of	Model No. SV	Packs of	Model No. SV
			For enclosure depth 600 mm		For enclosure depth 800 mm	
Flat-PLS 60	Roof section/base section	L1, L2, L3	1 set	9674.451	1 set	9674.453
Flat-PLS 60	Roof section/base section	N	1 set	9674.452	1 set	9674.454
Flat-PLS 60	Rear section top/bottom	L1, L2, L3	1 set	–	1 set	9674.473
Flat-PLS 60	Rear section top/bottom	N	1 set	–	1 set	9674.474
Flat-PLS 100	Roof section/base section	L1, L2, L3	1 set	9674.455	1 set	9674.457
Flat-PLS 100	Roof section/base section	N	1 set	–	1 set	9674.458
Flat-PLS 100	Rear section top/bottom	L1, L2, L3	1 set	–	1 set	9674.477
Flat-PLS 100	Rear section top/bottom	N	1 set	–	1 set	9674.478
Maxi-PLS 1600/2000	Roof section/base section	L1, L2, L3	1 set	9674.441	1 set	9674.443
Maxi-PLS 1600/2000	Roof section/base section	N	1 set	9674.442	1 set	9674.444
Maxi-PLS 1600/2000	Rear section top/bottom	L1, L2, L3	1 set	9674.461	1 set	9674.463
Maxi-PLS 1600/2000	Rear section top/bottom	N	1 set	9674.462	1 set	9674.464
Maxi-PLS 3200	Roof section/base section	L1, L2, L3	1 set	9674.445	1 set	9674.447
Maxi-PLS 3200	Roof section/base section	N	1 set	–	1 set	9674.448
Maxi-PLS 3200	Rear section top/bottom	L1, L2, L3	1 set	–	1 set	9674.467
Maxi-PLS 3200	Rear section top/bottom	N	1 set	–	1 set	9674.468



Terminal block distribution busbar

for switch-disconnector-fuse section

Terminal block for connecting the connection brackets to the distribution busbar system of the switch-disconnector-fuse section, no drilling required.

Material:
E-Cu

Supply includes:
Assembly parts.

Detailed drawing,
see page 128.

For distribution busbar width mm	Packs of	Model No. SV
50/60	1	9674.485
80/100	1	9674.488



Also required:

Connection bracket for switch-disconnector-fuse section, see page 108.
Distribution busbar for switch-disconnector-fuse section, see page 106.





1 Busbars

made from E-Cu

Suitable for


- Direct installation in TS 8 enclosures
- Busbar support
 - SV 9340.000/.010, see page 66
 - SV 9340.004, see page 74
 - SV 9340.030/.040, see page 110
 - SV 9342.014, see page 76
 - SV 3052.000, see Cat. 32, page 391
 - SV 3073.000, see Cat. 32, page 387
- PE/PEN combinations in conjunction with combination angle and baying bracket.



For enclosure width mm	Packs of	Length mm	30 x 5 mm	30 x 10 mm	Length mm	40 x 10 mm	80 x 10 mm
			Model No. SV	Model No. SV		Model No. SV	Model No. SV
300	2	265	9661.335	9661.330	292	9661.030	9661.130
400	2	365	9661.345	9661.340	392	9661.040	9661.140
600	2	565	9661.365	9661.360	592	9661.060	9661.160
800	2	765	9661.385	9661.380	792	9661.080	9661.180
1000	2	965	9661.305	9661.300	992	9661.000	9661.100
1200	2	1165	9661.325	9661.320	1192	9661.020	9661.120
A mm			15	15		20	20
B mm			–	–		158,5	158,5
C mm			Ø 11	Ø 11		Ø 14	Ø 14

Accessories

2 Baying bracket E-Cu	4	95	9661.355	9661.350	–	–	–
		–	–	–	88	9661.050	9661.150



PE/PEN combination angle

for PE/PEN combinations

The PE/PEN combination, comprised of busbars, combination angles and baying brackets, facilitates type-tested assembly to IEC 60 439-1.

The pre-manufactured combination angles and baying brackets, and the busbars customised to the individual enclosure width, facilitate inexpensive, time-saving assembly.

Material:

E-Cu

Supply includes:

Assembly parts.

Technical specifications:

Tested short-circuit resistance
PE/PEN combination

- 30 x 5 mm:
I_{cw} 18 kA, 1 sec.
- PE/PEN combination
30 x 10 mm:
I_{cw} 30 kA, 1 sec.
- PE/PEN combination
40/80 x 10 mm:
I_{cw} 60 kA, 1 sec.



Combination angle for	Packs of	For busbars mm		
		30 x 5	30 x 10	40 x 10/80 x 10
Form 2-4 insert	4	9661.235	9661.230	2 9661.240 ¹⁾
Other applications	4	9661.235	9661.230	1 9661.200 ¹⁾

¹⁾ Material of PE/PEN combination angles E-Cu 40 x 10 mm




Base isolators

For configuring busbar systems with any given bar centre distances and for assembling PE or PEN bars.

Material:


Duroplastic polyester (UP resin).
Continuous operating temperature max. 135°C.

Rated operating voltage	1 kV	1 kV
Tensile strength	12 kN	13 kN
Torsional strength	75 Nm	90 Nm
Bending strength	6 kN	6 kN
Tightening torque	40 Nm	40 Nm
A mm	40	50
B mm	15	19
Ø C mm	32	42
D mm	SW 36	SW 50
Packs of	6	6
Model No. SV	3031.000	3032.000



Form 2-4 busbar systems


Accessories



Busbars

made from E-Cu
To DIN EN 13 601.
Length: 2400 mm/bar.

Dimensions mm	Weight/bar kg	Packs of	Model No. SV
12 x 5	1.28	6	3580.000
15 x 5	1.60	6	3581.000
20 x 5	2.14	6	3582.000
25 x 5	2.67	6	3583.000
30 x 5	3.20	6	3584.000
12 x 10	2.56	6	3580.100
15 x 10	3.20	6	3581.100
20 x 10	4.27	6	3585.000
30 x 10	6.41	6	3586.000
40 x 10	8.55	3	3587.000
50 x 10	10.68	3	3588.000
60 x 10	12.82	3	3589.000
80 x 10	17.09	3	3590.000
100 x 10	21.38	3	3590.010




Busbar cover section

Contact hazard protection via full encapsulation of the busbars. May be cut to required length.

Material:
Thermally modified hard PVC.
Continuous operating temperature max. 91°C.
Fire protection corresponding to UL 94-V0.

For busbars mm	Width (B) mm	Packs of	Model No. SV
12 x 5 – 30 x 10	40.6	10 @ 1 m	3092.000
40 – 60 x 10	70.6	10 @ 1 m	3085.000




Busbar support

1- and 2-pole

Material:
Polyamide (PA 6.6), 25% fibreglass-reinforced.
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Colour:
RAL 7035



Version	1 1-pole	2 2-pole	3 1-pole
Bar centre distance	– ¹⁾	60 mm	– ¹⁾
For busbars E-Cu	12 x 5 – 30 x 10 mm	12 x 5 ²⁾ – 30 x 10 mm	PLS 1600
Tightening torque	(M5 x 16) 3 – 5 Nm	(M5 x 16) 3 – 5 Nm	(M6 x 20/35 ³⁾) 3 – 5 Nm
• Assembly screw M5 x 16	1 – 3 Nm	1 – 3 Nm	0.7 Nm
• Cover attachment/busbar anti-slip guard			
Packs of	4	4	4
Model No. SV	9340.030⁴⁾	9340.040⁵⁾	9342.030⁴⁾

- ¹⁾ Bayable for a bar centre distance of 60 mm.
²⁾ If 12 x 5/10 mm busbars are used, the spacer SV 9340.090 is additionally required.
³⁾ 35 mm when using the additional raised section.
⁴⁾ PEN/N/PE support
⁵⁾ N/PE support

+ Accessories:

4 Additional attachment for SV 9340.030
Optional anti-twist guard for SV 9340.030.
Facilitates support alignment with horizontal or vertical mounting.

Packs of	Model No. SV
4	9340.035



Busbar connectors

For connecting busbars, no drilling required.


Material:

SV 9350.075

Top part: St 37, nickel-plated surface finish
Base: E-Cu

SV 9320.020/SV 9320.030

Top part: Sheet steel, zinc-plated, passivated
Contact plate: E-Cu, silver-plated




For busbars mm	Application		Tightening torque	Packs of	Model No. SV
	Single connection	Bayed connection ¹⁾			
12 x 5 – 15 x 10	1	–	5 Nm/15 Nm ²⁾	3	9350.075
20 x 5 – 30 x 10	2	–	20 Nm	3	9320.020
	–	3	20 Nm	3	9320.030

¹⁾ From enclosure to enclosure

²⁾ Hex socket

– Screw M8 = 5 Nm

– Grub screw M8 = 15 Nm



PLS busbar connectors



For connecting the PLS special busbars; no drilling required.

Material:

E-Cu, nickel-plated

For	Packs of	Model No. SV for system	
		PLS 800	PLS 1600
A Single connection	3	3504.000	3514.000
B Baying connection ¹⁾	3	3505.000	3515.000
Tightening torque		10 – 15 Nm	15 – 20 Nm

¹⁾ From enclosure to enclosure (TS 8)



PLS expansion connectors

For thermal and mechanical compensation during connection of PLS special busbars from enclosure to enclosure (TS 8).

Material:


E-Cu

Packs of	Model No. SV for system	
	A PLS 800	B PLS 1600
3	9320.060	9320.070

Also required

PLS busbar connectors ¹⁾	3504.000	3514.000
-------------------------------------	----------	----------

¹⁾ Two busbar connectors are needed to fit one expansion connector.




Note:

With a temperature increase of 30 K, the busbars will expand in length by around 0.5 mm/m. Consequently, the use of an expansion connector is recommended for busbar systems with lengths in excess of 3 m.

Form 2-4 busbar systems

Laminated copper bars and accessories



Laminated copper bars Rittal Flexibar "S"

Length: 2000 mm/bar.

Material: Cu lamina

- High-purity electrolyte copper F20

Insulation

- High-strength vinyl compound
- Expansion 370%
- Temperature range: -30°C to +105°C
- Flame retardant version to UL 94-V0
- Dielectric strength: 20 kV/mm

Note:

Short-circuit protection diagram, see page 119.

Configuration ¹⁾ mm	I _n for 50 K ²⁾	I _n for 30 K ²⁾	I _n for 10 K ²⁾	Packs of	Model No. SV
8 x 6.0 x 0.5	165 A	125 A	–	1	3565.010
6 x 9.0 x 0.8	250 A	220 A	120 A	1	3565.000
6 x 13.0 x 0.5	200 A	150 A	110 A	1	3566.000
4 x 15.5 x 0.8	300 A	210 A	140 A	1	3567.000
6 x 15.5 x 0.8	350 A	290 A	170 A	1	3568.000
10 x 15.5 x 0.8	450 A	350 A	190 A	1	3569.000
5 x 20.0 x 1.0	400 A	300 A	180 A	1	3570.000
5 x 24.0 x 1.0	450 A	370 A	230 A	1	3571.000
10 x 24.0 x 1.0	800 A	600 A	340 A	1	3572.000
5 x 32.0 x 1.0	550 A	470 A	280 A	1	3573.000
10 x 32.0 x 1.0	1000 A	800 A	460 A	1	3574.000
5 x 40.0 x 1.0	800 A	600 A	340 A	1	3575.000
10 x 40.0 x 1.0	1200 A	950 A	500 A	1	3576.000
5 x 50.0 x 1.0	900 A	700 A	400 A	1	3577.000
10 x 50.0 x 1.0	1400 A	1000 A	600 A	1	3578.000
10 x 63.0 x 1.0	1600 A	1240 A	715 A	1	3579.000

¹⁾ Number of lamina x lamina width x lamina thickness

²⁾ The conductor temperature of the laminated copper bar is derived by adding the ambient temperature and the temperature increase together.

Example:

SV 3565.000 carrying 220 A, i.e. the temperature increases by 30 K. At an ambient temperature of 35°C, this produces a resultant conductor temperature of 35°C + 30 K = 65°C.



Universal support

For the attachment of laminated copper bars from 20 x 5 to 63 x 10 mm.

Material:

Fibreglass-reinforced, thermoplastic polyester (PBT).

Fire protection corresponding to UL 94-V0.


Supply includes:

Screws and "U" nuts for mounting on PS/TS mounting rails.

Packs of	Model No. SV
3	3079.000

Note:

Short-circuit protection diagram, see page 119.



Universal holder

For the attachment of multi-stacked laminated copper bars from 40 x 5 to 100 x 10 mm.

Material:

Fibreglass-reinforced, thermoplastic polyester (PBT).

Fire protection corresponding to UL 94-V0.

Supply includes:

Screws and sliding nuts for attachment on C rails.

Packs of	Model No. SV
3 set	3079.010

Note:

Short-circuit protection diagram, see page 119.



Accessories:

Support rails for stacking insulator, see page 105.



Spacers

for RiLine60 busbar supports (flat busbar system)

For adapting 12 x 5 and 12 x 10 mm size busbars.

For busbar supports

- SV 9340.000/.010 (3-pole), see page 66.
- SV 9340.004 (4-pole), see page 74.
- SV 9340.030 (1-pole), see page 110.

Material:

Polyamide (PA 6.6), 25% fibreglass-reinforced.
Continuous operating temperature max. 130°C.
Fire protection corresponding to UL 94-V0.

Colour:

RAL 7035



Packs of	Model No. SV
12	9340.090



Insert strip

for circuit-breaker component adaptors

To extend the construction width from 140 mm to 190 mm.

Width: 25 mm.

Material:

ABS

Colour:

RAL 7035

Note:

4 pieces (1 set) are needed to widen a component adaptor.

For	Packs of	Model No. SV
SV 9342.700 SV 9342.710	4 (1 set)	9342.720



Support rail 35 x 15 mm

for component adaptors

Width 72 mm.

Material:

Sheet steel, zinc-plated, passivated

Supply includes:

Assembly screws and side end brackets.

For	Packs of	Model No. SV
SV 9342.400 SV 9342.410	5	9320.120



Sliding blocks

for circuit-breaker component adaptors

For additional circuit breakers with more than two attachment points.

Colour:

RAL 7035


For	With threaded insert	Packs of	Model No. SV
SV 9342.500/.510 SV 9342.540/.550	M3/M4	6	9342.560
SV 9342.600/.610	M4/M5	6	9342.640

Form 2-4 busbar systems


RiLine60 accessories




SV 9342.570



SV 9342.660 – SV 9342.690



SV 9342.770 – SV 9342.790



Connection bracket

for circuit-breaker component adaptors

Pre-assembled, laminated flat copper for connecting standard, commercially available moulded case circuit-breakers (MCCB).

Material:

Electrolyte copper F20

Insulation:

Vinyl compound.

Temperature resistance up to 105°C.

Fire protection corresponding to UL 94-V0.

Dimensions ¹⁾ mm	For circuit-breaker component adaptor	For connecting moulded case circuit-breakers (MCCB), make (model)	Packs of ²⁾	Model No. SV
6 x 9 x 0.8	SV 9342.500/.510 SV 9342.540/.550	Moeller (NZM1)	3	9342.570³⁾
10 x 15.5 x 0.8	SV 9342.600/.610	ABB (T3), GE (FE)	3	9342.660
		Merlin Gerin (NS/NSX100/160/250), Telemecanique (GV7)	3	9342.670
		ABB (S3), Moeller (NZM2), Siemens (VL250)	3	9342.680
		Siemens (VL160X, VL160)	3	9342.690
10 x 32.0 x 1.0	SV 9342.700/.710	ABB (T5)	3	9342.770
		ABB (S5), Merlin Gerin (NS400/630)	3	9342.780
		Moeller (NZM3)	3	9342.790

¹⁾ Number of lamina x lamina width x lamina thickness

²⁾ 3 = 1 set

³⁾ Universal application for switchgear with a dimensional difference between the mounting level and the upper edge of the contact level of 20 ± 5 mm.

Model No. SV	A mm	B mm	C mm	D mm	E mm
9342.660	26	65	43	9	Ø 10
9342.670	19	66	36	10	Ø 10
9342.680	23	71	40	9	Ø 10
9342.690	23	67	40	11	Ø 7
9342.770	26	51	62	9	Ø 12
9342.780	29	57	46	12	Ø 12
9342.790	28	62	38	14	Ø 12

Rittal busbar systems

When developing the Rittal busbar systems and their components, Rittal drew on the latest state of the art and the currently valid standards and regulations. These applications are used by specialist companies worldwide. As well as permanent in-house controls at Rittal, the quality of the SV components is further reinforced by a vast array of tests and approvals.

As product development is an on-going process, we reserve the right to make amendments in line with technical progress.

Basic regulations for busbar systems

- **IEC/EN 60 439-1**
Low-voltage switchgear and controlgear assemblies
Part 1: Type-tested and partially type-tested combinations
- **IEC 61 439-1/-2**
Low-voltage switchgear and controlgear assemblies
Part 1: General Rules
Part 2: Power switchgear and controlgear assemblies
- **IEC/EN 60 947-1**
Low-voltage switchgear and controlgear assemblies
Part 1: General specifications
- **IEC/EN 60 947-3**
Low-voltage switchgear and controlgear: switches, disconnectors, switch disconnectors and fuse combination units
- **IEC/EN 60 664-1**
Coordination of insulation for electrical operating equipment in low-voltage systems
Part 1: Basic principles, requirements and tests
- **IEC/EN 60 999-1**
Connector parts – Electrical copper conductors –
Safety requirements for screw terminals and screwless terminals
General and specific requirements for terminals for conductors from 0.2 mm² up to and including 35 mm²
- **IEC/EN 60 999-2**
Connector parts – Electrical copper conductors –
Safety requirements for screw terminals and screwless terminals
Part 2: Special requirements for terminals for conductors greater than 35 mm² up to and including 300 mm²
- **DIN 43 671**
Copper busbars, dimensioning for constant current
- **DIN 43 673-1**
Busbar drill holes and screw fastenings,
busbars with rectangular cross-section
- **IEC/EN 60 715**
Dimensions of low-voltage switchgear –
Standardised support rails for the mechanical attachment of electrical components in switching systems
- **DIN EN 13 601**
Copper and copper alloys –
Copper rods and wires for general use in electrical engineering

Application

In order to avoid injury and damage to property, busbar systems must only be assembled and used by suitably trained and qualified personnel. The valid technical regulations, standards and provisions must, of course, be observed.

Users are required to carefully observe the information and instructions supplied by Rittal, and where necessary to forward them to downstream users and/or customers with a special advice note. In particular, the specified tightening torques of electrical terminal connections must be observed in order to achieve an optimum contact pressure.

Technical data and catalogue information

Power distribution components are used in conjunction with a wide range of different switchgear and other components for power distribution, and in relation to a wide range of operating and ambient conditions which are outside of Rittal's control. The horizontal position of busbars is considered the standard installation position for the busbar system. IEC/EN 60 439-1 and the ambient conditions specified therein should be considered the basis for the use of power distribution components.

At enclosure internal temperatures of > 35°C, application-specific derating should be provided where necessary. Specifically in relation to the temperature limits admissible in IEC/EN 60 439-1, the following factors should be critically reviewed:

- Arrangement of components inside the enclosure
- Heat loss of the circuit-breakers and fuses used
- Passive and/or active climate control measures
- Connected conductor cross-sections
- Operating mode of equipment (switching cycles etc.)
- Consideration of the operating and ambient conditions
- Consideration of the rated load factor.

Form 2-4 technical information

Short-circuit resistance diagrams RiLine60

Busbar support

up to 800 A, 3-pole Page 66

Model No. SV 9340.000/SV 9340.010

60 mm bar centre distance,
for busbars 15 x 5 – 30 x 10 mm.

Rated operating voltage: up to 690 V AC

Rated insulation voltage: 1000 V AC

Rated surge voltage: 8 kV



Overtoltage category: IV

Level of contamination: 3

Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk} (see diagram)
- Rated short-time current resistance I_{cw}



Busbar mm	l mm	$I_{cw}^{1)}$ kA
30 x 10	250	37.6
30 x 5	250	36.0
20 x 10	250	29.0

¹⁾ For 1 sec.

Busbar mm	Curve
30 x 10	a
20 x 10	b
25 x 5	c
15 x 5	d

Busbar mm	Curve
30 x 5	e
20 x 5	f
15 x 10	g

PLS busbar supports

up to 800 A/1600 A, 3-pole Page 68

Model No. SV 9341.000/SV 9342.000

60 mm bar centre distance,
for Mini-PLS special busbars.

Rated operating voltage: up to 690 V AC

Rated insulation voltage: 1000 V AC

Rated surge voltage: 8 kV


Overtoltage category: IV

Level of contamination: 3

Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk} (see diagram)
- Rated short-time current resistance I_{cw}



Busbar mm	l mm	$I_{cw}^{1)}$ kA
PLS 800	150	25.9
PLS 1600	150	37.5

¹⁾ For 1 sec.

Busbar mm	Curve
PLS 800	a
PLS 1600	b

Short-circuit resistance diagrams RiLine60

Busbar support

up to 800 A, 4-pole Page 74/76

Model No. SV 9340.004/SV 9342.014

60 mm bar centre distance,
for 30 x 10 mm busbars.

Rated operating voltage: up to 690 V AC

Rated insulation voltage: 1000 V AC

Rated surge voltage: 8 kV


Overvoltage category: IV

Level of contamination: 3

Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk} (see diagram)
- Rated short-time current resistance I_{cw}



Busbar mm	l mm	$I_{cw}^{1)}$ kA
30 x 10	250	29
	500	23

¹⁾ For 1 sec.

PLS busbar support

up to 1600 A, 4-pole Page 76

Model No. SV 9342.004

60 mm bar centre distance,
for Mini-PLS special busbars.

Rated operating voltage: up to 690 V AC

Rated insulation voltage: 1000 V AC

Rated surge voltage: 8 kV


Overvoltage category: IV

Level of contamination: 3

Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk} (see diagram)
- Rated short-time current resistance I_{cw}



Busbar mm	l mm	I_{cw} kA
PLS 1600	250	50 ¹⁾
	250	53 ²⁾
	500	38 ²⁾

¹⁾ For 3 sec.

²⁾ For 1 sec.

Form 2-4 technical information

Short-circuit resistance diagrams Flat-PLS

Busbar support Flat-PLS 60

1- to 4-pole Page 90/91

Model No. SV 9676.002/SV 9676.020

120 mm bar centre distance,
for busbars 40 x 10 – 60 x 10 mm.
Population: 2, 3 or 4 bars per support


Rated operating voltage: up to 690 V AC
Rated insulation voltage: 1000 V AC
Rated surge voltage: 8 kV

Overvoltage category: IV
Level of contamination: 3
Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk}
(see diagram)
- Rated short-time current resistance I_{cw}

Busbar mm	l mm	I_{cw} kA/1 sec.	Version
4 x 60 x 10	450	55.0	a
4 x 60 x 10	900	40.0	
4 x 60 x 10	450	60.0	b
4 x 60 x 10	900	45.0	
4 x 60 x 10	450	70.0	c
4 x 60 x 10	900	60.0	



Characteristic curve/design	Design of busbar attachment
a	basic version ¹⁾
b	with busbar claws ²⁾
c	with busbar stabilisers and busbar claws ²⁾

1) Basic version consists of system attachment with fitted busbar support.

2) Version see page 118.

Busbar support Flat-PLS 100

1- to 4-pole Page 90/91

Model No. SV 9676.004/SV 9676.021

165 mm bar centre distance,
for busbars 80 x 10 – 100 x 10 mm.
Population: 2, 3 or 4 bars per support


Rated operating voltage: up to 690 V AC
Rated insulation voltage: 1000 V AC
Rated surge voltage: 8 kV

Overvoltage category: IV
Level of contamination: 3
Rated frequency: 50/60 Hz

Test implemented:

- Rated surge current resistance I_{pk}
(see diagram)
- Rated short-time current resistance I_{cw}

Busbar mm	l mm	I_{cw} kA/1 sec.	Version
4 x 100 x 10	450	75.0	a
4 x 100 x 10	900	52.0	
4 x 100 x 10	450	81.6	b
4 x 100 x 10	900	55.9	
4 x 100 x 10	450	110.0	c
4 x 100 x 10	900	78.0	



Characteristic curve/design	Design of busbar attachment
a	basic version ¹⁾
b	with busbar claws ²⁾
c	with busbar stabilisers and busbar claws ²⁾

1) Basic version consists of system attachment with fitted busbar support.

2) Version see page 118.

Busbar claws

2-, 3- or 4-way Page 93

Model No. SV 9676.011 to SV 9676.019

Supplementary information on Flat-PLS short-circuit protection diagrams

Mounting distance of busbar claws:
In order to achieve the cited short-circuit protection, the busbar claws must be fitted at a spacing of 300 mm. If there is a busbar support, a contact maker or a longitudinal connector located within this 300 mm, there is no need to fit a claw at this point.

Max. distance	mm
Busbar claw – Busbar claw	≤ 300
Busbar claw – Busbar support	≤ 300
Busbar claw – Contact maker	≤ 300
Busbar claw – Longitudinal connector	≤ 300



Laminated copper bars Rittal Flexibar "S"

Page 112

Configuration ¹⁾ mm	I _n for 50 K ²⁾	I _n for 30 K ²⁾	I _n for 10 K ²⁾	Curve (short-circuit resistance)	Installation type	Model No. SV
8 x 6.0 x 0.5	165 A	125 A	–	–	–	3565.010
6 x 9.0 x 0.8	250 A	220 A	120 A	–	–	3565.000
6 x 13.0 x 0.5	200 A	150 A	110 A	–	–	3566.000
4 x 15.5 x 0.8	300 A	210 A	140 A	–	–	3567.000
6 x 15.5 x 0.8	350 A	290 A	170 A	a	1	3568.000
10 x 15.5 x 0.8	450 A	350 A	190 A	a	1	3569.000
5 x 20.0 x 1.0	400 A	300 A	180 A	a	1	3570.000
5 x 24.0 x 1.0	450 A	370 A	230 A	a	1	3571.000
10 x 24.0 x 1.0	800 A	600 A	340 A	b	1	3572.000
5 x 32.0 x 1.0	550 A	470 A	280 A	b	2/3	3573.000
10 x 32.0 x 1.0	1000 A	800 A	460 A	c	2/3	3574.000
5 x 40.0 x 1.0	800 A	600 A	340 A	b	2/3	3575.000
10 x 40.0 x 1.0	1200 A	950 A	500 A	c	2/3	3576.000
5 x 50.0 x 1.0	900 A	700 A	400 A	b	2/3	3577.000
10 x 50.0 x 1.0	1400 A	1000 A	600 A	c	2/3	3578.000
10 x 63.0 x 1.0	1600 A	1240 A	715 A	d	2/3	3579.000

¹⁾ Number of lamina x lamina width x lamina thickness

²⁾ The conductor temperature of the laminated copper bar is derived by adding the ambient temperature and the temperature increase together.


Example:

SV 3565.000 carrying 220 A, i.e. the temperature increases by 30 K. At an ambient temperature of 35°C, this produces a resultant conductor temperature of 35°C + 30 K = 65°C.

Short-circuit resistance diagrams


Basis of test:
VDE 0660, part 500/IEC 60 439-1.
Test implemented:
Dynamic short-circuit resistance
to IEC 60 439-1.

The dimensions for the support spacing (l) and for the centre-to-centre spacing (a) must be within the specified min./max. limits. The quotients of l/a can be used to determine the permissible short-circuit current I_p by using curves a to d. The prescribed installation type must be taken into account.



Curve	Support spacing (l) mm		Centre-to-centre spacing (a) mm	
	min.	Max.	min.	Max.
a	150	300	34	60
b	150	350	42	85
c	200	400	51	85
d	200	450	81	100

Type of assembly with universal support SV 3079.000



Form 2-4 technical information

Rated currents of busbars E-Cu (DIN 43 671)

DIN 43 671 specifies the continuous currents for busbars at an ambient temperature of 35°C and an average busbar temperature of 65°C. With the aid of a correction factor (k_2), the continuous currents specified in the following table may be adjusted to alternative operating temperatures.

For safe operation with thermal reserve, it is advisable to limit the busbar temperature to a maximum of 85°C. However, the decisive factor is the lowest permissible continuous temperature of the components which directly contact the busbar system (fuse bases, outgoing cables etc.). The ambient air temperature of the busbars or busbar system should not exceed 40°C; an average of 35°C maximum is recommended.

For the continuous temperatures specified in the table, an emission level of 0.4 applies, equivalent to an oxidating copper bar. In modern busbar systems – built into enclosures with a protection category of IP 54 and above – a more favourable emission level can be assumed. The lower emission level facilitates an additional increase in continuous currents compared with the figures in DIN 43 671, irrespective of the specified air and busbar temperature. Experience has shown an increase in the continuous current of 6 – 10% compared with the table figures for uncoated copper bars, and 60% for surface-oxidised copper bars.

Example:

For a Cu bar 30 x 10 mm (E-Cu F30), DIN 43 671 specifies a constant current of $I_{N65} = 573$ A.

The correction factor diagram for square cross-sections indicates a correction factor $k_2 = 1.29$ at an air temperature of 35°C and a busbar temperature of 85°C. Thanks to the favourable emission level, the continuous current is increased by a further 6 – 10%. In this example, a mean value of 8% is used. Compared with the table figure from DIN 43 671, the Rittal rated current specification for a Cu bar 30 x 10 mm is:

$$I_{N85} = I_{N65} \cdot k_2 + 8\% \\ = 573 \text{ A} \cdot 1.29 \cdot 1.08 \\ I_{N85} = 800 \text{ A}$$

Continuous currents for busbars

Made from E-Cu with square cross-section in indoor locations at 35°C air temperature and 65°C bar temperature, vertical position or horizontal position of the bar width.

Width x thickness mm	Cross-section mm ²	Weight ¹⁾	Material ²⁾	Continuous current in A			
				AC current up to 60 Hz		DC current + AC current 16 Hz	
				Bare bar	Coated bar	Bare bar	Coated bar
12 x 2	23.5	0.209	E-Cu F30	108	123	108	123
15 x 2	29.5	0.262		128	148	128	148
15 x 3	44.5	0.396		162	187	162	187
20 x 2	39.5	0.351		162	189	162	189
20 x 3	59.5	0.529		204	237	204	237
20 x 5	99.1	0.882		274	319	274	320
20 x 10	199.0	1.770		427	497	428	499
25 x 3	74.5	0.663		245	287	245	287
25 x 5	124.0	1.110		327	384	327	384
30 x 3	89.5	0.796		285	337	286	337
30 x 5	149.0	1.330		379	447	380	448
30 x 10	299.0	2.660		573	676	579	683
40 x 3	119.0	1.060		366	435	367	436
40 x 5	199.0	1.770		482	573	484	576
40 x 10	399.0	3.550		715	850	728	865
50 x 5	249.0	2.220		583	697	588	703
50 x 10	499.0	4.440		852	1020	875	1050
60 x 5	299.0	2.660		688	826	696	836
60 x 10	599.0	5.330		985	1180	1020	1230
80 x 5	399.0	3.550		885	1070	902	1090
80 x 10	799.0	7.110	1240	1500	1310	1590	
100 x 10	999.0	8.890	1490	1810	1600	1940	

¹⁾ Calculated with a density of 8.9 kg/dm³


²⁾ Reference basis for the continuous current levels (figures taken from DIN 43 671)

Rittal PLS current load


According to DIN 43 671, the correction factor k_2 (correction diagram) is used to correct the basic current with reference to the existing temperatures of the ambient air and the busbar. In accordance with DIN 43 671, the load figures of the Rittal PLS special bars have been determined on the basis of measurement trials, as follows:

PLS special busbars	Rated current AC 50/60 Hz	
	for 35/75°C	for 35/65°C (basic value)
E-Cu PLS 800	800 A	684 A
E-Cu PLS 1600	1600 A	1368 A

Correction factor diagram to DIN 43 671



Correction factor diagram for PLS



Rated currents of Flat-PLS busbar systems

DIN 43 671 specifies the continuous currents for busbars surrounded by air, giving defined temperatures for the ambient and busbar temperature (35°C/65°C). The air temperature around the busbars is considered the ambient temperature, not the air temperature around the enclosure housing. However, in certain circumstances, a busbar system installed in an enclosure may be subject to completely different conditions. Similarly, the figures in DIN 43 671 do not make allowance for the effect of airflows inside the enclosure caused by fan systems, which may influence the maximum rated currents.

In addition to the rated currents for copper busbars to DIN 43 671, the following table lists additional values for rated currents of Flat-PLS busbar systems with bare copper bars for AC currents up to 60 Hz.

These values were determined on Flat-PLS busbars fitted in enclosures with various protection categories, as well as with and without forced ventilation. Depending on the busbar system and protection category, two figures are given, representing the rated current at an overtemperature of 30°K and 70°K. In contrast to the rated currents to DIN 43 671, the temperature outside the enclosure is measured as the ambient temperature here.

The benefit of this approach is that the enclosure housing, which may exert a major influence on the busbar system, is taken into account in the ratings data for the busbar system. Designing a busbar system to DIN 43 671 without consideration of the enclosure housing may lead to thermal problems in the enclosure interior, particularly with higher currents.

Although IEC 60 439-1/IEC 61 439-1/-2 permits higher overtemperature limits than 70°K, the absolute busbar temperature at an ambient temperature of 35°C and 70°K overtemperature limit is 105°C. This figure of 105°C is high, but significantly below the thermal softening of copper material, and therefore acceptable.

Example:

If a rated current is used at an overtemperature of 30°K, this means that the temperature of the busbars is 30°K above the ambient temperature of the enclosure. Expressed in absolute figures, therefore, at an ambient temperature of 35°C around the enclosure housing, this produces a maximum absolute busbar temperature of 65°C.

Rated AC currents of Flat-PLS busbar system up to 60 Hz for bare copper bars (E-Cu F30) in A

Design of Flat-PLS busbar system	Protection category of enclosure										
	Ri4Power DIN 43 671	IP 2X with forced ventilation ¹⁾		IP 2X		IP 43		IP 54 with forced ventilation ²⁾		IP 54	
	$\Delta T = 30^\circ K$	$\Delta T = 30^\circ K$	$\Delta T = 70^\circ K$	$\Delta T = 30^\circ K$	$\Delta T = 70^\circ K$	$\Delta T = 30^\circ K$	$\Delta T = 70^\circ K$	$\Delta T = 30^\circ K$	$\Delta T = 70^\circ K$	$\Delta T = 30^\circ K$	$\Delta T = 70^\circ K$
2 x 40 x 10 mm	1290	1800	2700	1200	1900	1000	1536	1700	2400	950	1500
3 x 40 x 10 mm	1770	2100	3250	1350	2150	1150	1650	2000	3000	1150	1800
4 x 40 x 10 mm	2280	2300	3400	1400	2300	1250	2040	2050	3100	1200	1900
2 x 50 x 10 mm	1510	2200	3260	1340	2140	1200	1920	1980	2920	1140	1800
3 x 50 x 10 mm	2040	2660	3900	1580	2540	1400	2240	2320	3440	1320	2100
4 x 50 x 10 mm	2600	2700	4040	1640	2660	1440	2340	2360	3500	1380	2220
2 x 60 x 10 mm	1720	2300	3600	1500	2450	1300	2200	2200	3200	1250	2000
3 x 60 x 10 mm	2300	2450	4050	1700	2700	1500	2500	2400	3520	1450	2300
4 x 60 x 10 mm	2900	2740	4220	1740	2840	1580	2540	2420	3580	1460	2360
2 x 80 x 10 mm	2110	2760	4160	1740	2840	1600	2560	2540	3720	1480	2360
3 x 80 x 10 mm	2790	3300	5060	2000	3260	1840	2960	3060	4520	1680	2700
4 x 80 x 10 mm	3450	3680	5560	2060	3440	1900	3280	3220	4880	1780	2820
2 x 100 x 10 mm	2480	3240	4840	1920	3200	1800	2880	2900	4340	1660	2660
3 x 100 x 10 mm	3260	3580	5400	2200	3720	1980	3240	3320	4880	1920	2980
4 x 100 x 10 mm	3980	4020	5760	2320	3820	2000	3400	3380	4900	1960	3120

¹⁾ For $I_N \leq 2000$ A using fan-and-filter unit SK 3326.107, for $I_N > 2000$ A using fan-and-filter unit SK 3327.107.

²⁾ For $I_N \leq 2000$ A using fan-and-filter unit SK 3326.107 and outlet filter SK 3326.207, for $I_N > 2000$ A using fan-and-filter unit SK 3327.107 and outlet filter SK 3326.207.

For calculating rated currents at temperatures between the overtemperature limits of Flat-PLS busbar systems, the correction factor diagram may be used. If data is available regarding the maximum ambient temperature and the maximum bar temperature, a correction factor k_2 may be calculated using the correction factor diagram. With a correction factor k_2 and a specified rated current at 30°K overtemperature limit, the new rated current is calculated.

Example:

Flat-PLS 100 busbar system with 4 x 100 x 10 mm


I_{N30} at IP 2X = 2320 A
 ambient temperature = 35°C
 Bar temperature = 85°C

From the diagram, this produces a factor $k_2 = 1.29$

The new rated current under these conditions is then calculated as follows:

$$\begin{aligned}
 I_N &= I_{N30} \cdot k_2 \\
 &= 2320 \text{ A} \cdot 1.29 \\
 &= 2992 \text{ A}
 \end{aligned}$$

Correction factor diagram



Form 2-4 technical information


Planning and configuration of Ri4Power systems

Tightening torques for Flat-PLS busbar systems

There is separate documentation available containing all the requisite torque information for the configuration of Ri4Power systems with the new Flat-PLS busbar system. Organised according to item numbers, information is provided on screws, screw drive and rated torque.

This documentation is available for downloading at the Rittal website www.rittal.com. Alternatively, a printed copy may be ordered quoting the following item number.

Packs of	Model No. SV
1	9676.001



Assembly instructions for Ri4Power low-voltage switchgear


for Form 2-4, with Flat-PLS, Maxi-PLS and RiLine60

These assembly instructions explain the configuration of type-tested Ri4Power field types and possible busbar systems, divided into 3 sections. The first section explains the assembly sequence for the individual stages of the possible field types in diagrammatic form.

The second section provides detailed assembly instructions using diagrams and data tables. The final section explains the installation of optional accessories and general work operations.

This documentation is available for downloading at the Rittal website www.rittal.com. Alternatively, a printed copy may be ordered quoting the following item number.

Packs of	Model No. SV
1	9676.000



Assembly instructions for Ri4Power low-voltage switchgear

for Form 1 (open design), with Maxi-PLS

Assembly instructions for the configuration of type-tested low-voltage switchgear, open design (without internal compartmentalisation of the functional areas) with the Maxi-PLS busbar system. The document uses diagrams and data tables to explain the assembly of the various field types.

This documentation is available for downloading at the Rittal website www.rittal.com. Alternatively, a printed copy may be requested from your specialist Rittal advisor.



Rittal Power Engineering


Planning software for type-tested low-voltage switchgear

with the System Ri4Power configuration tool for simple, fast planning and calculation of type-tested low-voltage switchgear with the Ri4Power systems Form 1, Form 2-4 and ISV.

The multi-lingual software package includes the following functions:

- Project handling, from the initial enquiry through to ordering
- Complete, automatic function for the generation of bills of materials and a calculation program for producing a quote
- Input and evaluation of assembly times to calculate man hours
- Access to the entire range of Rittal products
- Output of orders, including combining several projects into one order

- Generation of special fields configured by the customer with graphical processing in the CAD view
- Import/export interfaces for product and CAD data
- Export function of order and parts lists in Excel or CSV format
- Calculation based on current copper price
- Interface to EPLAN Electric P8, for the export of CAD data and bills of materials
- The extra benefit for engineering and planning offices: Output of detailed tender texts on the basis of plant project-planned in Power Engineering in MS Word format.
- Output of generated project-specific assembly sketches
- Integral configurator for the generation of drawings and bills of materials to create connector kits for connecting air circuit-breakers (ACB).




Supply includes


CD-ROM

Language: German/English/
French/Dutch/Danish/
Swedish/Czech/Italian/
Spanish/Polish/Russian

Model No. SV	3020.300
---------------------	-----------------



With the graphical user interface, plant configurations may be planned and designed very quickly and easily.



As a stand-alone module, the integral configurator for connector kits also supports the manual generation of production documents of air circuit-breaker connector kits for air circuit-breakers from ABB, Merlin Gerin, Mitsubishi, Moeller, Siemens and Terasaki.


Engineering support for project handling

For individual project handling, Rittal offers an extra service with specially trained expert advisors and technical support staff for the generation of quotes, technical order handling, and after-sales service.

Following technical coordination, individual low-voltage switchgear may be configured. On request, we can supply you with assembly drawings and bills of materials to match your project. As a planner, you have the option of requesting a tender text for your project based on Power Engineering project planning.

During the execution of your plant, our expert advisors can also provide technical support with the assembly and execution.

For initial contact with our engineering support team, please contact your local expert advisor. He or she will make a note of your request and forward it to our technical team. Further information is available at www.rittal.com.



Form 2-4 technical information

Planning and configuration of Ri4Power systems

Planning and project management in line with regulations

As a general principle, low-voltage switchgear and distributors should be planned to meet the operating conditions of their final installation site. To this end, the operator of the plant, in collaboration with the manufacturer, should stipulate the operating and ambient conditions. Moreover, as a general rule, the operator or planning office should also supply the manufacturer with full electrical specifications of both the mains supply end and the distributor outlet end. This makes it possible to plan and manufacture a cost-effective system with optimum adaptation to the technical requirements.

Important basic data for planning and project management

- Applicable regulations and standards, both regional and international
- Electricity supply company conditions
- Operator-specific regulations
- Mains-specific protective measures/mains type
- Rated voltage and frequency
- Rated current with due regard for the number of conductors (infeed and busbars)
- Rated insulation voltage
- Short-circuit current at the point of installation
- Location of incoming cables, from above or below
- Number of incoming cables, specifying the type and cross-section
- Number of outlets, specifying the operating load and the envisaged outgoing cables with type and cross-section
- For the outlet side, specification of the simultaneity factor and rated load factor of the relevant equipment items

Important operating and ambient conditions

- Rated operating voltage U_e
- Mains frequency f_N
- Rated insulation voltage U_i
- Busbar rated current I_{sas}
- Rated current for the supply end I_{zu}
- Rated surge current resistance I_{pk}
- Rated short-time current resistance I_{cw}
- Ambient temperature condition ϑ
- Atmospheric climatic stress, specifying the relative humidity and temperature
- Protection category of the overall system IP . . .
- Specification to DIN EN 60 529
- Protection category

Rated diversity factor

The rated diversity factor of a switchgear combination or part thereof (e.g. a field) comprising several main circuits refers to the ratio between the largest sum total of all currents anticipated at any given time in

the affected main circuits and the sum total of the rated currents of all main circuits of the switchgear enclosure or observed part thereof.

Application suggestion to IEC/EN 60 439-1

Number of main circuits	Load factor
2 and 3	0.9
4 and 5	0.8
6 and 7	0.7
10 or more	0.6

Rated currents and short-circuit currents of standard transformers

Rated voltage $U_N = 400 \text{ V}$	400 V		
Short-circuit voltage U_k	4% ¹⁾		6% ²⁾
Rated power S_{NT} [kVA]	Rated current I_N [A]	Short-circuit current $I_{k''}^{(3)}$ [kA]	
50	72	1.89	1.20
100	144	3.61	2.41
160	230	5.77	3.85
200	288	7.22	4.81
250	360	9.02	6.01
315	455	11.36	7.58
400	589	14.43	9.62
500	722	18.04	12.03
630	910	22.73	15.15
800	1156	28.86	19.24
1000	1444	36.08	24.05
1250	1805	45.09	30.06
1600	2312	57.72	38.48
2000	2882	72.15	48.10
2500	3613	90.32	60.21

¹⁾ $U_k = 4\%$ standardised to DIN 42 503 for $S_{NT} = 50 \dots 630 \text{ kVA}$


²⁾ $U_k = 6\%$ standardised to DIN 42 511 for $S_{NT} = 100 \dots 1600 \text{ kVA}$

³⁾ $I_{k''}^{(3)}$ = Initial symmetrical short-circuit current of transformer when connecting to a mains supply with unlimited short-circuit lead


Maxi-PLS 1600/2000

Page 84


Busbar supports
Model No. SV 9640.000, SV 9649.000



Busbar support, suitable for top mounting
Model No. SV 9640.160




End supports
Model No. SV 9640.010, SV 9649.010




Maxi-PLS 3200

Page 86


Busbar supports
Model No. SV 9650.000, SV 9659.000




Busbar support, suitable for top mounting
Model No. SV 9650.160



End supports
Model No. SV 9650.010, SV 9659.010



Stabiliser
Model No. SV 9650.140



Form 2-4 technical information

Maxi-PLS connection components


Maxi-PLS 1600/2000

Page 85

Maxi-PLS 3200


Page 87

Isolator chassis




Model No. SV	A	B	C	D	E
9640.020	89	61	346	100	89
9650.020	89	61	479	150	94
9650.030	129	101	479	150	94

Connection clamp
Model No.
SV 9640.325
SV 9650.325




Connection plates




Model No. SV	Size	A	B	C	T-head screws	Tightening torque
9640.330	1	81	73	46	M10	20 Nm
9640.340	2	112	104	77	M10	25 Nm
9640.350	3	149	141	114	M10	30 Nm
9650.330	1	81	73	46	M12	25 Nm
9650.340	2	112	104	77	M12	30 Nm
9650.350	3	149	141	114	M12	35 Nm

Terminal studs
(1600/2000)




Terminal studs
(3200)




Model No. SV	A	B
9640.370	M12	-
9640.380	M16	-
9650.370	-	M12
9650.380	-	M16

Sliding nuts
(1600/2000)




Sliding nuts
(3200)



Model No. SV	A	B
9640.900	M6	-
9640.910	M8	-
9640.920	M10	-
9650.900	-	M6
9650.910	-	M10
9650.920	-	M12

Flat-PLS 60/100

Busbar claw Page 93




B = Width
T = Depth

Model No. SV	B1	B2	H1	H2	T1
9676.011	35.7	-	80	57 - 62	30
9676.012	55.7	20	80	57 - 62	30
9676.013	75.7	40	80	57 - 62	30
9676.014	35.7	-	120	97 - 102	30
9676.015	55.7	20	120	97 - 102	30
9676.016	75.7	40	120	97 - 102	30
9676.017	35.7	-	Without screw	+2/-3 ¹⁾	30
9676.018	55.7	20	Without screw	+2/-3 ¹⁾	30
9676.019	75.7	40	Without screw	+2/-3 ¹⁾	30


¹⁾ With reference to the required screw H2 = H1 - 20 (H1 \pm length of screw).

Contact makers Page 96



Model No. SV	B1	B2	H1	H2	H3	T1	T2
9676.526	60	36	40 - 100	20	10	30	-
9676.546	60	36	40 - 100	20	10	70	40
9676.528	80	50	40 - 100	20	10	30	-
9676.548	80	50	40 - 100	20	10	70	40
9676.520	100	50	40 - 100	20	10	30	-
9676.540	100	50	40 - 100	20	10	70	40


Longitudinal connector Page 98



Model No. SV	B1	B2	B3	H1	H2	H3	H4	T1	T2
9676.626	140	110	40	100	60	20	10	30	-
9676.646	140	110	40	100	60	20	10	70	40
9676.628	140	110	40	120	80	20	10	30	-
9676.648	140	110	40	120	80	20	10	70	40
9676.620	140	110	40	140	100	20	10	30	-
9676.640	140	110	40	140	100	20	10	70	40
9676.621	140	110	40	X ¹⁾	H1 - 40	20	10	30	-
9676.641	140	110	40	X ¹⁾	H1 - 40	20	10	70	40


¹⁾ Length of screw (to be ordered separately).

Edge cover section without spacer Page 94




Model No. SV	B1	H1
9676.041	10.2	12.9
9676.042	21.3	12.9
9676.043	32.3	12.9

Edge cover section with spacer Page 94



Model No. SV	B1	H1
9676.052	10.3	16.65
9676.053	10.3	16.65
9676.054	10.3	16.65

Side cover section Page 94




Model No. SV	B1	H1
9676.056	49.2	7.65
9676.058	69.2	7.65
9676.059	89.2	7.65

Form 2-4 technical information

Flat-PLS connection components

Flat-PLS 60/100


Connection plates with bolts M12/M16 Page 95



Model No. SV	B1	B2	B3	H1	H2	H3	H4	T1
9676.700	70	40	M12	¹⁾	H1 - 21.5	30.6	15.6	60
9676.704	70	40	M16	¹⁾	H1 - 21.5	30.6	11.1	60

¹⁾ Length of screw connection.


Direct connection terminals Page 94



Model No. SV	B1	B2	H1	H2	T1	T2
9676.730	35.7	35	¹⁾	H1 - 60	50.5	30
9676.731	35.7	35	120	60	50.5	30
9676.733	35.7	35	160	100	50.5	30

¹⁾ Length of screw connection.


Connection plates with bolts M10 Page 95



Model No. SV	B1	B2	B3	B4	B5	H1	H2	H3	T1	T2
9676.710	50	-	30	M10	-	¹⁾	H1 - 40	5	35	35.7
9676.714	80	52	30	M10	82	¹⁾	H1 - 40	10	50	35.7


¹⁾ Length of screw connection.

Connection plates for laminated copper bars Page 96



Model No. SV	Size	A	B	C	Screw	Tightening torque
9676.741	1	81	73	46	M10 x 115	20 Nm
9676.742	2	112	104	77	M10 x 115	25 Nm
9676.743	3	149	141	114	M10 x 115	30 Nm
9676.744	1	81	73	46	M10 x 150	20 Nm
9676.745	2	112	104	77	M10 x 150	25 Nm
9676.746	3	149	141	114	M10 x 150	30 Nm
9676.747	1	81	73	46	without	20 Nm
9676.748	2	112	104	77	without	25 Nm
9676.749	3	149	141	114	without	30 Nm

Terminal block distributor bar Page 108



Model No. SV	B1	B2	B3	B4	B5	H1	H2	H3	T1
9674.485	160	130	61	51	29.5	40	20	25	20
9674.488	160	130	101	81	29.5	40	20	25	20


Form 2-4 technical information

Dimensions SV-TS 8 enclosures


SV-TS 8 enclosures

for incoming/outgoing circuit (Form 1 only)

Catalogue 32, page 438




B = Width
T = Depth
i.L. = Clearance width



Cross-sections

vertical

horizontal



Model No. SV	B1 mm	B2 mm	B3 mm	B4 mm	H1 mm	H2 mm	H3 mm	H4 mm	T1 mm	T2 mm	T3 mm	T4 mm	T5 mm	T6 mm	Door(s)
9660.665	597	512	475	535	2005	1997	1912	1850	601.5	475	512	568	440	535	1
9660.675	597	512	475	535	2005	1997	1912	1850	601.5	475	512	568	440	535	3
9660.865	797	712	675	735	2005	1997	1912	1850	601.5	475	512	568	440	535	1
9660.875	797	712	675	735	2005	1997	1912	1850	601.5	475	512	568	440	535	3




Form 2-4 technical information

Dimensions SV-TS 8 enclosures

SV-TS 8 modular enclosures

Page 30 – 32

Cross-sections



B = Width
T = Depth
i.L. = Clearance width




Model No. SV	B1 mm	B2 mm	B3 mm	B4 mm	H1 mm	H2 mm	H3 mm	H4 mm	T1 mm	T2 mm	T3 mm	T4 mm	T5 mm	T6 mm
9670.406	397	312	275	335	2005	1997	1912	1850	601.5	475	512	568	440	535
9670.408	397	312	275	335	2005	1997	1912	1850	801.5	675	712	768	640	735
9670.426	397	312	275	335	2205	2197	2112	2050	601.5	475	512	568	440	535
9670.428	397	312	275	335	2205	2197	2112	2050	801.5	675	712	768	640	735
9670.486	397	312	275	335	1805	1797	1712	1650	601.5	475	512	568	440	535
9670.606	597	512	475	535	2005	1997	1912	1850	601.5	475	512	568	440	535
9670.608	597	512	475	535	2005	1997	1912	1850	801.5	675	712	768	640	735
9670.626	597	512	475	535	2205	2197	2112	2050	601.5	475	512	568	440	535
9670.628	597	512	475	535	2205	2197	2112	2050	801.5	675	712	768	640	735
9670.686	597	512	475	535	1805	1797	1712	1650	601.5	475	512	568	440	535
9670.806	797	712	675	735	2005	1997	1912	1850	601.5	475	512	568	440	535
9670.808	797	712	675	735	2005	1997	1912	1850	801.5	675	712	768	640	735
9670.826	797	712	675	735	2205	2197	2112	2050	601.5	475	512	568	440	535
9670.828	797	712	675	735	2205	2197	2112	2050	801.5	675	712	768	640	735
9670.886	797	712	675	735	1805	1797	1712	1650	601.5	475	512	568	440	535

Form 2-4 technical information

Dimensions SV-TS 8 enclosures

SV-TS 8 switch-disconnector-fuse enclosures

Page 36 – 37




B = Width
T = Depth
i.L. = Clearance width

Cross-sections

vertical

horizontal







Model No. SV	B1 mm	B2 mm	B3 mm	B4 mm	B5 mm	H1 mm	H2 mm	H3 mm	T1 mm	T2 mm	T3 mm	T4 mm	T5 mm	T6 mm
9670.006	997	912	875	935	350.5	1997	1912	1850	601.5	475	512	568	440	535
9670.008	997	912	875	935	350.5	1997	1912	1850	801.5	675	712	768	640	735
9670.026	997	912	875	935	350.5	2197	2112	2050	601.5	475	512	568	440	535
9670.028	997	912	875	935	350.5	2197	2112	2050	801.5	675	712	768	640	735
9670.106	1197	1112	1075	1135	550.5	1997	1912	1850	601.5	475	512	568	440	535
9670.108	1197	1112	1075	1135	550.5	1997	1912	1850	801.5	675	712	768	640	735
9670.126	1197	1112	1075	1135	550.5	2197	2112	2050	601.5	475	512	568	440	535
9670.128	1197	1112	1075	1135	550.5	2197	2112	2050	801.5	675	712	768	640	735

SV-TS 8 busbar enclosures

Page 38

Cross-sections

vertical



B = Width
T = Depth
i.L. = Clearance width

Model No. SV	B1 mm	B2 mm	B3 mm	B4 mm	H1 mm	H2 mm	H3 mm	T1 mm	T2 mm	T3 mm	T4 mm	T5 mm
9670.206	197	112	75	75	1997	1912	1850	605	475	512	561	535
9670.208	197	112	75	75	1997	1912	1850	805	675	712	761	735
9670.226	197	112	75	75	2197	2112	2050	605	475	512	561	535
9670.228	197	112	75	75	2197	2112	2050	805	675	712	761	735

Form 2-4 technical information

System data

Type-tested Ri4Power low-voltage switchgear combinations

The section types of Ri4Power low-voltage switchgear combinations are type-tested to IEC 60 439-1. If planned and executed in accordance with the specifications and assembly instructions for Ri4Power systems, the combination of section types corresponds to a type-tested low-voltage switchgear combination to IEC 60 439-1. Alternatively, design verification to IEC 61 439-1/-2 is possible. For further information please contact your local expert advisor.

Type testing of Ri4Power systems was carried out with the following switchgear brands:

- ABB
- Jean Müller
- Merlin Gerin
- Mitsubishi
- Moeller Electric
- Siemens
- Terasaki

and with RiLine components from Rittal. In contrast to a non-type-tested switchgear combination, the requirements for the selection of components and switchgear are linked to the tested types. When planning air circuit-breakers, where necessary, reduction factors should be taken into account for use at increased temperatures in the enclosure interior.

Before planning and assembling a type-tested switchgear combination, the technical parameters of a type-tested switchgear combination should be coordinated between the user and switchgear manufacturer. For type-tested execution of the Ri4Power system, we recommend use of the Rittal Power Engineering software. All parameters are integrated into this software, which guides users to the required solution.

Type-testing of a switchgear combination confirms the combination of enclosure, busbar system and switchgear as a functioning unit, and verifies compliance with all technical limits. The technical data of a type-tested switchgear combination may deviate from the tested values of the individual components, since these components are often subject to different test requirements.

For busbar systems, too, the data within a type-tested switchgear combination may deviate from the data pursuant to DIN 43 671, since in addition to the enclosure and busbar system, type-testing also makes allowance for heat loss in switchgear. For this reason, the technical system data on the following pages is decisive for the type-tested switchgear combinations. If field types with different ratings data are combined, please note that the lowest values for the main busbar system and the overall enclosure protection category prescribe the rated for the overall switchgear combination.

Ri4Power low-voltage switchgear assemblies without type-testing certificate

Ri4Power components may also be used outside of type-tested switchgear and controlgear assemblies. However, the technical

data for the products and the short-circuit protection data and ratings data of the busbar systems must be observed.

Operating and ambient conditions for Ri4Power switchgear assemblies

The siting conditions for Ri4Power systems are identical for all field types. Any requirements which deviate from this should be agreed with the product management team.

Operating and ambient conditions	Ambient temperature	Short-term peak	+40°C	IEC 60 439-1
		Maximum on a 24 h average	+35°C	
		Low	-5°C	
	Atmospheric conditions	Normal climatic stress		IEC 60 439-1
		Relative humidity	50% at 40°C 90% at 20°C (without condensation due to temperature fluctuations)	
		Operation up to 1000 m above sea level		

Additional field-specific technical data for the type-tested field types is listed in detail on the following pages. This data represents the maximum, tested figures. For optimum

adaptation of customer requirements to the possible system assemblies, we recommend use of the latest version of the Rittal Power Engineering software.

SV-TS 8 enclosures

for air circuit-breakers and moulded case circuit-breakers (ACB + MCCB)

Enclosures						
Mechanical parameters	Dimensions	Enclosure width	400/600/800 mm ³⁾			
		Enclosure height	1800/2000/2200 mm ³⁾			
		Enclosure depth	600/800 mm ³⁾			
	Protection category	Pitch pattern	25 mm			
	Design		Max. IP 54			
				1 – 4		
Surface protection/ Material	Enclosure frame	Dipcoat-primed				
	Panels (roof plate, rear panel)	Dipcoat-primed, powder-coated in RAL 7035 on the outside				
	System attachment	Stainless steel				
	System rails and punched sections with mounting flanges	Sheet steel, zinc-plated, passivated				
General ratings data						
Electrical parameters	Rated voltage	Rated insulation voltage U_i	1000 V			
		Rated operating voltage U_e	690 V			
		Rated surge voltage resistance U_{imp}	8 kV			
		Overvoltage category	IV			
		Level of contamination	3			
		Rated frequency	50 Hz			
			EN 60 439-1			
Maxi-PLS busbar system						
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2800 A	IP 54
			1600 A	2000 A	3000 A	IP 2X ¹⁾
			1800 A	2500 A	4000 A	IP 2X ²⁾
		Rated surge current resistance I_{pk}	110 kA		220 kA	EN 60 439-1
	Rated short-time current resistance I_{cw}	50 kA		100 kA		
	Testing under accidental arc conditions	Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
Test voltage		420 V				
Permissible arc duration		0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	
RiLine60 busbar system						
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	800 A		1150 A	IP 54
			860 A		1300 A	IP 43
			1000 A ⁵⁾		1600 A ²⁾	IP 2X
		Rated surge current resistance I_{pk}	68 kA		110 kA	EN 60 439-1
	Rated short-time current resistance I_{cw}	32 kA, 1 sec.		50 kA, 1 sec./50 kA, 3 sec.		
	Testing under accidental arc conditions	Permissible prospective short-circuit current	30 kA		50 kA	EN 61 641
Test voltage		690 V				
Permissible arc duration		0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare			
		Version (cross-section)	30 x 10 mm (300 mm ²)		PLS 1600 (900 mm ²)	
Flat-PLS busbar system						
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	3500 A		4000 A	IP 54
			3650 A		4200 A	IP 43
			4100 A ²⁾		5500 A ²⁾	IP 2X
		Rated surge current resistance I_{pk}	154 kA		220 kA	EN 60 439-1
Rated short-time current resistance I_{cw}	70 kA, 1 sec.		100 kA, 1 sec.			
Mechanical parameters	Busbar	Material	E-Cu, bare			
		Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)		Up to 4 x 100 x 10 mm (max. 4000 mm ²)	

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

⁵⁾ Using fan-and-filter unit SK 3325.107 (230 m³/h) and roof plate IP 2X.

Form 2-4 technical information

System data

SV-TS 8 enclosures

for coupling sections

Enclosures				
Mechanical parameters	Dimensions	Enclosure width	600/800/1000 mm ³⁾	
		Enclosure height	2000/2200 mm ³⁾	
		Enclosure depth	600/800 mm ³⁾	
	Protection category	Pitch pattern	25 mm	
	Design		Max. IP 54	EN 60 529
				1 – 4
Surface protection/ Material	Enclosure frame	Dipcoat-primed		
	Panels (roof plate, rear panel)	Dipcoat-primed, powder-coated in RAL 7035 on the outside		
	System attachment	Stainless steel		
	System rails and punched sections with mounting flanges	Sheet steel, zinc-plated, passivated		

General ratings data				
Electrical parameters	Rated voltage	Rated insulation voltage U_i	1000 V	
		Rated operating voltage U_e	690 V	
		Rated surge voltage resistance U_{imp}	8 kV	
		Overvoltage category	IV	
		Level of contamination	3	
		Rated frequency	50 Hz	
				EN 60 439-1

Maxi-PLS busbar system						
		Maxi-PLS 1600	Maxi-PLS 2000	Maxi-PLS 3200		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2000 A	For IP 54
			1600 A	2000 A	2400 A	For IP 2X ¹⁾
			1800 A	2500 A	3400 A	For IP 2X ²⁾
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	110 kA		165 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	50 kA		75 kA	
		Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
Test voltage		420 V				
Permissible arc duration	0.3 sec.					
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	

RiLine60 busbar system					
		E-Cu 30 x 10 mm	PLS 1600		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	800 A	1150 A	IP 54
			860 A	1300 A	IP 43
			1000 A ⁵⁾	1600 A ²⁾	IP 2X
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	68 kA	110 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	32 kA, 1 sec.	50 kA, 1 sec./50 kA, 3 sec.	
		Permissible prospective short-circuit current	30 kA	50 kA	EN 61 641
Test voltage		690 V			
Permissible arc duration	0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	30 x 10 mm (300 mm ²)	PLS 1600 (900 mm ²)	

Flat-PLS busbar system					
		Flat-PLS 60	Flat-PLS 100		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	2500 A	2500 A	IP 54
			2550 A	2550 A	IP 43
			3200 A ²⁾	3600 A ²⁾	IP 2X
Mechanical parameters	Busbar	Rated surge current resistance I_{pk}	154 kA	220 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	70 kA, 1 sec.	100 kA, 1 sec.	
		Material	E-Cu, bare		
	Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)	Up to 4 x 100 x 10 mm (max. 4000 mm ²)		

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

⁵⁾ Using fan-and-filter unit SK 3325.107 (230 m³/h) and roof plate IP 2X.

SV-TS 8 enclosures for modular outgoing sections

Enclosures				
Mechanical parameters	Dimensions	Enclosure width	400/600/800 mm ³⁾	
		Enclosure height	1800/2000/2200 mm ³⁾	
		Enclosure depth	600/800 mm ³⁾	
	Protection category	Pitch pattern	25 mm	
	Design		Max. IP 54	EN 60 529
			1 – 4	EN 60 439-1
	Surface protection/ Material	Enclosure frame	Dipcoat-primed	
Panels (roof plate, rear panel)		Dipcoat-primed, powder-coated in RAL 7035 on the outside		
System attachment		Stainless steel		
System rails and punched sections with mounting flanges		Sheet steel, zinc-plated, passivated		

General ratings data				
Electrical parameters	Rated voltage	Rated insulation voltage U_i	1000 V	
		Rated operating voltage U_e	690 V	
		Rated surge voltage resistance U_{imp}	8 kV	
		Overvoltage category	IV	
		Level of contamination	3	
		Rated frequency	50 Hz	
			EN 60 439-1	

Maxi-PLS busbar system						
		Maxi-PLS 1600	Maxi-PLS 2000	Maxi-PLS 3200		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2800 A	For IP 54
			1600 A	2000 A	3000 A	For IP 2X ¹⁾
			1800 A	2500 A	4000 A	For IP 2X ²⁾
		Rated surge current resistance I_{pk}	110 kA		220 kA	EN 60 439-1
	Rated short-time current resistance I_{cw}	50 kA		100 kA		
	Testing under accidental arc conditions	Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
		Test voltage	690 V			
Permissible arc duration		0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	

RiLine60 busbar system					
		E-Cu 30 x 10 mm	PLS 1600		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	800 A	1150 A	IP 54
			860 A	1300 A	IP 43
			1000 A ⁵⁾	1600 A ²⁾	IP 2X
		Rated surge current resistance I_{pk}	68 kA	110 kA	EN 60 439-1
	Rated short-time current resistance I_{cw}	32 kA, 1 sec.	50 kA, 1 sec./50 kA, 3 sec.		
	Rated current (distribution busbar)	Rated operating current $I_e^{4)}$	800 A	1600 A ⁶⁾	IP 54
			860 A	1600 A ⁶⁾	IP 43
			1000 A ⁵⁾	1600 A ²⁾	IP 2X
		Rated surge current resistance I_{pk}	68 kA	110 kA	EN 60 439-1
	Rated short-time current resistance I_{cw}	32 kA, 1 sec.	50 kA, 1 sec./50 kA, 3 sec.		
Testing under accidental arc conditions	Permissible prospective short-circuit current	30 kA	50 kA	EN 61 641	
	Test voltage	690 V			
	Permissible arc duration	0.3 sec.			
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	30 x 10 mm (300 mm ²)	PLS 1600 (900 mm ²)	

Flat-PLS busbar system					
		Flat-PLS 60	Flat-PLS 100		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	3500 A	4000 A	IP 54
			3650 A	4200 A	IP 43
			4100 A ²⁾	5500 A ²⁾	IP 2X
		Rated surge current resistance I_{pk}	154 kA	220 kA	
	Rated short-time current resistance I_{cw}	70 kA, 1 sec.	100 kA, 1 sec.		
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)	Up to 4 x 100 x 10 mm (max. 4000 mm ²)	

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

⁵⁾ Using fan-and-filter unit SK 3325.107 (230 m³/h) and roof plate IP 2X.

⁶⁾ In conjunction with RiLine60 as the main busbar system: Rated currents on request.

Form 2-4 technical information

System data

SV-TS 8 enclosures

for switch-disconnector-fuse sections

Enclosures				
Mechanical parameters	Dimensions	Enclosure width	1000/1200 mm ³⁾	
		Enclosure height	2000/2200 mm ³⁾	
		Enclosure depth	600/800 mm ³⁾	
		Pitch pattern	25 mm	
	Protection category		Max. IP 31	
	Design		1 – 4	
				EN 60 529
Surface protection/ Material	Enclosure frame	Dipcoat-primed		
	Panels (roof plate, rear panel)	Dipcoat-primed, powder-coated in RAL 7035 on the outside		
	System attachment	Stainless steel		
	System rails and punched sections with mounting flanges	Sheet steel, zinc-plated, passivated		
			EN 60 439-1	

General ratings data				
Electrical parameters	Rated voltage	Rated insulation voltage U_i	1000 V	
		Rated operating voltage U_e	690 V	
		Rated surge voltage resistance U_{imp}	8 kV	
		Overvoltage category	IV	
		Level of contamination	3	
		Rated frequency	50 Hz	
			EN 60 439-1	

Maxi-PLS busbar system						
		Maxi-PLS 1600	Maxi-PLS 2000	Maxi-PLS 3200		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2800 A	For IP 54
			1600 A	2000 A	3000 A	For IP 2X ¹⁾
			1800 A	2500 A	4000 A	For IP 2X ²⁾
		Rated surge current resistance I_{pk}	110 kA		220 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	50 kA		100 kA	
	Testing under accidental arc conditions	Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
Test voltage		690 V				
Permissible arc duration		0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	

Flat-PLS busbar system						
		Flat-PLS 60	Flat-PLS 100			
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	3500 A	4000 A		IP 54
			3650 A	4200 A		IP 43
			4100 A ²⁾	5500 A ²⁾		IP 2X
		Rated surge current resistance I_{pk}	154 kA	220 kA		EN 60 439-1
	Rated short-time current resistance I_{cw}	70 kA, 1 sec.	100 kA, 1 sec.			
Mechanical parameters	Busbar	Material	E-Cu, bare			
		Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)	Up to 4 x 100 x 10 mm (max. 4000 mm ²)		

Flat-PLS distribution busbar system							
		Flat-PLS					
Electrical parameters	Rated current (distribution busbar)	Rated operating current $I_e^{4)}$	1000 A	1250 A	1600 A	2100 A	IP 31
		Rated surge current resistance I_{pk}	154 kA	165 kA	187 kA	220 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	70 kA, 1 sec.	75 kA, 1 sec.	85 kA, 1 sec.	100 kA, 1 sec.	
Mechanical parameters	Busbar	Material	E-Cu, bare				
		Version (cross-section)	50 x 10 mm (500 mm ²)	60 x 10 mm (600 mm ²)	80 x 10 mm (800 mm ²)	100 x 10 mm (1000 mm ²)	

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

SV-TS 8 enclosures

for cable chambers

Enclosures						
Mechanical parameters	Dimensions	Enclosure width	300/400/600 mm ³⁾			
		Enclosure height	1800/2000/2200 mm ³⁾			
		Enclosure depth	600/800 mm ³⁾			
	Protection category	Pitch pattern	25 mm			
	Design		Max. IP 54			EN 60 529
	Surface protection/ Material	Enclosure frame	1 – 4			EN 60 439-1
		Panels (roof plate, rear panel)	Dipcoat-primed			
System attachment		Dipcoat-primed, powder-coated in RAL 7035 on the outside				
System rails and punched sections with mounting flanges		Stainless steel				
		Sheet steel, zinc-plated, passivated				

Maxi-PLS busbar system		Maxi-PLS 1600	Maxi-PLS 2000	Maxi-PLS 3200		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2800 A	For IP 54
			1600 A	2000 A	3000 A	For IP 2X ¹⁾
			1800 A	2500 A	4000 A	For IP 2X ²⁾
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	110 kA		220 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	50 kA		100 kA	
		Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
		Test voltage	420 V			
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	
		Permissible arc duration	0.3 sec.			

RiLine60 busbar system		E-Cu 30 x 10 mm	PLS 1600		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	800 A	1150 A	IP 54
			860 A	1300 A	IP 43
			1000 A ⁵⁾	1600 A ²⁾	IP 2X
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	68 kA	110 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	32 kA, 1 sec.	50 kA, 1 sec./50 kA, 3 sec.	
		Permissible prospective short-circuit current	30 kA	50 kA	EN 61 641
		Test voltage	690 V		
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	30 x 10 mm (300 mm ²)	PLS 1600 (900 mm ²)	
		Permissible arc duration	0.3 sec.		

Flat-PLS busbar system		Flat-PLS 60	Flat-PLS 100		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	3500 A	4000 A	IP 54
			3650 A	4200 A	IP 43
			4100 A ²⁾	5500 A ²⁾	IP 2X
	Rated surge current resistance I_{pk}	154 kA	220 kA	EN 60 439-1	
Rated short-time current resistance I_{cw}	70 kA, 1 sec.	100 kA, 1 sec.			
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)	Up to 4 x 100 x 10 mm (max. 4000 mm ²)	

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

⁵⁾ Using fan-and-filter unit SK 3325.107 (230 m³/h) and roof plate IP 2X.

Form 2-4 technical information

System data

SV-TS 8 enclosures

for busbar sections

Enclosures				
Mechanical parameters	Dimensions	Enclosure width	200/300/400 mm ³⁾	
		Enclosure height	1800/2000/2200 mm ³⁾	
		Enclosure depth	600/800 mm ³⁾	
	Protection category	Pitch pattern	25 mm	
	Design		Max. IP 54	EN 60 529
			1 – 4	EN 60 439-1
	Surface protection/ Material	Enclosure frame	Dipcoat-primed	
Panels (roof plate, rear panel)		Dipcoat-primed, powder-coated in RAL 7035 on the outside		
System attachment		Stainless steel		
System rails and punched sections with mounting flanges		Sheet steel, zinc-plated, passivated		

General ratings data				
Electrical parameters	Rated voltage	Rated insulation voltage U_i	1000 V	
		Rated operating voltage U_e	690 V	
		Rated surge voltage resistance U_{imp}	8 kV	
		Overvoltage category	IV	
		Level of contamination	3	
		Rated frequency	50 Hz	
			EN 60 439-1	

Maxi-PLS busbar system ⁶⁾						
		Maxi-PLS 1600	Maxi-PLS 2000	Maxi-PLS 3200		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	1400 A	1800 A	2800 A	For IP 54
			1600 A	2000 A	3000 A	For IP 2X ¹⁾
			1800 A	2500 A	4000 A	For IP 2X ²⁾
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	110 kA		165 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	50 kA		75 kA	
		Permissible prospective short-circuit current	50 kA		70 kA	EN 61 641
Test voltage		420 V				
Permissible arc duration	0.3 sec.					
Mechanical parameters	Busbar	Material	E-Cu, bare			
		External dimensions (cross-section)	45 x 45 mm (1000 mm ²)	45 x 45 mm (1380 mm ²)	60 x 60 mm (2700 mm ²)	

RiLine60 busbar system ⁶⁾					
		E-Cu 30 x 10 mm	PLS 1600		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	800 A	1150 A	IP 54
			860 A	1300 A	IP 43
			1000 A ⁵⁾	1600 A ²⁾	IP 2X
	Testing under accidental arc conditions	Rated surge current resistance I_{pk}	68 kA	110 kA	EN 60 439-1
		Rated short-time current resistance I_{cw}	32 kA, 1 sec.	50 kA, 1 sec./50 kA, 3 sec.	
		Permissible prospective short-circuit current	30 kA	50 kA	EN 61 641
Test voltage		690 V			
Permissible arc duration	0.3 sec.				
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	30 x 10 mm (300 mm ²)	PLS 1600 (900 mm ²)	

Flat-PLS busbar system ⁶⁾					
		Flat-PLS 60	Flat-PLS 100		
Electrical parameters	Rated current (primary busbar)	Rated operating current $I_e^{4)}$	3500 A	4000 A	IP 54
			3650 A	4200 A	IP 43
			4100 A ²⁾	5500 A ²⁾	IP 2X
	Rated surge current resistance I_{pk}	154 kA	220 kA		
	Rated short-time current resistance I_{cw}	70 kA, 1 sec.	100 kA, 1 sec.		
Mechanical parameters	Busbar	Material	E-Cu, bare		
		Version (cross-section)	Up to 4 x 60 x 10 mm (max. 2400 mm ²)	Up to 4 x 100 x 10 mm (max. 4000 mm ²)	

¹⁾ Using outlet filter SK 3326.207 and roof plate IP 2X.

²⁾ Using fan-and-filter unit SK 3327.107 (700 m³/h) and roof plate IP 2X.

³⁾ Other sizes available on request.

⁴⁾ Other rated currents for different protection categories on request.

⁵⁾ Using fan-and-filter unit SK 3325.107 (230 m³/h) and roof plate IP 2X.

⁶⁾ Usability of the various busbar systems depends on the enclosure width.

Form 2-4 technical information

Busbar screw connections to DIN 43 673

Drilling templates and drilled holes


Bar widths mm		12 to 50		25 to 60			60			80 to 100		
Form ¹⁾		1		2			3			4		
Drilled holes in the bar ends (drilling pattern)												
Hole size	Nominal width b	d	e ₁	d	e ₁	e ₂	e ₁	e ₂	e ₃	e ₁	e ₂	e ₃
	12	5.5	6	-	-	-	-	-	-	-	-	-
	15	6.6	7.5	-	-	-	-	-	-	-	-	-
	20	9.0	10	-	-	-	-	-	-	-	-	-
	25	11	12.5	11	12.5	30	-	-	-	-	-	-
	30	11	15	11	15	30	-	-	-	-	-	-
	40	13.5	20	13.5	20	40	-	-	-	-	-	-
	50	13.5	25	13.5	20	40	-	-	-	-	-	-
	60	-	-	13.5	20	40	17	26	26	-	-	-
	80	-	-	-	-	-	-	-	-	-	20	40
100	-	-	-	-	-	-	-	-	-	20	40	50

Permissible deviations for hole-centre distances ± 0.3 mm


¹⁾ Form designations 1 – 4 match DIN 46 206, part 2 – Flat-type screw terminal

Examples of busbar screw connections


Longitudinal connections



Angular connections



T-connections



Note:

Figures for dimensions b, d, e₁ and e₂ see table "Drilling templates and drilled holes". Longitudinal holes are permissible at the end of a bar or bar stack.

List of model numbers

3020.300 to 9640.940

Model No.	Page	Model No.	Page	Model No.	Page	Model No.	Page	Model No.	Page
3020.300	123	3588.000	110	8602.085	40	9342.100	69	9640.060	84
3031.000	109	3589.000	110	8602.095	40	9342.110	69	9640.080	84
3032.000	109	3590.000	110	8602.100	40	9342.120	69	9640.088	84
3079.000	112	3590.010	110	8602.200	40	9342.130	69	9640.098	84
3079.010	112	4157.000	61	8602.400	40	9342.134	77	9640.150	84
3085.000	110	4169.000	61	8602.500	40	9342.140	69	9640.160	84
3092.000	110	4171.000	61	8602.600	40	9342.170	69	9640.170	85
3439.010	71	4172.000	61	8602.605	40	9342.200	70	9640.180	85
3504.000	111	4179.000	61	8602.800	40	9342.210	70	9640.190	84
3505.000	111	7825.601	40	8602.805	40	9342.220	70	9640.201	84
3509.000	68	7825.603	40	8602.850	40	9342.224	78	9640.206	84
3509.200	68	7825.605	40	8602.905	40	9342.230	70	9640.211	84
3514.000	111	7825.801	40	8602.915	40	9342.234	78	9640.216	84
3515.000	111	7825.803	40	8602.920	40	9342.240	70	9640.221	84
3516.000	68	7825.805	40	8700.000	41	9342.244	78	9640.226	84
3516.200	68	8106.235	39	8800.370	61	9342.250	70	9640.231	84
3524.000	68	8108.235	39	8800.430	41	9342.254	78	9640.236	84
3524.200	68	8126.235	39	8800.490	41	9342.260	70	9640.241	84
3525.000	68	8128.235	39	9320.020	111	9342.264	78	9640.246	84
3525.010	68	8186.235	39	9320.030	111	9342.270	70	9640.251	84
3525.200	68	8601.000	40	9320.060	111	9342.274	78	9640.256	84
3525.210	68	8601.010	40	9320.070	111	9342.280	70	9640.261	84
3526.000	68	8601.015	40	9320.120	113	9342.290	70	9640.266	84
3526.200	68	8601.025	40	9340.000	66	9342.300	70	9640.271	84
3527.000	68	8601.026	40	9340.004	74	9342.310	71, 79	9640.276	84
3527.200	68	8601.030	40	9340.010	66	9342.314	79	9640.281	84
3528.000	68	8601.040	40	9340.030	110	9342.320	71, 79	9640.286	84
3528.010	68	8601.050	40	9340.035	110	9342.324	79	9640.291	84
3528.200	68	8601.060	40	9340.040	110	9342.400	72	9640.296	84
3528.210	68	8601.065	40	9340.070	66	9342.410	72	9640.301	84
3529.000	68	8601.080	40	9340.074	74	9342.500	72	9640.306	84
3529.200	68	8601.085	40	9340.090	113	9342.504	80	9640.311	84
3565.000	112	8601.086	40	9340.100	67	9342.510	72	9640.316	84
3565.010	112	8601.092	40	9340.110	67	9342.514	80	9640.325	85
3566.000	112	8601.095	40	9340.120	67	9342.540	72	9640.330	85
3567.000	112	8601.200	40	9340.130	67	9342.550	72	9640.340	85
3568.000	112	8601.300	40	9340.134	75	9342.560	113	9640.350	85
3569.000	112	8601.400	40	9340.140	67	9342.570	114	9640.360	84
3570.000	112	8601.500	40	9340.170	67	9342.600	73	9640.365	84
3571.000	112	8601.600	40	9340.200	67, 69	9342.604	80	9640.370	85
3572.000	112	8601.602	40	9340.210	67, 69	9342.610	73	9640.380	85
3573.000	112	8601.605	40	9340.214	75, 77	9342.614	80	9640.433	85
3574.000	112	8601.800	40	9340.220	67, 69	9342.640	113	9640.434	85
3575.000	112	8601.802	40	9340.224	75, 77	9342.660	114	9640.443	85
3576.000	112	8601.805	40	9341.000	68	9342.670	114	9640.444	85
3577.000	112	8601.850	40	9341.070	68	9342.680	114	9640.453	85
3578.000	112	8601.905	40	9341.100	69	9342.690	114	9640.454	85
3579.000	112	8601.915	40	9341.110	69	9342.700	73	9640.473	85
3580.000	110	8601.920	40	9341.120	69	9342.710	73	9640.474	85
3580.100	110	8602.000	40	9341.130	69	9342.720	113	9640.483	85
3581.000	110	8602.015	40	9341.140	69	9342.770	114	9640.484	85
3581.100	110	8602.025	40	9341.170	69	9342.780	114	9640.700	102
3582.000	110	8602.030	40	9342.000	68	9342.790	114	9640.705	102
3583.000	110	8602.040	40	9342.004	76	9350.075	111	9640.900	85
3584.000	110	8602.050	40	9342.014	76	9640.000	84	9640.910	85
3585.000	110	8602.060	40	9342.030	110	9640.010	84	9640.920	85
3586.000	110	8602.065	40	9342.070	68	9640.020	85	9640.930	85
3587.000	110	8602.080	40	9342.074	76	9640.050	84	9640.940	85

List of model numbers

9640.960 to 9672.013

Model No.	Page								
9640.960	85	9650.940	87	9661.150	109	9670.626	32	9671.181	43
9640.970	85	9650.960	87	9661.160	109	9670.628	32	9671.182	43
9640.980	85	9650.980	87	9661.180	109	9670.636	35	9671.183	43
9649.000	84	9650.990	87	9661.200	109	9670.638	35	9671.184	43
9649.010	84	9659.000	86	9661.230	109	9670.686	30	9671.186	43
9649.020	85	9659.010	86	9661.235	109	9670.696	33	9671.187	43
9649.060	84	9659.020	87	9661.240	109	9670.806	31	9671.188	43
9649.076	84	9659.030	87	9661.300	109	9670.808	31	9671.190	43
9649.078	84	9659.060	86	9661.305	109	9670.826	32	9671.196	43
9649.170	85	9659.078	86	9661.320	109	9670.828	32	9671.198	43
9649.190	84	9659.170	87	9661.325	109	9670.886	30	9671.204	43
9649.360	84	9659.180	87	9661.330	109	9671.003	42	9671.206	43
9650.000	86	9659.190	86	9661.335	109	9671.004	42	9671.208	43
9650.010	86	9659.360	86	9661.340	109	9671.006	42	9671.446	44
9650.020	87	9659.403	87	9661.345	109	9671.008	42	9671.448	44
9650.030	87	9659.404	87	9661.350	109	9671.013	41	9671.468	44
9650.050	86	9659.413	87	9661.355	109	9671.014	41	9671.488	44
9650.060	86	9659.414	87	9661.360	109	9671.016	41	9671.536	44
9650.076	86	9659.423	87	9661.365	109	9671.018	41	9671.538	44
9650.080	86	9659.424	87	9661.380	109	9671.033	41	9671.546	44
9650.098	86	9659.473	87	9661.385	109	9671.034	41	9671.548	44
9650.100	86	9659.474	87	9665.750	45	9671.036	41	9671.568	44
9650.140	86	9659.483	87	9665.760	45	9671.038	41	9671.586	44
9650.150	86	9659.484	87	9665.770	45	9671.043	41	9671.588	44
9650.160	86	9659.493	87	9665.780	45	9671.044	41	9671.636	44
9650.170	87	9659.494	87	9665.785	45	9671.046	41	9671.638	44
9650.180	87	9659.525	44	9665.903	44	9671.048	41	9671.646	44
9650.190	86	9659.535	44	9670.006	36	9671.120	43	9671.648	44
9650.201	86	9659.545	44	9670.008	36	9671.126	43	9671.666	44
9650.211	86	9659.555	44	9670.026	37	9671.128	43	9671.668	44
9650.221	86	9660.200	105	9670.028	37	9671.130	43	9671.686	44
9650.231	86	9660.235	44	9670.106	36	9671.132	43	9671.688	44
9650.241	86	9660.245	44	9670.108	36	9671.134	43	9671.736	44
9650.251	86	9660.255	44	9670.126	37	9671.135	43	9671.738	44
9650.261	86	9660.265	44	9670.128	37	9671.138	43	9671.746	44
9650.271	86	9660.313	102	9670.206	38	9671.140	43	9671.748	44
9650.281	86	9660.314	102	9670.208	38	9671.141	43	9671.766	44
9650.291	86	9660.318	102	9670.226	38	9671.142	43	9671.768	44
9650.301	86	9660.319	102	9670.228	38	9671.143	43	9671.786	44
9650.311	86	9660.363	102	9670.316	34	9671.144	43	9671.788	44
9650.325	87	9660.368	102	9670.318	34	9671.146	43	9671.846	44
9650.330	87	9660.369	102	9670.336	35	9671.147	43	9671.848	44
9650.340	87	9660.935	44	9670.338	35	9671.148	43	9671.906	39
9650.350	87	9660.945	44	9670.396	33	9671.150	43	9671.908	39
9650.360	86	9660.955	44	9670.406	31	9671.156	43	9671.926	39
9650.370	87	9660.965	44	9670.408	31	9671.158	43	9671.928	39
9650.380	87	9660.970	54	9670.416	34	9671.160	43	9671.986	39
9650.400	87	9661.000	109	9670.418	34	9671.161	43	9671.996	39
9650.410	87	9661.020	109	9670.426	32	9671.162	43	9671.998	39
9650.420	87	9661.030	109	9670.428	32	9671.163	43	9672.000	44
9650.470	87	9661.040	109	9670.436	35	9671.164	43	9672.002	44
9650.480	87	9661.050	109	9670.438	35	9671.166	43	9672.003	44
9650.487	87	9661.060	109	9670.486	30	9671.167	43	9672.004	44
9650.700	102	9661.080	109	9670.496	33	9671.168	43	9672.006	44
9650.900	87	9661.100	109	9670.606	31	9671.170	43	9672.008	44
9650.910	87	9661.120	109	9670.608	31	9671.176	43	9672.010	42
9650.920	87	9661.130	109	9670.616	34	9671.178	43	9672.012	42
9650.930	87	9661.140	109	9670.618	34	9671.180	43	9672.013	42

List of model numbers

9672.014 to 9675.156

Model No.	Page								
9672.014	42	9673.426	53	9673.648	56	9673.983	57	9674.416	106
9672.016	42	9673.428	53	9673.651	56	9673.990	57	9674.418	106
9672.018	42	9673.430	55	9673.652	56	9673.991	57	9674.420	106
9672.020	42	9673.431	54	9673.653	56	9673.995	57	9674.425	106
9672.022	42	9673.432	54	9673.654	56	9674.003	103	9674.426	106
9672.023	42	9673.434	55	9673.657	56	9674.004	103	9674.428	106
9672.024	42	9673.436	55	9673.660	56	9674.006	103	9674.430	106
9672.026	42	9673.437	55	9673.661	56	9674.008	103	9674.435	106
9672.028	42	9673.438	55	9673.662	56	9674.036	59	9674.436	106
9672.030	42	9673.439	55	9673.663	56	9674.038	59	9674.438	106
9672.032	42	9673.440	54	9673.664	56	9674.046	59	9674.441	108
9672.033	42	9673.441	54	9673.666	56	9674.048	59	9674.442	108
9672.034	42	9673.444	54	9673.667	56	9674.056	59	9674.443	108
9672.036	42	9673.445	54	9673.668	56	9674.058	59	9674.444	108
9672.038	42	9673.448	54	9673.671	56	9674.102	90	9674.445	108
9672.040	42	9673.449	54	9673.672	56	9674.104	90	9674.447	108
9672.042	42	9673.450	55	9673.673	56	9674.122	90	9674.448	108
9672.043	42	9673.454	55	9673.674	56	9674.124	90	9674.451	108
9672.044	42	9673.456	55	9673.677	56	9674.152	90	9674.452	108
9672.046	42	9673.457	55	9673.680	56	9674.154	90	9674.453	108
9672.048	42	9673.458	55	9673.681	56	9674.162	90	9674.454	108
9672.050	42	9673.459	55	9673.682	56	9674.164	90	9674.455	108
9672.052	42	9673.460	54	9673.683	56	9674.172	90	9674.457	108
9672.053	42	9673.461	54	9673.684	56	9674.174	90	9674.458	108
9672.054	42	9673.464	54	9673.686	56	9674.182	90	9674.461	108
9672.056	42	9673.465	54	9673.687	56	9674.184	90	9674.462	108
9672.058	42	9673.468	54	9673.688	56	9674.192	90	9674.463	108
9673.004	54	9673.469	54	9673.691	56	9674.194	90	9674.464	108
9673.006	54	9673.470	55	9673.692	56	9674.196	59	9674.467	108
9673.008	54	9673.471	55	9673.693	56	9674.198	59	9674.468	108
9673.051	51	9673.474	55	9673.694	56	9674.305	60	9674.473	108
9673.052	51	9673.475	55	9673.697	56	9674.306	60	9674.474	108
9673.055	51	9673.476	55	9673.901	58	9674.307	60	9674.477	108
9673.061	51	9673.477	55	9673.902	58	9674.308	60	9674.478	108
9673.062	51	9673.478	55	9673.903	58	9674.325	60	9674.485	108
9673.065	51	9673.479	55	9673.915	57	9674.326	60	9674.488	108
9673.066	51	9673.480	54	9673.920	57	9674.327	60	9674.701	52
9673.069	51	9673.481	54	9673.930	57	9674.328	60	9674.702	52
9673.081	51	9673.484	54	9673.931	57	9674.340	46	9674.703	52
9673.082	51	9673.485	54	9673.940	57	9674.342	46	9674.704	52
9673.085	51	9673.488	54	9673.941	57	9674.346	60	9674.706	52
9673.086	51	9673.489	54	9673.942	57	9674.348	60	9674.707	52
9673.089	51	9673.504	55	9673.943	57	9674.350	46	9674.761	56
9673.152	51	9673.506	55	9673.950	57	9674.352	46	9674.762	56
9673.155	51	9673.508	55	9673.951	57	9674.356	46	9674.763	56
9673.162	51	9673.530	52	9673.952	57	9674.358	46	9674.764	56
9673.165	51	9673.532	52	9673.953	57	9674.362	60	9674.781	56
9673.166	51	9673.540	52	9673.960	57	9674.364	60	9674.782	56
9673.182	51	9673.542	52	9673.961	57	9674.366	60	9674.783	56
9673.185	51	9673.560	52	9673.962	57	9674.368	60	9674.784	56
9673.186	51	9673.562	52	9673.963	57	9674.380	107	9675.130	100
9673.192	51	9673.640	56	9673.970	57	9674.381	107	9675.133	100
9673.195	51	9673.641	56	9673.971	57	9674.400	106	9675.136	100
9673.405	53	9673.642	56	9673.972	57	9674.405	106	9675.140	100
9673.406	53	9673.643	56	9673.973	57	9674.406	106	9675.143	100
9673.408	53	9673.644	56	9673.980	57	9674.408	106	9675.146	100
9673.416	53	9673.646	56	9673.981	57	9674.410	106	9675.153	100
9673.418	53	9673.647	56	9673.982	57	9674.415	106	9675.156	100

List of model numbers

9675.163 to 9676.987

Model No.	Page								
9675.163	100	9675.503	101	9676.014	93	9676.305	97	9676.815	104
9675.166	100	9675.504	101	9676.015	93	9676.313	97	9676.816	104
9675.210	102	9675.505	101	9676.016	93	9676.315	97	9676.817	104
9675.212	102	9675.506	101	9676.017	93	9676.317	97	9676.819	104
9675.218	102	9675.507	101	9676.018	93	9676.321	97	9676.832	104
9675.220	102	9675.508	101	9676.019	93	9676.322	97	9676.910	88
9675.222	102	9675.511	101	9676.020	91	9676.323	97	9676.912	88
9675.230	102	9675.513	101	9676.021	91	9676.324	97	9676.961	104
9675.232	102	9675.514	101	9676.022	91	9676.325	97	9676.962	104
9675.238	102	9675.515	101	9676.023	91	9676.326	97	9676.963	104
9675.240	102	9675.516	101	9676.024	91	9676.333	97	9676.966	104
9675.242	102	9675.517	101	9676.025	91	9676.334	97	9676.967	104
9675.303	100	9675.521	101	9676.026	91	9676.335	97	9676.968	104
9675.304	100	9675.522	101	9676.027	91	9676.336	97	9676.971	103
9675.306	100	9675.523	101	9676.041	94	9676.337	97	9676.972	103
9675.307	100	9675.524	101	9676.042	94	9676.338	97	9676.973	103
9675.311	100	9675.525	101	9676.043	94	9676.503	103	9676.976	103
9675.313	100	9675.526	101	9676.046	93	9676.504	103	9676.977	103
9675.314	100	9675.527	101	9676.047	93	9676.505	103	9676.981	103
9675.315	100	9675.528	101	9676.048	93	9676.520	96	9676.982	103
9675.316	100	9675.531	101	9676.052	94	9676.526	96	9676.983	103
9675.317	100	9675.533	101	9676.053	94	9676.528	96	9676.986	103
9675.321	100	9675.534	101	9676.054	94	9676.540	96	9676.987	103
9675.322	100	9675.535	101	9676.056	94	9676.546	96		
9675.323	100	9675.536	101	9676.058	94	9676.548	96		
9675.324	100	9675.537	101	9676.059	94	9676.620	98		
9675.325	100	9675.543	101	9676.184	105	9676.621	98		
9675.326	100	9675.544	101	9676.186	105	9676.626	98		
9675.327	100	9675.546	101	9676.188	105	9676.628	98		
9675.328	100	9675.547	101	9676.194	105	9676.640	98		
9675.331	100	9675.553	101	9676.196	105	9676.641	98		
9675.333	100	9675.554	101	9676.198	105	9676.646	98		
9675.334	100	9675.556	101	9676.201	97	9676.648	98		
9675.335	100	9675.557	101	9676.202	97	9676.700	95		
9675.336	100	9675.563	101	9676.203	97	9676.704	95		
9675.337	100	9675.564	101	9676.204	97	9676.710	95		
9675.343	100	9675.566	101	9676.205	97	9676.714	95		
9675.344	100	9675.567	101	9676.206	97	9676.730	94		
9675.346	100	9675.573	101	9676.213	97	9676.731	94		
9675.347	100	9675.574	101	9676.214	97	9676.733	94		
9675.353	100	9675.576	101	9676.215	97	9676.741	96		
9675.354	100	9675.577	101	9676.216	97	9676.742	96		
9675.356	100	9675.842	98	9676.217	97	9676.743	96		
9675.357	100	9675.843	98	9676.218	97	9676.744	96		
9675.361	100	9675.882	98	9676.221	97	9676.745	96		
9675.362	100	9675.883	98	9676.222	97	9676.746	96		
9675.363	100	9675.892	98	9676.223	97	9676.747	96		
9675.364	100	9675.893	98	9676.224	97	9676.748	96		
9675.365	100	9676.000	122	9676.225	97	9676.749	96		
9675.366	100	9676.001	122	9676.226	97	9676.806	104		
9675.367	100	9676.002	90	9676.233	97	9676.807	104		
9675.368	100	9676.004	90	9676.234	97	9676.808	104		
9675.373	100	9676.006	92	9676.235	97	9676.809	104		
9675.374	100	9676.007	92	9676.236	97	9676.810	104		
9675.376	100	9676.008	92	9676.237	97	9676.811	104		
9675.377	100	9676.011	93	9676.238	97	9676.812	104		
9675.501	101	9676.012	93	9676.301	97	9676.813	104		
9675.502	101	9676.013	93	9676.303	97	9676.814	104		

A

Accessories	100 – 114
Adaptor extension piece	
– for circuit-breaker component adaptors	113
Additional attachment	
– for busbar support 1-pole	110
Air circuit-breaker support bar	54
Angular baying bracket	
– for TS	41
Angular connector	
– for Flat-PLS	98
Assembly kit	
– for switch-disconnector-fuse section	46
Attachment set	
– for air circuit-breaker installation	54

B

Base isolators	109
Base tray infill	67, 69
Base trays	67, 69, 75, 77
Base/plinth components	
– front and rear	40
Base/plinth trim panels	
– Side	40
Baying brackets	
– PE/PEN	109
Baying connector	
– for TS	41
Bolts Maxi-PLS	85, 87, 103
Bracket for mounting rail	61
Busbar claw	
– for Flat-PLS	93
Busbar connection adaptor	
– 3-pole	70, 71
– 4-pole	78, 79
Busbar connectors	111
Busbar stabiliser bars	
– for busbar support Flat-PLS	91
Busbar support	
– Flat-PLS	90
– for switch-disconnector-fuse section	106
– for RiLine60 flat copper busbars	66, 74
– for stabiliser bar	91
– Maxi-PLS	84, 86
Busbar support RiLine60	
– 3-pole	66
– 3-pole PLS	68
– 4-pole	74
– 4-pole PLUS	76
Busbar systems	
– 1- and 2-pole	110
– 3-pole (RiLine60)	66 – 73
– 4-pole (RiLine60)	74 – 80
– Flat-PLS	90 – 97
– Maxi-PLS	84 – 89
– Technical information	115
Busbars	
– Cover section	110
– Cover section for Flat-PLS	94
– E-Cu	102, 109, 110
– Maxi-PLS	84, 86
– PE/PEN	109
– PLS	68, 102
– Screw connections	141

C

Cable chamber	21 – 23
Cable chamber enclosures SV-TS 8	33 – 35
Cable connection system	
– for Maxi-PLS/Flat-PLS	99
Cable entry gland	
– for roof plates	45
– for side panel modules	51
Circuit-breaker component adaptor	
– 3-pole	72, 73
– 4-pole	80
Circuit-breaker section	9 – 11
Clamps	
– Maxi-PLS	85, 87
Claw with nut	104
Combination angle	
– PE/PEN	109
Compartment configuration	50
Component adaptor	
– 3-pole	72, 73
– 4-pole	80
Connection brackets	
– for circuit-breaker component adaptors	114
– for Flat-PLS	97
– for switch-disconnector-fuse section	108
– Maxi-PLS	85, 87
Connection clamps	
– Maxi-PLS	85, 87
Connection kits	
– for busbar riser	102
Connection plates	
– for laminated copper bars	
– for Flat-PLS	96
– Maxi-PLS	85, 87
– with studs M10/12/16 for Flat-PLS	95
Connection terminals	
– Flat-PLS	94
Connector	
– for busbars	111
– for Flat-PLS	98
– for Mini-TS profile	58
– Maxi-PLS	84, 86
Connector kits	
– for Flat-PLS/RiLine60	101
– for Maxi-PLS/Flat-PLS	88, 89
– for Maxi-PLS/RiLine60	100
Connector pieces	
– for Mini-TS profile	58
Contact hazard protection	
– for cable chamber	
– for switch-disconnector-fuse section	60
Contact makers	
– for Flat-PLS	96
– Maxi-PLS	85, 87
Copper bars	
– Busbars	109, 110
– Maxi-PLS	84, 86
– PLS special busbars	68
– Rittal Flexibar “S”	112
Copper busbars	
– RiLine60	66
Corner bracket for Maxi-PLS	102
Corner connector	
– for Mini-TS profile	58
Coupling set mounting kit	59
Coupling section	13, 15
Cover plates	52
Cover sections	
– for base tray	67, 69, 75, 77
– for busbars	110
– for Flat-PLS	94
– Maxi-PLS	84, 86
Cover, distribution busbar	
– for ABB/Siemens switch-disconnector-fuse section	107
– for Jean Müller switch-disconnector-fuse section	107

Covers	
– for busbar claws	93
Cross members	
– for TS	42

D

Direct connection components	
– for Maxi-PLS	85, 87
Direct connection terminals	
– for Flat-PLS	94
Distribution busbars	102
– for switch-disconnector-fuse section	106
Divider panel	
– for switch-disconnector-fuse section	60
Dividing plate	
– for switch-disconnector-fuse section	60

E

Enclosure configuration	39 – 46
Enclosures, SV-TS 8	30 – 38
– Busbar enclosures	38
– Cable chamber enclosures	33 – 35
– Modular enclosures	30 – 32
– Switch-disconnector-fuse enclosures	36 – 37
– System data	134 – 140
End covers for busbar supports	
– 3-pole	66, 68
– 4-pole	74, 76
– Flat-PLS	92
– Maxi-PLS	84, 86
– PLS	68
– PLUS	76
End support	
– for switch-disconnector-fuse section	106
– Maxi-PLS	84, 86
Expansion connector PLS	111

F

Filler pieces	
– for busbar support Flat-PLS	92
Flat-PLS busbar systems	90 – 97
Frame adaptor piece	
– for Mini-TS profile	58
Front trim panels	
– for switch-disconnector-fuse section	46
– for TS	41, 42
Functional space divider	
– for TS	54, 55
– Mounting bracket	53
Functional space side panel modules	
– for cable connection space	51
– for TS	51

G

Gland plates	
– for cable entry	45
– for side panel modules	51
– to shroud the opening for vertical busbar systems	55

I			
Isolator chassis			
– Maxi-PLS	85, 87		
L			
Laminated copper bars	112		
Locks (twist locks)	43		
Longitudinal connector			
– for Flat-PLS	98		
– Maxi-PLS	84, 86		
M			
Maxi-PLS			
– Bar systems	84 – 89		
Mini-TS profiles	57		
Modular enclosures SV-TS 8	30 – 32		
Mounting accessories			
– for RiLine60 distribution busbar system	61		
Mounting bracket	61		
– for functional space divider	53		
– for functional space divider and air circuit-breaker support bar	53		
Mounting claw with nut	104		
Mounting kit, coupling set	59		
Mounting plates			
– for Ri4Power Form 2-4	56		
Mounting rails	61		
N			
Nuts for mounting rails	61		
O			
Outgoing section	17		
P			
Partial doors			
– for TS	43		
Partial mounting plates			
– for TS	56		
PE/PEN			
– Busbars	109		
– Combination angle	109		
Perforated mounting strip			
– for partial doors	43		
Planning and configuration of Ri4Power systems	122		
PLS			
– Busbar connectors	111		
– Busbars	68, 102		
– Expansion connectors	111		
Power Engineering software	123		
Punched rail			
– 17 x 15.5 mm for TS	57		
Punched rails			
– for Jean Müller switch-disconnector-fuse section	107		
Punched section with mounting flange			
– for coupling set	59		
R			
Rated currents			
– Busbars E-Cu	120		
– Flat-PLS busbar systems	121		
Ri4Power assembly instructions	122		
RiLine60 busbar support			
– 1- and 2-pole	110		
RiLine60 busbar systems	66 – 80		
Roof frame strips			
– for TS	44		
Roof plates			
– for TS	44		
S			
Screw connections			
– for connection brackets	104		
– for Flat-PLS busbar systems	104		
Short-circuit protection diagrams			
– for RiLine60	116		
Short-circuit resistance diagrams			
– Flat-PLS	118		
– Laminated copper bars	119		
Side panel modules			
– for cable connection space	51		
– for TS	51		
Side panels			
– for TS	39		
Sliding blocks			
– for circuit-breaker component adaptor	113		
– Maxi-PLS	85, 87		
Sliding nuts			
– Maxi-PLS	85, 87		
Spacer rolls	103		
Spacers			
– for Flat-PLS busbar support	92		
– for RiLine60 busbar supports	113		
Special busbars			
– Maxi-PLS	84, 86		
– PLS	68, 102		
Stabiliser			
– for connection kit	105		
– Maxi-PLS	86		
Stabiliser bars			
– Flat-PLS	91		
Stacking insulator	105		
Support			
– for Flat-PLS	90, 91		
– for laminated copper bars	112		
– for Maxi-PLS	84, 86		
Support bars			
– for air circuit-breakers	54		
Support frame			
– for DIN rail-mounted devices	56		
Support panel			
– for cover sections	67, 69, 75, 77		
Support rails			
– for component adaptors	113		
– for stacking insulators	105		
SV-TS 8 enclosures	30 – 38		
Switch-disconnector-fuse section	25 – 27		
Switch-disconnector-fuse enclosures	36 – 37		
System accessories			
– for SV-TS	39 – 46		
System attachment			
– for Flat-PLS	90		
– for Maxi-PLS	84, 86		
– for RiLine60	103		
System benefits			
– Maxi-PLS	83		
– RiLine60	63		
System data	134 – 140		
T			
T-connector kits			
– for Flat-PLS/RiLine60 bar systems	101		
– for Maxi-PLS/RiLine60 bar systems	100		
– for RiLine60	100		
T-connector piece			
– for Mini-TS profile	58		
Technical information	115 – 141		
Terminal box Form 4b	52		
Terminal block, distribution busbar			
– for switch-disconnector-fuse section	108		
Terminal studs			
– for connector kits and connection brackets	103		
– Maxi-PLS	85, 87		
Terminals			
– Flat-PLS	94		
Threaded bolts			
– for connector kits and connection brackets	103		
– Maxi-PLS	85, 87		
Trim panels			
– for TS	41, 42		
TS 8 system platform	29		
Twist locks	43		
U			
U contact makers			
– Maxi-PLS	85, 87		
U nut	61		
Universal support			
– for laminated copper bars	112		
Upgrade kit			
– for front panels	41, 42		
– for side panels	39		

All in all – solutions from Rittal



Industrial Enclosures



Power Distribution



Busbar systems RiLine60
Busbar systems 40/100/150/185 mm
Ri4Power low-voltage switchgear



Electronic Packaging



System Climate Control



IT Solutions



Communication Systems

Rittal has one of the largest ranges of enclosures available for immediate delivery. However, Rittal also supplies integrated solutions – up to Level 4. This comprises mechanical installation, power supply, electronic components, climate control and central monitoring. For all of your requirements.

Fully assembled and functional. Wherever in the world you develop and implement solutions for yourself and your customers, we are close at hand. The global alliance between production, distribution and service guarantees closeness to the customer. Worldwide!

09/09 • E470

Rittal GmbH & Co. KG · Postfach 1662 · D-35726 Herborn
Telephone: +49(0)2772 505-0 · Telefax: +49(0)2772 505-2319 · eMail: info@rittal.de · www.rittal.com



Switch to perfection **RITTAL**