

# Twist-Lock® Devices 30A, 125V AC, 2 Pole, 3 Wire Grounding Watertight Safety-Shroud® Reverse Service Connector

# HUBBELL



## Features

- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Superior cord grip design protects terminations from excess strain
- UL Type 4X Environmental seal protects connection while in use.

## Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Reverse service, black housing, white clamps.	.350"-1.150"(9-29)	783585458090	HBL2613SR



## Listings

Listed to UL 498  
Fed.Spec. W-C-596  
Certified to CSA C22.2 No.42

## Accessories

Watertight Safety Shroud	HBL2615SWR
Reverse Service Inlet	

## Specifications

Housing / Cord Clamp	PBT
Terminal Retainer	Clear polycarbonate
Contacts	Brass
Terminal Screws	#10-32 Brass (Phillips / Slotted / Robertson)
Terminal Clamp	Cold rolled steel – nickel plated
Assembly Screws	Stainless Steel
Watertight Gland	Neoprene

## Resources

[eCatalog](#)

## Performance

### Electrical

Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

### Mechanical

Terminal Accommodation	#16 AWG - #8 AWG stranded copper wire only.
------------------------	---

Terminal Identification	Terminals identified in accordance with UL 498
-------------------------	--

### Environmental

Flammability	HB or better per UL94/CSA 22.2 No.0.17
Moisture Resistance	IP20 Suitability
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

